

IBM PS/2 (53 to 57)

IBM® PS/2®:	Type-model	Diskette Disk: std-max internal ms seek / interface	CPU Speed	Upgrade MHz	L2 cache std / max	Memory in MB; std / max	Video; std/max memory	Std features	Slots available 16+32 bit	Total bays	SUP ¹	Available date
53	9553-OB7	d 120M-1.05G 14 IDE	486SLC2		0KB/0KB	4 /16	SVGA	m/K	3+0	☆3	\$ 795	Nov 93
53	-0BB	d 250M-1.05G 14 IDE	at		" "	4 /16	GD5426	m/K	3+0	☆3	960	Nov 93
53 LS	" -1BX	Opt: 1 diskette, 2 IDE	50/25 MHz	all: none	" "	4 /16	1 MB	m/K Ethernet	2+0	☆3	667	Nov 93
53 LS	" -2BX	Opt: 1 diskette, 2 IDE			" "	4 /16		m/K Token-Ring	2+0	☆3	1033	Nov 93
56 SLC2	9556-DB6	D 104M-2.0G 12 scsi	486SLC2	all:	0 /0	8 /16	XGA-2	m/K	3+0	☆3	1333	Aug 93
56 SLC2	" -DBA	D 208M-2.0G 12 scsi	at	① 486SLC3 at 75/25	" "	8 /16	1 MB	m/K	3+0	☆3	1467	Aug 93
56 SLC3	9556-DE9	D 170M-2.0G 13 scsi	486SLC3		0 /0	8 /16	XGA-2	m/K	3+0	☆3	1680	Feb 94
56 SLC3	-DEB	D 245M-2.0G 16 scsi	at	all:	" "	" "	1 / 1 MB	m/K	" "	" "	1800	Feb 94
56 SLC3	" -DED	D 340M-2.0G 14 scsi	75/25 MHz	none	" "	" "	" "	m/K	" "	" "	1920	Feb 94
56 LS	" -1EX	Opt: 2 diskette, 2 scsi	"		" "	4 /16	"	m/K Ethernet	2+0	☆3	1333	Feb 94
56 LS	" -2EX	Opt: 2 diskette, 2 scsi	"		" "	4 /16	"	m/K Token-Ring	2+0	☆3	1667	Feb 94
57 SLC2	9557-DB6	D 104M-6.0G 12 scsi	486SLC2	all:	0 /0	8 /16	XGA-2	m/K	5+0	☆4	1467	Aug 93
57 SLC2	-DBA	D 208M-6.0G 12 scsi	at	① 486SLC3 at 75/25	" "	8 /16	1 MB	m/K	5+0	☆4	1600	Aug 93
57 SLC2	" -DBG	D 540M-6.0G 10 scsi	50/25 MHz		" "	8 /16	"	m/K	5+0	☆4	1933	Aug 93
57 SLC3	9557-DE9	D 170M-6.0G 13 scsi	486SLC3	all:	0 /0	8 /16	XGA-2	m/K	5+0	☆4	1813	Feb 94
57 SLC3	-DEB	D 245M-6.0G 16 scsi	at	none	" "	8 /16	1 MB	m/K	5+0	☆4	1933	Feb 94
57 SLC3	" -DED	D 340M-6.0G 14 scsi	75/25 MHz		" "	8 /16	"	m/K	5+0	☆4	2053	Feb 94
57 SLC3	" -DEG	D 540M-6.0G 10 scsi			" "	8 /16	"	m/K	5+0	☆4	2187	Feb 94
M57	9557-6EB	D 245M-6.0G 16 scsi	486SLC3	all:	0 /0	8 /16	XGA-2	m/K CD/Audiv/W	4+0	☆4	2733	Mar 94
M57	-7EB	D 245M-6.0G 16 scsi	at	none	" "	8 /16	1 MB	m/K CD/Audiv/2	4+0	☆4	2733	Jun 94
M57	" -6EG	D 540M-6.0G 10 scsi	75/25 MHz		" "	8 /16	"	m/K CD/Audiv/W	4+0	☆4	2987	Mar 94
M57	" -7EG	D 540M-6.0G 10 scsi			" "	8 /16	"	m/K CD/Audiv/2	4+0	☆4	2987	Jun 94

MODELS 53, 56, and 57

Choice of operating sys (until 11/21/94):

IBM OS/2® 2.1

IBM OS/2 2.00.1

IBM DOS 6.1 / Windows™ 3.1

IBM DOS 5.02 / Windows 3.1

After September 20, 1994:

IBM OS/2 2.11

IBM DOS 6.3 / Windows 3.11

Includes all software publications and all diskettes (op sys is not preinstalled); 53 LS and 56 LS do not include op sys

Audiv = 16 bit sound adapter (Audiovation)
 CD = CD-ROM/XA (double speed)
 d = 1.44 MB 3.5" diskette drive
 D = 2.88 MB 3.5" diskette drive with media sense
 E = 10 Mbps Ethernet adapter 10BaseT
 K = Choice of 84, 101 or 122 host key keyboard
 K = Choice of Enhanced or Quiet 101 keyboard with mouse or Enhanced 101 key with TrackPoint II or Quiet Touch 84 key with TrackPoint II (TrackPoint II keyboards available at additional cost)
 m = PS/2 mouse
 T = 16/4 Mbps Token-Ring Adapter
 W = DOS 6.1/Windows 3.1 preinstalled
 2 = OS/2 2.1 preinstalled
 256 = (italics) write-back L2 cache
 256 = (no italics) write-through L2 cache

PS/2 DESKTOP FEATURES

- ✦ Micro Channel® Architecture
- ✦ Performance (20 MB/sec data transfer)
- ✦ Automatic configuration (no switches, jumpers)
- ✦ Multiple busmaster support (high throughput)
- ✦ Parity memory
- ✦ 70 ns memory speed standard
- ✦ All memory on planar; 72 pin SIMMs
- ✦ Extensive embedded diagnostics
- ✦ Selectable boot capability
- ✦ 32 bit XGA-2® graphics busmaster or SVGA
- ✦ 640x480, 800x600, 1024x768, 1280x1024
- ✦ ISO 9241-3 compliant
- ✦ Maximum total disk capacity (internal and external) about 54 GB w/ IBM 2.0 GB disks
- ✦ Cover key lock (unique for every PS/2)
- ✦ U-bolt holes to lock to furniture
- ✦ Choice of keyboards
- ✦ IBM mouse included
- ✦ Numerous hard copy documentation
- ✦ High parts availability; high resale value
- ✦ **24 hr/day support via fax (1-800-426-3395), bulletin board (1-919-517-0001), and phone (HelpWare at 1-800-772-2227)**

PS/2

WARRANTY SERVICE SUPPORT

- ⇨ 3 year warranty
- ⇨ On site warranty all 3 years
- ⇨ All cities in all states
- ⇨ 24 hour / 7 day service coverage
- ⇨ 4 hour response time
- ⇨ 24 hour / 7 day telephone support
- ⇨ 24 hour / 7 day bulletin board
- ⇨ 24 hour / 7 day fax support
- ⇨ IBM or dealer warranty/service
- ⇨ 30 day money back guarantee

scsi = 16 bit SCSI-1 busmaster on planar
 SCSI = 32 bit SCSI-1 busmaster on planar
 SCSI = 32 bit SCSI-1 busmaster adapter

Note 1: Price (retail USD)

Note 2: P24T: Intel Pentium OverDrive

- ☆ Micro Channel architecture
- ✕ Systems withdrawn
- ↘ Price decrease effective October 3, 1994
- ↘ Price decrease effective October 17, 1994

No warranties are expressed in this summary.
 (1PS2) Compiled by Roger Dodson, IBM

Current as of November 1994