

IBM PS/2 (76 to 90)

IBM® PS/2®:	Type-model	Diskette Disk: std-max internal ms seek / interface	CPU Speed / Upgrade MHz	L2 cache std / max	Memory in MB; std / max	Video; std/max memory	Std features	Micro Channel 32 bit slots available	Total bays	SUP ¹	Available date
76	9576-DU6	D 104M-2.0G 12 scsi	486SX at 33 MHz	0 / 0	8 / 32	XGA-2	K	2 ☆ 3	3	\$1833	Aug 93
76	" -DUA	D 208M-2.0G 12 scsi	at 33 MHz	" "	8 / 32	1 MB	K	2 ☆ 3	3	1933	Aug 93
76i	9576-AU9	D 170M-1.54G 14 IDE	486SX-33	all:	0 / 256	8 / 64	S3-928	K/VMC	/40 3 ☆ 3	2000	Jun 94
76i	" -AUB	D 270M-1.54G 14 IDE	486SX-33	all:	0 / 256	1 / 2 MB	K/VMC	/40 3 ☆ 3	3	2100	Jun 94
76i	" -ANB	D 270M-1.54G 14 IDE	DX2-66/33	all:	128 / 256	"	K/VMC	/40 3 ☆ 3	3	2400	Jun 94
76i	" -ATB	D 270M-1.54G 14 IDE	DX4-100/33	① 486DX2-66/33 ② DX4-100/33 (2)	256 / 256	"	K/VMC	/40 3 ☆ 3	3	2867	Jun 94
76s	9576-BUB	D 270M-2.0G 12 s2f	486SX-33	③ P24T (3)	0 / 256	8 / 64	S3-928	K/VMC	/40 2 ☆ 3	2300	Jun 94
76s	" -BNB	D 270M-2.0G 12 s2f	486DX2-66/33	all:	128 / 256	1 / 2 MB	K/VMC	/40 2 ☆ 3	3	2600	Jun 94
76s	" -BTB	D 270M-2.0G 12 s2f	DX4-100/33	all:	256 / 256	"	K/VMC	/40 2 ☆ 3	3	3067	Jun 94
77	9577-DUA	D 208M-6.0G 12 scsi	486SX at 33 MHz	0 / 0	8 / 32	XGA-2	K	4 ☆ 4	4	2067	Aug 93
77	" -DUG	D 540M-6.0G 10 scsi	at 33 MHz	" "	8 / 32	1 MB	K	4 ☆ 4	4	2300	Aug 93
77	77-DNA	D 208M-6.0G 12 scsi	486DX2 at 66/33 MHz	all:	0 / 0	8 / 32	XGA-2	K	4 ☆ 4	2333	Aug 93
77	77-DNG	D 540M-6.0G 10 scsi	at 66/33 MHz	② P24T (3)	" "	8 / 32	1 MB	K	4 ☆ 4	2567	Aug 93
77i	9577-AUB	D 270M-1.54G 14 IDE	486SX-33	all:	0 / 256	8 / 64	S3-928	K/VMC	/40 5 ☆ 4	2233	Jun 94
77i	" -ANB	D 270M-1.54G 14 IDE	DX2-66/33	all:	128 / 256	1 / 2 MB	K/VMC	/40 5 ☆ 4	4	2533	Jun 94
77i	" -ANG	D 527M-1.54G 12 IDE	DX2-66/33	① 486DX2-66/33 ② DX4-100/33 (2)	128 / 256	"	K/VMC	/40 5 ☆ 4	4	2767	Jun 94
77i	" -ATB	D 270M-1.54G 14 IDE	DX4-100/33	③ P24T (3)	256 / 256	"	K/VMC	/40 5 ☆ 4	4	3000	Jun 94
77i	" -ATG	D 270M-1.54G 12 IDE	DX4-100/33	all:	256 / 256	"	K/VMC	/40 5 ☆ 4	4	3233	Jun 94
77s	9577-BUB	D 270M-4.54G 12 s2f	486SX-33	all:	0 / 256	8 / 64	S3-928	K/VMC	/40 4 ☆ 4	2433	Jun 94
77s	" -BNB	D 270M-4.54G 12 s2f	DX2-66/33	all:	128 / 256	1 / 2 MB	K/VMC	/40 4 ☆ 4	4	2733	Jun 94
77s	" -BNG	D 540M-4.54G 8.7 s2f	DX2-66/33	① 486DX2-66/33	128 / 256	"	K/VMC	/40 4 ☆ 4	4	2967	Jun 94
77s	" -BTB	D 270M-4.54G 12 s2f	DX4-100/33	② DX4-100/33 (2)	256 / 256	"	K/VMC	/40 4 ☆ 4	4	3200	Jun 94
77s	" -BTG	D 540M-4.54G 8.7 s2f	DX4-100/33	③ P24T (3)	256 / 256	"	K/VMC	/40 4 ☆ 4	4	3433	Jun 94
77s	" -VTG	D 540M-4.54G 8.7 s2fw	DX4-100/33	all:	256 / 256	16/64	K/VMC	/40 4 ☆ 4	4	4133	Jun 94
77s	9577-6NB	D 270M-4.0G 12 s2f	DX2-66/33	all:	128 / 256	8 / 64	S3-928	K/V /M/CD/A/W	/40 3 ☆ 4	3600	Nov 94
77s	" -7NB	D 270M-4.0G 12 s2f	DX2-66/33	all:	128 / 256	1 / 2 MB	K/V /M/CD/A/2	/40 3 ☆ 4	4	3600	Nov 94
77s	" -6NG	D 540M-4.0G 8.7 s2f	DX2-66/33	① 486DX2-66/33	128 / 256	"	K/V /M/CD/A/W	/40 3 ☆ 4	4	3833	Nov 94
77s	" -7NG	D 540M-4.0G 8.7 s2f	DX2-66/33	② DX4-100/33 (2)	128 / 256	"	K/V /M/CD/A/2	/40 3 ☆ 4	4	3833	Nov 94
77s	" -6TG	D 540M-4.0G 8.7 s2f	DX4-100/33	③ P24T (3)	256 / 256	"	K/V /M/CD/A/W	/40 3 ☆ 4	4	4300	Nov 94
77s	" -7TG	D 540M-4.0G 8.7 s2f	DX4-100/33	all:	256 / 256	"	K/V /M/CD/A/2	/40 3 ☆ 4	4	4300	Nov 94

MODELS 76 and 77

Choice of operating sys (until 11/21/94):

- IBM OS/2® 2.1
- IBM OS/2 2.00.1
- IBM DOS 6.1 / Windows™ 3.1
- IBM DOS 5.02 / Windows 3.1

After September 20, 1994:

- IBM OS/2 2.11
- IBM DOS 6.3 / Windows 3.11

Includes all software publications and all diskettes (op sys is not preinstalled)

A = 16 bit sound adapter (Audiovision)
 CD = CD-ROM/XA (double speed)
 D = 2.88 MB 3.5" diskette drive with media sense
 K = Choice of 84, 101 or 122 host key keyboard
 K = Choice of Enhanced or Quiet 101 keyboard with mouse or Enhanced 101 key with TrackPoint II or Quiet Touch 84 key with TrackPoint II (TrackPoint II keyboards available at additional cost)
 M = MediaBurst Movie Adapter
 V or VMC = VESA Media Channel media access slot
 W = DOS 6.3/Windows 3.11 preinstalled
 2 = OS/2 2.11 preinstalled
 256 = (no italics) write-through L2 cache
 256 = (italics) write-back L2 cache
 40 = 40 MB/sec streaming data transfer

MODELS 76i, 76s, 77i, and 77s

Choice of operating system:

- IBM OS/2 2.1 (until 11/21/94)
- IBM OS/2 2.11
- IBM DOS 6.3 / Windows 3.11
- IBM DOS 6.1 / Windows 3.1 (until 11/21/94)
- IBM DOS 5.02 / Windows 3.1 (until 11/21/94)

Includes all software publications and all diskettes (op sys is not preinstalled)

PS/2 FEATURES

- ✦ Micro Channel® Architecture
- ✦ 32 bit adapters (Models 76, 77, 90)
- ✦ Automatic configuration (no switches, jumpers)
- ✦ Multiple busmaster support (high throughput)
- ✦ Parity memory; 70 ns memory
- ✦ All memory on planar; 72 pin SIMMs
- ✦ Extensive embedded diagnostics
- ✦ ISO 9241-3 compliant
- ✦ Cover key lock (unique for every PS/2)
- ✦ U-bolt holes to lock to furniture
- ✦ Choice of keyboards
- ✦ IBM mouse included (except TrackPoint models)
- ✦ Numerous hard copy documentation
- ✦ **24 hr/day support via fax (1-800-426-3395), bulletin board (1-919-517-0001), and phone (HelpWare at 1-800-772-2227)**

PS/2

WARRANTY SERVICE SUPPORT

- ⇒ 3 year warranty
- ⇒ On site warranty all 3 years
- ⇒ All cities in all states
- ⇒ 24 hour / 7 day service coverage
- ⇒ 4 hour response time
- ⇒ 24 hour / 7 day telephone support
- ⇒ 24 hour / 7 day bulletin board
- ⇒ 24 hour / 7 day fax support
- ⇒ IBM or dealer warranty/service
- ⇒ 30 day money back guarantee

scsi = 16 bit SCSI-1 busmaster on planar
 s2f = 16 bit SCSI-2 fast slave adapter
 SCSI = 32 bit SCSI-1 busmaster adapter
 s2fw = 32 bit SCSI-2 fast/wide busmaster adapter

Note 1: Price (retail USD)
 Note 2: Intel 486 OverDrive (in future)
 Note 3: P24T: Intel Pentium OverDrive

- Multimedia models
- ☆ Micro Channel architecture
- ☞ Products announced June 14, 1994 or later
- ☞ Systems withdrawn
- ♣ Price decrease effective October 17, 1994
- ⊗ ECC - Error Checking & Correcting memory

No warranties are expressed in this summary (2PS2) Compiled by Roger Dodson, IBM

Current as of October 1994