## IBM Displays (S/S series)

SUPER VGA COLOR (S/S = Sight and Sound)	
Name Type-model Screen Actual viewable diagonal size Type Dot pitch (mm) Viewing area (inches) Max view area (inches) Viewing area (mm) Max view area (mm) Frequency Vertical refresh rate range	17S/S 7091-7S1 17" FST 15.9" / 404 mm SVGA color .27 11.8 x 8.8" 12.8 x 9.4" 300 x 225 325 x 240  Multiscanning 50 to 160 Hz
Horizontal line rate range Maximum pel rate	30 to 82 kHz 148 MHz
640 x 480 NI (presets) 800 x 600 NI (presets) 900 x 720 NI (presets) 1024 x 768 NI, I (presets) 1280 x 496 NI (presets) 1280 x 1024 NI or I (presets) 3270 MFI emulation modes	60, 72 Hz to 85 Hz to 85 Hz 112 Hz StereoScopic 76 Hz I 43.5 to 77 Hz 120 Hz StereoScopic 60, 72, 77 Hz to 77 Hz 2, 3, 4, 5
Emission ISO 9241-3 Lift/tilt/swivel option	MPR-II ISO 9241-3 No (too big)
On screen menu Brightness/contrast control Vertical position/size control Horizontal position/size control Trapezoidal/pincushion control Paralellogram control Rotation control Vertical/Horizontal moire control Color select (red, green, blue) Degauss Display refresh rates Vert/Horz converg adj button Connector Apple/RS/6000/Sun attach	On screen menu On screen - digital No 13W3 with cable choice RS/6000 only
Microprocsr (detects modes) Factory preset modes User modes that can save Ability to save a new setting Prevent overwriting presets Geometry reset button Auto-borderless Focus adjustment	Microprocessor 8 8 Automatic Yes Reset button No None
Stereo speakers Microphone Video camera Audio jacks	Stereo speakers Integrated microphone Optional camera In/out jacks
DPMS compliant Power management Power mgmt flashing LED Power mgmt on/off switch Available date Warranty Price (retail USD)	DPMS compliant Energy Star compliant No No No November 1994 3 year \$ 1,410

### 17S/S strengths:

- ⇒ Integrated stereo speakers
- ⇒ Integrated microphone
- ⇒ Video camera enabled
- On-screen display menu
- On-screen display of refresh rates
- On-screen self test menu
- ⇒ Microphone and headphone jacks

A **video camera compartment** is located on the top left of the display. It can be removed for installation of an optional video camera. It contains a 8-pin Mini-Din connector for attachment of the camera. IBM intends to provide a video camera that can be integrated into the 17S/S as an option

Video signal cable - customer choses either:

- ① 13W3 D-shell (display) to 13W3 D-shell (system unit); 88G3097 or
- 2 13W3 D-shell (display) to a 15 pin D-shell (system unit);11H3991

A **multimedia cable** is included which is a single cable with a 26 pin D-shell that contains the video camera and audio signal lines

## Stereo speakers

- Mounted on left and right sides on front
- 2.5 watts each
- Dial volume control on front of 17S/S

Dimensions: 16.7"H x 17.2"W x 17.2"D; 45 pounds

#### **ON-SCREEN DISPLAY MENU CONTROLS**

- Brightness
- ⇒ Geometry
  - Horizontal position
  - Horizontal size
  - Vertical position
  - Vertical size
  - Vertical pincushion
  - Trapezoid
  - Paralellogram
  - Rotation
  - Horizontal moire connection
  - Vertical moire connection
- Color select
  - 9300 degrees Kelvin (blue tint)
  - 6550 degrees Kelvin (whiter tint)
- User selectable (red and blue adjustment; green is fixed)
- ⇒ Video level (0.7 volts or 1 volt)
- ⇒ Degauss (also at power-on)
- Display vertical and horizontal refresh rates
- Recall factory presets
- ⇒ Self test (when system off or cable disconnected)

# 17S/S DISPLAY WARRANTY SERVICE SUPPORT

- ⇒ 3 year warranty
- On-site first year
- Mail-in repair second & third year (with option of upgrade to on-site)
- ⇒ All cities in all states
- 24 hr/7 day service coverage 1st yr
- 4 hr average response time (1st yr)
- Option to upgrade yrs 2 and 3 to: 9-5 Mon-Fri cov, next day resp (\$25 each year) or 24 hr/7 day coverage, 4 hr resp (\$34 each year)
- 24 hour / 7 day telephone support
- 24 hour / 7 day bulletin board
- ⇒ 24 hour / 7 day fax support
- ⇒ IBM® or dealer warranty/service
- ⇒ 30 day money back guarantee

## **STANDARD FEATURES 17S/S**

Universal power supply Anti-static screen Anti-glare screen (AGRAS™) Tilt/swivel stand Automatic degauss