IBM ThinkPad 350, 350C, 500, 510Cs

IBM® ThinkPad®:	≈ 350	⊱< 350C	500		510Cs		
	monochrome	passive color	sub-notebook		color sub-notebook		
Processor type Processor speed Memory cache Coprocessor socket Diskette drive	All: 80486 SL (no math co) All: 25 MHz All: 8 KB internal (no L2) All: No All: 3.5" 1.44 MB		80486 SLC2 50/25 MHz 16 KB internal (no L2) No External 3.5" 1.44 MB		Blue Lightning 486BL2-50 50/25 MHz 16 KB internal (no L2 cache) No External 3.5" 1.44 MB (9 oz.)		
Price (retail USD) Type - model Hard drive - size Hard drive - speed Avail / withdrawal date	\$ 1,499 2618-J0A 125 MB 15 ms	\$1,599 \ \$\ \] \$1,999 \ \] 2618-N0A 2618-P0A 125 MB 15 ms 12 ms June 93 / withd Sep 94	\$ 799 \(\) 2603-08N 85 MB 15 ms Dec 93		\$ 1,799 \ 2604-C2U 200 MB 17 ms June 94	Fn+F2 = Fuel guage Fn+F3 = Setup Fn+F4 = Suspend Fn+F5 = Speaker Fn+F6 = Sys request	
Display - type Display - grey scales Display - techology Display - light source Display - size (diag) Display - contrast ratio 180 degree display tilt	VGA mono 64 grey scales STN LCD - Backlit 9.5 inch 18 to 1 Yes (external SVGA)	VGA color 256 colors 640 x 480 STN - passive matrix LCD - Backlit 9.2 inch 13 to 1; Single scan Yes (external SVGA)	VGA mono 64 grey scales STN LCD - backlit 7.24 inch 18 to 1 Yes (external SVGA)		VGA color 256 colors 640 x 45 STN - passive mati LCD - backlit 7.7 inch 14 to 1; Single scal Yes (external SV0	GA)	
Graphics - controller Graphics - vendor Graphics - arch/data patl	All: 65530 / External VGA is ISO capable (75Hz) All: Chips & Tecnologies, Inc. nAll: Local bus / 16 bit / Peripheral Interface		WD90C26 Western Digital ISA 16 bit		WD90C24A2 / 1 MB video mem Western Digital VL-Bus / VESA 32 bit local bus		
Memory - std / max Mem - sockets empty Mem - options available	All: 4 / 20 MB 80 ns All: 1 socket (non-parity) All: 4, 8, 16 MB SIMMs Suspend/resume buttn		4 / 12 MB 80 ns 1 socket (non-parity) 4, 8 MB ICs (3.3 volt)		4 / 20 MB 80 ns 1 socket (non-parity) 4, 8, 16 MB ICs (3.3 volt)		
Keyboard / # of keys Fn key functions Keyboard slope Mouse/pointing Ext keyboard support	All: Full size alp/num/ 85 above keyboard All: 2 (in any appl) Fn+F1=Configuration Utility All: TrackPoint II™ Fn+F2=Reverse video All: Yes (with opt cable) Fn+F3=Contrast text		90% size alp/num/ 81 11 (in any appl) No TrackPoint II No		90% size alp/num/ 81 15 (in any appl) No TrackPoint II Yes (on MultiPort)		
Dimensions Cubic inches Carrying case Color Weight (with battery)	11.7 x 8.3 x 1.9" 184 inches Many options Black 5.2 pounds	11.7 x 8.3 x 2.0" 194 inches Many options Black 5.8 pounds	10.1 x 7.2 x 116 inches Many optio Black 3.4 pounds	-	10.1 x 7.2 x 1.7" 124 inches Many options Black 4.0 pounds	Fn+Q=Inc brightness Fn+A=Dec brightness Fn+W=Inc contrast Fn+S=Dec contrast	
Battery - type Batt - life (per battery) Charge time - on / off	Nickel hydride (NiMH) 2.7 to 9 hours 2 hrs / 1 hr	Nickel hydride (NiMH) 2 to 7.5 hours 2 hrs / 1 hr	Nickel hydr 3.5 to 9 ho 3 hrs / 1.5	urs ` ′	Nickel hydride (NiN 2.5 to 8 hours 2.5 hrs / 1.5 hrs	MH) Enter Setup by CTRL+ALT+F3 from DOS prompt	
Architecture Docking Station Port replicator Modem/serial slot PCMCIA 2.01 slots Visible LEDs - closed Serial / parallel ports	All: AT bus (ISA) All: No All: No All: Modem only All: 1 Type I or 1 Type II All: Yes All: Yes / Yes		No had so No acid be 1 Type I or Yes	rawn 500 ealed lead attery)	AT bus (ISA) No Yes (MultiPort ships standard) No 1 Type I or 1 Type II Yes Yes (MultiPort) / Yes (EPP)		
APM-aware BIOS Other features	All: APM-aware BIOS All: Wallmount AC adapter		APM-aware		APM-aware BIOS Microsaver™ security connector Hibernation mode		
Preinstalled software	All: Personalized nameplate in indentation All: Coupon book with \$4,000 in savings All: IBM DOS 5.02, PRODIGY®				Personalized nameplate in indentation Personal greeting screen at startup IBM DOS 6.3, Windows 3.1, Demo, and 8 appls listed below		
Warranty	All: 1 year - carry in or EasyServ (opt onsite)		1 year - carry in or 1		1 year - carry in or EasyServ (optional onsite for \$40 a year)		

FEATURES OF 500 and 510Cs

500: External cable has 2 connectors for serial port and external diskette drive

510: External cable has 1 connector for external diskette drive (serial port on MultiPort).

MultiPort: A port replicator with connectors for diskette drive, external display, mouse/ keyboard, and serial device (ships with 510Cs). Plugs into 160 pin connector on back.

3 power saving modes: doze, suspend, hibernation.

Batteries in 500 and 510Cs are NOT compatible

Withdrawn from marketing

SOFTWARE PREINSTALLED ON 500-17N (after July 1, 1994) and 510Cs

IBM DOS 6.3, Windows 3.1, Demo, and 8 appls:

① Lotus cc:Mail, ② Lotus Organizer 1.12, 3 Lotus ScreenCam 1.0, 4 Official Airline Guide Flight Disk 1.0, ⑤ Triton CoSession Host, @ PRODIGY, @ America Online,

SofNet FaxWorks 3.0

EasyPlaying (PC Card Director™) is preloaded and on the utility diskette for DOS, Windows and OS/2; it provides status and info on PCMCIA cards installed. In Windows and OS/2, it can register an appl for PCMCIA cards and execute them automatically. Auto Configurator and Memory Device Driver enables supported PCMCIA cards by sensing them automatically (so do not need to install their device drivers).

FEATURES OF ALL PRODUCTS

Suspend/resume mode; battery life indicator Non-disruptive battery exchange Simultaneous LCD and external CRT US EPA Energy Star compliant International travelers warranty IBM or dealer warranty/service 30 day money back guarantee 24 hour / 7 day fax support 24 hour / 7 day bulletin board support 24 hour / 7 day telephone support at 1-800-772-2227

ThinkPad 500 memory (4. 8 MB IC 3.3 volt) is compatible with ThinkPad 510Cs.

ThinkPad 510Cs MultiPort is NOT compatible with ThinkPad 500.