

IBM ThinkPad 730T

IBM® ThinkPad®:	730T pen tablet			
Processor type	80486SX (3.3 volt SL Enhanced)			
Processor speed	33 MHz			
Memory cache	8 KB internal (no L2 cache)			
Coprocessor socket	No			
Diskette drive	Optional 3.5" 1.44 MB (same as ThinkPad 710T)			
Price (retail USD)	\$ 2,569	\$ 2,879	\$ 3,119	\$ 3,429
Type - model	2524-801	2524-901	2524-80F	2524-90F
Hard drive - size	Option (required via PCMCIA disk)	Option (required via PCMCIA disk)	105 MB PCMCIA	105 MB PCMCIA
Hard drive - speed			15 ms	15 ms
Preinstalled software			IBM DOS 6.3 Windows for Pen Computing	IBM DOS 6.3 Windows for Pen Computing
Available date	May 1994	May 1994	May 1994	May 1994
Memory - std / max	4 / 20 MB	8 / 24 MB	4 / 20 MB	8 / 24 MB
Mem - sockets empty	Uses a specific Type III PCMCIA slot; this will then permit a Type I or II PCMCIA card in rest of slot			
Memory - type	70 ns / Non-parity / 5.0 volt			
Memory - options	4, 8, 16 MB ICs (same options as ThinkPad 360)			
Display - type	VGA 640 x 480 monochrome	(External display is 640 x 480 with 16 colors)		
Display - grey scales	16 grey scales	(Simultaneous LCD and CRT display)		
Display - technology	STN Transflective	Transflective: can turn on backlight in dark areas or turn it off in bright areas		
Display - light source	LCD - Backlit			
Display - size (diag)	9.5 inch			
Display - contrast ratio	3 to 1			
Keyboard	External (any IBM keyboard is supported; attach to port replicator)			
Mouse/pointing	Electromagnetic pen/digitizer/stylus that realistically simulates the feel of pen-to-paper / untethered / batteryless (a mouse is not supported) / stylus is stored in a compartment on bottom			
Dimensions	10.6 x 8.3 x 1.4"			
Cubic inches	123 inches			
Carrying case	Blk nylon standard (many options also available)			
Color	Black			
Weight (with battery)	3.5 pounds (1 battery); 3.9 pounds (2 batteries)			
Battery - type	Nickel hydride			
Battery - quantity	Two batteries ship standard / can use one or two batteries			
Batt - life (per battery)	1 battery: 2 to 5 hours 2 battery: 4 to 10 hours			
Charge time - on / off	N/A / 1.5 hours (unit off or suspend only)			
Architecture	Local memory bus / ISA			
Docking Station	No			
Port replicator	Yes (ships standard / attach to 200 pin connector)			
Modem/serial slot	Port Replicator includes ① 15 pin external CRT port, ② 9 pin 16550A serial port, ③ 25 pin EPP parallel port, ④ diskette drive connector, ⑤ keyboard port, ⑥ DC port for AC connector			
PCMCIA 2.01 slots	No (use PCMCIA) 3 Type II or 2 Type III as follows: 1st slot: 2 Type II or 1 Type III (but any additional memory must go into this slot; so adding IC DRAM memory will leave 1 Type II slot remaining) 2nd slot: 2 Type II or 1 Type III (105 MB PCMCIA disk in Models 80F/90F is installed here)			
Serial / parallel ports	Yes (on Port Replicator) / Yes (on Port Replicator)			
Warranty	3 year - ThinkPad EasyServ™ only: customer calls 1-800-772-2227, courier service picks up ThinkPad at any location, IBM repairs and mails back within 4 business days (no shipping charges, most shipping is overnight) Includes International Travelers Warranty			


The ThinkPad 730T requires a bootable operating system with Pen capability. Supported is:

- PenDOS® 2.2 with IBM DOS 6.3
84G9180 - PCMCIA HDD 105 MB PenDOS preloaded
- Pen for OS/2 1.0 with OS/2® 2.11
84G9190 - PCMCIA HDD 105 MB Pen for OS/2 preloaded
- Windows for Pen Computing® 3.1 with IBM DOS 6.3
Models 80F/90F are preloaded with Windows for Pen Computing
- PenRight!® (available at dealers)

Options:	Description	Part number	Cost
	Quick Charger	66G9540	\$155
	Car Adapter	66G9545	175
	NiMH Battery (dual)	66G9550	189
	AC Adapter	84G0480	135
	PortReplicator	84G0485	139
	External 3.5" 1.44 MB diskette drive	48G8263	275
	105 MB HDD (PenDOS)	84G9180	549
	105 MB HDD (PenOS2)	84G9190	549
	Hand Strap	84G0495	25
	Soft Case	84G0490	99
	Battery Carrier	84G0500	19

PCMCIA SLOT CONFIGURATION

Two Type III (10 mm high):



PCMCIA Type III
105 MB disk in this slot
(Models 80F and 90F)

FEATURES OF THINKPAD 730T

- Suspend/resume mode
- Battery life indicator
- Non-disruptive battery exchange
- US EPA Energy Star compliant
- IBM or dealer warranty/service**
- 30 day money back guarantee**
- 24 hour / 7 day fax support**
- 24 hour / 7 day bulletin board support**
- 24 hour / 7 day telephone support at 1-800-772-2227**