

# Processor Performance

	PROCESSOR SPEED RANKED FROM LOW TO HIGH							
	Processor	MHz	BAPCo	Norton	Norton	iCOMP	SPEC SPEC	
			SI 6.0	SI 7.0		int92	fp92	
The following comparisons are processor intensive comparisons; application throughput (which utilizes all subsystems) will have less of a difference.								
The <b>80386 SLC</b> at <b>25 MHz</b> is (325T): ☞ Equivalent to a 33 MHz 386 DX	386SX	20	-	11.2	-	32	3.5	-
The <b>80486 SLC2</b> at <b>40/20 MHz</b> is (Upgrade for 56/57 SX & 56/57 SLC): ☞ Up to 3.71 times faster than a 20 MHz 386 SX with no memory cache ☞ Up to 99% faster than a 20 MHz 386 SLC (Model 56 SLC & 57 SLC) ☞ Equivalent to a 25 MHz 486 SX	386SX 386SL 386DX 386SLC 386DX	25 25 25 20 33	- - - - -	12.3 12.3 27.0 29.4 36.0	- - - - -	39 41 49 - 68	4.5 4.3 6.5 6.2 8.4	- - - - -
The <b>80486 SLC2</b> at <b>50/25 MHz</b> is (9556/9557 SLC2): ☞ Equivalent to a 33 MHz 486 SX	386SLC 486SLC 486SX	25 25 25	- - -	36.9 37.1 54.1	- - -	- - 100	- - 14.2	- - -
The <b>80486 SLC3</b> at <b>60/20 MHz</b> is: ☞ Up to 4.24 times faster than a 20 MHz 386 SX with no memory cache ☞ Up to 187% faster than a 20 MHz 386 SLC	486SL 486DX 486SLC2	25 25 40/20	- - -	54.1 54.1 57.3	- - -	- 122 -	- 14.2 -	- - -
The <b>80486 SLC3</b> at <b>75/25 MHz</b> is: ☞ Up to 32% faster than a 486 SX at 33 MHz ☞ Up to 40% faster than a 486 SLC2 at 50/25 MHz ☞ Up to 113% faster than a 486 SX at 25 MHz	486SX 486SL 486DX 486SX2 486DX2 486SLC2	33 33 33 50/25 40/20 50/25	- - 142.3 - - -	71.9 71.9 71.9 - - 74.1	- - 71.8 - - -	136 166 166 180 182 -	18.5 - 18.5 - 20.4 -	- - - - - -
The <b>80486 DX2</b> at <b>50/25 MHz</b> is: ☞ Up to 70% faster than a 486 SX/DX at 25 MHz ☞ Up to 20% faster than a 486 DX at 33 MHz	Blue Lightning 486DX2 486DX	50/25 50/25 50	160.4 179.1 -	- 93.1 108.1	74.4 108.3 -	- 231 249	- 25.7 27.9	- - 13
The <b>80486 DX2</b> at <b>66/33 MHz</b> is: ☞ Up to 70% faster than a 486 SX/DX at 33 MHz ☞ Up to 20% faster than a 486 DX at 50 MHz	Blue Lightning 486DX2 DX4	66/33 75/25 66/33 75/25	204.2 208.5 223.5 -	- - 122.1 -	98.7 111.7 143.6 -	- - 297 319	- - 32.4 -	- - 18.6 -
The <b>Blue Lightning™</b> at <b>50/25 MHz</b> is: ☞ 7% faster than a 486 DX2 at 50/25 (integer performance) ☞ 2% faster than a 486 DX2 at 50/25 (92% integer, 8% floating pt)	PowerPC 601 DX4 Blue Lightning	601 100/33 100/33	66 245.5 259.2	- - 148.1	- - -	- 435 -	60 51.4 -	70 26 -
The <b>Blue Lightning</b> at <b>66/33 MHz</b> is: ☞ 5% slower than a 486 DX2 at 66/33 (integer performance) ☞ 9% slower than a 486 DX2 at 66/33 (92% integer, 8% floating pt)	PowerPC 603 Pentium Pentium	66 60 66	66 - -	- 210.0 -	- - -	- 510 567	62 62.9 70.0	72 53 58.6
The <b>Blue Lightning</b> at <b>75/25 MHz</b> is: ☞ 33% faster than a 486 DX2 at 66/33 (integer performance) ☞ 26% faster than a 486 DX2 at 66/33 (92% integer, 8% floating pt)	PowerPC 603 PowerPC 601 Pentium Pentium	80 80 90/60 100/66	80 80 -	- - -	- - -	- - 735 815	75 77 90.1 100.0	85 93 72.7 80.6
The <b>IntelDX4™</b> at <b>75/25 MHz</b> is: ☞ 50% faster than a 486 DX2 at 50/25 MHz	PowerPC 601	100	-	-	-	-	105	125
The <b>IntelDX4</b> at <b>100 MHz</b> is: ☞ 50% faster than a 486 DX2 at 66/33 MHz ☞ 200% faster (3 x faster) than a 486 SX at 33 MHz								
The <b>Pentium™</b> at <b>60 MHz</b> is: ☞ Up to twice as fast as a 486 DX2 at 66/33 MHz ☞ Floating point performance is up to five times faster than a 486 DX's math cop.								
The <b>Pentium</b> at <b>90/60 MHz</b> is: ☞ 50% faster than a Pentium at 60 MHz ☞ Slightly faster than the PowerPC 601 at 80 MHz for integer performance ☞ Slower than the PowerPC 601 at 80 MHz for floating point performance								
The <b>PowerPC 601™</b> at <b>66 MHz</b> is: ☞ Falls between a 486 DX2 at 66/33 MHz and Pentium at 66 MHz processor for integer performance (SPECint92 for Pentium: 70; SPECint92 for PowerPC 601: 62) ☞ Faster than a Pentium processor for floating point performance (SPECfp92 for Pentium: 56.9; SPECfp92 for PowerPC 601: 72)								

BAPCo uses commonly available software applications.  
Norton Utilities® System Information version 6.0 is CPU intensive without requiring math coprocessor.  
Intel's iCOMP™ is made up of 16 bit integer (67%), 16 bit floating point (3%), 32-bit integer (25%), and 32 bit floating point (5%).  
SPECint92 is a 32 bit industry standard CPU benchmark. Measurements made with L2 cache.

All trademarks are the property of their respective owners (listed on Trademark sheet)

No warranties are expressed or implied in this summary (PERF) Compiled by Roger Dodson, IBM. April 1994