

## MultiPro 386SX Specifications:

- Model 1: 5.25" CD-ROM with Disk Caddy, 380ms avg. access time  
Model # M3S25-1204-11/10
- Model 2: 5.25" CD-ROM, caddyless, 350ms avg. access time  
Model # M3S25-1204-11/00
- Compatibility: Fully **MPC** compatible and **MPC** Licensed
- CPU: 80386SX-25MHz CPU
- Hard drive: 120 MB Hard Disk, 19ms Avg. Access
- Floppy drive: 3.5" 1.44MB/720K
- Slots: 3 open 16-bit AT (ISA) slots
- RAM: 4MB RAM expandable to 20MB
- Video: Built-in Super VGA with 512K RAM (max.)  
1024x768x16 colors, non-interlaced, 60Hz  
1024x768x16 colors, interlaced, 44Hz  
800x600x256 colors, non-interlaced, 56 or 60 Hz  
800x600x16 colors, non-interlaced, 56, 60, or 72Hz  
640x480x256 colors, non-interlaced, 60 or 72Hz  
132 Column Text, 70Hz one font, 60Hz two fonts  
Accelerated performance in Windows (256 color modes)  
Cirrus Logic GD5402 chip set
- Sound Card: Media Vision Pro Audio Spectrum 16  
Sound Blaster and AdLib compatible  
True 16-bit Sampling and Playback (PCM 4kHz in stereo)  
Advanced 20 Voice Stereo Synthesizer (Yamaha OPL-3)  
General MIDI compatible  
Frequency response 30Hz-20kHz (+-3dB)  
4 Watt/Channel Stereo Amplifier
- Power Supply: 85 watt international autoswitching (50-60Hz)
- Keyboard: 101 key keyboard, AT type, 12 function keys
- I/O ports: 1 Serial port  
1 PS/2 mouse port  
1 Parallel port  
1 Analog VGA port  
1 AT keyboard port  
1 MIDI/Joystick port  
1 Stereo line OUT port  
1 Stereo and Microphone IN port
- BIOS: AMI System BIOS
- Core Logic: Headland Technology
- Software: **Lotus 1-2-3 for Windows with Multimedia Smart Help**, installed  
**MS-DOS**, installed  
**MS-Windows**, installed  
System utilities, installed

VGA software drivers for:

MS-Windows, AutoCad 9/10/11, AutoShade 2.0 & 3D Studio,  
WordStar 3.3, WordStar Professional 4.0, Word Perfect  
4.2/5.0/5.1, Ventura Publisher 2.0 or GEM 3.0, MS-  
Word 5.0,  
and Frame  
Colorix, VPIC,  
Pro.

Speakers: Pair of **MLi** Multimedia Speakers

**Built-in Amplifier:**

Magnetically shielded  
AC powered  
Rated output power per channel 5.0 (4 ohms, 1kHz@ 0.5% THD)  
Music power per channel 9.0 W (4 ohms, 1kHz @ 10% THD)  
Total Harmonics distortion <0.1% (4 ohms, 1kHz)  
Frequency response 20-20kHz, -2dB  
Input sensitivity 200mV - 1.22V  
Input Impedance 2k ohms  
Tone Controls: Bass, Treble, & Volume  
100Hz-10kHz, + or - 10 dB

**Speakers:**

Drive unit 3" (7.5 cm) cone type  
Max output 10W  
Frequency response 90Hz-15Hz

**Headphones and microphone**

Form factor: Low profile "Baby" case  
14"(w) x 16.25"(d) x 4.75"(h)

Warranty: 1 year parts and labor  
1 year on-site service

Certification: FCC Class B

Origin: Assembled in USA

The multimedia PC logo is a trademark of the Multimedia PC Marketing Council, Inc. Lotus 1-2 and Lotus 1-2-3 for Windows with Multimedia Smart Help are trademarks of Lotus Development Corporation. MultiPro is a trademark of Technology integrated Products, Inc. MLI is a trademark of Midi Lane, Inc. Pro Audio Spectrum 16 is a trademark of Media Vision, Inc. All other product names are trademarks of their respective companies.