SCSI: DB-25

Serial Ports: 2 LocalTalk/GeoPort, 2 USB ports (Universal Serial Bus),

<u> 2 RS-232 ports</u>

Sound Output: 16-bit stereo

Ethernet: Add-in card

Machine Gestalt ID: ???

PRAM Battery: 4.5V alkaline (Rayovac 840)

Minutiae:

<u>Available only in Europe.</u>

This is the PIOs entry into the Amiga market. It is supplied with pOS from proDAD, which spans the bridge to the Amiga world.

<u>transAM can take only 3.3 volt EDO DIMMs. It does not support</u> <u>interleaved memory.</u>

Modular concept places system RAM, cache, CPU and control circuitry on CPU module. Motherboard contains all 1/0.

In addition to the Macintosh style ports, this machine also has 2 PC-style game ports, a Centronics compatible parallel printer port, a proprietary sound slot, MIDI in and out, and provision for an IR remote control.

Supports both SCSI and EIDE drives.

Ships with PC-standard serial mouse and keyboard.

Manufactured by:

PIOS Computer AG

Borsigstr. 5

D-31135 Hildesheim

Germany

Tel. +49 - 5121 - 7533-0

Fax +49 - 5121 - 7533-75

website: http://www.pios.de/

email: info@pios.de