

PhxLnk ii

COLLABORATORS					
	TITLE :				
ACTION	NAME	DATE	SIGNATURE		
WRITTEN BY		July 1, 2022			

	REVISION HISTORY				
E DESCRIPTION	NAME				
	E DESCRIPTION				

PhxLnk

Contents


l	PhxLnk				
	1.1	PhxLnk V4.20 (24-Dec-95)			
	1.2	Introduction			
	1.3	History since V3.00			
	1.4	Instructions			
	1.5	Sytem Requirements			
	1.6	Starting PhxLnk			
	1.7	Description of command line parameters			
	1.8	Linker Symbols			
	1.9	Small Data			
	1.10	Known Bugs			
	1.11	My Address			

PhxLnk 1/8

Chapter 1

PhxLnk

1.1 PhxLnk V4.20 (24-Dec-95)



P h x L n k V4.20

AMIGA-DOS Module Linker

Contents

Introduction

History since V3

Instructions

Bugs

Author's Address

1.2 Introduction

PhxLnk was written in pure assembler-code, assembled with PhxAss and linked with BLink (first version) and PhxLnk itself. It supports all features of a standard Amiga-DOS linker (like BLink), except of overlay hunks and automatic link vectors (ALV).

PhxLnk is FREEWARE and copyright © 1992,93,94,95 by Frank Wille and Volker Barthelmann.

Commercial usage of this program is strictly forbidden!

PhxLnk 2/8

1.3 History since V3.00

```
V4.20 (20-Dec-95)
                                        Since v4.20 there are two versions of \leftarrow
                   PhxLnk.
                        One for OS2.x and the other for OS3.x. This
                        splitting is a result of the intensive usage
                        of MemPool functions, which are part of the
                        exec.library under OS3.x (the OS2.x version
                        gets their MemPool functions from amiga.lib).
                        The MemPool adaption was done by Volker Bar-
                        thelmann <volker@vb.franken.de>. It enables
                        library-linking with a multiple speed.
                        There were some crashes, when empty sections,
                        which contained some required XDEFs, were
                        automatically removed. The only possibility
                        to prevent it was by setting the PRESERVE/S
                        switch.
V4.17 (24-May-95)
                        Partial support for the SLink (SAS/C). PhxLnk
                        defines \_\_ctors and \_\_dtors as NULL to avoid
                        errors during linking. Complete SLink-support
                        may follow in a later release. (if somebody needs
                        it :-)
                        Fixing the bug with \_MERGED sections in V4.10
V4.16 (18-May-95)
                        generated a new one in the 'normal' small data
                        mode.
                        The shortening of sections, as introduced in
                        V4.00, doesn't work very well.
V4.15 (19-Mar-95)
                        PhxLnk can generate RELOC32SHORT blocks.
V4.10 (21-Feb-95)
                        Linking of __MERGED sections had a bug.
                        When PhxLnk discovers a read error, while reading
V4.03 (09-Feb-95)
                        a '@'-file, it crashed.
V4.02 (25-Jan-95)
                        PhxLnk can read the object and library names from
                        one or several files.
V4.00 (18-Nov-94)
                        PhxLnk V4.00 requires OS2.04 as a minimum. As a
                        result it offers the standard ReadArgs()-Command
                        Line parsing and is much shorter.
                        DEBUG Hunk blocks are treated the same way as with
                        SAS/C's BLink, which gives the possibility to gene-
                        rate load files for a Source Level Debugger.
                        The latest version of the PowerVisor Debugger,
                        V1.42, unfortunately has still some problems with
                        BLinked programs, consisting of several source
                        files, so there is a compatibility switch, called
                PVCOMPAT
                        The new argument DEFINE (see
                CLI Parameters
```

PhxLnk 3/8

gives the possibility to define an absolute Linker-Symbol (quite similar to the small data symbols supplied by PhxLnk).

By utilitzing the new switch

BLINKCOMPAT

PhxLnk

will treat small data modules the same way like SAS/C's BLink does.

Data and Bss sections, which were named "__MERGED", will be coalesced into a small data section (without having to specify the SMALLDATA switch). Zero bytes at the end of a Code or Data section will be ignored, which shortens the resulting load file. Because that doesn't work under Kickstart 1.x, there is a compatibility switch called

KICK1

.

V3.10 (04-Aug-94)

Fixed a bug with catastrophic proportions, which sometimes appeared when linking with libraries. To be honest: I don't think, that one of the pre-V3.10 versions are safe enough to link libraries; -) PhxLnk was completely localized. Until now, german and polish catalogs are available. Documentation was converted into Amiga-Guide format.

V3.05 (31-Jul-94)

Fixed a linker-library bug: Sometimes sections of a library, though not included, appeared in HUNK_HEADER with random length.
HUNK_RELOC and HUNK_SYMBOL of zero length will no longer be included.

V3.01 (22-Jan-94)

Because of massive changes in V3.00, there was a little bug with the name of the output file.

V3.00 (18-Jan-94)

Fixed many problems with library linking, which could lead to a FreeMemoryTwice Guru (or even worse).

Some linker symbols of Lattice/SAS (_LinkerDB, __BSSBAS, __BSSLEN) and DICE (__RESIDENT, __DATA_BAS, __DATA_LEN, __BSS_LEN) are supported.

The special library format of Lattice/SAS, using HUNK_LIB and HUNK_INDEX, is also supported. PhxLnk converts them into standard library format.

1.4 Instructions

Requirements

Starting PhxLnk

Parameters

Linker Symbols

PhxLnk 4/8

Small Data

1.5 Sytem Requirements

Since PhxLnk V4.00 you *must* have OS2.04 (V37) as a minimum. This makes PhxLnk much shorter, faster and easier for me to code. I don't think that this limitation (which is a progress in my eyes) doesn't hurt anybody nowadays, if you use your Amiga for more than just playing :-) (even my good old A1000 has OS3.1 installed).

PhxLnk is tested with the following configurations: A4000(68040), 2 Chip, 16 Fast, OS3.1 A1000(68010), 0.5 Chip, 2 Fast, OS3.1

1.6 Starting PhxLnk

Normally, PhxLnk is started from your shell. You should copy $\ \leftarrow$ PhxLnk

from the OS2.x directory, if you have OS2.x installed, or from the OS3.x directory otherwise, and copy it to C: or define a path or link. The OS2.x version will run on OS3.x Amigas too, but it's a bit larger.

Format: PhxLnk [FROM] {<object module|library module>}

[TO <output file>] [SMALLCODE] [SMALLDATA] [NODEBUG] [CHIP] [PRESERVE] [PVCOMPAT] [BLINKCOMPAT] [KICK1] [MAXSECTS=<n>]

[DEFINE "<symbol>[=value][,<symbol>...]"]

Template: FROM/M, TO/K, SC=SMALLCODE/S, SD=SMALLDATA/S, ND=NODEBUG/S, CHIP/S,

PRESERVE/S, PV=PVCOMPAT/S, B=BLINKCOMPAT/S, K1=KICK1/S,

MAXSECTS/K/N, DEF=DEFINE/K

Starting PhxLnk with no argument or with a single $^\prime\,?^\prime$ will display a short description. For a more precise description, refer to

Parameters

There are three types of modules which can be linked:

- o Object modules with extension ".o" or ".obj" which normally consist of one unit. PhxLnk also links object modules with several units.
- o Library modules with extension ".lib" which can consist of any number of units. PhxLnk will only include units, if at least one ext_def-symbol is referenced in an object module unit or in an already included library unit.
- o Lattice/SAS Extended Library modules (also with ".lib" extension). They are translated into the standard library format by PhxLnk (not a very good solution but it works).

Names with another extension will be rejected.

The module names can appear in any order, provided the first is an object module which contains the startup code.

PhxLnk 5/8

IMPORTANT!

Load files created by PhxLnk are NOT Kickstart 1.x compatible by default! PhxLnk deletes zero bytes at the end of a section and tries to use the much shorter RELOC32SHORT blocks, unless you set the KICK1 switch

1.7 Description of command line parameters

FROM/M All parameters without a keyword specify the names \leftarrow of the

object and library modules to link. For valid name extensions refer to Starting PhxLnk

Names which start with an '@' specify the name of an ascii file, which contains object and library names (or even more '@'s, if you like). These names can be separated by blanks, tabs, linefeeds or whatever you want. ""' are supported.

TO/K

Determines the name of the output file to be produced. If not specified, the output file has the name of the first module without its extension. Example: "PhxLnk prog1.o prog2.o c.lib m.lib" will generate a load file with the name "prog1".

CHIP/S

This switch forces all sections to be loaded to Chip memory.

PRESERVE/S

The normal case is, that PhxLnk removes all section with zero length to save memory. Choose this switch, if you want to preserve empty sections.

B=BLINKCOMPAT/S PhxLnk will be compatible to BLink, when linking small data modules. That means, that if the small data section is smaller than 32k, PhxLnk will use a small data pointer (_LinkerDB) which points to the beginning of this section instead 32766 bytes into it. As a result all near-offsets will start with 0 instead -32766.

K1=KICK1/S

PhxLnk creates a load file which is compatible to Kickstart 1.x. That will prevent PhxLnk from deleting zerobytes at the end of a section or trying to generate these nice RELOC32SHORT blocks.

SC=SMALLCODE/S Normally only the sections with the same type and name will be coalesced. This switch makes PhxLnk to ignore the names of Code sections and to produce one large Code sections. Usually SMALLCODE is chosen, when using the small code model with your assembler or compiler.

SD=SMALLDATA/S As with SMALLCODE the section names are ignored, but now for all Data and Bss sections. Important: Data and Bss will not be mixed. This large section will contain first all Data and then all Bss sections.

PhxLnk 6/8

Because the Bss part has no definite contents (only zeros), only the Data part will be stored. The size of Bss is stored together with the Data size in the load file's header. Since OS2.0 the Bss part will be initialized to zero, when it's loaded (e.g. by LoadSegment()). But beware (!!), this is not the case with Kickstart 1.x! If you don't want to see your programs crash on some Kick 1.3 dinosaurs, I recommend to clear the Bss part manually by using the special Linker-symbols _DATA_BAS_, _DATA_LEN_ and _BSS_LEN_ (refer to Linker Symbols for more information). All references to symbols of this Small Data section will

be calculated as if the Bss sections were directly behind the ${\tt Data.}$

You should use this switch, when compiling/assembling your code with Small Data

model enabled.

ND=NODEBUG/S The HUNK_SYMBOL and HUNK_DEBUG blocks, which contain infor-

mations for a debugger will not be included in the output

file.

PV=PVCOMPAT/S This switch activates the PowerVisor compatibility mode,

which is necassary when using Source Level Debugging informations in your program. Unfortunately the author of PowerVisor, Jorrit Tyberghein, currently does not plan a

new release.

MAXSECTS/K/N Determines the maximum number of sections per unit. The

default value ist 16, which should be enough for most cases.

DEF=DEFINE/K Defines an absolute Linker Symbol. Definition of multiple

symbols must be seperated by commas. Don't forget the to embed the whole term, which follows DEFINE, in quotes

(because of some problems with ReadArgs()) !

1.8 Linker Symbols

The linker itself creates some ext_def(\$01xxxxxx) and ext_abs(← \$02xxxxxx)

symbols which will be needed by the startup code of a program using the Small Data model.

_DATA_BAS_ (ext_def) Base address of the small-data section.
_DATA_LEN_ (ext_abs) Length of the Data-part of the small-data section.
_BSS_LEN_ (ext_abs) Length of the Bss-part of the small-data section.

For compatibility with Lattice/SAS or DICE you may also use these symbols:

PhxLnk 7/8

```
Lattice/SAS:
LinkerDB
            (ext_def) This symbol can be used to initialize your small
            data base register. Normally it will point 32766 bytes into the
            small data section, but when the
                BLink compatibility switch
                            was selected and the small data area is smaller than \,\,\,\,\,\,\,\,\,
                                32k,
            it will point to its beginning.
            (ext_def) Base address of the Bss-part of the small-data
BSSBAS
            section.
            (ext_abs) Length of the Bss-part in longwords.
__BSSLEN
___ctors and ___dtors are always zero.
DICE:
___DATA_BAS
           (ext_def) Base address of the small-data section.
__DATA_LEN
            (ext_abs) Length of the Data-part of the small-data section in
            longwords.
__BSS_LEN
            (ext_abs) Length of the Bss-part of the small-data section in
            longwords.
RESIDENT
           (ext_abs) Always zero.
```

1.9 Small Data

```
Small-data symbols can be accessed in a range of 65534 ($fffe) ← bytes. When
a symbol is outside of this range, the linker will display an error.
The small data model must be initialized by the startup code. When you're using A4 as small data pointer, the initialization would look like this:

xref _DATA_BAS__ ;
_DATA_BAS__ is a linker symbol

lea _DATA_BAS_+32766,a4 ; a4 always points to the mid. of small data
```

1.10 Known Bugs

```
o If the output file has more than 1000 sections there could be a stack overflow :-)

If any bugs or questions occur, please write to :

My Address
```

1.11 My Address

PhxLnk 8/8

Standard Mail:

Frank Wille

Auf dem Dreische 45

32049 Herford

GERMANY

Electronic Mail:

frank@phoenix.owl.de



 $\XX/$ A M I G A F O R E V E R !