data²

Data Sheet · Handheld · Issue March 2004

Pocket LOOX 610 The mobile office in your hand



People who spend time out and about will appreciate this pocket office. The Pocket LOOX 610 is the ideal platform for mobility solutions.

Manage contacts, send and receive e-mails, and access your office data whilst on the move. The integrated Windows Mobile Software 2003 for Pocket PC offers you a wide range of office applications on your Pocket LOOX.

Pocket LOOX 610 is designed as an open platform. Thanks to its flexible connectivity, mobile applications, like accessing data on a SAP server, secure VPN solutions or thin client based mobility solutions can be easily implemented. Fujitsu Siemens Computers can offer support in finding the right mobile solution for you and your business.

Mobility

- Wireless data transmission wherever you are via BluetoothTM or optional WLAN
- Two Pocket LOOX 610 versions with integrated connectivity to perfectly meet customer requirements
- High expandability due to integrated SD/MM card slot and CF card slot for even more mobile functions
- Choose the type of connection that suits you best: Fast Infrared, Bluetooth*, WLAN (optional) or GPRS (additional accessory)
- Broad range of accessories like GPS navigation kit, WLAN, GSM/GPRS, CF/SD memory cards or batteries
- Optional EASY2CONNECT connection manager for convenient access
- Stylish, high-end design for every profile in and out of the office

Reliability

- Mechanical and functional stability through extensive quality tests
- Global warranty, service and spare part supply to suit your needs
- Exchangeable batteries for flexible and long operation times
- Connectivity via Bluetooth and / or WLAN combined with high performance for reliable mobile business applications

Security

- Easy and secure access and data protection for your business intelligence
- Automatic password protection when powered off (depending on operating system settings)
- Flashable ROM (LOOXstore) to save your data in case of hard reset
- F-Secure FileCrypto for Pocket PC Personal Edition
- Optional VPN solutions for secure data transaction

Ergonomics

- Enjoy the viewing quality of the brilliant transflective color TFT TouchScreen display for indoor and outdoor use
- Advanced one hand use with Fujitsu Siemens Computers SpeedMenu
- Fast access to your favorite applications through programmable buttons
- Optional foldable keyboard for easy data entry

* ActiveSync and certain profiles are dependent on third party Bluetooth hardware capabilities. Please check profile availability on remote device to ensure compatibility. Fujitsu Siemens Computers Bluetooth dongle is recommended for maximum device compatibility (order code: S26391-F2461-L200).

FUJITSU COMPUTERS

Data Shee

www.fujitsu-siemens.com

System architecture		Dimensions / weight		
Two versions available		Dimensions (H x W x D)	147.5 x 78 x 18.2 mm	
Pocket LOOX 610 BT	with integrated Bluetooth	Weight	197 g Pocket LOOX 610 BT	
POCKELLOOX 610 B1/WLAN	with integrated Bluetooth and Wireless LAN		205 g Pocket LOOX 610 BT/WLAN	
Applications processor Intel® PXA255 400 MHz		Import and usage of wireless technologies		
	based on Intel® XScale™	According to country specific regulations		
	microarchitecture	Operating system	<u>_</u>	
Flash memory (ROM)	64 MB	Microsoft Windows Mobile [™] Software 2003 for Pocket PC		
	Remaining flash memory usable as file store	Applications		
	(LOOXstore)	Fujitsu Siemens Computer		
System memory (RAM)		CONNECT2AIR Bluetooth and Wireless application Manager		
Pocket LOOX 610 BT	64 MB	Fujitsu Siemens Computers Panning for easy navigation		
Pocket LOOX 610 BT/WLAN		across documents with your stylus Pocket Outlook, Pocket Word, Pocket Excel, Calculator 		
Interfaces		MSN® Messenger	oru, Focket Excel, Calculator	
1 x built-in microphone		Pocket Internet Explorer		
1 x speaker		Microsoft Reader 2.0 for P	ocket PC	
1 x headphone (3,5mm)		Windows Media® Player 9		
1 x Fast IrDA (up to 4 Mbit/s)		Pictures		
USB 1.1 via sync cable		Terminal Services Client		
Serial (RS232) via sync cable		Jawbreaker™		
1 x power jack		Voice recorder		
Display 3.5-inch, 240 x 320 color transflective TFT TouchScreen,		Microsoft Active Sync 3.7		
65.536 colors, LED backlight		SyncSoftware support		
Active area: 53.6(H) x 71.5(V), 0.22 mm pixel pitch		(Microsoft Outlook 98, 2000, 2002, XP, 2003)		
Expansion slots		Additional software		
SD/MM card		F-Secure File Crypto Personal Edition		
Compact Flash type I and II s	slot	Derdack Mobile Client Nyditot Virtual Display		
Bluetooth module		Space2Go		
Power class 2		Westtek ClearVue		
Profiles*	BNEP, DUN-DT, FT-Client,	bSQUARE Java Virtual Machine		
	GAP, File Transfer, Object	Fujitsu Siemens Computers EASY2CONNECT (eval. Version)		
	Push, OPP Client, Point to	Certicom movian VPN (test version)		
	Multipoint (PAN), FT-Server,	Standard delivery packa	ge	
	LAN-DT, Point to Point (LAP),	Handheld device		
	OPP Server, PAN-User, SDAP, SDP, SerialDevA, SerialDevB	USB docking station		
Wireless LAN module	SDF, SellaiDevA, SellaiDevB	Protection bag with belt cli	p	
(Pocket LOOX 610 BT/WLAN only)		USB sync cable AC adapter with cable (country specific EU/UK)		
Vendor	ASUS (Intersil chipset)	Companion CD	unity specific E0/0K)	
Туре	WL-155	Pocket LOOX AddOn & Doc (CD)		
Spec	IEEE802.11b (Wi-Fi)	Getting started (printed manual)		
Battery	, <i>, , , , , , , , , , , , , , , , </i>	Safety instructions and warranty booklet		
Exchangeable battery		Easy Guide on CD	· · · · · ·	
Lithium-Ion, rechargeable;		Options / accessories		
Main battery	capacity 1500 mAh	CONNECT2AIR WLAN CH	⁼ card	
Main battery XL	capacity 3000 mAh	CONNECT2AIR GPRS CF card		
(available as accessory for P		SD/MM Cards		
Buffer battery, time for batter	y exchange: 30 min	Main battery; Main battery	XL	
Power supply		GPS navigation kit		
Rated voltage	100 to 240 AC (50 to 60 Hz)	Foldable keyboard		
Power cord	to 5 V DC 2,4 Amp (switched) with EU cable, UK cable	Leather cases		
Power cord	additionally available, standard	USB docking station	<i>x</i>	
	in UK versions	Stylus / CF slot cover pack AC adapter, car adapter	X .	
Operating time		USB sync cable		
Standby	up to 300 h with main battery	Additional accessories like serial sync cable and much more		
Working	up to 12 h (depending on	will be available on project		
~	usage) with main battery	. · ·		

*ActiveSync and certain profiles are dependant on third party Bluetooth hardware capabilities. Please check profile availability on remote device to ensure compatibility. Fujitsu Siemens Computers Bluetooth dongle is recommended for maximum device compatibility (order code: S26391-F2461-L200).

Published by	All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved.	Company stamp
Fujitsu Siemens Computers http://www.fujitsu-siemens.com/	Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.	
	Copyright © Fujitsu Siemens Computers, 03/2004	