

C:\CONFIG.GAM

```
DEVICE=C:\dos\HIMEM.SYS
rem DEVICE=C:\dos\EMM386.EXE ram 6144
DEVICE=C:\DOS\EMM386.EXE NOEMS
DEVICEhigh=C:\SB16\DRV\SLCD.SYS /B:230 /D:MSCD001 /M:P /V /C
FILES=20
DOS=HIGH,UMB
LASTDRIVE=d
buffers=20
REM shell = c:\command.com c:\ /p /e:800
STACKS=9,256
```

C:\REELMAGC\CONFIG.OLD

```
DEVICE=C:\SB16\DRV\SLCD.SYS /B:230 /D:MSCD001 /M:P /V /C
DEVICE=C:\SB16\DRV\CTSB16.SYS /UNIT=0 /BLASTER=A:220 I:7 D:1 H:7
DEVICE=C:\SB16\DRV\CTMMSYS.SYS
FILES=40
DEVICE=C:\WINDOWS\HIMEM.SYS
DEVICE=C:\WINDOWS\EMM386.EXE RAM 3072
DOS=HIGH,UMB
LASTDRIVE=d
REM ** FILES=30
buffers=20
shell = c:\command.com c:\ /p /e:800
STACKS=9,256
rem DEVICEHIGH=C:\SCSI\ASPI2DOS.SYS /D /P140
rem DEVICE=C:\SCSI\ASPICD.SYS /D:ASPICD0
```

C:\CONFIG.SYS

```
REM ReelMagic Setup 1-03-1995
DEVICE=C:\REELMAGC\RMDEV.SYS
DEVICE=C:\SB16\DRV\SLCD.SYS /B:230 /D:MSCD001 /M:P /V /C
DEVICE=C:\SB16\DRV\CTSB16.SYS /UNIT=0 /BLASTER=A:220 I:7 D:1 H:7
DEVICE=C:\SB16\DRV\CTMMSYS.SYS
FILES=40
DEVICE=C:\WINDOWS\HIMEM.SYS
DEVICE=C:\WINDOWS\EMM386.EXE RAM 3072
DOS=HIGH,UMB
LASTDRIVE=d
REM ** FILES=30
buffers=20
shell = c:\command.com c:\ /p /e:800
STACKS=9,256
rem DEVICEHIGH=C:\SCSI\ASPI2DOS.SYS /D /P140
rem DEVICE=C:\SCSI\ASPICD.SYS /D:ASPICD0
```