

SMTPsend V1.0

COLLABORATORS

	<i>TITLE :</i> SMTPsend V1.0		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		October 9, 2022	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	SMTPsend V1.0	1
1.1	SMTPsend V1.0 Guide V1 ©SJR 1998	1
1.2	Introduction to SMTPsend	1
1.3	Installing SMTPsend	2
1.4	Using SMTPsend	2
1.5	Whats new?	3
1.6	Whats comming in the next version?	3
1.7	Know Bugs	3

Chapter 1

SMTPsend V1.0

1.1 SMTPsend V1.0 Guide V1 ©SJR 1998

Contents

Introduction

Installing SMTPsend

How to use it

Whats New

Future

Bugs

1.2 Introduction to SMTPsend

Welcome to SMTPsend V1.0

What is SMTPsend?

Basically it allows you to use SMTPsend as an offline-email poster.

It examines a given directory, find all emails that have been queued to there by SMTPsend and attempts to post them, using SMTPsend. It does this the instant its run.

In a way its a replacement for SMTPd, although it doesn't wait around in memory and check the directory again later on as SMTPsend does.

Why did I write it?

When I started using SMTPsend as an external mailer, I wanted to write email off-line and post it when I went on-line. I tried using SMTPd but

found that this waits for a while before trying to send the queued email, which I didn't want. My program sends the email instantly and then quits.

Is it free?

Yes. It is copywrite so you can't alter it in any way. It must be distributed in the archive SMTPsend.lha which must contain...

SMTPsend	The executable
SMTPsend.guide	What your reading now
Changes.txt	Whats new in this version
Warning.txt	Warning to previous users of SMTPsend

1.3 Installing SMTPsend

How do I install it?

Its really easy. Simply put the program file (thats SMTPsend) anywhere you want. SMTPpost must also be in the same directory, otherwise it won't work!

Most people are already using SMTPpost so they just put SMTPsend in the same directory.

Thats all there is to it.

1.4 Using SMTPsend

Using SMTPsend

```
SMTPsend [-l] <maildir> [-m <movedir>]
```

-l Switches on the logging. A default logfile SMTPsend.log will be opened in the directory the program is run. You cannot specify the name of the logfile.

<maildir> The directory where the emails are stored.

-m causes emails to be moved to <movedir> instead of being deleted after being sent.

Examples

```
SMTPsend Work:Mailspool/
```

- Will send all email in Work:Mailspool and delete them when their sent.

```
SMTPsend -l Work:Mailspool/
```

- Same as above but will write results to SMTPsend.log

```
SMTPsend -l Work:Mailspool/ -m Work:Sentmail/
```

```
- Send all emails in Work:Mailsool/ and move sent ones to Work:Sentmail/  
Also write to the logfile SMTPsend.log
```

1.5 Whats new?

This is the first release so theres nothing new yet. Any suggestions for improvements should be emailed to:

```
moonchild@enterprise.net
```

See changes.txt which comes with the archive for further details.

1.6 Whats comming in the next version?

In Version 1.1

```
- You will be able to specify the name of the logfile
```

Any other suggestions are welcome. Just email me at:

```
moonchild@enterprise.net
```

1.7 Know Bugs

Appart from the bad spelling in the amigaguide there are no known bugs.

Bug reports should be email to me at:

```
moonchild@enterprise.net
```
