FindPhone

COLLABORATORS			
	TITLE : FindPhone		
ACTION	*NAME*	*DATE*	*SIGNATURE*
WRITTEN BY		August 4, 2022	

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

Chapter 1

FindPhone

1.1 FindPhone 1.8

```
                                     FindPhone version 1.8

                        Searches the nodelist for nodes
                        those phonenumber matches a wildcard.

                        Copyright ©1995 Lee Kindness.


             Introduction
             : What does it do?

             Installation
             : Setting it up.

                Usage
             : Using It.
                      History    : Version History.

                Legal
             : Legal Mumbo.

               Contact
             : How to contact the author.
                     Try Them    : Other programs to try.
```

1.2 Introduction

```
Ever wanted to freq a node but didn't know the FQFA number?? Well help is
here now!

FindPhone searches through the nodelist for nodes whose phonenumber matches a
wildcard.
```

1.3   Installation

```
To install simply follow the steps below (clicking on the button will
automatically do the action!)

1. Copy FindPhone to MAIL:bin
2. Copy FindPhone.guide to MAIL:docs
```

1.4   Usage

```
FindPhone can only be run from the Shell. It accepts arguments which
match the following template:

 PATTERN/M/A,START/K,FULL/S,VERBATIM/S,STRIPDASHES/S,BUFSIZE/K/N,NODELIST/K

PATTERN -- Wildcard to search the nodelist for. All standard Amiga wildcards
    are supported. The search is case-insensitive. At least one pattern must
    be given but you can supply more.

START --- Node to start the search from. For example "START=2:" would start
    the search at zone 2, skiping zone 1. If not given the search starts at
    the front of the nodelist.

FULL --- Specifies the output mode. If this switch is not specified then for
    each node found only 1 line of information is display. However if it
    is specified then more data is displayed.

VERBATIM --- Specifies that the wildcard should act on the phonenumbers as
    they appear in the nodelist. The numbers will not be subject to the
    DIAL

STRIPDASHES --- Specifies that the search should be made on the phonenumbers
    after the dashes in them have been removed. For example the imagine the
    phone number of a node is "1-604-589-8562" then the comparison will be
    between "16045898562" the the wildcard.

BUFSIZE --- Size of the nodelist scanning buffer (in records). Values below
    32 will use the default buffer size.

NODELIST --- Directory where the nodelist files are kept. Defaults to
    "NodeList:"
```

1.5   Version History

```
1.4  (29.08.95)
    - First release.

1.8  (31.08.95)
    - Added STRIPDASHES option.
```

1.6 **Disclaimer, Distrubution and Copyright**

```
Disclaimer
~~~~~~~~~~
I hereby reject any liability or responsibility for these or any
other consequences from the use of FindPhone whatsoever. This includes,
but is not limited to, damage to your equipment, to your data,
personal injuries, financial loss or any other kinds of side effects.
Although FindPhone has been tested thoroughly on several different
machines, I cannot rule out the possibility that FindPhone

     1. is somehow incompatible to your equipment

     2. has bugs that show up on your equipment

     3. does not do what it is supposed to do on your equipment

It is your responsibility to take any precautions necessary to
protect yourself from these or any other effects. I explicitly
reject any liability or responsibility from the consequences of you
using FindPhone

Distribution
~~~~~~~~~~~~

FindPhone may be freely distributed and copied, as long as the following
conditions are fulfilled:

     1. All parts of the program and the documentation must be complete.
        The distribution of single parts or incomplete subsets of the
        original distribution is forbidden.

     2. If FindPhone is to be included in a commercial distribution (including
        magazines!) then I must be sent a copy of the product (or if it is a
        mag that I am subscribed to then an increase in subscription). It
        would be better if you contacted me beforehand to ensure you have the
        latest version. In any case full credit must be given within the
        program documentation or magazine.

     3. If the included source code is used in another program then credit
        must be given in the documentation.

Note To Magazines
~~~~~~~~~~~~~~~~~~

In the past I have had some of my programs included on magazine coverdisks
without my permission when in the documentation it was stated that this
was required... I want my programs on coverdisks but you _MUST_ read and
fufil the "Distribution" section above. If you disagree then contact me
or write a message in the AMIGA_MAGS echo...
```

1.7 **Contact**

```
I can be contacted at the following addresses:
```

```
Mail:
 Lee Kindness
 8 Craigmarn Road
 Old Portlethen Village
 Aberdeen
 SCOTLAND
 AB1 4QR

Fidonet:
 2:259/26.20 "Lee Kindness"

Internet:
 wangi@fido.zetnet.co.uk


I hope you find the program useful.
```