

DTools Contents



[TAnalogClock](#)



[TBalloonHint](#)



[TLEDClock](#)



[TLEDLabel](#)



[TNeatoMeter](#)



[TPieMeter](#)



[TRotaryKnob](#)



[TVisualApp](#)

Active Property

Applies to

TBalloonHint object

Declaration

`property Active: Boolean;`

Description

The Active property determines if balloon hints will be displayed. If Active is False, then standard Delphi hints will be displayed.



TBalloonHint Component

[Properties](#) [Method](#)

Unit

Balloon

Description

TBalloonHint is a descendent of TComponent. TBalloonHint is a component to display hint strings in a cartoon style balloon. Several properties are provided to customize the appearance of the balloon.

To add balloon hints to your application, simply place a TBalloonHint control on your main form and set the Active property to True.

Color

The color of the balloons is determined by the Application.HintColor property. The outline of the balloon is drawn as cIWindowFrame.

Font

Balloons use the standard THintWindow font (if you have not modified the VCL source code, this will be MS Sans Serif 8 point regular).

Properties

▶ Run-time only

 Active

 MaxWidth

Key Properties

Position

ShadowDepth

Shape

MaxWidth Property

Applies to

TBalloonHint object

Declaration

```
property MaxWidth: Integer;
```

Description

The `MaxWidth` property determines the maximum width in pixels the balloon will occupy on the screen. If this value is less than zero, `TBalloonHint` will use the absolute value of the number as a divisor to the width of the screen. For example: If `MaxWidth = -4`, the maximum width in pixels would be `Screen.Width div 4`. To get the actual maximum width in pixels no matter what `MaxWidth` is set to, use the [GetMaxWidthPixels](#) method.

Position Property

Applies to

TBalloonHint, TRotaryKnob objects

Declaration

TBalloonHint:

property Position: TBalloonPosition;

TRotaryKnob:

property Position: Integer;

Description

TBalloonHint:

The Position property determines the preferred location to display the balloon hint.

TRotaryKnob:

The Position property determines position of the indicator on the knob.

ShadowDepth Property

Applies to

TBalloonHint object

Declaration

property ShadowDepth: TShadowDepth;

Description

The ShadowDepth property determines the number of pixels to offset the balloon shadow.

Shape Property

Applies to

TAnalogClock, TBalloonHint, TPieMeter objects

Declaration

TAnalogClock:

property Shape: TAnalogClockShape;

TBalloonHint:

property Shape: TBalloonShape;

TPieMeter

property Shape: TPieShape;

Description

The Shape property determines the basic shape or outline of the object.

TBalloonShape Type

Unit

Balloon

Declaration

```
TBalloonShape = (bsRoundRect, bsRectangle);
```

Description

The TBalloonShape type is used by the Shape property to determine the shape of a TBalloonHint component.

TBalloonPosition Type

Unit

Balloon

Declaration

```
TBalloonPosition = (bpAboveLeft, bpAboveRight, bpBelowLeft, bpBelowRight);
```

Description

The TBalloonPosition type is used by the Position property of the TBalloonHint component to determine the default positioning of the balloon.

TShadowDepth Type

Unit

Balloon

Declaration

```
TShadowDepth = 0..16;
```

Description

The TShadowDepth type is used by the ShadowDepth property to determine the pixel offset of the balloon shadow of a TBalloonHint object.

Balloon Unit

The Balloon unit contains the classes and types used to implement balloon hints. The following items are declared in the Balloon unit:

Objects

TBalloonHint

Types

TBalloonShape

TBalloonPosition

TShadowDepth



TNeatoMeter Component

Properties

Unit

Feedback

Description

TNeatoMeter is a descendent of TGraphicControl. TNeatoMeter is a component to give user feedback for lengthy operations.

Feedback Unit

The Feedback unit contains the classes and types used to implement progress meters. The following items are declared in the Feedback unit:

Objects

TNeatoMeter

TPieMeter

Types

TBevelDepth

TBevelType

TBitmapDrawStyle

TMeterDirection






TMeterStyle

TPieDirection

TPieShape

Properties

▶ Run-time only

 BackColor
 BevelDepth
 BevelType
 Bitmap
 BitmapDrawStyle
BorderStyle
Caption

Key Properties

 Completed
Direction
Font
ForeColor
ParentFont
ParentShowHint
 Percent

ShowHint
ShowPercent
Style
Total
UseFontColor
Visible

TBevelType Type

Unit

Feedback

Declaration

```
TBevelType = (btNone, btInset, btRaised);
```

Description

The TBevelType type is used by the BevelType property to give a TNeatoMeter component 3-D appearance.

BackColor Property

Applies to

TAnalogClock, TLEDClock, TLEDLabel, TNeatoMeter, TPieMeter objects

Declaration

property BackColor: TColor

Description

TAnalogClock:

The BackColor property determines the color of the area around the clock.

TLEDClock and TLEDLabel

The BackColor property determines the color of the area around the segments.

TNeatoMeter and TPieMeter:

The BackColor property determines the color of the incomplete area of the meter.

BevelDepth Property

Applies to

TNeatoMeter object

Declaration

property BevelDepth: TBevelDepth;

Description

The BevelDepth property is used to set the 3-D depth of the meter.

BevelType Property

Applies to

TNeatoMeter object

Declaration

property BevelType: TBevelType;

Description

The BevelType property is used to give a meter a 3-D appearance.

Bitmap Property

Applies to

TNeatoMeter object

Declaration

```
property Bitmap: TBitmap;
```

Description

The Bitmap property is used to show progress with a graphic instead of simple filled rectangles. The BitmapDrawStyle property determines the appearance of the bitmap.

BitmapDrawStyle Property

Applies to

TNeatoMeter object

Declaration

property BitmapDrawStyle: TBitmapDrawStyle;

Description

The BitmapDrawStyle property is used to determine how the bitmap will be displayed in a meter.

Percent Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

`property` Percent: Integer;

Description

The Percent property indicates the amount completed.

Caption Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

```
property Caption: string;
```

Description

The Caption property contains the text that will be displayed on the meter. If Caption is an empty string and ShowPercent is True, the percent complete will be displayed.

Completed Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

`property Completed: Longint;`

Description

The Completed property determines how many items out of a possible Total have been completed.

Direction Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

TNeatoMeter

property Direction: TMeterDirection;

TPieMeter

property Direction: TPieDirection;

Description

The Direction property determines the way a meter will indicate progress.

ForeColor Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

```
property ForeColor: TColor;
```

Description

The ForeColor property determines the color of the complete area of the meter.



TPieMeter Component

Properties

Unit

Feedback

Description

TPieMeter component is a descendent of TGraphicControl. TPieMeter is a component to give user feedback for lengthy operations.

ShowPercent Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

```
property ShowPercent: Boolean;
```

Description

The ShowPercent property determines whether or not the percent complete will be displayed when Caption is an empty string.

Style Property

Applies to

TNeatoMeter object

Declaration

property Style: TMeterStyle;

Description

The Style property determines the look of the meter.

Total Property

Applies to

TNeatoMeter, TPieMeter objects

Declaration

`property Total: Longint;`

Description

The Total property determines the number of Completed items required to reach 100 percent.

UseFontColor Property

Applies to

TNeatoMeter object

Declaration

```
property UseFontColor: Boolean;
```

Description

The UseFontColor property determines whether text displayed on the meter will be displayed using the color of the font or using the inverse color of the meter sections.

Note: When a bitmap has been assigned, the meter will always use the font color.

TBevelDepth Type

Unit

[Feedback](#)

Declaration

```
TBevelDepth = 0..10;
```

Description

The TBevelDepth type is used by the [BevelDepth](#) property to set the 3-D depth of a [TNeatoMeter](#) component.

TBitmapDrawStyle Type

Unit

[Feedback](#)

Declaration

```
TBitmapDrawStyle = (dsStretch, dsTile, dsTileInvert);
```

Description

The TBitmapDrawStyle type is used by the [BitmapDrawStyle](#) property to determine how the [bitmap](#) will be displayed in a [TNeatoMeter](#) object. The following table describes the meaning of each value:

Value	Meaning
dsStretch	The bitmap will be stretched in the completed section of the meter. The remainder of the meter will be filled with the background color.
dsTile	The bitmap will be tiled in the completed section of the meter. The remainder of the meter will be filled with the background color.
dsTileInvert	The bitmap will be tiled in the completed section of the meter. The remainder of the meter will be tiled with the inverted image of the bitmap.

TMeterDirection Type

Unit

Feedback

Declaration

```
TMeterDirection = (mdLeftToRight, mdRightToLeft, mdTopToBottom,  
mdBottomToTop);
```

Description

The TMeterDirection type is used by the Direction property to determine which way a TNeatoMeter object will indicate progress.

TMeterStyle Type

Unit

[Feedback](#)

Declaration

```
TMeterStyle = (msStandard);
```

Description

The TMeterStyle type is used by the [Style](#) property to determine the look of a [TNeatoMeter](#) object.

Note: Future versions will hopefully support more styles (segments, etc.).


Properties

▶ Run-time only

BackColor

BorderStyle

Caption

 Completed

 Direction

Key Properties


Font

ForeColor


ParentFont

ParentShowHi
nt

Percent

 Shape

ShowHint

 ShowPercent

Total

Visible

Properties

 Key Properties

 HelpFile

 HintColor

HintPause

Icon

Title



TVisualApp Component

[Properties](#) [Events](#)

Unit

[VisApp](#)

Description

TVisualApp is a descendent of TComponent. TVisualApp is a component to allow you to easily manipulate the global Application objects properties and attach event handlers.

AnaClock Unit

The AnaClock unit contains the classes and types used to implement an analog clock component.

The following items are declared in the AnaClock unit:

Objects

TAnalogClock

Types

TAnalogClockShape

TPieShape Type

Unit

[Feedback](#)

Declaration

```
TPieShape = (psCircle, psEllipse);
```

Description

The TPieShape type is used by the [Shape](#) property to determine the shape of a [TPieMeter](#) object.

TPieDirection Type

Unit

Feedback

Declaration

```
TPieDirection = (pdClockwise, pdCounterClockwise);
```

Description


The TPieDirection type is used by the Direction property to determine the direction a TPieMeter will indicate progress.


Events

 Key Events

 OnActivate

 OnDeactivate

 OnException

 OnHelp

OnHint

OnIdle

OnMessage

OnMinimize

OnRestore

OnShowHint

OnTimer Event

Applies to

TAnalogClock, TLEDClock objects

Declaration

property OnTimer: TNotifyEvent;

Description

The OnTimer event is used to execute code at regular intervals. The Interval property of a TAnalogClock object determines how often this event occurs.

Note: The **sender** parameter of the event will be a TAnalogClock or TLEDClock object not a TTimer.

VisApp Unit

The VisApp unit contains the classes and types used to implement the visual application component.

The following items are declared in the VisApp unit:

Objects

TVisualApp



TAnalogClock Component

[Properties](#)

[Events](#)

Unit

[AnaClock](#)

Description

TAnalogClock is a descendent of TCustomControl. TAnalogClock is a component to display a standard analog clock. TAnalogClock can also be used as a timer by setting the [Interval](#) property and writing a handler for the [OnTimer](#) event.

Properties

▶ Run-time only

Align

BackColor

Enabled

FaceColor

HandsColor

Hint

Key Properties



Interval

OutlineColor

ParentShowHint

PopupMenu

SecHandColor



Shape

ShowHint




ShowSeconds

TickColor

Visible

Events

 Key Events

[OnClick](#)

[OnDbIcClick](#)

[OnDragDrop](#)


[OnDragOver](#)

[OnEndDrag](#)

[OnMouseDown](#)

[OnMouseMove](#)

[OnMouseUp](#)

 [OnTimer](#)

TAnalogClockShape Type

Unit

AnaClock

Declaration

```
TAnalogClockShape = (csCircle, csSquare);
```

Description

The TAnalogClockShape type is used by the Shape property to determine the displayed shape of a TAnalogClock component.

FaceColor Property

Applies to

TAnalogClock object

Declaration

```
property FaceColor: TColor;
```

Description

The FaceColor property determines the color of the face of the clock.

HandsColor Property

Applies to

TAnalogClock object

Declaration

```
property HandsColor: TColor;
```

Description

The HandsColor property determines the color of the minute and hour hands of the clock.

Interval Property

Applies to

TAnalogClock, TLEDClock objects

Declaration

property Interval: Word;

Description

The Interval property determines how often the clock will update the time display and generate OnTimer events.

OutlineColor Property

Applies to

TAnalogClock object

Declaration

```
property OutlineColor: TColor;
```

Description

The OutlineColor property determines the color of the clock border.

SecHandColor Property

Applies to

TAnalogClock object

Declaration

```
property SecHandColor: TColor;
```

Description

The SecHandColor property determines the color of the second hand of the clock.

ShowSeconds Property

Applies to

TAnalogClock, TLEDClock objects

Declaration

property ShowSeconds: Boolean;

Description

The ShowSeconds property determines the whether or not seconds will be displayed.

TickColor Property

Applies to

TAnalogClock object

Declaration

```
property TickColor: TColor;
```

Description

The TickColor property determines the color of the markers around the clock.



TLEDLabel Component

[Properties](#) [Events](#)

Unit

[LEDGadgt](#)

Description

TLEDClock is a descendent of TGraphicControl. TLEDLabel is a component to display a standard segmented LED readout.

GetMaxWidthPixels Method

Applies to

TBalloonHint object

Declaration

```
function GetMaxWidthPixels: Integer;
```

Description

The GetMaxWidthPixels method returns the actual maximum width in pixels of the balloon no matter what MaxWidth is set to.

IndicatorColor Property

Applies to

TRotaryKnob object

Declaration

```
property IndicatorColor: TColor;
```

Description

The IndicatorColor property determines the color used to paint the position indicator.

Note: The area around the knob is painted using the value of the Color property. The rest of the knob colors are determined by the current system colors.

MMGadget Unit

The MMGadget unit contains the classes and types used to implement stereo-style rotary knobs.

The following items are declared in the MMGadget unit:

Objects

TRotaryKnob

Method

GetMaxWidth
Pixels



TRotaryKnob Component

[Properties](#) [Events](#)


Unit

MMGadget

Description

TRotaryKnob is a descendent of TCustomControl. TRotaryKnob is a component to allow users to select a value within a range using a familiar stereo-style rotary knob. TRotaryKnob can update the Caption or Text property of another control automatically using the Control property.

Events

 Key Events

 OnChange

Properties

▶ Run-time only

Align

Color

 Control

Enabled

Key Properties

IndicatorColor

 Max

Min

ParentShowHint

PopupMenu

ShowHint

Position

Visible

Min Property

Applies to

TRotaryKnob object

Declaration

`property` Min: Integer;

Description

The Min property along with the Max property determines the number of possible positions a knob can have.

Max Property

Applies to

TRotaryKnob object

Declaration

`property Max: Integer;`

Description

The Max property along with the Min property determines the number of possible positions a knob can have.

Control Property

Applies to

TRotaryKnob object

Declaration

```
property Control: TControl;
```

Description

When the Position changes, the knob control will automatically update the value of the Caption or Text property of the assigned control.

OnChange Event

Applies to

TRotaryKnob object

Declaration

property OnChange: TNotifyEvent;

Description

The OnChange is triggered whenever the Position of the knob changes.

TSegmentSize Type

Unit

LEDGadgt


Declaration

```
TSegmentSize = 1..16;
```

Description

The TSegmentSize type is used by the SegmentSize property to determine the thickness of LED segments.

Events

 Key Events

[OnClick](#)

[OnDragOver](#)

[OnMouseMove](#)

[OnDbClick](#)

[OnEndDrag](#)

[OnMouseUp](#)

[OnDragDrop](#)

[OnMouseDown](#)



TLEDClock Component

[Properties](#) [Events](#)

Unit

[LEDGadgt](#)

Description

TLEDClock is a descendent of [TLEDLabel](#). TLEDClock is a component to display a standard LED clock. TLEDClock can also be used as a timer by setting the [Interval](#) property and writing a handler for the [OnTimer](#) event.

Events

 Key Events

[OnClick](#)

[OnDbIcClick](#)

[OnDragDrop](#)


[OnDragOver](#)

[OnEndDrag](#)

[OnMouseDown](#)

[OnMouseMove](#)

[OnMouseUp](#)

 [OnTimer](#)

Properties


▶ Run-time only

BackColor

Caption

Columns

 DrawMode

 DrawOnScreen
n

Enabled

Key Properties

Hint

 Interval

LitColor

ParentShowHint

PopupMenu

Rows

 SegmentSize

ShowHint

 ShowSeconds

UnlitColor


Visible


Properties


▶ Run-time only

BackColor

Caption

 Columns

 DrawMode

 DrawOnScreen

Key Properties

Hint

LitColor

ParentShowHint

PopupMenu

Rows

 SegmentSize

ShowHint

UnlitColor

Visible

DrawMode Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

property DrawMode: TLEDDrawMode;

Description

The DrawMode property determines the method used to draw the LED segments.

Note: When SegmentSize is 1, the drawing mode will be dmLine regardless of the DrawMode setting.

Columns Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

property Columns: **Integer**;

Description

The Columns property combined with the Rows property determine the number of LED characters in a LED display.

TLEDDrawMode Type

Unit

LEDGadgt

Declaration

```
TLEDDrawMode = (dmPolygon, dmLine);
```

Description

The TLEDDrawMode type is used by the DrawMode property to determine what method will be used to draw LED segments.

LEDGadgt Unit

The LEDGadgt unit contains the classes and types used to implement an LED label and clock components.

The following items are declared in the LEDGadgt unit:

Objects

TLEDClock

TLEDLabel

Types

DrawOnScreen Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

```
property DrawOnScreen: Boolean;
```

Description

The DrawOnScreen property determines whether or not the LED Paint method will use an off-screen bitmap. Off-screen bitmaps result in less flicker - direct to screen may result in a more realistic LED.

LitColor Property

Applies to

TLEDClock, TLEDDLabel objects

Declaration

```
property LitColor: TColor;
```

Description

The LitColor property determines the color of LED segments which should be "lit".

Rows Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

property Rows: **Integer**;

Description

The Rows property combined with the Columns property determine the number of LED characters in an LED display.

SegmentSize Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

property SegmentSize: TSegmentSize;

Description

The SegmentSize type is used to determine the thickness of LED segments.

UnlitColor Property

Applies to

TLEDClock, TLEDLabel objects

Declaration

```
property UnlitColor: TColor;
```

Description

The UnlitColor property determines the color of LED segments which should not be "lit".

Note: If UnlitColor and BackColor are the same, the unlit segments will not be drawn to improve performance.

