



AppleVision 850Av

Features

Outstanding image quality

- Features Sony Trinitron technology and anti-reflective coating for clear, sharp pictures and vivid color
- Includes Apple DigitalColor technology, which offers outstanding color matching and remarkably accurate on-screen color representation
- Adjusts for white point to emulate different viewing environments
- Keeps colors accurate and balanced over time, by compensating for ambient lighting and CRT phosphor aging

Advanced technologies

- Uses multiple-scan electronics that deliver switch-on-the-fly resolution flexibility
- Offers a range of resolution modes—up to 1,600 by 1,200 pixels
- Provides intuitive software control of brightness, contrast, centering, convergence, pincushion, parallelogram, keystone, white-point, and gamma adjustments

Multimedia integration

- Provides high-quality stereo sound
- Includes a directional microphone capable of voice recognition
- Is completely integrated with Macintosh computers that feature Apple AV Technologies

Ergonomic design

- Includes anti-reflective, antistatic screen coating for comfortable viewing
- Features a tilt-and-swivel display for maximum comfort and ease of use
- Connects keyboard and mouse easily via Apple Desktop Bus (ADB) connectors integrated directly into monitor base
- Complies with TCO 92 environmental certification

Compatibility

- Works with Power Macintosh, Macintosh Performa, and Macintosh Quadra computers with 68040 or later microprocessors running Macintosh System 7.1 or later
- Windows 95 Plug and Play certified

The AppleVision 850Av is an exceptional 20-inch (19-inch diagonal viewable image size) audiovisual display designed for business professionals, desktop publishers, and multimedia authors. It has built-in software and hardware to handle the most demanding graphics work. And it unites Sony Trinitron tube technology with built-in stereo speakers and microphone.

The AppleVision 850Av also delivers plug-and-play compatibility with DOS and Windows software-based computers, as well as Macintosh and Power Macintosh systems.

For high-accuracy color, the AppleVision 850Av includes Apple DigitalColor internal calibration technology, which ensures that the display's color accuracy remains true over time and in a variety of ambient lighting conditions. And it features automatic screen-to-print color matching using Apple

ColorSync 2.0 technology. It also incorporates a new anti-reflective screen coating that provides superior visibility.

Because sound is such an important part of multimedia, the AppleVision 850Av has high-quality built-in stereo speakers that rival the sound of bookshelf speakers. And the built-in microphone is engineered for close-up recording, voice annotation, speech recognition, and speakerphone use.

The AppleVision 850Av uses Sony Trinitron technology—the industry standard for bright, sharp, vivid screen imaging. And multiple-scan capability allows you to view more than two full pages of text or graphics at an impressive 1,600 by 1,200 pixels.

So if you're looking for a large, high-quality display for your applications, we invite you to look closely at the AppleVision 850Av.





AppleVision 850Av

Ordering Information

AppleVision 850Av

Order No. M5228LL/A

- AppleVision 850Av with built-in stereo speakers
- AppleVision software
- PC adapter
- Integrated, attached video and Apple Desktop Bus (ADB) cable
- Integrated microphone and audio input/output cable
- Power jumper cable
- Ambient light wand
- User's guide
- Limited warranty

Product specifications are subject to change. Check with your Apple reseller for the most current information about product specifications and configurations.

Technical Specifications

Picture tube

- 20-in. (diagonal) Trinitron CRT
- 19-in. (diagonal viewable image size)
- 0.26-mm aperture grille pitch

Resolution*

Macintosh computers

- 640 x 480 pixels
- 800 x 600 pixels
- 832 x 624 pixels
- 1,024 x 768 pixels
- 1,152 x 870 pixels
- 1,280 x 1,024 pixels
- 1,600 x 1,200 pixels

PC-compatible systems

- 640 x 480 pixels
- 800 x 600 pixels
- 1,024 x 768 pixels
- 1,280 x 1,024 pixels
- 1,600 x 1,200 pixels

Scanning rates

- 30 kHz to 94 kHz (horizontal)
- 48 Hz to 120 Hz (vertical)

Apple DigitalColor technology

- Internal calibration to original factory measurements
- Adjustment for ambient lighting
- Adjustment for CRT phosphor aging

Multimedia features

- Integrated high-quality stereo speakers
- Directional microphone
- Stereo headphone connector

Screen treatment

- Antistatic, anti-reflective coating

Digital software and hardware controls

- Power on/off
- Brightness
- Contrast
- Horizontal size and centering
- Vertical size and centering
- Convergence
- Rotation
- Pincushion
- Keystone
- Parallelogram
- Gamma curve
- Completely variable white-point selection: 4,100°K to 9,300°K
- Bass control
- Treble control
- Volume control
- Microphone mute
- Speaker mute

Audio

- Watts: 5 volts RMS, each channel
- Frequency response: 80 Hz to 17 kHz
- Speaker output > 90 (dB) SPL at 1 kHz at 0.5 meters
- Headphones: 600 ohm > 0.5 volts RMS

Connector

- 15-pin DSub connector for Macintosh systems
- 15-pin DSub VGA mini-adapter for PCs

Degauss circuitry

- Automatic at power up

Electrical requirements

- Line voltage: 90 to 132 V AC and 198 to 264 V AC
- Frequency: 47 to 63 Hz, single phase
- Power: 180 W (maximum) when operating; less than 30 W in standby mode; 5 W (speakers off) or 30 W (speakers on) in suspend mode and when CPU is in energy-saver mode

Environmental operating requirements

- Temperature: 50° to 104° F (10° to 40° C)
- Humidity: 20% to 95%, noncondensing
- Altitude: 0 to 10,000 ft. (0 to 3,048 m)

Size and weight

- Height: 21.8 in. (55.5 cm)
- Width: 19.1 in. (48.5 cm)
- Depth: 23.4 in. (59.5 cm)
- Display weight: 78.0 lb. (35.4 kg)
- Fully boxed weight: 92.1 lb. (41.9 kg)

Agency approvals

- FCC Part 15 Class A
- CISPR 22 Class A (EN5008211)—complies with European EMC directive
- DOC Class A
- MPR-II
- VCCI Class 1
- CE Mark
- EPA Energy Star compliant
- IEC 950
- UL 1950
- CSA 950
- EN60950
- NUTEK
- TCO 92

System requirements

- Works with Power Macintosh, Macintosh Performa, and Macintosh Quadra computers with 68040 or later microprocessors running Macintosh System 7.1 or later*
- Windows 95 Plug and Play certified

**Not all models and configurations are capable of driving the monitor to the highest resolution it supports.*



Apple Computer, Inc.
1 Infinite Loop
Cupertino, CA 95014
(408) 996-1010
<http://www.apple.com/>

©1997 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, AppleVision, ColorSync, the ColorSync logo, Macintosh, Macintosh Quadra, Performa, and Power Macintosh are trademarks of Apple Computer, Inc., registered in the U.S.A. and other countries. Trinitron is a trademark of Sony Corporation, registered in the U.S.A. and other countries. Mention of non-Apple products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users.
April 1997. Product specifications are subject to change without notice.
Printed in the United States of America
L02370A