

## HTML Code Help

Scroll through this list. Copy what you need to use. Most common codes are shown on the first line with other options indented.

`<!-- .. -->` (Comments)

`<!DOCTYPE>` (Version of HTML)

`<A HREF=reference NAME=name> </A>`  
(Designates a Link)  
    `CLASS=type`  
    `ID=value`  
    `onClick=function`  
    `onMouseOver=function`  
    `REL=SAME|NEXT|PARENT|PREVIOUS`  
    `REV=value`  
    `STYLE=style`  
    `TARGET=window`  
    `TITLE=title`

`<ADDRESS></ADDRESS>` (Ownership Information)

`<APPLET CODE=appletFile CODEBASE=codebaseURL  
HEIGHT=pixels WIDTH=pixels>`  
(Inserts JAVA Script)  
    `ALIGN=LEFT|CENTER|RIGHT|TOP|MIDDLE|BOTTOM`  
    `ALT=alternateText`  
    `DOWNLOAD=n`  
    `HSPACE=pixels`  
    `NAME=appletInstanceName`  
    `TITLE=text`  
    `VSPACE=pixels`  
`<PARAM NAME=AttributeName ...>`  
`</APPLET>`

`<AREA SHAPE=RECT|RECTANGLE|CIRC|CIRCLE  
|POLY|POLYGON COORDS=coords HREF=url>`  
(defines a hot spot)  
    `ALT=text`  
    `CLASS=type`  
    `ID=value`  
    `NOHREF`  
    `NOTAB`  
    `STYLE=css1 properties`  
    `TABINDEX=n`  
    `TARGET=window`  
    `TITLE=text>`

`<B></B>` (bold text)

`<BASE HREF=url>` (document's URL in HEAD)  
    `TARGET=window`

`<BASEFONT SIZE=n>` (base font values)  
    `COLOR=color`  
    `NAME=name`

`<BGSOUND LOOP=n|INFINITE SRC=url>`  
(plays background sound)

`<BIG></BIG>` (enlarges text one size)

`<BLOCKQUOTE></BLOCKQUOTE>`  
(indents both margins)

`<BODY ALINK=color BACKGROUND=url BGCOLOR=color`

LINK=color TEXT=color VLINK=color>  
(sets document body)  
  BGPROPERTIES=FIXED  
  CLASS=type  
  ID=value  
  LEFTMARGIN=n  
  STYLE=css1 properties  
  TOPMARGIN=n  
</BODY>

<BR> (line break)  
  CLASS=type  
  CLEAR=NONE|LEFT|RIGHT|ALL

<CAPTION ALIGN=CENTER|LEFT|RIGHT  
  VALIGN=TOP|BOTTOM>  
(table caption)  
</CAPTION>

<CENTER></CENTER> (centers text and images)

<CITE></CITE> (cites reference material)

<CODE></CODE> (displays computer code)

<COL ALIGN=LEFT|CENTER|RIGHT SPAN=n>  
(individual column properties of COLGROUP)

<COLGROUP SPAN=n HALIGN=CENTER|LEFT|RIGHT>  
  VALIGN=MIDDLE|TOP|BOTTOM  
  WIDTH=n  
(column properties in a TABLE)

<COMMENT></COMMENT> (comment)

<DD> (dictionary definition in DL)  
  CLASS=type  
  ID=value  
  STYLE=css1 properties

<DFN></DFN> (displays a definition)

<DIR> (encases a list, uses LI)  
  COMPACT  
</DIR>

<DIV> (encases a section)  
  ALIGN=LEFT|CENTER|RIGHT|JUSTIFY  
  CLASS=type  
  ID=value  
  LANG=iso  
  NOWRAP  
</DIV>

<DL> (encases a dictionary list)  
  CLASS=type  
  COMPACT  
  ID=value  
  STYLE=css1 properties>  
</DL>

<DT> (dictionary term in DL)

<EM></EM> (emphased text, usually italics)

<EMBED SRC=url HEIGHT=n WIDTH=n>  
(embedded object)  
NAME=text  
[optional parameter=&quot;value&quot;]  
PALETTE=#rgb|#rgb  
UNITS=PIXELS|EN  
</EMBED>

<FONT COLOR=color FACE=name SIZE=n>  
(font characteristics)

<FORM ACTION=url METHOD=GET|POST>  
(form)  
onSubmit=event  
TARGET=window  
</FORM>

<FRAME ALIGN=LEFT|CENTER|RIGHT|TOP|BOTTOM  
SCROLLING=yes|no SRC=address FRAMEBORDER=1|0>  
(single frame characteristics in FRAMESET)  
MARGINHEIGHT=height  
MARGINWIDTH=width  
NAME=name  
NORESIZE

<FRAMESET COLS=col-widths FRAMEBORDER=1|0  
SCR=url SCROLLING=yes|no>  
(encases FRAME, FRAMESET, NOFRAMES)  
FRAMESPACING=spacing  
ROWS=row-heights>  
</FRAMESET>

<Hn> (heading levels)  
ALIGN=LEFT|CENTER|RIGHT>  
</Hn>

<HEAD></HEAD> (HTML document heading)

<HR ALIGN=LEFT|CENTER|RIGHT SIZE=n WIDTH=n>  
(horizontal line)  
CLASS=type  
COLOR=color  
ID=value  
NOSHADE  
STYLE=css1 properties

<HTML></HTML> (encases HTML document)

<i></i> (italics)

<IFRAME FRAMEBORDER=1|0 SCROLLING=yes|no  
SRC=address>  
(floating frame)  
ALIGN=LEFT|CENTER|RIGHT|TOP|BOTTOM  
HEIGHT=height  
MARGINHEIGHT=height  
MARGINWIDTH=width  
NAME=name  
WIDTH=width  
</IFRAME>

<IMG ALIGN=TOP|MIDDLE|CENTER|BOTTOM|LEFT|RIGHT  
ALT=text SRC=url>  
(Image)  
BORDER=n  
CLASS=type

CONTROLS  
DYN SRC=url  
HEIGHT=n  
HSPACE=n  
ID=value  
ISMAP=image  
LOOP=n  
START=start-event  
STYLE=css1 properties  
TITLE=text  
USEMAP=url  
VSPACE=n  
WIDTH=n

<INPUT NAME=name TYPE=TEXT|TEXTAREA|PASSWORD  
|CHECKBOX|RADIO|SUBMIT|RESET|FILE|HIDDEN  
|IMAGE|BUTTON VALUE=value>  
(form control in FORM)  
ALIGN=TOP|MIDDLE|BOTTOM|LEFT|RIGHT  
CHECKED  
CLASS=type  
ID=value  
MAXLENGTH=length  
NOTAB  
onBlur=event  
onChange=event  
onClick=event  
onFocus=event  
onSelect=event  
SIZE=size  
SRC=url  
STYLE=css1 properties  
TABINDEX=n  
TITLE=text

<ISINDEX ACTION=url PROMPT=prompt-text>  
(searchable index in HEAD)

<KBD></KBD> (keyboard text)

<LI>  
(one item of DIR, MENU, OL, UL)  
CLASS=type  
ID=value  
STYLE=css1 properties  
TYPE=order-type  
VALUE=n

<LINK HREF=url>  
(relational information in HEAD)  
REL=forward link type  
REV=reverse link type  
TITLE=title  
TYPE=type

<LISTING></LISTING> (shows fixed-width text)

<MAP NAME=name></MAP>  
(collection of hot spots, used with AREA)

<MARQUEE BEHAVIOR=SCROLL|SLIDE|ALTERNATE LOOP=n>  
(scrolling text marquee)  
ALIGN=LEFT|CENTER|RIGHT|TOP|BOTTOM  
BGCOLOR=color  
DIRECTION=direction  
HEIGHT=n  
HSPACE=n

SCROLLAMOUNT=n  
SCROLLDELAY=n  
VSPACE=n  
WIDTH=n  
</MARQUEE>

<MENU> (list of items, used with LI)  
COMPACT  
</MENU>

<META HTTP-EQUIV=response NAME=description URL=url>  
(instructions to other applications in HEAD)  
CHARSET=charset  
CONTENT=description

<NOBR> (turns off line break)

<NOFRAMES></NOFRAMES>  
(displays only on no frame browsers)

<OBJECT> (inserts object in document)  
ALIGN=LEFT|TEXTTOP|MIDDLE|TEXTMIDDLE  
|BASELINE|TEXTBOTTOM|CENTER|RIGHT  
BORDER=n  
CLASSID=url  
CODEBASE=url  
CODETYPE=codetype  
DATA=url  
DECLARE  
HEIGHT=n  
HSPACE=n  
NAME=url  
NOTAB  
SHAPES  
STANDBY=message  
TABINDEX=n  
TITLE=text  
TYPE=type  
USEMAP=url  
VSPACE=n  
WIDTH=n  
</OBJECT>

<OL> (encases numbered list, uses LI)  
CLASS=type  
COMPACT  
ID=value  
START=n  
STYLE=css1 properties  
TYPE=order-type

<OPTION VALUE=value>  
(shows item in a list box in SELECT)  
SELECTED

<P> (paragraph break)  
ALIGN=LEFT|CENTER|RIGHT  
CLASS=type  
ID=value  
STYLE=css1 properties

<PARAM NAME=name TYPE=type VALUE=value  
VALUETYPE=type>  
(property values of an object in OBJECT)

<PLAINTEXT></PLAINTEXT>  
(fixed-width text disabling HTML parsing)

<PRE></PRE> (fixed-width text)

<S></S> (strike-through text)

<SAMP></SAMP> (sample text in small font)

<SCRIPT LANGUAGE=scripting language>  
(insert script)  
SRC=filename  
TYPE=MIME type  
</SCRIPT>

<SELECT NAME=name> (list or drop down box)  
SIZE=n  
</SELECT>

<SMALL></SMALL> (reduces text by one size)

<SPAN STYLE=css1 properties></SPAN>  
(text style and HTML information)

<STRIKE></STRIKE> (strike-through text)

<STRONG></STRONG> (emphasizes text, bold)

<STYLE>  
(style sheet settings)  
TITLE=title  
TYPE=MIME type  
</STYLE>

<SUB></SUB> (subscript text)

<SUP></SUP> (superscript text)

<TABLE BORDER=n CELLPADDING=n WIDTH=n>  
(table uses TR, TD, TH)  
ALIGN=LEFT|CENTER|RIGHT|BLEEDLEFT  
|BLEEDRIGHT|JUSTIFY  
BACKGROUND=url  
BGCOLOR=color  
BORDERCOLOR=color  
BORDERCOLORDARK=color  
BORDERCOLORLIGHT=color  
CELLSPACING=n  
CLASS=type  
CLEAR=LEFT|RIGHT|ALL|NO  
COLS=n  
FRAME=frame-type  
ID=value  
NOWRAP  
RULES=rule-type  
STYLE=css1 properties  
VALIGN=TOP|MIDDLE|BOTTOM|BASELINE  
</TABLE>

<TBODY> (multiple sections in TABLE)  
CLASS=type  
ID=value  
STYLE=css1 properties  
</TBODY>

<TD COLSPAN=n HEIGHT=n ROWSPAN=n WIDTH=n>  
(creates a cell in TABLE)

ALIGN=CENTER|LEFT|RIGHT|JUSTIFY  
BACKGROUND=url  
BGCOLOR=color  
BORDERCOLOR=color  
BORDERCOLORDARK=color  
BORDERCOLORLIGHT=color  
CLASS=type  
ID=value  
NOWRAP  
STYLE=css1 properties  
VALIGN=MIDDLE|TOP|BOTTOM|BASELINE

<TEXTAREA> (user input text area)  
COLS=n  
NAME=name  
ROWS=n  
</TEXTAREA>

<TFOOT> (footer for TABLE at page breaks)  
CLASS=type  
ID=value  
STYLE=css1 properties  
</TFOOT>

<TH> (creates a bold cell in TABLE)  
ALIGN=CENTER|LEFT|RIGHT|JUSTIFY  
BACKGROUND=url  
BGCOLOR=color  
BORDERCOLOR=color  
BORDERCOLORDARK=color  
BORDERCOLORLIGHT=color  
CLASS=type  
COLSPAN=n  
ID=value  
NOWRAP  
ROWSPAN=n  
STYLE=css1 properties  
VALIGN=TOP|MIDDLE|BOTTOM|BASELINE  
WIDTH=n

<THEAD> (heading in TABLE at page breaks)  
ALIGN=LEFT|CENTER|RIGHT|JUSTIFY  
CLASS=type  
ID=value  
STYLE=css1 properties  
VALIGN= MIDDLE|TOP|BOTTOM

<TITLE></TITLE> (title of document in HEAD)

<TR> (creates a row in TABLE)  
ALIGN=CENTER|LEFT|RIGHT|JUSTIFY  
BGCOLOR=color  
BORDERCOLOR=color  
BORDERCOLORDARK=color  
BORDERCOLORLIGHT=color  
CLASS=type  
ID=value  
NOWRAP  
STYLE=css1 properties  
VALIGN=MIDDLE|TOP|BOTTOM|BASELINE>  
</TR>

<TT></TT> (teletype text)

<U></U> (underlined text)

<UL> (bulleted list using LI)

```
CLASS=type  
COMPACT  
ID=value  
STYLE=css1 properties>  
</UL>
```

<VAR></VAR> (variable text)

<WBR> (suggested line break in NOBR)

<XMP></XMP> (fixed width text)





