

MExtras VCL's for Delphi

The purpose with most of these components is to make the internationalization work very easy. However, you can use the components in which way you want. This package is a part of the real sharp multi language package found on CompuServe and Internet.

MDialogs This unit includes all 16-bit common dialogs for translation to other languages. Supports different fonts for special languages. Can be translated at run-time.

MButtons Message dialogs like ShowMessage, MessageDlg, InputQuery etc. have predefined button names in the CONSTS.RES file. This component can change the titles and captions of those buttons to the desired language. They can be translated at run-time.

Author:

Patrik Wang
PWang@MSN.COM

© 1995 Patrik Wang. All text, information and instructions contained in this helpfile is provided as is, the author disclaims all warranties expressed or implied, including, without limitation.

MDialogs Unit

The MDialogs unit contains the declarations for the common dialog boxes which are found on the Multi Language page of the Component palette. Components declared in this unit are descendants of the respective dialog in the Dialogs unit.

When you add a component declared in this unit to a form, the unit is automatically added to the **uses** clause of that form's unit.

The following items are declared in the MDialogs unit:

Components

TMColorDialog

TMFindDialog

TMFontDialog

TMOpenDialog

TMPrintDialog

TMPrinterSetupDialog

TMReplaceDialog

TMSaveDialog

TMColorDialog Component

[Properties](#)

Unit

MDialogs

Description

The TMColorDialog component is descendant of TColorDialog and adds on properties for translating the Color dialog captions and font.

For all inherited properties, methods and events please see the [TColorDialog](#)

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

Properties

▶ runtime properties

🔑 key properties

- 🔑 CaptionAdd
- 🔑 CaptionDefine
- 🔑 CaptionRed
- 🔑 CaptionBasic
- 🔑 CaptionGreen
- 🔑 CaptionSat
- 🔑 CaptionBlue
- 🔑 CaptionHelp
- 🔑 CaptionSolid
- 🔑 CaptionCancel
- 🔑 CaptionHue
- 🔑 Font
- 🔑 CaptionColor
- 🔑 CaptionLum
- 🔑 Title
- 🔑 CaptionCustom
- 🔑 CaptionOK

CaptionAdd Property

Applies to

TMColorDialog

Declaration

Property CaptionAdd: String

Description

Contains the text of the 'Add to Custom colors' button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionBasic Property

Applies to

TMColorDialog

Declaration

Property CaptionBasic: String

Description

Contains the text of the 'Basic Colors' label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionBlue Property

Applies to

TMColorDialog

Declaration

Property CaptionBlue: String

Description

Contains the text of the 'Blue' label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionCancel Property

Applies to

TMColorDialog, TMFindDialog, TMFontDialog, TMOpenDialog, TMPrintDialog, TMPrinterSetupDialog, TMReplaceDialog, TMSaveDialog

Declaration

Property CaptionCancel: String

Description

Contains the text of the 'Cancel' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

TMFindDialog Component

[Properties](#)

Unit

[MDialogs](#)

Description

The TMFindDialog component is descendant of TFindDialog and adds on properties for translating the Find dialog captions and font.

For all inherited properties, methods and events please see the [TFindDialog](#)

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TMFontDialog Component

[Properties](#)

Unit

MDialogs

Description

The TMFontDialog component is descendant of TFontDialog and adds on properties for translating the Font dialog captions and font.

For all inherited properties, methods and events please see the [TFontDialog](#)

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TOpenDialog Component

[Properties](#)

Unit

MDialogs

Description

The TOpenDialog component is descendant of TOpenDialog and adds on properties for translating the Open dialog captions and font.

For all inherited properties, methods and events please see the [TOpenDialog](#).

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TMPrintDialog Component

[Properties](#)

Unit

[MDialogs](#)

Description

The TMPrintDialog component is descendant of TPrintDialog and adds on properties for translating the Print dialog captions and font.

For all inherited properties, methods and events please see the [TPrintDialog](#).

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TMPrinterSetupDialog Component

[Properties](#)

Unit

MDialogs

Description

The TMPrinterSetupDialog component is descendant of TPrinterSetupDialog and adds on properties for translating the Print setup dialog captions and font.

For all inherited properties, methods and events please see the [TPrinterSetupDialog](#).

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TMReplaceDialog Component

[Properties](#)

Unit

[MDialogs](#)

Description

The TMReplaceDialog component is descendant of TReplaceDialog and adds on properties for translating the Find & Replace dialog captions and font.

For all inherited properties, methods and events please see the [TReplaceDialog](#).

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

TMSaveDialog Component

[Properties](#)

Unit

[MDialogs](#)

Description

The TMSaveDialog component is descendant of TSaveDialog and adds on properties for translating the Save dialog captions and font.

For all inherited properties, methods and events please see the [TSaveDialog](#).

Use this component when you need multi language support in common dialogs.

When this dialog is shown with the Execute method, it will display the text according to all the Caption????? properties.

CaptionColor Property

Applies to

TMColorDialog, TMFontDialog

Declaration

Property CaptionColor: String

Description

Contains the text of the 'Color' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionCustom Property

Applies to

TMColorDialog

Declaration

Property CaptionCustom: String

Description

Contains the text of the 'Custom Colors' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionDefine Property

Applies to

TMColorDialog

Declaration

Property CaptionDefine: String

Description

Contains the text of the 'Define Custom Colors' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionGreen Property

Applies to

TMColorDialog

Declaration

Property CaptionGreen: String

Description

Contains the text of the 'Green' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionHelp Property

Applies to

TMColorDialog, TMFindDialog, TMFontDialog, TMOpenDialog, TMPrintDialog, TMPrinterSetupDialog, TMReplaceDialog, TMSaveDialog

Declaration

Property CaptionHelp: String

Description

Contains the text of the 'Help' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionHue Property

Applies to

TMColorDialog

Declaration

Property CaptionHue: String

Description

Contains the text of the 'Hue' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionLum Property

Applies to

TMColorDialog

Declaration

Property CaptionLum: String

Description

Contains the text of the 'Lum' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionOK Property

Applies to

TMColorDialog, TMFontDialog, TMOpenDialog, TMPrintDialog, TMPrinterSetupDialog, TMSaveDialog

Declaration

Property CaptionOK: String

Description

Contains the text of the 'OK' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRed Property

Applies to

TMColorDialog

Declaration

Property CaptionRed: String

Description

Contains the text of the 'Red' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSat Property

Applies to

TMColorDialog

Declaration

Property CaptionSat: String

Description

Contains the text of the 'Sat' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSolid Property

Applies to

TMColorDialog

Declaration

Property CaptionSolid: String

Description

Contains the text of the 'Solid' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Font Property

Applies to

TMColorDialog, TMFindDialog, TMFontDialog, TMOpenDialog, TMPrintDialog, TMPrinterSetupDialog, TMReplaceDialog, TMSaveDialog

Declaration

Property Font: TFont

Description

Contains the font of dialog buttons and labels.

This property is useful when displaying text of languages that has characters not included in the normal font.

Title Property

Applies to

TMButtons, TMColorDialog, TMFindDialog, TMFontDialog, TMPrintDialog, TMPrinterSetupDialog, TMReplaceDialog

Declaration

Property Title: String

Description

Contains the text of the dialog title. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

▶ runtime properties

🔑 key properties

🔑 CaptionCancel

🔑 CaptionFindNext

🔑 CaptionUp

🔑 CaptionDirection

🔑 CaptionHelp

🔑 Font

▶ CaptionDown

▶ CaptionMatchCase

▶ Title

▶ CaptionFind

▶ CaptionMatchWord

CaptionDirection Property

Applies to

TMFindDialog

Declaration

Property CaptionDirection: String

Description

Contains the text of the 'Direction' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionDown Property

Applies to

TMFindDialog

Declaration

Property CaptionDown: String

Description

Contains the text of the 'Down' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFind Property

Applies to

TMFindDialog, TMReplaceDialog

Declaration

Property CaptionFind: String

Description

Contains the text of the 'Find What' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFindNext Property

Applies to

TMFindDialog, TMReplaceDialog

Declaration

Property CaptionFindNext: String

Description

Contains the text of the 'Find Next' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionMatchWord Property

Applies to

TMFindDialog, TMReplaceDialog

Declaration

Property CaptionMatchWord: String

Description

Contains the text of the 'Match Whole Word Only' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionMatchCase Property

Applies to

TMFindDialog, TMReplaceDialog

Declaration

Property CaptionMatchCase: String

Description

Contains the text of the 'Match Case' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionUp Property

Applies to

TMFindDialog

Declaration

Property CaptionUp: String

Description

Contains the text of the 'Up' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

- ▶ runtime properties
- ▶ key properties

- ▶ CaptionApply
- ▶ CaptionFontStyle
- ▶ CaptionStrikout
- ▶ CaptionCancel
- ▶ CaptionHelp
- ▶ CaptionUnderline
- ▶ CaptionColor
- ▶ CaptionOK
- ▶ Font
- ▶ CaptionEffects
- ▶ CaptionSample
- ▶ Title
- ▶ CaptionFont
- ▶ CaptionSize

CaptionApply Property

Applies to

TMFontDialog

Declaration

Property CaptionApply: String

Description

Contains the text of the 'Apply' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionEffects Property

Applies to

TMFontDialog

Declaration

Property CaptionEffects: String

Description

Contains the text of the 'Effects' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFont Property

Applies to

TMFontDialog

Declaration

Property CaptionFont: String

Description

Contains the text of the 'Font' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFontStyle Property

Applies to

TMFontDialog

Declaration

Property CaptionFontStyle: String

Description

Contains the text of the 'Font Style' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSample Property

Applies to

TMFontDialog

Declaration

Property CaptionSample: String

Description

Contains the text of the 'Sample' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSize Property

Applies to

TMFontDialog, TMPrinterSetupDialog

Declaration

Property CaptionSize: String

Description

Contains the text of the 'Size' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionStrikeout Property

Applies to

TMFontDialog

Declaration

Property CaptionStrikeout: String

Description

Contains the text of the 'Strikeout' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionUnderline Property

Applies to

TMFontDialog

Declaration

Property CaptionUnderline: String

Description

Contains the text of the 'Underline' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

- ▶ runtime properties
- ▶ key properties

- ▶ CaptionCancel
- ▶ CaptionHelp
- ▶ CaptionTypeList
- ▶ CaptionDirectory
- ▶ CaptionNetwork
- ▶ Font
- ▶ CaptionDrives
- ▶ CaptionOK
- ▶ Title
- ▶ CaptionFileName
- ▶ CaptionReadOnly

CaptionDirectory Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionDirectory: String

Description

Contains the text of the 'Directories' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionDrives Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionDrives: String

Description

Contains the text of the 'Drives' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFileName Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionFileName: String

Description

Contains the text of the 'File Name' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionNetwork Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionNetwork: String

Description

Contains the text of the 'Network' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionReadOnly Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionReadOnly: String

Description

Contains the text of the 'Read Only' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionTypeList Property

Applies to

TMOpenDialog, TMSaveDialog

Declaration

Property CaptionTypeList: String

Description

Contains the text of the 'List Files of Type' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

- ▶ runtime properties
- ▶ key properties

- ▶ CaptionCancel
- ▶ CaptionPrinter
- ▶ CaptionRangeSelection
- ▶ CaptionCollate
- ▶ CaptionQuality
- ▶ CaptionSetup
- ▶ CaptionCopies
- ▶ CaptionRange
- ▶ Font
- ▶ CaptionFileOption
- ▶ CaptionRangeAll
- ▶ Title
- ▶ CaptionHelp
- ▶ CaptionRangeFrom
- ▶ CaptionOK
- ▶ CaptionRangePages

CaptionCollate Property

Applies to

TMPrintDialog

Declaration

Property CaptionCollate: String

Description

Contains the text of the 'Collate Copies' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionCopies Property

Applies to

TMPrintDialog

Declaration

Property CaptionCopies: String

Description

Contains the text of the 'Copies' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionFileOption Property

Applies to

TMPrintDialog

Declaration

Property CaptionFileOption: String

Description

Contains the text of the 'Print to File' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionPrinter Property

Applies to

TMPrintDialog, TMPrinterSetupDialog

Declaration

Property CaptionPrinter: String

Description

Contains the text of the 'Printer' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionQuality Property

Applies to

TMPrintDialog

Declaration

Property CaptionQuality: String

Description

Contains the text of the 'Print Quality' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRange Property

Applies to

TMPrintDialog

Declaration

Property Captionrange: String

Description

Contains the text of the 'Range' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRangeAll Property

Applies to

TMPrintDialog

Declaration

Property CaptionRangeAll: String

Description

Contains the text of the 'All' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRangeFrom Property

Applies to

TMPrintDialog

Declaration

Property CaptionRangeFrom: String

Description

Contains the text of the 'From' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRangePages Property

Applies to

TMPrintDialog

Declaration

Property CaptionRangePages: String

Description

Contains the text of the 'Pages' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionRangeSelection Property

Applies to

TMPrintDialog

Declaration

Property CaptionRangeSelection: String

Description

Contains the text of the 'Selection' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSetup Property

Applies to

TMPrintDialog

Declaration

Property CaptionSetup: String

Description

Contains the text of the 'Setup' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

- ▶ runtime properties
- ▶ key properties

- ▶ CaptionCancel
- ▶ CaptionOptions
- ▶ CaptionSource
- ▶ CaptionDefault
- ▶ CaptionOrientation
- ▶ CaptionSpecific
- ▶ CaptionDefaultText
- ▶ CaptionPaper
- ▶ Font
- ▶ CaptionHelp
- ▶ CaptionPortrait
- ▶ Title
- ▶ CaptionLandscape
- ▶ CaptionPrinter
- ▶ CaptionOK
- ▶ CaptionSize

CaptionDefault Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionDefault: String

Description

Contains the text of the 'Default Printer' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionDefaultText Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionDefaultText: String

Description

Contains the text of the '(No Default Printer)' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionLandscape Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionLandscape: String

Description

Contains the text of the 'Landscape' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionOptions Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionOptions: String

Description

Contains the text of the 'Options' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionOrientation Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionOrientation: String

Description

Contains the text of the 'Orientation' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionPaper Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionPaper: String

Description

Contains the text of the 'Paper' Group Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionPortrait Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionPortrait: String

Description

Contains the text of the 'Portrait' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSource Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionSource: String

Description

Contains the text of the 'Source' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionSpecific Property

Applies to

TMPrinterSetupDialog

Declaration

Property CaptionSpecific: String

Description

Contains the text of the 'Specific Printer' Option Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

▶ runtime properties

▶ key properties

- ▶ ▶ CaptionCancel
- ▶ CaptionMatchCase
- ▶ CaptionReplaceWith
- ▶ ▶ CaptionFind
- ▶ CaptionMatchWord
- ▶ Font
- ▶ ▶ CaptionFindNext
- ▶ CaptionReplace
- ▶ Title
- ▶ ▶ CaptionHelp
- ▶ CaptionReplaceAll

CaptionReplace Property

Applies to

TMReplaceDialog

Declaration

Property CaptionReplace: String

Description

Contains the text of the 'Replace' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionReplaceAll Property

Applies to

TMReplaceDialog

Declaration

Property CaptionReplaceAll: String

Description

Contains the text of the 'Replace All' Button. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

CaptionReplaceWith Property

Applies to

TMReplaceDialog

Declaration

Property CaptionReplaceWith: String

Description

Contains the text of the 'Replace With' Label. If this property is empty it will display the default text. Windows supply the default text according to the installed language version of Windows.

Properties

▶ runtime properties

▶ key properties

- ▶ ▶ CaptionCancel
- ▶ ▶ CaptionHelp
- ▶ ▶ CaptionTypeList
- ▶ ▶ CaptionDirectory
- ▶ ▶ CaptionNetwork
- ▶ ▶ Font
- ▶ ▶ CaptionDrives
- ▶ ▶ CaptionOK
- ▶ ▶ Title
- ▶ ▶ CaptionFileName
- ▶ ▶ CaptionReadOnly

TMButtons Component

[Properties](#)

Unit

MButtons

Description

This component will translate dialog buttons and titles. Can also be used to to change text of labels on dialogs.

Drop this component on your form when you for example want to display a multi language message with the ShowMessage function. This component will automatically translate all buttons, labels and titles in subforms according to the [Captions](#) and [Title](#) properties.

Edit or add your translations in the [Captions](#) property.

The component will only translate subforms if the [Translate](#) property is true.

Translate the [Captions](#) and [Title](#) properties of this component with the [TMultLang](#) component to be able to switch languages at run-time.

Properties

- ▶ runtime properties
- ▶ key properties

- ▶ Captions
- ▶ Title
- ▶ Translate

Captions Property

Applies to

TMButtons

Declaration

Property Captions: TStrings

Description

The Captions property contains strings to translate together with the translation, separated by a | character. Each row contains one translation. Ex.

```
Yes|Ja  
No|Nej  
Cancel|Avbryt  
Ignore|Ignorera
```

This tells the component to translate the button called 'Yes' to 'Ja', 'No' to 'Nej', 'Cancel' to 'Avbryt' and 'Ignore' to 'Ignorera' for the swedish language.

The left word should always be the english word of the button or label unless you are using a non-english version of Delphi. Since Delphi retrieves the button names from the CONSTS.RES file when compiling, it does not matter which language version of Windows the application is running under.

The right word is the translated word.

Translate Property

Applies to
TMButtons

Declaration
Property Translate: Boolean

Description
This property tells the component to translate subdialogs created by ShowMessage, MessageDlg, InputQuery etc. according to the Captions property.

When this property is true it will translate the subdialog. When this property is false it will not make any calls to check for subdialogs. It is a good practice to always keep this property false and when it is necessary to translate a subdialog, change it to true.

