

in

COLLABORATORS

	<i>TITLE :</i> in	
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>
WRITTEN BY		July 26, 2024

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	in	1
1.1	ModuleInformation	1

Chapter 1

in

1.1 ModuleInformation

```
ShowModule v1.10 (c) 1992 $#%
now showing: "devices/serial.m"
NOTE: don't use this output in your code, use the module instead.

(----) OBJECT ioextser
(  0)    iostd:iostd (or ARRAY OF iostd)
( 48)    ctlchar:LONG
( 52)    rbuflen:LONG
( 56)    extflags:LONG
( 60)    baud:LONG
( 64)    brktime:LONG
( 68)    termarray:termarray (or ARRAY OF termarray)
( 76)    readlen:CHAR
( 77)    writelen:CHAR
( 78)    stopbits:CHAR
( 79)    serflags:CHAR
( 80)    status:INT
(----) ENDOBJECT      /* SIZEOF=82 */

(----) OBJECT termarray
(  0)    ta0:LONG
(  4)    ta1:LONG
(----) ENDOBJECT      /* SIZEOF=8 */

CONST SERF_7WIRE=4,
       SERB_7WIRE=2,
       SERERR_PARITYERR=9,
       IOSTF_XOFFWRITE=8,
       IOSTB_XOFFWRITE=3,
       IOSTF_OVERRUN=1,
       IOSTB_OVERRUN=0,
       SERERR_TIMERERR=11,
       SERF_XDISABLED=$80,
       SERB_XDISABLED=7,
       SERERR_INVPARAM=5,
       SEXTF_MARK=1,
       SEXTB_MARK=0,
       SERF_QUEUEDBRK=8,
```

```
SERB_QUEUEDBRK=3,  
SER_DEVFINISH=11,  
SERERR_LINEERR=6,  
SDCMD_QUERY=9,  
SEXTF_MSPON=2,  
SEXTB_MSPON=1,  
SERF_SHARED=$20,  
SERB_SHARED=5,  
SERERR_BUFOVERFLOW=12,  
SERF_PARTY_ODD=2,  
SERB_PARTY_ODD=1,  
SERF_RAD_BOOGIE=16,  
SERB_RAD_BOOGIE=4,  
SERERR_DEVBUSY=1,  
SERF_EOFMODE=$40,  
SERB_EOFMODE=6,  
SERF_PARTY_ON=1,  
SERB_PARTY_ON=0,  
SDCMD_SETPARAMS=11,  
SERERR_BAUDMISMATCH=2,  
SERERR_NODSR=13,  
IOSTF_XOFFREAD=16,  
IOSTB_XOFFREAD=4,  
SERERR_BUFERR=4,  
SERERR_DETECTEDBREAK=15,  
IOSTF_WROTEBREAK=2,  
IOSTB_WROTEBREAK=1,  
IOSTF_READBREAK=4,  
IOSTB_READBREAK=2,  
SDCMD_BREAK=10,  
SER_DEFAULT_CTLCHAR=$11130000  
  
#define SERIALNAME/0
```