

# **Sending; ↗ Pathlight PCI SSA Adapter**

216461\_PixelRule.tiff ↗

## **366446\_SCSI.tiff ↗ SCSI Devices**

This PCI Bus driver automatically detects the target adapter and configures itself.

### **Supported Hardware:**

Pathlight PCI SSA Adapter

### **Configuring the Pathlight PCI SSA Adapter Device Driver**

**Note:** See Configure's Help for general information on running the Configure Application.

1. Click the SCSI icon at the top of Configure's Summary window.
2. If you're planning to use the Pathlight PCI SSAI Adapter in place of another adapter named in the list, select the other adapter's name, and click Remove.

3. Click Add in the window.
4. In the Add SCSI Devices panel that opens, select the radio button labeled "Show Drivers for Detected Devices." Select "Pathlight PCI SSA Adapter (v4.03)" from the list, and click Add.  
**Note:** If the Pathlight driver does not show up in the list of detected devices, this indicates a problem with the system setup. You need to run the system's setup program at boot time to ensure that the system BIOS knows about the Pathlight board.
5. Click Done, and then click Save.
6. Choose Quit from the Configure menu.

486444\_PixelRule.tiff ↗

## See also

- "Add a Device" in Configure's on-line help.
- See NeXTanswer 1824 for general information on installing and configuring device drivers.