

# Quick Interrupts

by Michael Sinz

*[Editor's note: This article was written from the programmer's perspective, and doesn't discuss any of the hardware issues. See the ``Appendix K: Zorro Expansion Bus'' section of the third edition of the Amiga Hardware Reference Manual for more information.]*

One of the features of the Zorro III bus is the Quick Interrupt, also known as the vectored interrupt. This feature allows Zorro III hardware to supply a vector number to the system when an interrupt occurs. The system uses this vector number to go directly to an interrupt routine.

## Conventional Amiga Interrupts

The Amiga handles normal interrupts from Zorro II cards using an interrupt server chain. There are two interrupts available from the Zorro II bus, the PORTS and EXTER interrupt server chains. If a driver for a Zorro II card needs to use an interrupt, it adds an interrupt routine to the appropriate chain. When the interrupt occurs, Exec calls each routine in the interrupt chain, which are sorted in priority order. Exec continues until it finds the routine that corresponds to the device that triggered the interrupt.

The server chain allows several routines to share a single interrupt. This means that several devices trigger the same interrupt, so each interrupt routine must do some processing to determine if its card triggered the interrupt or if some other source caused the interrupt. For example, an interrupt routine might examine a register on

its card to determine that the card triggered the interrupt.

Although this scheme allows unrelated pieces of software to easily share an interrupt, it can make the interrupt overhead rather high. These two interrupt server chains also handle interrupts from the CIA chips, which are used to trigger a variety of events. As a result, these server chains can contain a multitude of interrupt routines.

Consider what happens when a Zorro II card generates a PORTS interrupt. Exec has to perform some set up and then step through the PORTS server chain. Exec calls each interrupt routine in priority order looking for the routine that services this interrupt. If there are 20 interrupt routines of higher priority than the card's interrupt routine in the server chain, Exec has to call 20 other routines before it gets to the correct routine.

## Zorro III Quick Interrupts

Quick interrupts avoid the overhead involved in Exec's interrupt server chains. Exec only helps set up the quick interrupt, which it does via the *exec.library* function `ObtainQuickVector()` (see the Autodoc at the end of this article). Once Exec has set up the quick interrupt routine, it does not intervene. Unlike conventional Amiga interrupt routines, which are called as subroutines from Exec's main interrupt code, the Amiga quick interrupt routine jumps directly to the quick interrupt routine using a private vector. This behavior requires quick interrupt routines to take some special precautions.

There are two important differences between a conventional Amiga interrupt routine and a quick interrupt routine. *A quick interrupt routine must save and restore all of the registers it changes, including D0, D1, A0, and A1.* It must do this because, unlike regular interrupt routines, Exec doesn't do it for you. Also, a quick interrupt routine ends with a RTE (return from exception) instruction.

If your quick interrupt routine is 100% self-contained and does not access any operating system structures or routines, then the work is rather simple. Just save the registers you use, perform your interrupt processing, restore the registers, and end with an RTE. If, however, the routine needs to call the OS or use an OS structure, it must check if the interrupt has been delayed. This is necessary in case the interrupt occurred while the CPU just after the CPU had told the hardware to hold off interrupts (see the Autodoc for `ObtainQuickVector()` to find out how to perform this test).

As the Amiga OS is a dynamic operating system, quick interrupts are allocated by the

f software to easily share an interrupt, it  
These two interrupt server chains also  
e used to trigger a variety of events. As  
tude of interrupt routines.

generates a PORTS interrupt. Exec has  
he PORTS server chain. Exec calls  
for the routine that services this  
higher priority than the card's interrupt  
other routines before it gets to the

n Exec's interrupt server chains. Exec  
oes via the *exec.library* function  
nd of this article). Once Exec has set up  
e. Unlike conventional Amiga interrupt  
Exec's main interrupt code, the Amiga  
ing a private vector. This behavior  
special precautions.

conventional Amiga interrupt routine  
*interrupt routine must save and restore*  
*A0, and A1.* It must do this because,  
do it for you. Also, a quick interrupt

ntained and does not access any  
e work is rather simple. Just save the  
ssing, restore the registers, and end  
call the OS or use an OS structure, it  
his is necessary in case the interrupt hit  
are to hold off interrupts (see the  
ow to perform this test).

a, quick interrupts are allocated by the

OS. If your hardware/software wants to  
with ObtainQuickVector(). This routine  
(*not* a pointer  
to an Interrupt structure). If Exec instal  
the vector number. When the quick inte  
vector number to the CPU, which tells th

ObtainQuickVector() returns 0 if there a  
vectors is limited, any Zorro III device th  
back to the Amiga's conventional interr

The LVO for ObtainQuickVector() was a  
implemented until after the initial releas  
the Amiga 4000 and Amiga 1200, Releas  
currently exists to correct this, but a futu  
only works in the developer releases of th  
Zorro III device driver must handle the c  
function should never cause a hardware  
obtain a vector before V39.

exec.library/ObtainQuickVector

NAME  
Function to obtain an install a

SYNOPSIS  
vector=ObtainQuickVector(interr  
d0 a0  
ULONG ObtainQuickVector(APTR);

FUNCTION  
This function will install the  
vector it allocates and returns  
your Quick Interrupt system nee

This function may also return 0  
hardware should be able to ther  
interrupt server chain should t

The interrupt code is a direct  
This means that it is the respo  
of the context saving/restoring

Also, due to the performance o  
need to also watch for "false"  
that come in just after a DISA  
because the interrupt may have  
hardware access is completed.

```
myInt:      move.l  d0,-(sp)
            move.w  _intena
```

If your hardware/software wants to use a quick interrupt, it must allocate a vector and call `ObtainQuickVector()`. This routine accepts a pointer to the quick interrupt code

(and an Interrupt structure). If Exec installed the vector, `ObtainQuickVector()` returns the vector number. When the quick interrupt occurs, the Zorro III card sends this vector number to the CPU, which tells the CPU where the interrupt code is.

`ObtainQuickVector()` returns 0 if there are no more vectors. Since the number of vectors is limited, any Zorro III device that uses quick interrupts must be able to fall back to the Amiga's conventional interrupt scheme.

A LVO for `ObtainQuickVector()` was added for V39, but it was not fully implemented until after the initial release. This means the OS that currently ships with the Amiga 4000 and Amiga 1200, Release 3.00, will always return 0 (no `SetPatch` currently exists to correct this, but a future `SetPatch` may do so). `ObtainQuickVector()` works in the developer releases of the OS that followed the initial release. Since a Zorro III device driver must handle the case where it cannot obtain a vector, this situation should never cause a hardware product to fail. There is no reliable way to obtain a vector before V39.

`exec.library/ObtainQuickVector`

`exec.library/ObtainQuickVector`

Function to obtain and install a Quick Interrupt vector (V39)

```
vector=ObtainQuickVector(interruptCode)
d0                                a0
```

```
ULONG ObtainQuickVector(APTR);
```

This function will install the code pointer into the quick interrupt vector it allocates and returns to you the interrupt vector that your Quick Interrupt system needs to use.

This function may also return 0 if no vectors are available. Your hardware should be able to then fall back to using the shared interrupt server chain should this happen.

The interrupt code is a direct connect to the physical interrupt. This means that it is the responsibility of your code to do all of the context saving/restoring required by interrupt code.

Also, due to the performance of the interrupt controller, you may need to also watch for "false" interrupts. These are interrupts that come in just after a `DISABLE`. The reason this happens is because the interrupt may have been posted before the `DISABLE` hardware access is completed. For example:

```
myInt:      move.l  d0,-(sp)      ; Save d0...
            move.w  _intenable,d0 ; Get interrupt enable state
```

# Amiga Mail

Volume II

```
                                btst.l  #INTB_INTEN,d0  ; Check if pending disable
                                bne.s   realInt          ; If not, do real one...
exitInt:                        move.l  (sp)+,d0         ; Restore d0
                                rte                     ; Return from int...
;
realInt:                        ; Now do your int code... d0 is already saved
                                ; ALL other registers need to be saved if needed
                                ; This includes a0/a1/d0/d1 as this is an interrupt
                                ; and not a function call...
                                ;
                                bra.s   exitInt          ; Exit interrupt...
```

If your interrupt will not play with system (OS) structures and your own structures are safe to play with you do not need to check for the disable. It is only needed for when the system is in disable but that "one last interrupt" still got through.

## NOTE

This function was not implemented fully until V39. Due to a miscue it is not safe to call in V37 EXEC. (Sorry)

## INPUTS

A pointer to your interrupt code. This code is not an EXEC interrupt but is directly connected to the hardware interrupt. Thus, the interrupt code must not modify any registers and must return via an RTE.

## RESULTS

The 8-bit vector number used for Zorro-III Quick Interrupts. If it returns 0, no quick interrupt was allocatable. The device should at this point switch to using the shared interrupt server method.

## SEE ALSO



---

```
0 ; Check if pending disable
; If not, do real one...

; Return from int...

e... d0 is already saved
need to be saved if needed
/d0/d1 as this is an interrupt
```

```
; Exit interrupt...

system (OS) structures and your
you do not need to check for
when the system is in disable but
```

ly until V39. Due to a miscue

is code is not an EXEC interrupt  
ware interrupt. Thus, the  
gisters and must return via

o-III Quick Interrupts  
as allocatable. The device  
the shared interrupt server

