

Technical Note TN1114

LW 8.5.1 CopyBits Support: Transparent and Clipped Images

CONTENTS

[Transparent Mode](#)

[MaskRgn Clipping](#)

[Limitations](#)

[Summary](#)

[References](#)

[Downloadables](#)

In the current LaserWriter 8 driver, the Chooser lists printers which are available on the AppleTalk network (either LocalTalk or AppleTalk) with an NBP type of "LaserWriter". When the user selects one of these printers, LaserWriter 8 creates a desktop printer by sending an Apple Event to the Finder. In the past, this mechanism of setting up printers has served the needs of most users. However, with LaserWriter 8.5.1, Apple is responding to several requests for more flexible desktop printing functionality. To this end, Apple has introduced a new application called Desktop Printer Utility which enables users to create additional types of desktop printers. Users can now create desktop printers which use the Unix *lpr* protocol for printing, in addition to the regular AppleTalk PAP printers. There are also "hold" printers which represent local print queues and "virtual" printers which represent printers which are not available on the network.

Along with the expanded capabilities, Desktop Printer Utility is also customizable. LaserWriter 8.5.1 and Desktop Printer Utility (together) support the creation and use of desktop printers known as Custom DTPs. When printed to, Custom DTPs cause the LaserWriter 8.5.1 driver to create a PostScript file and to launch an application that can post-process the PostScript. This post-processing application can do anything it likes with the PostScript file, such as

converting the PostScript into another file format, transferring the file to another location using a modem or a network connection, or displaying the PostScript file to the user. This Technote describes how a developer might customize Desktop Printer Utility for use with an application.

Updated: [Feb 06 1998]

Transparent Mode

One transfer mode previously unsupported by the LaserWriter driver is the transparent transfer mode. This mode allows drawing of images other than 1-bit deep so that any sample in the source which is the transparent color (defined as the QuickDraw background color) will not be painted to the destination. The advantage of this mode is that it lets a deep (> 1-bit) image have holes in it by coloring the holes in the image with the transparent color. Whereas previously the LaserWriter driver would paint these images as if the transfer mode were `srcCopy`, LaserWriter 8.5.1's new imaging code now handles the transparent mode.

[Back to top](#)

maskRgn Clipping

Another previously unsupported feature of `CopyBits()` was the ability to pass in a mask (via the `maskRgn` field) to clip out portions of the destination image. Previous LaserWriter drivers completely ignored the `maskRgn` passed to `CopyBits()`. The new imaging code in LaserWriter 8.5.1 now supports the supplied `maskRgn`.

Note:

While the LaserWriter 8.5.1 driver now handles a supplied `maskRgn` to a `CopyBits` call, we do not do any special handling of the clip provided in the `grafPort`. `GrafPort` clipping is still handled by clipping only to the bounding rectangle of the port's `clipRgn`, both for `CopyBits` calls as well as line art and text drawing. Apple considered more generalized support for the port `clipRgn` but has rejected it to date mainly due to compatibility concerns.

[Back to top](#)

Limitations

There are some known limitations with the added `CopyBits()` support that you should be aware of. They are:

- Extremely complex clipping regions may occasionally fail on Level 1 or Level 2 devices in low printer memory conditions. The result is that the output will not preserve the clip, and the image will print as if the `maskRgn` parameter is ignored. Specifically, for PostScript Level 1 printers, there is a hard coded limit to how complex a clip can be, regardless of the printer's installed memory. If the clip is more complex than this limit, the LaserWriter driver ignores the

`maskRgn` parameter. For Level 2 printers, the limits are completely memory-based and generally much more flexible. However, once again, in low-memory conditions, the clip may still fail. On PostScript Level 3 printers, all clips should always print correctly regardless of the complexity of the clip since the driver uses the PostScript Level 3 masked image to support this feature.

- Since the LaserWriter driver implements the transparent mode via clipping, complex transparent regions may occasionally fail on Level 1 or Level 2 devices in low-memory conditions as described above. The result is that the output does not preserve the transparency, and the pixels image with the background color instead.
- For 2, 4, and 8-bit images with a color look-up table (CLUT), the LaserWriter 8.5.1 driver only supports one index which maps to the background color. Although the CLUT may contain many index values which have the background color and are therefore, in principle, transparent when displayed onscreen, the driver searches the look-up table for the first index which corresponds to the background color. Index samples with that index value are printed as transparent. Other index values which correspond to the background color are not treated as transparent but are printed as the background color.
- In order to maintain compatibility with many applications, the LaserWriter 8.5.1 driver will ignore a `maskRgn` which is an empty region under some circumstances (e.g. some rotated text and graphics). Some applications have used the fact that previous drivers always ignored the `maskRgn` parameter to clip out certain data when printing to QuickDraw printers. Relying on this 'feature' is not recommended, and the fact that there are some edge cases where a zero clip is ignored for compatibility reasons may be a temporary 'feature' of the driver. To avoid accidentally encountering these cases, when you really want a zero clip, either do not draw the image (preferred) or use `grafPort` clipping to clip it.

[Back to top](#)

Summary

New imaging code in the LaserWriter has opened up some new functionality for the QuickDraw `CopyBits()` call. We encourage you to try LaserWriter 8.5.1 with your application and any PostScript device.

[Back to top](#)

References

[Inside Macintosh: Imaging With QuickDraw, Chapter 3 and Appendix B.](#)

[Apple's Technote web site](#)

PostScript Level 3 documentation from [Adobe Systems Incorporated.](#)

[Back to top](#)

Downloadables



Acrobat version of this Note (K).

[Download](#)