

MASTERSEAL® 330

Penetrating concrete sealer

DESCRIPTION:

MASTERSEAL 330 is a low viscosity one component urethane sealer designed for use on concrete. The penetrating properties of MASTERSEAL 330 ensure the concrete surface is sealed, providing a moisture-resistant barrier and reducing dusting.

RECOMMENDED FOR:

- Warehouse floors
- Processing areas

FEATURES/BENEFITS:

- One component system for easy application
- Multiple coat capability for higher build
- Penetrates to resist liquid absorption
- Minimal recoat time to reduce downtime
- Helps reduce dusting
- Extended shelf life

PACKAGING/ESTIMATING:

MASTERSEAL 330 is packaged in 1, 3.5 and 55 U.S. gallon (3.78, 13.25 and 208 liter) units. Coverage rates are 300 ft²/gallon @ 5 mil/coat (7.35 m²/liter).

PERFORMANCE DATA:

Composition	One component moisture cured urethane
Solids Content	30% by weight
Viscosity	Range - 30 cps to 40 cps. @ 77 °F (25 °C)
Penetration	Up to 30 mils
Flash Point	111°F (43 °C)
	<i>(Pensky-Martens Closed Cup)</i>
Unit Weight	7.93 lb/gal (0.95 kg/liter)
Number of Coats	One coat is normally required for new, "once over" steel troweled surfaces. Multiple coats may be applied if prior coat is tack-free.

Final Curing	Allow 16 hours at 77 °F (25 °C) before service
Pot Life	Longer than 8 hours 77 °F (25 °C)
Recoat Time	Typically 1 to 2 hours 77 °F (25 °C)
Color	Clear
Storage & Shelf Life	MASTERSEAL 330 is stable for at least 1 year if stored in a cool, dry place and kept in original, unopened containers.

APPLICATION:

MASTERSEAL 330 may be applied in successive coats with minimal recoat time, thus, the desired gloss can be easily achieved in situations where light reflectivity of the floor surface is a requirement. Application is done using a standard paint roller, brush or conventional spray equipment.

Use methyl ethyl ketone (MEK) or lacquer thinner for cleaning application tools.

LIMITATIONS:

- Storage temperatures should be maintained between 60 °F and 75 °F (16 °C and 24 °C). **KEEP FROM FREEZING!** Do not store at temperatures above 110 °F (43 °C).
- MASTERSEAL 330 is a one component polyurethane sealer which is formulated for industrial and professional use only, and must be kept out of the reach of children. These products contain chemicals which are **COMBUSTIBLE** and may be potentially **HARMFUL** to your health if not stored and used properly. Hazards can be significantly reduced by observing all precautions which are found on Material Safety Data Sheets, product labels, and technical literature. Please read this literature carefully before using product.

**Master Builders, Inc.
United States**

23700 Chagrin Boulevard
Cleveland, Ohio 44122-5554
(800) MBT-9990
Fax (216) 831-6910

Canada

3637 Weston Road
Toronto, Ontario M9L 1W1
(800) 387-5862
Fax (416) 741-7925

Mexico

Bld. M. Avila Camacho 80, 3er Piso
53390 Naucalpan, México
011-525-557-5544
Fax 011-525-395-7903