



# Power Macintosh 7600 Series

DISCONTINUED

## Features

### High performance

- 120-MHz PowerPC 604 processor
- Built-in floating-point processor and 32K cache
- 256K level 2 cache
- Built in graphic acceleration

### Communications and multimedia

- 64-bit VRAM graphics subsystem
- Two high-speed serial ports compatible with GeoPort and LocalTalk cables
- Quadruple-speed CD-ROM drive
- 16-bit stereo audio input and output
- 24-bit composite and S-video input
- Support for speech-recognition and text-to-speech capabilities
- Optimized for QuickTime Conferencing software

### Expandability

- Three industry-standard PCI expansion slots
- SCSI connector for hard disks, CD-ROM drives, and other SCSI devices
- Internal expansion bay for additional hard disk drive

### Compatibility

- Includes 10BASE-T and AAUI Ethernet connectors
- Supports Open Transport networking software (TCP/IP and AppleTalk)
- Runs most 680x0 Macintosh applications as well as applications accelerated for Power Macintosh computers
- Reads Mac OS, Windows, MS-DOS, OS/2, and ProDOS floppy disk formats
- Runs MS-DOS and Windows applications via optional PC Compatibility Cards
- Comes with all of the software required for Internet access

### System 7.5 software

- Makes working with different applications consistent, so they're easier to learn and use
- Allows easy customization of your Macintosh to reflect the way you work
- Provides active assistance in learning new features with Apple Guide

If you need a computer that offers increased performance and expandability for your business, regardless of its size, the Power Macintosh 7600/120 delivers. With a 120-megahertz PowerPC 604 RISC processor, the Power Macintosh 7600/120 gives you all the advantages of PowerPC technology. Built-in video-input capability, high-resolution graphics, and CD-quality stereo sound add vitality to everyday business projects. And because the Power Macintosh 7600/120 optimizes the transfer of video data, it is an ideal system for videoconferencing.

The three industry-standard Peripheral Component Interconnect (PCI) expansion slots on the Power Macintosh 7600/120 let you customize the computer easily to more precisely meet your needs. You can find many PCI cards for a variety of uses, including graphics, storage, and high-speed networking. And if you want to use your Power Macintosh 7600/120 to run MS-DOS and Windows applications as well as software written for the Macintosh, you can install an Apple PC Compatibility Card in one

of the system's PCI slots—and switch instantly between the two computing environments.

Connecting your Power Macintosh 7600/120 computer to an Ethernet network is easy, because it includes both AAUI and 10BASE-T connectors. With an optional PC Compatibility Card, you can connect both the card and Power Macintosh to a network simultaneously.

Today, more and more computer users are discovering the wealth of information, communications resources, and opportunities offered by the Internet. The Power Macintosh 7600/120 makes it easy to get involved in this rapidly expanding community, because it comes with all of the software you need for easy Internet access.

Whether you are selecting computers for a large corporation or a single-person home office, the Power Macintosh 7600/120 system offers PowerPC performance and PCI expandability giving you the versatility you need for professional computing.





# Power Macintosh 7600 Series

## Ordering Information

### Power Macintosh 7600/120

- Power Macintosh 7600/120 computer with 16MB of RAM, a built-in 1.4MB Apple SuperDrive floppy disk drive, an internal 1.2GB hard disk drive, an internal quadruple-speed CD-ROM drive, and a PlainTalk microphone. Includes mouse; system software version 7.5.3 or later; Internet access software; complete setup, learning, and reference documentation; and limited warranty.

### PC Compatibility Card Solutions

Order No. M4092LL/A

- PC Compatibility Card with Pentium 100-MHz processor

Order No. M4091LL/A

- PC Compatibility Card with 586 100-MHz processor

### Power Macintosh Processor Upgrade Card

Order No. M4731LL/A (120 MHz) and M4875LL/A (132 MHz)

### Power Macintosh GeoPort Telecom Adapter

Order No. M3127LL/C

### Apple QuickDraw 3D Accelerator Card

Order No. M4333LL/A

Product specifications are subject to change. Check with your Apple reseller for the most current information about product specifications and configurations.

## Technical Specifications

### Microprocessor

- PowerPC 604 microprocessor running at 120 MHz
- Integrated floating-point unit and 32K cache
- High-speed system bus (up to 50 MHz)

### Memory

- 16MB of RAM, expandable to 512MB via 8 DIMM sockets
- 4MB of ROM
- 256K level 2 cache

### Disk drives

- Internal 1.2GB SCSI hard disk
- Internal Apple SuperDrive floppy disk drive
  - Accepts high-density 1.4MB disks and 800K disks
  - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks
- Internal AppleCD 600i quadruple-speed CD-ROM drive
- Expansion bay for additional 3.5-inch hard disk

### Interfaces

- Three PCI expansion slots compatible with PCI 2.0-compliant cards
- Two high-speed DMA serial (RS-232/RS-422) ports compatible with LocalTalk and GeoPort cables
- 10BASE-T and AAUI-15 Ethernet connectors; optional PC Compatibility Cards provide multinode support for simultaneous network connections
- Internal Fast SCSI bus (up to 10MB/s)
- External SCSI bus (up to 5MB/s)
- Apple Desktop Bus (ADB) expansion port
- RCA phono jacks for line-level stereo audio input and output
- Mini jacks for stereo audio input and output
- All sound ports support 16-bit audio and up to 44.1-kHz sampling rate
- DB-15 connector for monitor
- Composite connectors (RCA phono jacks) for composite video input
- S-video input connector
- Internal digital audio/video (DAV) connector for video compression/decompression cards

### 24-bit video input

- Real-time video playthrough of up to 640 by 480 pixels with NTSC; 768 by 576 pixels with PAL and SECAM
- Up to 320- by 240-pixel capture up to 15 frames per second with NTSC
- Maximum capture size of 640 by 480 pixels with NTSC

### Graphics support

- 2MB of VRAM, expandable to 4MB
- Fast 64-bit data path to VRAM
- Support for display resolutions of up to 1,280 by 1,024 pixels
- 24-bit color up to 1,152- by 870-pixel resolution
- Refresh rate of up to 75 Hz

### GeoPort telephony\*

- 14.4-Kbit/s modem support
- V.17 fax support
- GeoPort Fax and GeoPort Telephony software included
- Speakerphone and answering-machine capability

### Clock/calendar

- Custom integrated circuit with long-life battery

### Keyboard and mouse

- Supports ADB keyboards with numeric keypads
- Comes with an ADB Mouse II

### Electrical requirements and compliance

- Line voltage: 100 to 240 V AC, RMS single phase
- Frequency: 50 to 60 Hz, single phase
- Power: 150 W maximum, not including display

### ADB power requirements

- Maximum current draw for all devices: 500 mA (a maximum of three ADB devices is recommended)
- Mouse draws 10 mA
- Keyboard draws 25 to 80 mA (varies with keyboard used)

### Size and weight

- Height: 6.15 in. (15.6 cm)
- Width: 14.37 in. (36.5 cm)
- Depth: 16.93 in. (43.0 cm)
- Weight: 22 lb. (9.97 kg)

### Environmental requirements

- Operating temperature: 50° to 104° F (10° to 40° C)
- Storage temperature: -40° to 116° F (-40° to 47° C)
- Relative humidity: 5% to 95% noncondensing
- Maximum altitude: 10,000 ft. (3,048 m)

\* Requires GeoPort Telecom Adapter

Apple Computer, Inc.  
1 Infinite Loop  
Cupertino, CA 95014  
(408) 996-1010  
<http://www.apple.com>

© 1997 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, Apple SuperDrive, AppleTalk, GeoPort, LocalTalk, Macintosh, PlainTalk, Power Macintosh, ProDOS, and QuickTime are trademarks of Apple Computer, Inc., registered in the U.S.A. and other countries. AppleCD and Mac are trademarks of Apple Computer, Inc. MS-DOS and Windows are registered trademarks of Microsoft Corporation. OS/2 is a trademark of International Business Machines Corporation; PowerPC is a trademark of International Business Machines Corporation, used under license therefrom. Mention of non-Apple products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place between the vendors and the prospective users. April 1996. Product specifications are subject to change without notice. Printed in the U.S.A. L01072B