

InsideScan™

Upgrade

**InsideScan™ 1.0.1
Version for Mac OS**

**© 2000 PowerSolutions S.r.l.
All rights reserved**

This page intentionally left blank

INTRODUCTION

This document describes changes to InsideScan that were made after the 1.0 release.

NEW FUNCTIONS

InS-Register (function added to version 1.0.1)

Syntax

```
External ( "InS-Register";  
          "licensee name  
          |registration code" )
```

Parameters

licensee name: licensee developer name

registration code: distribution registration code

Result

InS-Register returns an empty result if there aren't any problems. In the case of an error, an error code is returned.

Description

InS-Register allows you to register InsideScan to distribute software solutions, by specifying in *licensee name* and in *registration name* the information reported on your developer license.

This function must be executed first, to remove all the demo restrictions.

InS-Register is an external function useful only to developers that purchase a Developer License to distribute its own software solutions to third parties.

Examples

In the next example, InsideScan is registered by the developer Mario Rossi to distribute it as a part of its own software solution:

```
Set Field [ "gResult", External( "InS-Register";  
                                "Mario Rossi|ABCD-EFGH-IJKL-MNOP-QRST" ) ]  
  
If [ "not (IsEmpty(gResult))" ]  
    Show Message [ "Invalid registration code." ]  
End If
```

NEW ERROR CODES

Registration Errors

| Code | Description |
|-------------|---------------------------|
| 70003 | Invalid registration code |