

C VERSUS C++

C is a subset of C++. Any C program file should compile on a C++ compiler*. If your wondering whether you should learn one or the other - don't. They are "virtually" the same (pun intended). However, most people would probably recommend learning C++ versus just C. It's sort of like running a marathon only to stop just short of the finish line and say, "well, I've gone far enough".

As a note, every program in this reference has been compiled and run to verify syntax and assure that the code snippets are correct.

PROGRAM FORM

As an ongoing tradition, the first program you write should be the infamous "Hello World" program.

```
// hello.cp
#include <iostream.h>

void main( void )

    cout << "hello world" << endl;

// end hello.cp
```

Anything on a line after a double slash (//) is ignored by the compiler and is the standard way of commenting code. Another way to comment your code is to use the slash-asterisk method. The following program "square.cp" is almost as simple as the one above, except it demonstrates the basics of using functions as well as both styles of comments.

```
// square.cp
/*
    Sometimes it convenient to use the "old" style comments, especially
    when you have more than one line of stuff to say.
*/

#include <iostream.h> // standard library.

#define MAX 10        // preprocessor directive.

int DoSquare(int);    // function prototypes required in C++.

void main( void )     // main is the start of all C programs.

    int n;
    for(n=1;n<MAX;n++)
        cout << n << " squared = " << DoSquare(n) << endl;

int DoSquare(int m)   // function definition.

    m = m * m;
    return m;         // return value.

// end square.cp
```

White space is ignored in C/C++. Brackets are used to group (or enclose) multiple statements. Function calls are depicted with parenthesis () at the end of a function name which enclose variables which are used during the function

call. Semicolons depict the end of a statement (i.e., you can place multiple statements on a single line separated by semicolons if you wanted).

DATA TYPES AND TYPE CONVERSION

The following program identifies the built-in data types supported by C and methods for converting between these data types.

```
// types.cp
#include <iostream.h>

void main( void )

// declarations
char          c = 'A'; // usually 1-byte long.
short int     si= 1;   // minimum range +/-32767.
short         s = 2;   // short same as short int.
int           i = 3;   // minimum range +/-32767.
long int      li= 4;   // minimum range +/-2147483647.
long          l = 5;   // long same as long int.
float         f = 10.1; // min 6 digits (decimal) precision.
double        d = 11.2; // min 10 digits (decimal) precision.
long double   ld= 12.3;

unsigned char  uc;      // unsigned integers can only store
unsigned short int usi; // positive numbers.
unsigned int   ui;
unsigned long int uli;

signed char    sc;      // signed integers can store positive
signed short int ssi;   // or negative numbers.
signed int     si2;
signed long int sli;

// simple assignment
s = 3;
cout << s << endl;

// automatic conversion
f = s * i / d;
cout << f << endl;

// inline conversions
ld = (long double)i;
s = short(d);
cout << ld << endl << s << endl;

// end types.cp
```

STRINGS

Strings in C are "null terminated". This means that the following declaration;

```
char *str = "Test string";
```

allocates a block of memory 12 bytes long and returns a pointer 'str' to the first character in the string. The first 11 bytes contain the characters "Test string", the 12th byte contains NULL (i.e., \0 or zero). To declare an empty string, use the following:

```
char *nullStr = "";
```

Since the MacOS is based on Pascal strings, it is important that the difference be discussed. The same string in Pascal would also be 12 bytes long, however, the first character in the string is actually the integer '11' which defines how many characters are in the string. Your compiler should provide functions such as CtoPstr() and PtoCstr() to convert between the two formats. If you want to declare a Pascal-style string in C, use the following:

```
char *Pstr = "\pThis is a Pascal string";
```

CONSTANTS

```
// constant definition examples
#define INTEGER      123
#define LONG         123L
#define UNSIGNED_LONG 123UL
#define FLOAT        12.3F
#define CHAR_CONST   'A'
#define OCTAL        037      /* leading zero */
#define HEXADECIMAL  0X5
#define STRING       "characters"

// escape sequences
#define ALERT        \a
#define BACKSPACE    \b
#define FORMFEED     \f
#define NEWLINE      \n
#define CARRIAGE_RETURN \r
#define HORIZ_TAB     \t
#define VERT_TAB      \v
#define BACKSLASH     \\
#define QUESTION_MARK \?
#define SINGLE_QUOTE  \'
#define DOUBLE_QUOTE  \"
#define OCTAL_SEQ     \o13     /* vertical tab */
#define HEX_SEQ       \x7      /* alert */

// enumeration constants
enum boolean FALSE, TRUE ;
enum identifiers first = 1, second, third ;
```

The first item in an enumeration statement has a value of 0, the next 1, the next 2, etc. unless specified values are provided.

TERMINOLOGY

There's a lot of fancy terminology in C++ which tends to confuse the novice. Here are some of the buzz words that are used in object-oriented programming and what they mean:

Instances - Variables of a pre-defined class type are called instances of that class, or objects.

Objects - Objects are variables which are instances of a class. Here is a simple example:

```
class Student          // define class Student

char *name;
char *address;
int id;
```

```
void input( void ); // class methods
void print( void );
```

```
Student freshman; // freshman is an object,
                  // a class variable, and
                  // an instance of the class Student.
```

Methods - Methods are nothing more than member functions of a class.

Polymorphism - When the same function works on different types of objects, it's called polymorphism. For example, you OPEN a door, you OPEN a window, and you OPEN your eyes. Polymorphism means "many different forms".

Encapsulation - The combination of member data and member functions (or methods) into an object. With C++, you assign an object data attributes and methods which operate on the data. Generally speaking, all of the code for a particular class of objects is maintained in a separate source code file, or in other words, it's encapsulated.

Inheritance - One of the coolest things about C++ is that you can create an object which inherits all of the capabilities of a parent object, and then make minor modifications to suit your needs. For example, if there was a window class which did everything you needed except for, say, window resizing. You could create a subclass of the window class and then add the code needed to perform the task. There are two important things to realize: 1) you only need to add the code to perform the specific task you need, and; 2) you don't need to original source code for the parent class to make modifications.

Multiple Inheritance - Inheriting capabilities or traits from more than one parent defines multiple inheritance. There are some problems with using multiple inheritance and many programmers avoid it at all costs (similar to using goto statements), but there are times when it can be useful.

Virtual Function (or method) - Allows polymorphism by defining a function which is called by an object at runtime (i.e., late binding) instead of at compile time (i.e., early binding).

* There are some minor things you need to worry about if your calling a function from a precompiled C object file within a C++ program. Reference the section "Functions" for more information.