

DIRQ COMMANDS

Command	Action
DIRQ_ADD	Tells the dictionary to add a word to the currently selected word list.
DIRQ_CLOSE	Signals the dictionary to close a word list, writing any changes to disk if necessary.
DIRQ_CONFIGURE	Tells the dictionary to display a configuration dialog to the user.
DIRQ_DELETE	Tells the dictionary to remove a word from the currently selected word list.
DIRQ_DESCRIPTION	Asks the dictionary to return the name of its module.
DIRQ_FLUSH	Signals the dictionary to reinitialize the currently selected word list, discarding any changes.
DIRQ_OPEN	Tells the dictionary to open the specified word list and return a handle for the word list (usually called with the name of a file from which the word list can be loaded).
DIRQ_QUERY	Asks the dictionary to return a TRUE or FALSE flag indicating whether the dictionary supports the specified DIRQ function.
DIRQ_RCCHANGE	Signals the dictionary that a change has occurred in an RC data structure that contains the dictionary's entry point.
DIRQ_SETwordlistS	Selects a word list that was previously opened with a DIRQ_OPEN command.
DIRQ_STRING	Presents a string to the dictionary for matching against its currently selected word list.
DIRQ_SUGGEST	Presents a string to the dictionary, asking for the best guess at a match against its currently selected word list.
DIRQ_SYMBOLGRAPH	Presents an entire symbol graph, which can be enumerated into many possible strings, to the dictionary for optional matching against its currently selected word list.
DIRQ_USER	Reserved for communication between applications and custom dictionaries.