

**NAME**

mpsym – locates missing symbolic information in an mpatrol log file

**SYNOPSIS**

mpsym [options] [progfile [logfile]]

**DESCRIPTION**

The mpsym command is used to parse a log file produced by the mpatrol library and uses a debugger to append symbol names and source level information to code addresses in stack tracebacks. This should be used if the USEDEBUG option is not supported on a particular platform or does not work properly with a specific program. It will replace all existing symbols and source level information associated with the stack tracebacks in the mpatrol log file and will display the resulting log file on the standard output file stream.

The progfile argument must be the filename of the executable file that produced the mpatrol log file but if progfile is omitted then mpsym will use a.out as the name of the executable file to use. The mpsym command will read the symbol table and debugging sections from this file in order to map the code addresses that appear in the mpatrol log file into symbol names and source level information. If the executable file does not contain a symbol table then no symbol names will be available and if it does not contain the appropriate debugging sections then no source level information will be available either. Obviously, if the executable file is not the same as the one that created the mpatrol log file then the final output will be wrong.

The logfile argument must be a valid mpatrol log filename but if logfile is omitted then mpsym will use mpatrol.log as the name of the log file to use, or progfile.log if it can't find that. The mpsym command makes two passes over the log file so the file must be randomly-accessible.

The mpsym command currently uses gdb as the debugger with which to obtain the additional information about the code addresses in the mpatrol log file. It also makes use of several UNIX text processing commands, including perl if it is installed, in order to extract information from the debugger's output and from the log file. As a result, the mpsym command is only likely to work on UNIX platforms or on systems which have the necessary commands installed. By default, it is set up to work on 32-bit platforms, but this can be changed by altering the POINTER definition in the mpsym file itself (this is only necessary if perl is not installed).

**OPTIONS**

--help [-h]

Displays a quick-reference option summary.

--version [-V]

Displays the version number of the mpsym command.

**SEE ALSO**

mpatrol(1), mprof(1), mptrace(1), mleak(1), mpedit(1), hexwords(1), gdb(1), perl(1), libmpatrol(3), libmpalloc(3).

The mpatrol manual and reference card.

<http://www.cbmamiga.demon.co.uk/mpatrol/>

**AUTHOR**

Graeme S. Roy <graeme.roy@analog.com>

**COPYRIGHT**

Copyright (C) 1997-2001 Graeme S. Roy <graeme.roy@analog.com>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.