

Contents

GoldWave is a sound editor, player, recorder, and converter. It can create sound files for music CDs, dance recitals, websites, answering machines, or Windows sounds. A full set of effects and editing features are included for professional sound production. Create high quality audio CDs by using GoldWave in conjunction with CD Recorder software.

Before using GoldWave, make sure sound drivers have been installed and configured with the Windows Device Manager.

To learn how to use help, press F1.

Introduction

[Main Window, Control Window, and Sound Windows](#)

[Editing Overview](#)

[Hard Drive Storage Versus RAM Storage](#)

[Developer](#)

Getting Started:

[Playing Sounds](#)

[Recording Sounds](#)

[Selecting Part of a Sound](#)

Commands

[File Menu Commands](#)

[Edit Menu Commands](#)

[Effect Menu Commands](#)

[View Menu Commands](#)

[Tool Menu Commands](#)

[Options Menu Commands](#)

[Window Menu Commands](#)

[Keyboard Commands](#)

How To...

[Convert files from one format or type to another](#)

[Directly edit the waveform with the mouse](#)

[Play a sound](#)

[Record a sound](#)

[Select part of a sound](#)

[Set reference/cue points](#)

[Select a device for playback or recording](#)

[Create a tremolo effect](#)

GoldWave Windows

GoldWave initially displays three types of windows: the **Main** window, the **Control** window, and **Sound** windows. The **Main** window contains a menu bar, tool bars, and information/status bars. This window keeps all the **Sound** windows together. It is similar to the main window of a word processor, where you can have several document windows open at once. In GoldWave, you can have several sounds open at once to copy and paste between them. The Options | Tool Bar command lets you configure and arrange tool bar buttons. You can right-click on some items in the upper status bar to change the format of the data shown.

The **Control** window contains real-time visuals and sound device controls. The visuals display the sound during playback or recorded. The controls determine the volume, left/right balance, and speed at which sounds are played. A set of standard cassette deck buttons for playing and recording sounds are contained in this window. Several features can be configured using the properties button.

Sound windows are created whenever sound files are opened. You can open as many sounds as you like, provided there is enough memory and storage space, but only one file can be edited or played at a time. **Sound** windows display a graph of the sound. Mono sounds are shown with a single green graph. Stereo sounds are shown using a green graph for the left channel and a red graph for the right channel.

Between the graph and time line is the Cue Points slot, which displays any cue points stored in the file. Right click on the slot to see a cue points menu.

Below the graph's time line is the **Overview Bar**. It always shows the entire file and provides useful information about what part of the sound is currently selected and what part of the sound is displayed in the upper graph.

You can zoom in on a section of a sound by using the View Menu Commands or by selecting a region with the right mouse button. The Options | Colour and the Options | Window commands let you configure the appearance of these windows.

See Also

File Menu Commands

View Menu Commands

Cue Points

Cue Points Menu

Control

Editing Overview

Almost all commands in GoldWave operate on the currently selected part of a sound. The selected part, or **selection**, is the highlighted part of the sound graph between two vertical markers. The vertical markers are cyan lines located at the far left side (**start marker**) and far right side (**finish marker**) of the graph.

GoldWave provides several ways of setting the selection. You can:

- Use the standard click-and-drag method used in most other Windows programs.
- Click the right mouse button to display a menu where you can choose **Set Start Marker** or **Set Finish Marker**.
- Click-and-drag the left mouse button over one of the cyan markers to drag it (useful for precise adjustments of the end points).
- Click-and-drag using the right mouse button, then choose **Select** from the menu that appears.
- Use the [Edit | Marker | Set](#) command.
- Use the [Edit | Channel](#) submenu to select one channel of a stereo file.

Mouse selection methods work in both the large sound graph or in the small Overview graph.

If you just click the left mouse button without dragging, the start marker is moved. If you just click the right mouse button, a context menu appears, which can be used to start playback at any position. If you click-and-drag with the right mouse button, you can play or zoom in on that area without altering the current selection.

To disable the right-click menu and use the older left/right mouse button selection method, select that setting under the [Options | Window](#) command.

See Also

[Edit | Marker | Set](#)

[Direct Editing of the Waveform](#)

[Edit Menu Commands](#)

[View Menu Commands](#)

[Cue Points](#)

[Hard Drive Versus RAM Storage](#)

Hard Drive Storage Versus RAM Storage

GoldWave supports **hard drive** based editing and **RAM** based editing. These features are described below. Hard drive storage is used by default. Use the [Options | Storage](#) command to configure the storage mode.

In **hard drive** based editing, the entire sound is stored in a temporary file on your hard drive where it can be modified. This allows you to edit huge files provided the required drive space is available. Only a small amount of RAM is required for each opened sound. The drawback is that editing and effects processing take more time since audio data must be transferred to and from the drive.

In **RAM** based editing, the entire sound is stored in your computer's memory. This allows you to edit and process files very quickly. It saves time and reduces the load on your hard drive. The drawback is that the size of the files must be small enough to fit in the available RAM. If you edit or record large files, Windows will start swapping memory to the hard drive, which degraded performance significantly and may cause defects when recording.

GoldWave does not copy a file to temporary storage until it is edited, unless the file is compressed. MP3 files, for example, have to be decompress into temporary storage before GoldWave can edit them. Such files may require over 20 times the amount of compressed storage when opened. A 10MB MP3 file could require over 200MB of storage space.

See Also
[Options | Storage](#)

File Format Plug-ins

GoldWave supports external file format plug-ins for opening and saving files. These plug-ins are created by other developers by using the [GoldWave Plug-in Development Kit](#) to handle file types that GoldWave does not support directly.

You can use the [Options | File Formats](#) command to enable and disable plug-ins or to change the order in which they are used.

When you open a file in GoldWave, these steps are followed:

- 1) If the file type is a CD audio (CDA) track, you are advised to use the [CD Reader](#) tool and no further processing occurs.
- 2) For all other file types, the file is passed to each file format plug-in module until one is able to handle the file. The order is configured under the **File Plug-in Precedence** tab of the [File Format Options](#) window.
- 3) If none of the plug-ins support the file format, then the **Undetectable Types** list under the [File Format Options](#) window is used to determine if type and attributes have been associated with the file type. If so, the file is open automatically using those attributes.
- 4) If there are no associations, then the [File Format](#) window is displayed so that the attributes can be specified manually. Chances are that compressed files cannot be open and decoded properly unless a new plug-in is installed for that file type.

See Also

[Options | Storage](#)

Developer

GoldWave Incorporated is a Canadian corporation founded in 2001 by Chris Craig after many years of independent software development. The company's goal is to provide high quality, inexpensive, and easy to use digital audio and video software.

Contact Information

Mail:

GoldWave Inc.
P.O. Box 51
St. John's, NF
CANADA A1C 5H5

Websites:

Company: <http://www.goldwave.com/>
Purchase: <http://www.goldwave.com/gwregister.html>
Contact: <http://www.goldwave.com/contact.html>

File Menu Commands

New

Displays the New Sound window where you can specify the attributes and length of a new file. New files are virtually created and require no storage until changes are made. When the new file is saved, the Wave (.wav) format is selected by default. Use the Options | File Formats command to change the "default save format".

Open

Opens an existing sound file. If GoldWave does not recognize the file's format, the File Format window is displayed. For unrecognized formats, you can associate a default format with a file name extension by using the Options | File Formats command. The settings in Options | Storage control where the file is stored for editing.

Close

Closes the current sound.

Information

Sets the file's title, author, description, and copyright information. This information is saved only in some file types, such as .wav, .aiff, .xac, and .mp3.

Batch Processing

Converts and/or processes a group of files.

Save

Saves the current sound.

Save As

Saves the current sound under a different name and/or format. This command can be used to convert files from one format to another by selecting appropriate type and attributes.

Save Selection As

Saves the selected part of the current sound to the hard drive under a different name and/or format. See type and attributes.

Exit

Exits GoldWave.

1..9 File History

At the bottom of the File menu is a history list of recently opened files. These files can be re-opened by selecting them from the menu.

Edit Menu Commands

Undo

Reverses the last edit or effect.

Cut

Copies the selection into the clipboard and deletes it from the sound.

Copy

Copies the selection into the clipboard.

Copy To

Copies the selection directly to a new file.

Paste

Pastes the clipboard into the sound.

Paste New

Pastes the clipboard to a new Sound window.

Paste At

Pastes the clipboard into the sound at a specified location.

Mix

Mixes the clipboard with the sound.

Crossfade

Crossfades the clipboard with the sound.

Overwrite

Overwrites the sound with the clipboard sound.

Replace

Replaces the selection with the sound in the clipboard.

Delete

Deletes the selection.

Trim

Deletes the ends of the sound outside the selection (trims off the ends).

Mute

Replaces the selection with silence.

Insert Silence

Inserts silence into the sound of a length you specify in seconds. The silence is inserted at the start marker's position.

Select View

Moves the start and finish markers to the left and right sides of the sound graph. This essentially selects all the sound currently displayed in the graph.

Channel

Controls which channel of a stereo sound will be used or modified by editing or effects. You can use this submenu to copy a single channel from a stereo sound or apply an effect to only

one channel. The currently selected channel is shown in the status bar. The channel setting has no effect when recording, using the [Expression Evaluator](#), or using rate modifying effects such as [Resample](#) and [Playback Rate](#).

Marker

Shows a submenu of marker related commands. These commands let you set markers to an exact time or sample position and move the markers to the current playback/recording position.

Cue Point

Shows a submenu of cue point related commands. These commands let you edit cue points, drop cue points during playback/recording, move the start marker to a cue point, or split a file based on cue points.

See Also

[Direct editing of the Waveform](#)

[Editing Overview](#)

[Cue Points](#)

Effect Menu Commands

Doppler

Dynamically changes pitch.

Dynamics

Distorts, compresses or limits output levels.

Echo

Produces an echo.

Compressor/Expander

Compresses, limits, or expands dynamic range.

Filter

Displays a submenu listing filter related commands.

Flanger

Creates a number of flanging related audio effects.

Interpolate

Uses linear interpolation to smooth out the waveform between the start and finish markers. Use this command on a tiny selection (a few milliseconds) to remove a pop or click.

Invert

Turns the sound upside-down.

Mechanize

Adds a mechanical characteristic.

Offset

Changes the dc offset.

Pitch

Changes or transposes the pitch (frequency).

Plug-in

Show a submenu listing all the effect plug-in modules currently installed. Plug-in effects can be selected from those submenus.

Reverb

Adds a reverb effect to a sound, giving it more depth.

Reverse

Reverses the selection so that it plays backwards. Helps find those "satanic" verses in controversial music.

Stereo

Displays a submenu showing stereo related effects.

Time Warp

Changes the speed and stretches or compresses the length of the selection.

Volume

Displays a submenu listing several volume related commands.

Playback Rate

Changes the rate at which the entire sound is played.

Resample

Changes the entire sound so that it can be played at a different sampling rate. Useful for converting files to the standard CD sampling rate of 44100Hz.

See Also

[Editing Overview](#)

[Edit Menu Commands](#)

View Menu Commands

View commands act like a zoom lens allowing you to zoom in or out of the sound graph. By using these commands, you can get a more detailed view of the selection and shape of the waveform. The **Overview Bar** at the bottom of a Sound window shows what part of the sound is currently graphed. In addition to these commands, you can right-click-and-drag to select a region to zoom in on.

All

Graphs the entire sound.

Specify

This magnifies the graph to any level you specify.

Selection

Magnifies the selection, increasing the detail of the graph. You can zoom in many times (by changing the selection and zooming again) until a single sample is shown in the graph.

Preset

Magnifies the sound to the level of detail specified under the Options | Window window. The start marker is used as the zoom location. The level can be set to any value you find convenient.

Previous

Returns the view to the previous zoom level. Use this to switch back and forward between two different zoom levels.

Zoom In

Magnifies the sound by a factor of 1.33. The middle of the Sound window is used as the zoom location.

Zoom Out

Reduces magnification to by a factor of 1.33. This shows more of the sound. The middle of the window is used as the zoom location.

Zoom 10:1

Magnifies the sound to give a very high level of detail. At this level, individual samples are easily visible. The start marker is used as the zoom location. Direct waveform editing with the mouse is possible at this level.

Zoom 1:1

Magnifies the sound to give a true representation of the waveform. The start marker is used as the zoom location.

1 Second, 10 Seconds, 1 Minute, 1 Hour

Shows the given amount of time of audio beginning at the start marker's position. You can use **View | Finish** to see the audio at the end.

Vertical Zoom All

Vertically zooms all the way out so that the entire vertical/amplitude range of the sound is shown.

Vertical Zoom In

Magnifies the graph vertically to show twice as much amplitude detail. Zooming is centered on the middle of the graph.

Vertical Zoom Out

Reduces vertical magnification to show half as much amplitude detail. This shows a larger range of the amplitude. Zooming is centered on the middle of the graph.

Start

Scrolls the graph to the start marker.

Finish

Scrolls the graph to the finish marker.

See Also

[Direct Editing of the Waveform](#)

Specify View

Use the **Specify View** window to magnify the graph to any level you specify. The level can be given as a time length or as a ratio. If the **Length** option is selected, then the length you specify is shown in the graph. For example, use **1:00** to show one minute of audio.

If the **Ratio** option is selected, then the given number of samples are mapped to a single pixel on the screen. Values greater than 1 display an approximation of the waveform. Values less than 1 (such as 0.1) reveal individual samples and allow direct editing of the waveform.

The Start time specifies what position in the file to begin drawing the zoomed waveform.

Tool Menu Commands

CD Reader

Displays the CD Reader tool for copying audio tracks from a CD to files on your hard drive.

Control

Shows or hides the Control window.

Cue Points

Displays the Cue Points tool, where cue points can be created or edited.

Effect Chain Editor

Displays the window where effect chains can be created or edited.

Expression Evaluator

Displays the window where sounds can be generated from mathematical expressions.

Options Menu Commands

Colours

Presents the window for configuring the colour scheme of Sound windows.

Control Properties

Presents the Control Properties window where playback and recording settings can be changed.

File Formats

Presents a window where you can associate a file extension to an audio format, set file format plug-in precedence, or set the default save format.

Plug-in

Displays a submenu listing any module configuration commands for plug-ins used by GoldWave.

Storage

Presents the window for configuring storage and undo related features.

Tool bar

Presents the window for configuring the tool bars.

Window

Presents the window for configuring Main and Sound window features and zoom levels.

Window Menu Commands

Cascade

Layers Sound windows on top of each other so that their title bars are visible.

Tile Horizontally

Arranges Sound windows above and below each other (or side by side if necessary) so that all windows are visible.

Tile Vertically

Arranges Sound windows side by side (or above and below each other if necessary) so that all windows are visible.

Minimize All

Minimizes all Sound windows so only a small title bar is shown.

Arrange All

Arranges all minimized title bars along the bottom of the Main window.

Classic Control

Places the Control window in the bottom right corner of the screen and arranges the controls and visuals in a layout similar to previous versions of GoldWave. The Control window can be resized in any direction.

Horizontal Control

Places the Control window along the bottom of the Main window and arranges the controls and visuals horizontally. Makes the visuals small. The Control window cannot be resized vertically in this mode.

Vertical Control

Places the Control window along the right side of the Main window and arranges the controls and visuals vertically. Makes the visuals large. The Control window can be resized in any direction.

Window List

A list of all files currently opened is added to the bottom of the Window menu. Select a file to make it the active one for editing and effects.

Keyboard Commands

Sound Windows

Keystroke	Action
Left	Scrolls the Sound window graph left.
Right	Scrolls the Sound window graph right.
Pg Up	Scrolls the Sound window graph left one screen.
Pg Dn	Scrolls the Sound window graph right one screen.
Home	Moves the Sound window view to the start marker's position.
End	Moves the Sound window view to the finish marker's position.
Ctrl+Home	Moves the Sound window view to the beginning of the sound.
Ctrl+End	Moves the Sound window view to the end of the sound.
Shift+Right	Moves the start marker right.
Shift+Left	Moves the start marker left.
Ctrl+Shift+Right	Moves the finish marker right.
Ctrl+Shift+Left	Moves the finish marker left.
Shift+R	Moves the start and finish markers to the stored locations (recall).
Shift+M	Stores the locations of the start and finish markers (memorize).
Shift+E	Displays the <u>Set Marker</u> window (enter).
Shift+Up	Horizontally zooms in.
Shift+Down	Horizontally zooms out.
Shift+A	Horizontally zooms all the way out.
Shift+P	Zooms to previous horizontal zoom.
Shift+S	Horizontally zooms in on the selection.
Shift+U	Horizontally zooms to the user defined level.
Shift+0	Zooms 10:1 horizontally.
Shift+1	Zooms 1:1 horizontally.
Ctrl+Up	Vertically zooms in.
Ctrl+Down	Vertically zooms out.
Shift+V	Vertically zooms all the way out.
Scroll Lock	When turned on, the Sound window graph automatically scrolls to follow the playback/recording position.

Main Window

Keystroke	Action
F1	Starts on-line help.
Alt+F6	Switches between Main window and Control window.

Ctrl+F6	Switches between Sound windows.
Ctrl+N	Creates a new file.
Ctrl+O	Opens a file.
Space	Starts or stops playback using green play button mode. See Control Properties .
Shift+Space	Starts or stops playback using yellow play button mode. See Control Properties .
F4, F5, F6, F7, F8	Plays (green mode), rewinds, fast forwards, pauses, and stops respectively.
Shift+F4	Plays the sound using the yellow play button mode.
Ctrl+F9	Starts recording.
Ctrl+F8	Stops recording.
Ctrl+F7	Pauses/unpauses recording.
F11	Displays Control Properties window.

Editing

Keystroke

Action

Ctrl+Z	Undoes last change.
Ctrl+X	Cuts the selection.
Ctrl+C	Copies the selection.
Ctrl+V	Pastes the clipboard into the sound at the position.
Ctrl+B	Pastes the clipboard into the sound at the position.
Ctrl+F	Pastes the clipboard into the sound at the position.
Ctrl+E	Pastes the clipboard into the sound at the position.
Ctrl+P	Pastes the clipboard into a new Sound window.
Del	Deletes the selection.
Ctrl+M	Mixes the clipboard with the sound at the position.
Ctrl+T	Trims the sound. Removes all audio outside the selection.
Ctrl+R	Replaces the selection with the sound in the clipboard.
Ctrl+A	Selects the entire sound.
Ctrl+W	Sets the selection to the view (what is currently visible in the Sound window).
Ctrl+Q	Drops a new cue point at the current playback position.
Ctrl+]	Jumps the start marker to the next cue point.
Ctrl+Shift+J	Jumps the start marker to the previous cue point.
Ctrl+Shift+L	Selects the left channel only.
Ctrl+Shift+R	Selects the right channel only.
Ctrl+Shift+B	Selects both left and right channels.
[Moves the start marker to the current playback position.
]	Moves the finish marker to the current playback position.

File Information

Use this window to store information within the audio file, including the title, artist, description, and copyright notice. Note that information is saved only in some file formats, such as **.wav**, **.aiff**, **.xac**, and ID3v2 **.mp3** files. Information is discarded for other file types. Older ID3 MP3 tags are not supported.

Batch Processing

Use the **File | Batch Processing** command to convert a set of files from one format to another and/or to apply effects to a set of files. Add files by using the **Add Files** button or by using drag-and-drop with Windows Explorer. You can add an entire folder or all the files in a folder of a specific type by using the Add Folder button.

You can remove items from the list by selecting one or more of the items and choosing the **Remove** button. The **Remove All** button removes all files and folders from the list.

The tabs along the bottom let you configure conversions, effects, destination folder, and file information. These are explained below.

Press the **Begin** button to start processing all the files. A status window will appear showing the progress and list any errors.

Convert Tab

If you check the **Convert files to this format** box, then all files will be converted to the format you specify on this tab. Otherwise no conversion is performed and the processed files will have the same format as the original files, if possible. If the same format cannot be used, then an error will be reported.

Use the **Save as type** drop down list to select the destination format for the conversion, then use the **Attributes** drop down list to select the specific attributes to use for the destination type.

If the attributes allow any sampling rate to be used, you can specify the destination rate to use. Some attributes have a fixed rate, so a separate rate cannot be specified for those. If no rate conversion is needed, make sure the Rate box is not checked. In that case, the processed files will have the same rate as the original files.

Process Tab

If you want to apply effects to a group of files, use this tab to add a set of effects or chains to the list. If no effect processing is required, make sure you remove all effects by using the **Remove All** button on this tab. To remove a single effect from the list, select the effect and use the **Remove** button.

To add an effect, use the Add Effect button. You'll be presented with a tree list of all effects available and their presets. Select the preset you want to use. Effect chains can be added by using the **Add Chain** button.

If you require different effect settings, you'll need to use the Effect menu or the Effect Chain Editor tool to create a preset or chain with the settings you require.

Folder Tab

If you want all processed files to be stored in the same folder where they currently reside, select the **Store all files in their original folder** option.

If you want all processed files to be stored in a specific folder, select the **Store all files in this folder** option and specify a folder in the box provided. You can click on

the folder button to browse for a folder.

To overwrite any files having the same name and folder as the processed file, check the **Overwrite existing files** box. GoldWave fully processes original files before overwriting them.

Information Tab

Use this tab to control how information is processed. See [File | Information](#). Select **Retain information currently in each file** if you do not want the file's information to be changed. Otherwise select **Replace information in all files** and use the **Set Info** button to provide all the information.

Note that all processed files will have exactly the same information, so care must be taken when specifying file specific information such as Title. Also note that not all file types can store information.

File Information

Use this window to add an effect to the Batch Processing process list. The tree list shows all plug-in modules, with the GoldWave branch expanded initially.

To add GoldWave effects:

- 1) Select and expand the effect branch under the GoldWave* branch to reveal all presets available for that effect.
- 2) Select one of the presets.
- 3) Choose the **Add** button.
- 4) Repeat the above steps to add more effects.
- 5) Choose **Close** to close the window.

To select an effect from a different plug-in module, scroll down the list and select the module name to expand its branch.

File Information

Use this window to add an entire folder or file type to the Batch Processing file/folder list.

Enter the folder path in the **Folder** box or use the folder button to browse for a folder.

Specify the file type in the **Type filter** box. To add all files in the folder, select the *.* item from the drop down list. To add Wave files only, select the *.wav item. To add MP3 files, select *.mp3. Other unlisted items can be entered manually.

Use the **Include all subfolders** checkbox to include all subfolders within the given folder. The entire tree of subfolders will be added to the list for processing.

Save As

This window lets you save a sound under a different name and format. You can convert a file from stereo to mono, 8 bits to 16 bits, **.wav** to **.mp3**, and a wide variety of compressed formats.

For more details about attributes, see **Attributes** under File Format. To set a default format, see the Option | File Format command.

To rename a sound:

- 1) Choose **Save As** from the **File** menu.
- 2) Type in a new name in the **File Name** box.
- 3) Choose **OK**.

To convert the sound to a different format:

- 1) Choose **Save As** from the **File** menu.
- 2) Type in a new name in the **File Name** box.
- 3) Choose the new file type from **Save as type** list.
- 4) Choose an appropriate set of attributes from the **Attributes** list.
- 5) Choose **OK**.
- 6) If you want the Sound window to have the new format, choose **Yes** if prompted to use the new format. If you want the Sound window to retain its current format, choose **No**.

If you choose **Yes** to update the Sound window, the sound is reopened from the new file on the hard drive.

If no filename extension is given, an appropriate one will be appended.

Note that different file types support different attributes. Always pick the type first to see what attributes are available.

This command is useful when files must be used on systems other than Microsoft Windows, such as audio files for websites.

To create an **.mp3** (MPEG Layer 3) compressed file, choose the **MPEG Audio (*.mp3)** type and select one of the listed attributes. You must have an MPEG encoder installed, otherwise an error message will appear. See the GoldWave [website](#) for details.

To convert a **.wav** file to a standard **.au** file, choose the **Sun (*.au)** type and the **Java/Web** attribute.

To save an **.au** file as a **.wav** file, you should choose the **Wave (*.wav)** type and the **signed 16-bit, mono** attributes.

Direct Editing of the Waveform

To directly edit/redraw the waveform with the mouse, you must first zoom in so that individual samples are visible (see [View Menu Commands](#)).

Direct editing:


- 1) Zoom in 1:1 or 10:1.
- 2) Place the mouse arrow directly over the waveform. The arrow will change into a target crosshair.
- 3) Click and hold the left mouse button.
- 4) Move the mouse up, down, left, or right to change the shape of the waveform.
- 5) Release the mouse button.

See Also

[Editing Overview](#)





[Edit Menu Commands](#)



Control Window

The **Control** window provides easy access to audio devices. Before playing or recording a sound, you should use the  (properties) button to make sure that the correct playback and recording devices have been selected. Many device related features can be configured through the [Control Properties](#) window. To save screen space or enlarge the visuals, you can resize the **Control** window. Use the [Window Menu Commands](#) to change the layout and position of the Control window.




You can right-click on some of the controls (buttons, faders, and visuals) to display a context menu for settings.

Playback Controls




The  (green play) and the  (yellow play) buttons can be configured to loop or play different parts of the sound. You can pause playback with the  (pause) button and stop playback with the  (stop) button. For more information, see [Playback](#).

The  (rewind) and  (fast forward) buttons move quickly through the file. The default speed for these buttons can be configured in the [Control Properties](#) window.

Recording Controls

The  (record) button starts recording. Use the  (stop record) button to stop recording. The  (record pause) button pauses recording. This button appears only during recording in place of the record button. For more detailed information, see [Recording](#).

Other Controls

The playback **volume** and **balance** can be set using the  (volume) and  (balance) faders. The **playback speed** can be controlled with the  (speed) fader. Right-click on the balance and speed faders to display a context menu of common settings.

Note these controls affect only the playback device. To change the volume, balance (pan), or speed within a file, use the corresponding command in the [Effect](#) menu. To change recording volumes, see [Recording](#). You can use the Windows Volume Control accessory to change the device volume levels.

See Also

[Editing Overview](#)


[Main Window, Control Window, and Sound Windows](#)

[Control Properties](#)


[Tool Menu Commands](#)

Playing Sounds

To play a sound:



- 1) Choose **Open** from the **File** menu.
- 2) Find and select the sound you want to play.
- 3) Choose the **Open** button. A Sound window is shown.
- 4) Choose the  button on the **Control** window.

To play part of a sound:

- 1) Open the sound, as above.
- 2) Select the part of the sound you want to play. See [Editing Overview](#) for details.
- 3) Choose the  button on the **Control** window.

To quickly select the entire sound again, use **Edit | Select All**.

To loop part of a sound:

- 1) Open the sound, as above.
- 2) Select the part of the sound you want to loop. See [Editing Overview](#) for details.
- 3) Choose the  (properties) button on the **Control** window, then choose the **Play** tab.
- 4) In the **Yellow play** group, choose the **Selection** option, check the **Loop** box, set the number of loops, and choose **OK**.
- 5) Choose the  (yellow play) button on the **Control** window.

The green and yellow play buttons can be configured to play different sections of the sound. Right-click on the button to display a context menu.

See Also


[Control Properties](#)

[Control Window](#)

[Recording](#)

Recording Sounds

To record a sound:


- 1) Choose **New** from the **File** menu.
- 2) Choose attributes (or choose a **Preset quality settings** item) and specify the length of time you want to record, then choose **OK**.
- 3) Select the correct recording source, as described below, such as line-in, microphone, or CD audio.
- 4) Choose the  button on the **Control** window.

To record within an existing sound, you can select the part of the sound you want to record over or use the **Edit | Insert silence** command to make room for recording.

Note that there are several options available for recording under the **Record** tab in the **Control Properties** window, including a countdown timer and level activated recording. See the [Control Properties](#) for more information.

To select a different recording source, such as the line-in, microphone, or CD audio, use one of the following methods:

Method 1: Use Control Properties

- 1) Select the  (properties) button.
- 2) Choose the **Volume** tab.
- 3) Check the appropriate **Select** box and adjust the volume.
- 4) If the device supports a master recording control, make sure the **Mute all** box is not checked and that the master volume is not zero.

Method 2: Use the Volume Control Accessory

- 1) Start the **Volume Control** accessory from the Windows **Start** menu.
- 2) Select **Properties** from the Volume Control **Options** menu.
- 3) In the Properties window, select the **Recording** option.
- 4) Make sure that all the needed sources are checked in the checklist.
- 5) Choose **OK**. You will now see the recording volume controls.
- 6) Choose the source you want by checking the appropriate **Select** check box and make sure the volume is not too low.

The **Monitor input** recording option can help you adjust the volume level before recording.

See Also

[Control Properties](#)

[Control Window](#)

[Playback](#)

Cue Points

Use **Cue Points** to remember and describe specific positions within audio files.

Cue points can be set by using this command, by right-clicking on the cue point slot in Sound windows, or by using the Edit | Cue Point submenu. Cue points are saved only in some file types, such as Wave (*.wav), Apple (*.aiff), and Extended (*.xac) files.

There are several ways to create a new cue point:

- Use the New button on the Cue Points tool window, then enter the name and position.
- Right-click on the cue points slot in the Sound window and choose **New Cue**, then enter the name. The position is already set based on the mouse position.
- Play the file and press Ctrl+Q or use **Edit | Cue Point | Drop Cue** to set a cue point at the current playback position. This also works while recording.

To edit an existing cue point, you can:

- Select the cue point from the list in the Cue Points tool window and choose the Edit button.
- Right-click on the cue point in the Sound window and choose **Edit Cue**.
- To change a cue point's position, drag-and-drop it to the new position in the Sound window.

To delete a cue point, you can:

- Select the cue point from the list in the Cue Points tool window and choose the **Delete** button.
- Right-click on the cue point in the Sound window and choose **Delete Cue**.

The **Copy all** button copies all the cue point information to the clipboard. You can then paste it into a text editor, such as the Notepad accessory.

The Split File button divides the file onto smaller files using the cue points as split points. If you've recorded one side of an album and need to divide it into individual songs, for example, you would set a cue point at the start of each song, then use this feature to automatically create separate files for each song. Each file can then be written to a CD-R disc as a separate audio track using CD Recorder software.

The Auto Cue button either searches the file for areas of silence and inserts a cue point or it sets a cue point at specific intervals. This is helpful for splitting a long recording into individual songs where there is silence between each song or for dividing a file into equal size sections.

Note that when editing or applying effects to one channel of a stereo sound, cue points may not be adjusted to account for changes in the audio.

See Also
Cue Point Menu

Split File

Use the **Split File** button on the Cue Points tool window to divide a large file into smaller files. The file is split at each cue point. Files are stored in the **Destination folder**. The **Base filename** is used together with the number symbol, #, to create the name of each file. If you entered "Track##", for example, the files would be named Track01, Track02, Track03, etc. The # symbol can be placed anywhere in the base filename, so names like "#### - CD1" or "#Track##" would be valid. The least significant digit is placed in the right-most # slot, so the first names would be "0001 - CD1" and "0Track01".

The **First number** box sets the first number to use when creating the names.

The **Overwrite existing files** option automatically replaces files with the same name that already exist in the folder. If the option is not checked, the GoldWave will stop splitting if a file with the same name is found.

The **File format** options specify what format and attributes to use when creating the files. The **Use CD compatible wave format and alignment** option ensures that each file is stored in CD compatible format and that the length of each file is exactly aligned to a CD sector boundary, eliminating gaps between files. This helps you create seamless tracks on a CD, provided you configure your CD-R software to not write silence between tracks. The **Use default save format and attributes** option uses the format given under the Default Save Format tab of the [Options | File Formats](#) window. The **Use file's current format and attributes** option uses the format and attributes of the file being split as shown in GoldWave's status bar.

Auto Cue

Use the **Auto Cue** feature to automatically create cue points. If the **Mark Silence** button is selected, you can set options for detecting silence, such as marking quiet sections between songs. If the **Spacing** button is selected, you can set an interval, such as having cue points every 5 minutes.

The **Split File** button on the Cue Point window can be used later to split a file into individual pieces based on these cue points.

Mark Silence Button

A single cue is added in the center of each detected silent region.

The **Threshold** value sets the volume level for the silence. In most cases, like vinyl recordings, the value should be -40dB or higher so that any background hiss, pops, or clicks will be treated as silence. Otherwise no silence would be marked at all. If you find that no cue points appear, try increasing this value to -30dB or higher. If you find that too many points appear, delete them, then decrease this value or change the values below. Using the Pop/Click filter effect first may improve silence detection.

The **Silence length** value determines how much silence is required before it is marked. Some songs contain brief silences that you usually do not want marked. This value helps to avoid marking any brief pauses within a song. Try values between 1.0 to 1.5 seconds to ignore these brief silences and only mark longer silences between songs.

The **Minimum separation between cues** value defines the minimum amount of time between one cue point and the next. If you know all the songs are longer than 2 minutes, then you can set this value to 2:00 to ensure no silences within a song are marked. All cue points will be at least two minutes apart.

The **Cue placement within area** value specifies where to place the cue point within the detected silent area. A value of 0 means at the beginning, a value of 100 means at the end. By default, a value of 50 places the cue point in the center of the silence area.

Spacing Button

Cue points are added at the specific interval, starting at the given time.

The **Start time** value sets the time to begin marking the file. If you enter 1:00, then the first cue point is inserted at time 00:01:00 in the file. Normally this value would be zero.

The **Interval** value specifies the time interval to use between each cue point. A value of 5:00 would set cue points at five minute intervals (00:05:00, 00:10:00, 00:15:00, etc.).

Effect Chain Editor

The **Effect Chain Editor** allows a number of effects to be chained together so they are all processed at once. There are many advantages to using chains, such as:

- Easier automation, less work. You can apply many effects with just a few mouse clicks.
- Less storage requirements. Extra temporary storage is not required for each effect in the chain.
- Faster, more efficient processing. Audio data is read from storage, processed, then written to temporary storage only once for the entire chain rather than for each effect.
- Create new effects. Chaining effects is a way of creating new effects.
- Advanced previewing. Preview how a series of effects will sound without ever having to process the entire file.

The left window is a tree list showing all the effect plug-in modules, with the GoldWave branch expanded initially. Only effects that can be chained are listed. Effects requiring special access to the audio data or ones that are time based cannot be chained.

You can drag-and-drop effects to the right "chain list" window or select an effect and choose the **Add** button. Effects are always added to the end of the chain list. Expand the branch of other listed modules to use effects in those plug-ins.

Use the **Remove Last** button to remove an effect from the chain list. Note that only the last effect in the list can be removed. An effect in the middle of the list cannot be removed unless all effects below it are removed first. Use the **Remove All** button to remove all effects in the chain list.

When an effect is added to the chain list, it appears as a button. Use the button to change settings for that effect. Settings can be changed while previewing the audio.

When you have finished creating the chain, use the **Presets** controls near the bottom of the Effect Chain Editor window to save the entire chain as a single preset.

See Also
[Using Presets](#)

Expression Evaluator

The **Expression Evaluator** is a versatile tool for manipulating and generating audio data. Expressions can be entered using the keyboard or by selecting an expression from the Presets tree list. For more detailed information, refer to the GoldWave Manual.

For example, to generate a simple tone (a sine wave), the mathematical equation is:

$$y = \sin(2\pi ft) \quad \text{where } \mathbf{f} \text{ is the frequency, } \mathbf{t} \text{ is the time and } \pi = 3.14159\dots$$

To generate this function in the current sound:

- 1) Choose **Expression Evaluator** from the **Tool** menu
- 2) Type in the expression in the large Expression edit box:
`sin(2*pi*f*t)`
- 3) Enter the desired frequency in the **f** edit box (500Hz, for example):
500
- 4) Choose the **OK** button. Processing will begin.

Evaluation can be stopped at any time with the **Cancel** button.

Use the play button to preview the expression before evaluation.

You can use the Expression Evaluator to implement new effects.

To create a tremolo effect:

- 1) Choose **Expression Evaluator** from the **Tool** menu
- 2) Type in the following expression:
`wave(n)*(0.6+0.4*sin(2*pi*f*t))`
- 3) Enter the tremolo rate in the "f" edit box (4 per second, for example):
4
- 4) Choose the **OK** button.

You can alter the depth of tremolo by changing the values 0.6 and 0.4 (to 0.8 and 0.2, for example).


Evaluator Presets

The **Presets** box in the Expression Evaluator window organizes expressions in a number of groups, such as Dial Tones, Effects, Noise, and Waves. You can create new groups or add expression to existing groups.


To retrieve an expression:

- 1) Expand the group containing the expression in the **Presets** list.
- 2) Select the expression from the expanded list.

To add an expression:

- 1) Enter the expression in the **Expression** box.
- 2) Choose the  (add) button in the **Presets** box.
- 3) Select an existing group name or type in a new group name.
- 4) Type in a preset name for the expression.
- 5) Choose the **OK** button.

To delete an expression:

- 1) Expand the group containing the expression in the **Presets** list.
- 2) Select the expression from the expanded list.
- 3) Choose the  (remove) button in the **Presets** box.

New Sound

GoldWave supports a number of sound attributes, as explained below. These attributes must be specified when creating a new sound. You can choose one of the **Preset quality settings** to automatically set appropriate attributes based on the class of audio, then just specify a length. The file is virtually created and requires no storage space initially. It is possible to create a file that is too large to save on your hard drive later.

Channels

Mono sounds have one channel of audio. Stereo sounds have two channels. Stereo sounds use twice as much storage as mono sounds and can take twice as long to process. You can edit individual channels of a stereo sound by using the Edit | Channel submenu.

Sampling Rate

This value affects the quality and quantity of the sound. Higher values allow a wider range of frequencies to be recorded and give better quality. Smaller values require less space. The drop down list box provides many standard rates. For high quality, a minimum of 44100 should be used.

8000	Telephone quality.
11025	Low end radio quality. Good for voice.
22050	Radio quality. Good for music and voice.
44100	CD quality.
48000	DAT quality.
96000	DVD quality.
192000	High-end DVD quality.

Time

This value specifies the length of the sound in hours, minutes and seconds. You can enter any time up to about 99 hours for the length. For example, enter **1:00** for one minute or **1:00:00** for one hour.

For CD quality sound, GoldWave requires about 20 million bytes (20MB) per minute of audio (60 seconds/minute x 44100Hz x 2 channels x 4 bytes/channel). You can save the file in a compressed format to use much less space, but you'll still need a large amount of storage space if you re-open the file.

If you plan to do some recording, make sure you specify attributes that are compatible with your audio device. Most devices do not support rates over 48000Hz. In some cases, GoldWave has no way of knowing if a device fails to support those rates.

File Format

The File Format window lets you open a file that GoldWave could not open automatically. If the file is not compressed or corrupted, GoldWave should still be able to interpret the audio data, provided the correct attributes are selected.

If you see this window for **.mp3** files, you need to re-install Windows Media Player available from Microsoft. GoldWave cannot decode **.mp3** files without the Windows Media Player modules.

The File Format window is presented if any of the following occur:

- The file has no header information and has no file association.
- The file does have a header, but the structure is incorrect for the detected file type.
- The file has a new format that GoldWave does not recognize.
- The file type or format is not supported by GoldWave or any of the [file format plug-ins](#).

File type

Specifies the file type for the audio data. GoldWave lists all the file format plug-ins that support reading raw audio data. If you are working with PCM or uncompressed binary data, select the Raw type. If you are working with **Telephony** files, select the Dialogic type. Other types may be listed depending on what plug-ins you have installed.

Attributes

Specifies the actual nature and organization of the audio amplitude data (samples). If you copied audio from a CD, for example, the attributes would be "PCM signed 16-bit, little-endian, stereo". Dialogic VOX files often use "4-bit VOX ADPCM, mono" attributes, but can also use μ -Law or A-Law. Attributes are as follows:

Mono versus stereo

Specifies that the file is either mono or stereo. Stereo data must be interleaved (i.e. left channel, right channel, left, right...). If you don't know, choose **Mono**.

Signed versus unsigned

Specifies that 8 bit, 12 bit, or 16 bit samples are signed. Amiga and Apple systems use signed 8 bit (-128 to 127) or signed 16 bit (-32768 to 32767). Wave and Sound Blaster files for PCs are usually unsigned 8 bit (0 to 255) or signed 16 bit (-32768 to 32767). In general files with 12 bit samples and greater are signed.

Little-endian versus Big-endian

When more than one byte is required for each sample, the order in which the bytes are stored can vary from system to system. Little-endian files have the least significant byte first, while big-endian files have the most significant byte first. Systems with Intel processors (0x86 & Pentium PCs) store bytes in a little-endian order. Systems with Motorola processors (Macs) store the bytes in big-endian order.

Sampling rate

Specifies the rate at which the sound was recorded. This value does not affect how the data is translated. If you select the wrong rate, the sound will either play too slow or too fast. You can fix this with the [Effect | Playback Rate](#) command. A CD audio recording has a sampling rate of 44100Hz. A Dialogic VOX file can have a rate of 6000Hz or 8000Hz.

If you have no idea how the data should be interpreted, experiment with trial-and-error. If the attributes are wrong, the sound will play distorted. You will have to close the sound window and re-open it using different attributes.

If you save the file later, use a different filename and type using [File | Save as](#).

If you want GoldWave to automatically assume a format for a particular file type, you can use Option | File Format to associate a format with the filename extension.

Undo

Reverses the most recent change made to a sound. The undo feature keeps a copy of the original sound in temporary storage. Use Option | Storage to configure storage and undo levels. If zero levels are specified, then undo is disabled.

Cut

Removes the selection from the sound and copies it to the clipboard. The contents of the clipboard can then be pasted or mixed into another sound. Note that if only the left or right channel is selected in a stereo sound, then only that channel is removed. Since it is not possible for one channel to be larger than the other, the end of the cut channel is padded with silence.

Use Delete instead if you do not need to copy the audio to the clipboard.

To cut:

- 1) Select the part of the sound to cut. See Editing Overview.
- 2) Choose **Cut** from the **Edit** menu or click on the **Cut** button.

See Also

Delete

Trim

Copy

Copy

Copies the selection into the clipboard. The selection is not removed. The contents of the clipboard can then be pasted or mixed into another sound.

To copy:

- 1) Select the part of the sound to copy. See Editing Overview.
- 2) Choose **Copy** from the **Edit** menu or click on the **Copy** button.

See Also

Cut

Copy To

Copy To

Copies the selection to a new file. This is the same as the **File | Save Selection As** command.

To copy:

- 1) Select the part of the sound to copy. See [Editing Overview](#).
- 2) Choose **Copy To** from the **Edit** menu or click on the **To** button.
- 3) Enter a filename and choose a save type and the attributes.
- 4) Choose **OK**.

See Also

[Save as](#)

[Copy](#)

[Cue Points, Split File](#)

Paste

Inserts the clipboard sound into the current sound at the start marker's position. The length of the current sound is increased so that the clipboard sound will fit. The clipboard sound is automatically converted to match the attributes of the current sound.

To paste:

- 1) Copy audio to the clipboard. See [Edit | Copy](#).
- 2) Move the start marker to the place where you want to paste the clipboard sound. See [Editing Overview](#).
- 3) Choose **Paste** from the **Edit** menu or click on the **Paste** button.

See Also

[Mix](#)

[Copy](#)

[Replace](#)

[Overwrite](#)

[Paste at](#)

[Paste new](#)

Paste New

Creates a new Sound window and copies the sound in the clipboard into the new sound. The new sound will have the same attributes and length of the clipboard sound.

To paste part of a sound into a new sound:

- 1) Select the part of the sound to copy to a new sound. See [Editing Overview](#).
- 2) Choose **Copy** from the **Edit** menu or click on the **Copy** button.
- 3) Choose **Paste new** from the **Edit** menu or click on the **PNew** button.

See Also

[Copy](#)

[Copy To](#)

[Overwrite](#)

[Replace](#)

[Paste](#)

[Paste at](#)

Paste At

Inserts the clipboard sound into the current sound at the location selected from the submenu. The length of the current sound is increased so that the clipboard sound will fit. The clipboard sound is automatically converted to match the attributes of the current sound.

To append the clipboard to the end of the current sound:

- 1) Copy audio to the clipboard. See [Edit | Copy](#).
- 2) Choose **End** from the **Edit | Paste at** submenu.

See Also

[Mix](#)

[Copy](#)

[Overwrite](#)

[Replace](#)

[Paste](#)

[Paste new](#)

Mix

This is a special editing feature for sounds. The sound in the clipboard is added to (or layered) with the current sound, such as adding vocals to music. You are prompted for the start time and the mix volume. The volume is applied to the clipboard sound.

To mix:

- 1) Copy audio to the clipboard. See [Edit | Copy](#).
- 2) Move the start marker to the approximate place where you want to mix the clipboard sound. See [Editing Overview](#).
- 3) Choose **Mix** from the **Edit** menu or click on the **Mix** button.
- 4) Enter the volume to mix the clipboard (0 dB is full volume).
- 5) Preview the mix using the play button and adjust the start time and volume as required. Note that you'll need to press the play button again before the new settings are previewed.
- 6) Choose **OK**.

See Also

[Copy](#)

[Overwrite](#)

[Replace](#)

[Paste](#)

[Crossfade](#)

[Volume](#)

Crossfade

Crossfade fades out one sound while fading in another. The **Duration** specifies how long the transition between the clipboard audio and file audio lasts. Audio must be copied to the clipboard before this command is enabled. The **Clipboard position** setting specifies which end of the file to fade the clipboard audio. If **End of file** is selected, then the clipboard is pasted and crossfaded at the end of the file. If **Beginning of file** is selected, then the clipboard is pasted and crossfaded at the beginning of the file. The **Fade curve** settings control how the audio is faded. The fade is shown graphically and can be previewed.

To crossfade between two songs:

- 1) Open a song and copy it to the clipboard. See [Edit | Copy](#).
- 2) Open a second song.
- 3) Choose **Crossfade** from the **Edit** menu or click on the **Xfade** button.
- 4) Change settings as needed.
- 5) Preview the crossfade using the play button. Note that you'll need to press the play button again before changed settings are previewed.
- 6) Choose **OK**.

See Also

[Copy](#)

[Overwrite](#)

[Replace](#)

[Paste](#)

[Mix](#)

[Fade In](#)

[Fade Out](#)

Replace

Replaces the selection with the clipboard sound. If the length of the clipboard is different than the length of the selection, then the length of the current sound is changed so that the clipboard sound will fit between the selection endpoints.

To replace:

- 1) Copy audio to the clipboard. See [Edit | Copy](#).
- 2) Select the part of the sound to replace. See [Editing Overview](#).
- 3) Choose **Replace** from the **Edit** menu or click on the **Repl** button.

See Also

[Mix](#)

[Copy](#)

[Overwrite](#)

[Paste](#)

[Paste at](#)

[Paste new](#)

Overwrite

Overwrites the current sound with the clipboard sound beginning at the start marker. The amount of sound overwritten depends on the length of the clipboard. Unlike [Replace](#), the length of the current sound is **not** changed and nothing is shifted. If the clipboard is longer than the current selection, then part of the sound outside the selection will be overwritten as well.

To overwrite:

- 1) Copy audio to the clipboard. See [Edit | Copy](#).
- 2) Move the start marker to the beginning of the area to be overwritten. See [Editing Overview](#).
- 3) Choose **Overwrite** from the **Edit** menu or click on the **Over** button.

See Also

[Mix](#)

[Copy](#)

[Paste](#)

[Paste at](#)

[Paste new](#)

[Replace](#)

Delete

Removes the selection from the sound. The selection is not copied to the clipboard. Note that if only the left or right channel is selected in a stereo sound, then only that channel is removed. Since it is not possible for one channel to be larger than the other, the end of the deleted channel is filled with silence.

To delete:

- 1) Select the part of the sound to delete. See [Editing Overview](#).
- 2) Choose **Delete** from the **Edit** menu or click on the **Del** button.

See Also

[Cut](#)

[Trim](#)

Trim

Removes the ends of the sound that are outside the selection, keeping only what is selected. The ends are not copied to the clipboard. Note that if only the left or right channel is selected in a stereo sound, then only that channel is trimmed. Since it is not possible for one channel to be larger than the other, the ends of the trimmed channel are padded with silence.

To trim:

- 1) Select the part of the sound to **keep**. See [Editing Overview](#).
- 2) Choose **Trim** from the **Edit** menu or click on the **Trim** button.

See Also

[Cut](#)

[Delete](#)

Insert Silence

Inserts silence at the start marker's position. **Duration of silence** specifies how much silence to insert.

To insert 10 seconds of silence:

- 1) Move the start marker to the place where you want to insert the silence. See [Editing Overview](#).
- 2) Choose **Insert silence** from the **Edit** menu or click the **Silen** button.
- 3) Enter 10 for the duration.
- 4) Choose **OK**.

See Also

[Mute](#)

[Delete](#)

Marker Menu

The **Edit | Marker** submenu contains selection marker related commands. For more information about markers, see [Editing Overview](#).

Set

Sets the start and finish markers to an exact time or sample position.

Drop Start

Drops the start marker at the current playback or recording position. This command is enabled only during playback and recording.

Drop Finish

Drops the finish marker at the current playback or recording position. This command is enabled only during playback and recording.

Store Selection Positions

Stores the start and finish marker positions. This acts like the "Store" button on a calculator.

Recall Selection Positions

Moves the start and finish markers to the previously stored locations. This acts like the "Recall" button on a calculator.

Snap To Zero-Crossing

If you check this option, whenever you move a marker its position is adjusted so that it is on near a place where the waveform approaches zero. This helps to reduce any clicks caused by a sudden change in the waveform after editing. Note that the marker may be snapped to a place that is several hundred samples away from the position where you released it. The best zero-crossing point is used, which is not necessarily the closest point.

When editing a stereo file, both the left and right channels are scanned for the best overall position for the marker. You can use the [Edit | Channel](#) command to limit the zero-crossing search to a single channel.

When zoomed in 1:1 or closer, snapping is automatically disabled so you can place the marker at any position.

See Also

[Editing Overview](#)

[Cue Points](#)

[Cue Point Menu](#)

Set Marker

Sets the start and finish markers to an exact time or sample position. To specify a time, choose the **Time based position** option and enter the time in hours, minutes, seconds, and fractions of a second. For example, you could enter **1:04:27.873**. To specify an exact sample position, choose the **Sample based position** option and enter the position.

If you want the length of the selection to be aligned to a **CD sector** or **1 kilobyte**, select the appropriate option. When the **OK** button is pressed, the finish marker will be adjusted to align the selection length.

See Also

[Editing Overview](#)

[Cue Points](#)

[Cue Point Menu](#)

Cue Point Menu

The **Edit | Cue Point** submenu contains cue point related commands. For more information about cue points, see [Tool | Cue Points](#).

Edit Cue Points

Displays the **Cue Points** tool.

Drop Cue

Drops a cue point at the current playback or recording position. The name of the cue point is set to the time position. This command is enabled only during playback and recording.

Jump To Next Cue

Moves the start marker to the next cue point in the file or to the end end of the file if there are no more cue points. If the start marker is at the end of the file already, then it is moved to the beginning of the file.

Jump To Previous Cue

Moves the start marker to the previous cue point in the file or to the beginning of the file if there are no previous cue points. If the start marker is at the beginning of the file already, then it is moved to the end of the file.

Split File

Divides the file onto smaller files using cue points as split points.

See Also

[Editing Overview](#)

[Cue Points](#)

[Marker Menu](#)

Edit Cue Point

Use this window to set the **Name**, **Position**, and **Description** of a cue point. The **Name** is the tip text that will appear when the mouse is over the cue point in the Sound window. A name is required, so it cannot be left blank. The **Position** is the time placement for cue point within the file. The **Description** can be any text or can be left blank.

See Also

[Editing Overview](#)

[Cue Points](#)

[Marker Menu](#)

Dynamics

Dynamics alters the amplitude mapping (dynamic range) of the selection. It can limit, compress, or expand a range of amplitudes. The amplitude mapping is set using [Shape Controls](#), where x-axis and y-axis both have a range of -1 to 1. When the line stretches diagonally from the lower left corner to the upper right corner, the input amplitude (x) and output amplitude (y) are the same for every point on the line. By changing the line, the output will be different from the input.

See Also

[Using Presets](#)

[Expander/Compressor](#)

Compressor/Expander

The Compressor/Expander effect is a general purpose dynamics processor commonly used as a compressor, limiter, expander, or a gate. See the [manual](#) for more detailed information. Note that this effect does not change the size of files (it does not control file compression).

The **Multiplier** specifies the level of volume change. For compression, this value should be less than 0dB. For expansion, the value should be less than 0 as well.

The **Threshold** specifies the audio level to activate the expander or compressor. Compressors change the volume level of all sounds above that level. Expanders change the volume level of all sounds below that level.

The **Attack** and **Release** times specify how quickly the expander/compressor is activated. An attack value of 0.100 means that the audio level will have to cross the for at least one tenth of a second before the multiplier is used at full force. A release value of 0.100 means the multiplier will continue to be used (decreasingly) for one tenth of a second after the threshold is no longer crossed.

Use the **Expander** and **Compressor** modes to specify what processing is required. Use Expander mode to change volumes of quiet sounds. Compressor mode to change volumes of loud sounds.

The **Anticipate attack** setting tells the effect to scan ahead for audio that crosses the threshold. If the **Attack** time is set to 0.100, then the effect scans ahead by 0.100 seconds. This means that the multiplier will be at full force the instant the threshold is crossed rather than building to full force 0.100 seconds later. The **Use smoother** setting smooths out any sudden volume changes which may occur during processing with small attack/release times.

The **Noise gate** preset is useful for removing noise in quiet sections of a sound.

See Also
[Using Presets](#)
[Dynamics](#)

Doppler

The Doppler effect dynamically alters or bends the pitch of the selection. [Shape Controls](#) are presented where the pitch can be varied over the length of the selection from one quarter to two times normal. A Doppler effect can be heard when an active fire truck passes by. The pitch of the siren appears to drop slowly as the truck speeds away. You can use [Effect | Volume | Shape](#) to dynamically alter the volume as well.

See Also

[Using Presets](#)

[Pitch](#)

[Time Warp](#)

Echo

Adds echoes to the selection. The number of echoes, delay, volume, and feedback can be set in this window.

Echoes

Sets the number of echoes to create. Each echo gets quieter, depending on the **Volume** setting below.

Delay

Specifies the time between each echo. The longer the delay, the longer it takes for the echo to bounce back.

Volume

The lower the volume, the quieter the echo will be. Values less than -6dB give good results.

Feedback

Specifies the volume of the regeneration of the echo. This gives the echo more depth or fullness.

Stereo

Makes the echo bounce between the left and right channels in a stereo sound.

To make the echo sound correct, the effect extends slightly outside the end of the selection. This may increase the length of the sound.

See Also

[Using Presets](#)

[Reverb](#)

[Flanger](#)

Filter Menu

This submenu lists filter related commands. Filters are used to remove ranges of frequencies from sounds and can produce a variety of effects.

Bandpass/stop

Applies a bandpass or bandstop filter to the selection with the specified frequency range.

Equalizer

Boosts or reduces fixed frequency bands using a 7-band equalizer.

Low/Highpass

Applies a lowpass or highpass filter to the selection at the specified cutoff frequency.

Noise Reduction

Reduces noise in the selection.

Parametric EQ

Boosts or reduces frequencies. Up to 40 bands can be created with precise control over the center frequency, gain, and bandwidth.

Pop/Click

Finds and repairs pops and clicks.

Silence Reduction

Searches for long silences and reduces them. Saves storage space.

Smoother

Averages the audio to reduce crackling and popping.

Noise Reduction

Noise reduction helps eliminate unwanted noise within a sound, such as a background hiss, a power hum, or random interference. It **cannot** be used to separate or remove complex sounds, such as vocals from music or coughing/laughing.

You are presented with a spectral analysis window, with a shape line, and several other controls. The **X** and **Y** coordinates are updated when you click-and-drag a shape point. The **X** coordinate is the frequency in Hertz and the **Y** coordinate is the magnitude in decibels. The time of the spectral analysis shown is given in the **Time** box. If you move the time scroll bar, located below the analysis window, the graph changes to show the spectral analysis of a different part of the sound.

A reduction envelope is used to remove noise. The envelope can be created in four different ways, depending on the **Reduction envelope** setting as explained below. The **Use clipboard** option often gives the best results.

Use shape

Lets you manually create an envelope shape or select a preset shape. See [Shape Controls](#) for information about creating shapes. By setting a horizontal line at about 80dB, you can remove a hiss from a sound. The shape is used only if the **Use shape** envelope option is selected. Otherwise it is ignored. [Presets](#) allow you to store or recall shapes.

Use current spectrum

Creates an envelope based on the shape of the spectral analysis graph shown in the window. This is useful for removing a buzz, hum, or hiss. Before using this effect, find a time in the sound where only the noise can be heard. Use that time for the analysis window by adjusting the time scroll bar. Select this option, then choose **OK**. If the noise is consistent through the sound, this is the easiest setting to use.

Use average

Applies an averaging envelope throughout noise reduction processing. The envelope is continuously updated. Use this setting if the noise changes throughout the sound.

Use clipboard

Analyzes the audio in the clipboard and creates an envelope based on it. To use this setting, you must first [copy](#) part of the sound where the noise exists by itself. Like the **Use current spectrum** setting, this can remove a buzz, hum, static, and other common noises. The clipboard noise can be based on audio copied from another file or audio outside the current selection. In general, this is the best setting to use.

Settings

The [FFT size](#) determines the detail of the spectral analysis and the noise reduction envelope. Usually values of 11 to 12 give the best results. The [Overlap](#) value specifies the percentage of the FFT size to overlap from one calculation to the next. A value of 88 is best. The **Scale** value lets you alter the reduction envelope scale. A value of 100 uses the envelope as it is. A value of 200 doubles the envelope, which double the amount audio removed from the sound. A value of 50 halves the envelope, which halve the amount removed. Normally it should be set to 100. Use lower values if you hear any tinkling distortion.

See Also

[Using Presets](#)

[Compressor/Expander \(Noise gate preset\)](#)

[Pop/Click](#)

Low/Highpass

Lowpass filters block high pitched frequencies (treble), but allow low pitched frequencies (bass) to pass. They can be used to reduce high end hiss noise or remove unwanted sounds **above** the given cutoff frequency. If you were to apply a lowpass filter with a cutoff frequency of 1000Hz on speech, it would make it sound mumbled and deep. Lowpass filters can also be used to eliminate aliasing when used before downsampling.

Highpass filters block low pitch frequencies, but allow high pitched frequencies to pass. They can remove deep rumbling noise or remove unwanted sounds **below** the given cutoff frequency. If you were to apply a highpass filter with a cutoff frequency of 1000Hz on speech, it would make it sound thin and hollow.

Cutoff frequency

The **Initial cutoff** box specifies the constant cutoff frequency for static filtering. If the **Dynamic** option is selected (see below), then a final cutoff frequency can be given in the **Final cutoff** box.

Filter options

Select **Lowpass** if you want to keep only the frequencies below the cutoff frequency. Select **Highpass** if you want to keep only the frequencies above the cutoff frequency.

If you want the cutoff frequency to remain constant throughout the selection during processing, select the **Static** option. If you want the cutoff frequency to change from the initial value to the final value, select the **Dynamic** option. Note that dynamic filtering will take more processing time.

The **Steepness** value specifies how sharply the filter cuts off frequencies outside the cutoff frequency. A higher steepness makes the filter sharper, but it also increases processing time. In technical terms, the steepness specifies the number of second order cascade filters used.

Examples

To make speech gradually become more hollow and thin:

- 1) Enter 60 in the **Initial cutoff** box.
- 2) Choose **Dynamic**.
- 3) Enter 1000 in the **Final cutoff** box.
- 4) Choose **Highpass**.
- 5) Choose **OK**.

Filtering before downsampling from 44100Hz to 22050Hz:

- 1) Enter 11025 in the **Initial cutoff** box.
- 2) Choose **Lowpass**.
- 3) Choose **Static**.
- 4) Enter 20 in the **Steepness** box.
- 5) Choose **OK**.

See Also

[Using Presets](#)
[Bandpass/stop](#)

Bandpass/stop

Bandpass filters block all frequencies outside the specified range, keeping only frequencies within the range.

Bandstop filters block all frequencies within the specified range, keeping all other frequencies outside the range.

Frequency range

The **From** and **To** boxes specify the frequency range of the filter. If the **Dynamic** option is selected, then a final frequency range can be given in the other **From** and **To** boxes.

Filter options

Select **Bandpass** if you want to keep only the frequencies within the range. Select **Bandstop** if you want to keep only the frequencies outside the range.

The remaining options are explained under the [Low/Highpass](#) command.

See Also

[Using Presets](#)

[Low/Highpass](#)

Equalizer

The **Equalizer**, which is commonly found on stereo systems, boosts or reduces certain ranges of frequencies.

Center frequencies for each of the 7-bands are given at the top of each fader. The faders can be adjusted to boost or reduce a band by +12dB to -24dB. The **Master** fader sets the overall output volume.

See Also
Using Presets

Pop/Click

A pop/click filter is a specially designed filter that searches for abrupt changes in the sound and eliminates them.

The **Tolerance** defines how abrupt a change can be before it is considered a click. It is best to start with a value near 1000%. Lower values will detect more clicks. Values less than 500% should be used on short selections only.

The filter requires a minimum selection of 4000 samples to establish a base line.

See Also
[Using Presets](#)

Parametric EQ

The **Parametric Equalizer** is a flexible tool for reducing or enhancing ranges of frequencies. GoldWave presents an easy to use interface where all the parameters for up to 40 bands can be quickly configured.

Graph window

The graph shows frequency on the x-axis in Hertz and the gain on the y-axis in decibels. Each band is displayed in the graph as a diamond shaped box located at its center frequency and gain. The width of the box shows its bandwidth. The currently selected band is shown in blue and its exact settings are given in edit box/fader controls below the graph. A short time frequency analysis graph is drawn with the left channel in green and the right channel in red. The time of the analysis can be changed using the scroll bar located at the bottom of the graph.

Controls

A band can be configured by selecting its number from the **Band** box and adjusting the Gain, Center, and Width controls. A quicker way is to **drag-and-drop** its diamond box to a new location on the graph. Note that because of the logarithmic frequency scale, the width of a diamond changes as you move it left or right. The bandwidth, however, remains constant.

More bands can be added by using the diamond plus button. Use the diamond minus button to remove the current band.

See Also

[Using Presets](#)

Silence Reduction

Use this filter to automatically remove long silences from a sound and save storage space.

Silence threshold specifies the volume level for the silence. Any audio below this level is considered silence and is subject to removal, provided it has a long enough duration.

Reduce to length specifies how short to make the silence. If you use a value of 1.0, then any silences longer than one second will be shortened to one second in length.

See Also
[Using Presets](#)

Smoother

Use this filter to reduce hiss and crackle.

Length sets the length of the smoother filter. The larger the value, the more averaging is applied to the audio and the duller it will sound.

Use the **Volume** setting to help offset the loss in volume for larger **Length** values.

See Also
[Using Presets](#)

Flanger

Flanger uses variable delays and mixing to create some unusual audio effects.

Volumes

Source specifies the volume of the unmodified sound to mix with the output.

Flanger specifies the volume of the delayed sound to mix with the output.

Feedback specifies the volume of the feedback to mix with the output.

Flanger settings

Variable delay specifies in milliseconds how much the flanger delay should vary. A value of 40 will let the delay vary from 0 to 40 milliseconds.

Frequency specifies how fast to vary the delay. A value of 2 will vary the delay over its depth twice a second. For a value of 0.2, the full depth is reached every 5 seconds.

Fixed delay is added to the variable delay to change the total delay. If the variable delay is 40 and the fixed delay is 10, the delay will vary from 10 to 50 milliseconds.

Sine modulator varies the delay based on a sine wave.

Triangle modulator varies the delay based on a linear triangular wave.

Stereo causes the flanger and feedback audio to be mixed with opposite channels, giving a more pronounced stereo effect.

See Also

[Using Presets](#)

[Reverb](#)

[Echo](#)

Invert

Reflects the selection about the x (time) axis, turning the waveform upside-down. This produces no noticeable effect in mono sounds and has a slight effect in stereo sounds. Inverting a single channel of a stereo sound will produce a simulated surround-sound effect.

See Also

[Channel Mix](#)

[Edit | Channel](#)

Mechanize

Adds a robotic or mechanical characteristic to the selection. **Frequency** sets the speed of modulation. High values produce an untuned two-way radio effect. Low values give a rough, distorted, or intermittent effect.

The modulator can be a sine wave, a triangular wave, a square wave, or a section of audio copied to the clipboard.

See Also
Using Presets
Flanger

Offset

Adjusts or removes a dc offset in the selection by shifting the waveform up or down. If you notice that silent sections of a sound are not at zero in the graph, you can use this effect to adjust them to zero.

The **Left** and **Right** offset values for a stereo sound can be set independently. A positive value shifts the graph up and a negative value shifts it down.

Use the **Scan Offset** button to automatically determine the values to remove any offset from the sound.

See Also
[Using Presets](#)

Pitch

Changes the pitch of the selection. This is useful for converting instrument samples from one note to another. The pitch can be changed by using a scale factor or by specifying semitone and fine tune values.

Scale

This option scales the pitch by a percentage. If you set the scale to **50**, that will be equivalent to a downward shift by one octave. A value of **200** is the same as an upward shift of one octave and would make a voice sound like a chipmunk. A value of **75** would make a woman's voice sound like a man's.

Semitone

This option changes the pitch by semitones (notes). If your sound is a note at middle C and the semitone value is **2**, the note will be changed to D. A value of **-1** changes the note to B. A value of **12** make the note one octave above middle C. The **Fine tune** value lets you make a slight pitch adjustment in hundredths of a semitone. For example, a value of **50** would let you change a note from middle C to halfway between C and C#.

Preserve length

If this option is checked, a complex algorithm will be used to keep the length of the original note the same as the new note. The tempo is preserved. In terms of a voice, this changes the pitch without speaking faster or slower. This option requires a substantial amount of processing time. In general, the FFT size should be set to 11 or 12 and the Overlap should be at least 88. Values of 90 and 95 will give better results, but require more processing time.

See Also

[Using Presets](#)

[Playback Rate](#)

[Doppler](#)

[Time Warp](#)

Plug-in Menu

Effect | Plug-in is a submenu listing all the effect plug-in modules detected by GoldWave. To use plug-in effects, select the module menu item containing the effect, then select the effect from the submenu that appears. For example, to use a DirectX plug-in, select the **DirectX** menu item from the **Effect | Plug-in** menu, then select the effect from the submenu that appears.

GoldWave checks for new plug-ins only during startup, so if you install a new plug-in, you must restart GoldWave for it to be detected.

Reverb

Adds a reverb to the selection. The reverb time, volume, and delay scale can be set in this window.

Reverb time

Sets the size of the reverb. A longer time implies a larger chamber or room.

Volume

The lower the volume, the quieter the reverb will be. Values less than -18dB give good results.

Delay scale

Alters the delay of the reverb for fine tuning. Use 1.0 for a standard reverb.

This effect extends outside the end of the selection, increasing the length of the sound slightly.

See Also

[Using Presets](#)

[Echo](#)

[Flanger](#)

Stereo Menu

Effect | Stereo displays a submenu containing stereo related commands. These commands work only with stereo sounds.

Channel Mix

Mixes, exchanges, inverts, or combines the left and right channels.

MaxMatch

Combines the maximize and match effects on a stereo file to match/balance and maximize the left and right volume levels within the file. After processing, the left and right channels will have the same average volume level and at least one channel will have full dynamic range (1.0 or 0dB). Note that it is rarely possible for channels to have the same average and both have full dynamic range at the same time.

Pan

Dynamically sets internal balance and left/right channel panning.

Reduce Vocals

Reduces vocals in music.

Channel Mix

Use this effect to swap, mix, invert, or combine the left and right channels. The drop-down lists provide options to replace each channel.

See Also

[Using Presets](#)

[Reduce Vocals](#)

Pan

Use the Shape Controls to alter the left and right balance. The shape graph is divided into green and red regions, representing the left and right channels respectively. The line, initially located between the regions, represents the center for panning. By bending and/or moving the line, you can dynamically alter the sound's left/right balance over time or pan to and from each channel.

See Also
Using Presets

Reduce Vocals

Use this effect to reduce vocals in music. In some stereo recordings it is possible to remove vocals by subtracting the left and right channels. In order for this to work perfectly, vocals must be identical (recorded equally) on both the left and right channels. If there is any stereo echo or reverb applied to the recording, vocals cannot be removed completely.

Note that any instruments recorded equally on both channels will be removed along with the vocals. This is unavoidable.

Usually subtracting the left and right channels destroys the stereo sound, giving mono output. However, by integrating a bandstop filter, GoldWave is able to restore some of the stereo, enhancing the output. Try the **Reduced vocals with more stereo** preset. Bring the **From** and **To** filter values closer together for increased stereo (increases the vocals) or farther apart for reduced stereo (decreases the vocals).

See Also

[Using Presets](#)
[Channel Mix](#)

Time Warp

Changes the playback speed or stretches/compresses the length of the selection. The **Change** value lets you specify a relative change in percent. A value of **50** makes the selection play twice as slow. A value of **200** makes the selection play twice as fast. The **Length** option lets you specify a new length for the selection. This is useful if you need to make a sound fit a certain time, such as squeezing a 35 second commercial into a 30 second spot.

Three different time altering algorithms are provided, each with advantages and disadvantages.

Rate

Changes the sampling rate of the entire sound so that it plays back at a different speed, similar to spinning a vinyl record faster or slower. It works the same way as the speed fader in the Control window, but in this case, the sound itself is changed. This technique is very fast and produces excellent quality, however, the pitch of the sound is changed as well.

Similarity

Uses correlation to add or overlap small, similar sections of the sound. This technique preserves the pitch and generally produces high quality for voice and fair quality for music, when using small changes. A large amount of time may be required for processing, depending on the **Search range** value. For voice, the **Window size** should be set between 20 and 30 and the **Search range** set to between 5 and 10. For music, a larger **Window size** and **Search range** gives better results, such as 100 and 25.

FFT

Uses Fourier transforms and interpolates or decimates the spectral analysis to change the length. This technique preserves the pitch, but can introduce some artifacts into the sound. Best quality is obtained by using the **Oscillator synthesis** option, but that requires significant processing time. The **FFT size** should be set to 11 or 12 and the **Overlap** should be at least 75, but can be set to 88, 90, or 95 for slightly better quality.

Note: If you changed the Control Window playback speed, remember to set it back to 1.00 so that the sound plays at the correct speed.

See Also

[Using Presets](#)

[Playback Rate](#)

[Resample](#)

[Pitch](#)

[Control Window](#)

Volume Menu

Displays a submenu containing volume related commands. Volumes are specified in decibels (dB), but a percentage value is shown as well.

Although the output volume of the playback device can be controlled in the Control window, volume effects change the internal volume of the sound itself.

Change

Changes the volume of the selection.

Fade In

Gradually increases the volume throughout the selection.

Fade Out

Gradually decreases the volume throughout the selection.

Match

Sets consistent volume levels across different files based on an average level.

Maximize

Increases volume as high as possible without distortion (sometimes referred to as normalizing). Shows current maximum volume levels.

Shape

Performs volume envelope shaping.

See Also

Pan

Change Volume

Modifies the selection so that it sounds louder or quieter. The volume is given in decibels with a 0dB reference level. Positive values above 0dB increase the volume. Negative values below 0dB decrease the volume. A value of 0dB leaves the volume unchanged. If you are unfamiliar with the decibel scale, adjust the fader and watch the percentage value.

See Also

[Using Presets](#)

[Maximize](#)

Fade In

Gradually increases the volume throughout the selection. The **Initial volume** specifies the starting volume level. To fade in from complete silence, use the lowest value possible (-160dB). The **Logarithmic** and **Linear** options control the shape of the fade.

To fade in the beginning of a sound from silence:

- 1) Select three seconds of audio at the beginning of the file. See [Editing Overview](#).
- 2) Choose **Fade In** from the **Effect | Volume** submenu.
- 3) Enter an **Initial volume** of -160.
- 4) Choose the **Linear** option.
- 5) Choose **OK**.

See Also

[Using Presets](#)

[Volume](#)

[Shape](#)

[Fade Out](#)

Fade Out

Gradually decreases the volume throughout the selection. The **Final volume** sets the volume level at the end of the fade. To fade to complete silence, use the lowest setting (-160dB). The **Logarithmic** and **Linear** options control the shape of the fade.

To fade out the end of a sound to silence:

- 1) Select three seconds of audio at the end of the file. See [Editing Overview](#).
- 2) Choose **Fade Out** from the **Effect | Volume** submenu.
- 3) Enter a **Final volume** of -160.
- 4) Choose the **Linear** option.
- 5) Choose **OK**.

See Also

[Using Presets](#)

[Volume](#)

[Shape](#)

[Fade In](#)

Match

Matches the volumes of separate files. If you have several songs with different volume levels you want to write to a CD, use this effect to adjust volume levels of each song so they sound similar.

Volume changes are based on the overall average volume level of the sound. The level is based on a root-mean-square average, with silent regions excluded. Files with similar average levels will seem to have similar overall volume levels.

You need to use this effect on each file to set the **Average** to the same value. Use the [File | Batch Processing](#) command to apply this effect to a group of files. The average value to use depends on the files.

You should open each file and display the **Match** effect to see what average value it has, then apply an overall average value to all the files. To avoid clipping distortion, it is best to use the minimum average across all files. For example, if one file has an average of -18dB and all the other files have a higher average, then use -18dB for all files.

Unlike the [Maximize](#) volume effect, the **Match** effect may result in clipping distortion if the average level is set too high. This effect should not be used with [Maximize](#). Use one or the other, but not both (one cancels the other).

See Also

[Using Presets](#)

[Volume](#)

[Maximize](#)

[MaxMatch](#)

Maximize

Searches the selection for the maximum volume level, then displays the maximum level and the time at which the maximum occurs for each channel. You can specify a new maximum for the sound.

A value of 0dB normalizes the volume so that it covers the full dynamic range. In other words, it makes the file as loud as possible without distorting or clipping the waveform. Values above 0dB will cause distortion. Values below 0dB will leave some unused dynamic range, which can be useful when using other effects.

This effect should not be used with the [Match](#) volume effect. Use one or the other, but not both (one cancels the other).

See Also

[Using Presets](#)

[Volume](#)

[Match](#)

Shape Volume

Use the [Shape Controls](#) to reshape the volume envelope of the sound. The shape line is initially horizontal at 1.0. By bending/moving the line, you can dynamically change the volume of the selection over time.

See Also

[Using Presets](#)

[Volume](#)

[Fade In](#)

[Fade Out](#)

Playback Rate

Changes the playback rate of the *entire* sound. The sound will play faster (or slower) and its pitch will be higher (or lower). Essentially, this just changes rate value shown in the status bar.

The playback rate of the audio device can be controlled using the speed fader in the [Control](#) window. This effect changes the playback rate of the file itself.

See Also

[Doppler](#)

[Resample](#)

[Time Warp](#)

[Pitch](#)

Resample

Changes the sampling rate of the *entire* sound. Unlike **Playback Rate**, this command recalculates and interpolates all the data so that the pitch and playback time are not affected. You are prompted to enter a new rate. Use this effect to convert files to a specific rate, such as the standard CD audio sampling rate of 44100Hz, or to the telephony rate of 8000Hz.

See Also

[Doppler](#)

[Playback Rate](#)

[Time Warp](#)

[Pitch](#)

CD Reader

The **CD Reader** tool digitally copies audio directly from an audio CD to your hard drive, without using your sound card. This features has several advantages over sound card recording:

- There is no need to create a new file.
- Audio can be compressed while extracting, saving hard drive space.
- Recording volume controls do not have to be selected or adjusted.
- Synchronizing sound card recording with CD playback is not required.
- Some CD-ROM drives can read audio several times faster than sound card recording.
- Information such as artist, title, and album can be downloaded and saved automatically.

The CD-ROM drive must be MMC compliant (Multimedia Command Standard). For Windows 95, 98, and ME an ASPI driver must be installed. For Windows 2000/XP either an ASPI driver or administrator privileges are required. Due to the wide variety of interfaces, inconsistent device standards, and problems with the Windows ASPI driver, incompatibilities may arise that will require a system reset. It is recommended that you close all other programs before proceeding.

If your system is configured correctly, you will see a window that allows you to select a CD device and specify the tracks or range of audio to copy. If you have only one CD-ROM drive, only one device will be listed in the drop down list. If you already have an audio CD in the drive, the track times will be shown in list. Otherwise you will need to insert an audio CD and select the CD device from the list.

Choose the **Get Titles** button to download information (album, titles, etc.) about the CD from the freedb.org website. An active connection to the Internet is required.

Select a single track from the list and use the **Rename** button (or Alt+R) to manually rename it.

Choose the **Select All** button to select all tracks or check each track you want to save. You can select any part of the CD or preview tracks by selecting the **Read Time Range** tab. A fast CD-ROM or DVD drive is required for previewing. You may have to increase the **Read speed** or the **Number of sectors per read** setting under the **Options** tab to get smooth playback. For defect free reading, the **Number of sectors to overlap** setting should be 2 or greater.

Choose the **Save** button to save all tracks to separate files or a time range to a single file. You can select the file format and other options on the [Save CD Tracks](#) window that appears.

Use the **Options** tab to changes settings for reading audio from the CD and the download database. The **Swap bytes** option changes the order of bytes extracted from the CD-ROM. If the files sound badly distorted or like a loud hiss, check this box and save the tracks again.

Troubleshooting

- If you get synchronization errors at the beginning, try continuing several times before giving up. Some drives are very inaccurate when spinning up and may require a dozen continues before synchronization can be reliably established. If that does not help, set the **Number of sectors to overlap** value to zero on the **Options** tab and try again.
- If you see an error message indicating a read problem, make sure that the CD is free of dust and finger prints.
- If preview playback is intermittent, increase the **Read speed** or the **Number of sectors per read** setting or reduce the **Number of sectors to overlap** setting under the **Options** tab.

Save CD Tracks

Use this window to set the destination folder, name, and format for all tracks read from the CD.

Destination folder specifies the location to store the tracks. Type in a folder name or use the folder button to browse for a folder.

The name of each track is the same as the name shown in the track list of the CD Reader window. If you've download track names from a database, then the **Replacement character** is used to replace any special characters, such as \, /, or : with safe characters so the files can be created properly.

Use the **Save as type** and the **Attributes** drop down lists to specify the format to use for the tracks. You can select one of many popular compressed formats, such as MP3, OGG, or WMA, to save hard drive space.

To overwrite any files with the same track name, check the **Overwrite existing files** box.

Colour Options

Use **Colour Options** to set the colours for Sound windows. A preview window shows the current colour scheme. Use the **Item** drop down list and the **Colour** button to change the colours or select a different scheme from the preset **Schemes**.

You can click the mouse in the preview window to select items.

See Also

[Using Presets](#)

[Window Options](#)

Storage Options

Use **Storage Options** to choose file and storage folders and set undo levels.

Sound Folder

Specifies the folder to use when you start GoldWave. The File | Open command uses this folder initially.

Temporary Storage

Specifies Hard Drive or RAM storage. When using hard drive storage, you can specify the folder to use when creating temporary files. This folder should be located on a large, local hard drive with plenty of free space. Changing this folder does not affect opened files already in temporary storage. Use RAM storage only when working with small files.

Undo levels specifies the number of times you can undo changes. A value of 5 means you can undo the five most recent changes performed on the file. A value of 0 means that you cannot undo any changes. Larger values use much more storage to store the previous audio data. When using the RAM storage option, this should be set to a small value. Otherwise RAM will be depleted quickly and system performance will degrade.

File Format Options

Use **File Format Options** to:

- Associate a filename extension (such as **.snd** or **.vox**) with an audio type and attributes.
- Change the precedence or enable and disable [file format plug-ins](#) used by GoldWave.
- Set a default format for saving files.

Undetectable Types Tab

Use this feature to associate a filename extension with an audio type and attributes. This is useful for automatically opening files that do not contain any information describing their format (raw files). For example, if you work with Dialogic files, you can associate the **.vox** extension with a specific plug-in type. In this case, you'd use the Dialogic type, usually with "ADPCM 4-bit, 8000Hz, 32 kbps, mono" attributes. Whenever you open a **.vox** file, GoldWave will assume that format without asking you to specify a format.

The list shows all current associations, if any. Use the [Add](#) button to create an association. Use the [Edit](#) button to modify an association. Use the **Remove** button to remove an association.

File Plug-in Precedence Tab

Use this feature to change the order that audio files are passed to plug-ins for opening, or to enable and disable plug-ins. By default all plug-ins found in the **File** plug-in folder are listed and enabled, with the built-in GoldWave plug-in listed first.

Select an item in the list and use the **Lower** and **Higher** buttons to change the order. The plug-in at the top of the list is the first one to be given the opportunity to open a file, if it recognizes the format. Otherwise, the file is passed to the next plug-in and so on until the file can be opened or no plug-ins are left. See [File Format Plug-ins](#) for more information. Check or uncheck an item to enable or disable that plug-in module.

Default Save Format Tab

Use this feature to set a default save format for new files when using the [File | Save](#) command. The same format can be used for all saving related commands as well if you check the **Use this format for...** box. Use the **Save as type** drop down list to select the type first, then use the **Attributes** drop down list to select appropriate attributes. Whenever you create and save a file, this format will be selected by default.

Associate Format

Use **Associate Format** settings to assign a specific plug-in module and attributes to a file extension.

Enter the file extension in the **Extension** box, such as vox, snd, raw. Do not insert a period before the type.

Select the plug-in module to assign to the extension using the **File type** drop down list.

Select the specific attributes from the **Attributes** drop down list.

If the file type and attributes support any sampling rate, set the sampling rate to use in the **Rate** box.

Some plug-in modules allow custom attributes to be set. If so, the **Custom** button will be enabled and can be used to set those attributes.

See Also

[File Format Options, Undetectable Types Tab](#)

Tool Bar Options

Configures the Main tool bar and Effect tool bar. Select an item and use the **Add** and **Remove** buttons or drag-and-drop items between the **Available** and **Current** lists to control the layout of the tool bars.

Use the **Visible** checkbox to show or hide the entire tool bar. Use the **Gray-scale** checkbox to convert the coloured images to blank-and-white. Use the **Captions** checkbox to display text within the Main tool bar buttons. Use the **Tool bar images in menu** checkbox to display images in GoldWave's main menu. Do not check this option if screen reader accessibility is required.

You can drag-and-drop the tool bars themselves within GoldWave's Main window to change their locations. Click on the double vertical bumps near the left edge of the tool bar to drag it.

Window Options

Use **Window Options** to configure the positions of windows, specify the zoom value for [View | Preset](#), and set the axes for Sound windows.

Main window size

Controls the startup position of the [Main window](#). Choosing **Normal** lets Windows determine the size and position. **Maximize** makes the Main window occupy the entire screen. **Save position** saves the Main window's position and size when GoldWave is closed so that it will appear in the same location next time.

Sound window size

Controls the position and size of [Sound windows](#). The **Normal** option lets Windows determine the size and position. **Maximize** makes a Sound window occupy the entire Main window. **Auto-tile** resizes all Sound windows whenever a new sound is opened or closed so all will be visible.

Y amplitude axis numbering

Sets the units of the vertical axis in [Sound windows](#). Selecting **Off** hides the axis completely. **Normalized** shows an axis with a range of -1.0 to 1.0. **Signed 16-bit** shows an axis ranging from -32768 to 32767, which is the range of 16-bit audio. **Unsigned 8-bit** shows an axis with a range of 0 to 255.

X time axis numbering

Sets the format for displaying the horizontal time axis in [Sound windows](#). **Hours : minutes : seconds** gives the time as three sets of numbers separated by colons, such as 12:23:56. **Minutes : seconds** gives the time as two sets of numbers separated by colons, such as 1234:56. **Seconds** gives the time as a floating point number, such as 1234.56.

Zoom

The **Preset** zoom value is used to for the [View | Preset](#) command. See [View | Specify](#) for more information. **Initial zoom** specifies the zoom level to use when a file is opened. If you choose **All**, then the entire waveform is shown using whatever zoom level is required.


Miscellaneous

If the **Always confirm before saving** option is checked, you will be asked to confirm saving whenever you use the [File | Save](#) command or **Save** tool bar button. If the **Draw overview graph** option is checked, then the overview is graphed based on audio from the file. Otherwise it is drawn as simple lines, which is quicker since the file does not have to be scanned. If the **Use left and right mouse button selection method** option is checked, then the start marker is set by using the left mouse button and the finish marker is set by using the right mouse button. No context menu appears. This is the way older versions of GoldWave worked. If the **Update default effect settings after each use** options is checked, then effect settings are stored after each use so that the same settings appear the next time the effect is used.

See Also

[View Menu Commands](#)

Control Properties

Use the Control Properties  button to display the **Control Properties** window. These properties lets you configure the playback and recording features, the real-time visuals, and the recording and playback devices:

[Play Properties](#)

[Record Properties](#)

[Volume Properties](#)

[Visual Properties](#)

[Device Properties](#)

See Also

[Control Window](#)

[Playing Sound](#)

[Recording Sound](#)

Control Play Properties

Use the **Control Play Properties** to configure the green and yellow play buttons and set the speed of the fast forward and rewind buttons.

Green/Yellow play button

All

Plays entire sound.

Selection

Plays region between start and finish markers. See [Editing Overview](#).

Unselected

Plays regions outside the start and finish markers. This lets you quickly test how a cut or delete will sound without actually changing the sound. When possible, playback is confined to the region shown in the Sound window view so that the entire file does not have to be played.

View

Plays the part of the sound currently shown in the [Sound window](#) graph.

Finish

Plays three seconds just before the finish marker, so you can determine if the marker is in the right place without listening to the entire selection. Note you can right-click on the Sound window graph and choose the **Play From Here** command.

Intro/loop/end

This is a special playback feature that plays the sound in three sections. The beginning of the sound, to the right of the start marker, is played first. Then the selection is played and looped. Finally the end of the sound, to the left of the finish marker, is played. This is useful for musical accompaniment or looped instrument samples.

Loop

Specifies the number of times playback should be repeated. A value of 1 loops playback once, so the region is played twice. A zero value loops forever. Check or uncheck the box to enable or disable looping.

Fast/Rewind speed

Configures the speed of the fast forward and rewind buttons. By entering a value of **3.00** for **Rewind speed**, for example, the rewind button will play the sound backwards three times faster than regular playback speed. By entering small numbers (such as **0.1**) the rewind and fast forward buttons will play slowly. This is useful for finding pops or clicks, since the visuals will move slowly through the data.

See Also

[Control Properties](#)

[Control Window](#)

[Playing Sound](#)

Control Record Properties

Use **Control Record Properties** to configure recording features and options. To set recording volumes, choose the [Volume](#) tab.

Recording options

Monitor input

Connects the recording device to the visuals so you can adjust recording levels before recording. See [Recording Sounds](#) for information about selecting a different recording source and setting volumes.

Ctrl key safety

Prevents you from accidentally recording over a sound. To record, you must hold down the **Ctrl** key. If you do not, a safety message appears.

Recording mode

Bounded to selection

Recording is confined to the selection. Recording starts at the start marker's position and stops at the finish marker's position. If you stop the audio before the finish marker is reached, the remainder of the selection is filed with silence.

Bounded and looped

Recording is confined to the selection, as above, but recording never stops. When the finish marker is reached, recording continues from the start marker's position. Looping repeats until the stop button is pressed. This is useful for capturing quotes from a TV show without having to store the entire show. By loop recording a 1 minute sound, you will always have the last minute of audio stored for recall.

Unbounded

Recording starts at the start marker's position and continues until the stop button is pressed or until no more storage is available. The recording replaces the selection. If the recording is a different length than the selection, then any audio beyond the finish marker is moved. Any audio beyond the finish marker is not recorded over.

Delayed recording

Timer

Delays recording until the specified **Time** and **Day**. Use this feature to automatically record something at a later time. The time is given in 24 hour time. A time of **06:00:00** is 6:00 AM and a time of **18:00:00** is 6:00 PM. **00:30:00** is 12:30 AM or 30 minutes past midnight. If entering the time directly, remember to include the seconds. Entering **18:00** means 00:18:00. **Important:** You must press the record button to activate the timer.

Level activated

Automatically starts recording when the sound source is above a given level and pauses recording when the sound is below the level. Level activated recording is useful for automatically synchronizing recording to a sound source or efficiently capturing airport or police radio where there may be a lot of silence that does not need to be recorded. The **Threshold** specifies how loud a sound should be before

recording begins. Normally, this value should be small (less than 0.2). The **Duration** specifies how long to continue recording after the sound becomes quiet again. Entering a zero value allows recording to continue without stopping (i.e. once activated, recording does not pause). The **Prebuffer** specifies the amount of audio to store prior to activation. When activation occurs, the prebuffer audio is inserted before the currently recorded audio, allowing you to hear the sound slightly before activation. The **Time stamp cues** option provides a way of marking the date, time, and position of each activation. Cue points with the current date and time are created and inserted in the file. Use the [Cue Points](#) tool to see the list of dates.

See Also

[Control Properties](#)

[Control Window](#)

[Recording Sound](#)

Control Volume Properties

Use **Control Volume Properties** to adjust recording volumes and select or unselect recording sources. Make sure the device given in the **Volume device** box matches the recording device under the **Device** tab.

A volume fader and checkbox are shown for each source. To select a source, check the appropriate checkbox. If your sound card supports a master control, make sure that the **Mute all** option is not checked and that the master volume is not zero.

You can use the **Monitor input** option under the Record tab to activate the real-time visuals without recording. With monitoring enabled, you can see the levels as you adjust the volume faders.

Note that volumes are changed regardless of whether you choose **OK** or **Cancel** to close the Control Properties window.

To select a different recording device, use the Device tab.

See Also

[Control Properties](#)

[Recording Sound](#)

Control Visual Properties

Use **Control Visual Properties** to configure real-time visuals. GoldWave displays four visuals: a status visual just below the playback and recording buttons, a level visual just below the volume and speed faders, and two larger visuals for displaying left and right audio data. Some visuals are designed to work in any of the four locations, but most work in a specific location, such as the **Time and Status** visual. Use the **Status visual**, **Level visual**, **Left visual** and **Right visual** drop down lists to select visuals for the given location.

Use the **Quick select menu** list to select your favourite visuals. You can quickly display a favourite visual by right-clicking on any compatible visual location in the Control window, then choosing one of the visuals from the menu that appears.

Frame rate controls the number of frames per second to draw the visuals. A high value (above 60) requires a fast system, while a low value improves performance on slow systems.

FFT window contains several common window functions used for FFT frequency analysis to minimize artifacts caused by a finite analysis window. The default **Kaiser 7** option usually works best.

Some visuals have properties you can change, such as axes ranges and display modes. To set a visual's properties (if any), close the Control Properties window, right-click on the visual in the Control window, then select **Properties** from the menu that appears.

See Also
[Control Properties](#)

Control Device Properties

Use **Control Device Properties** to select and configure recording and playback devices.

Playback device and **Record device** show the currently selected playback and recording devices. If more than one device is installed, you can select a different device from the drop down list. You can change playback and recording quality by selecting different bit depths from the **Quality** lists. Use **16 bit integer** quality unless your sound card supports higher bit depths.

Joystick control allows playback and recording to be controlled using a joystick or gamepad. The first detected joystick is used. The main directional pad controls playback. Left is rewind, right is fast forward, down is pause, and up unpauses. The first button (button 1 or A) starts or stops playback. The second button (button 2 or B) starts or stops recording.

High latency reduces intermittent, stuttered playback caused by older sound devices that require DirectX emulation under Windows. Higher latency means that more audio is buffered for playback. It also means that changes to the volume, balance, and speed take longer to register.

Alternative playback initialization solves some problems with certain drivers and plug-ins. Use this option if the GoldWave freezes when previewing a DirectX Audio Plug-in effect or if playback does not start properly in general.

See Also

[Control Properties](#)

Colour Scale Properties

Select one of the listed items to change the colour scale used to display the visual.

Colour scales are used by the 3D Bar visual, which displays a three dimensional frequency bar graph, and the Bulge visual, which display a double mirrored colour frequency graph.

Bulge

The Bulge visual displays a symmetrical colour scaled frequency graph where higher magnitude frequencies are shown with taller lines and more intense colours. The **X scale** setting controls whether the frequencies are drawn on a linear or logarithmic scale. The logarithmic scale greatly expands low end frequencies. The magnitudes (heights) are always drawn logarithmically.

Spectrogram Properties

The Spectrogram visual displays frequency information over time. The horizontal axis is time in seconds (s), the vertical axis is frequency in Hertz (Hz), and the colour represents the frequency's magnitude (dB). The louder a certain frequency is, the more intense its colour is. The bottom of the visual show the intensity colour scale (if the **Show axis** box is checked).


Use the properties to adjust the vertical frequency range shown in the graph. The **Automatic full frequency range** option automatically sets the range depending on the sampling rate of the file. For a 44100Hz file, the range is set from 0 to 22050Hz (the Nyquist rate). The **Fixed frequency range** option allows you to set a specific range down to a few hundred Hertz. Use the **Show axis** box to show or hide the horizontal and vertical axes and the intensity scale.

Spectrum Properties

The Spectrum visual displays a simple frequency graph. The horizontal axis is frequency in Hertz (Hz) and the vertical axis is magnitude in decibels (dB).


Use the properties to adjust the horizontal frequency range shown in the graph. The **Automatic full frequency range** option automatically sets the range depending on the sampling rate of the file. For a 44100Hz file, the range is set from 0 to 22050Hz (the Nyquist rate). The **Fixed frequency range** option allows you to set a specific range down to a few hundred Hertz. Use the **Show axis** box to show or hide the horizontal and vertical axes.

Presets


Presets store settings and shapes in the registry so they can be recalled again the next time the effect is used. Controls for presets consist of a drop down list box, an  add button, and a

 remove button. Most effects have a **Default** preset, which can be changed so that certain settings are used every time the effect window is shown.


To add a new preset:

- 1) Enter in all the new parameters and/or draw the new shape.
- 2) Type in a name for the preset in the drop down list box.
- 3) Choose the  (add) button.

To delete a preset:

- 1) Select the preset from the drop down list.
- 2) Choose the  (remove) button.
- 3) Choose **OK** to delete the preset.

To change a preset:

- 1) Select the preset from the drop down list.
- 2) Enter in all the new settings.
- 3) Choose the  (add) button.
- 4) Choose **OK** to overwrite the old preset.

Shape Controls

Shape controls usually consist of a graph window and a set of controls, including a point number box, an add point button, a remove point button, an X value box, and a Y value box.

Graph window

The graph window initially contains a single line with two endpoints (shown as large dots). By clicking the left mouse button anywhere inside the graph window, you can **add** new points to bend the line into a variety of zigzag shapes. To **move** a point, click on it and drag it to a new location. To **remove** a point, click the **right** mouse button over the point. Endpoints cannot be removed.

Controls

Points can be added, moved, and removed by using the controls. Use the **Point** box to select the current point. Change the **X** and **Y** values to move the point. Use the add point button to insert a new point between the current point and the next point. Use the remove point button to remove the current point, except if it is an endpoint.

Some dynamic effects, such as Doppler, Pan, and Volume Shape start previewing audio based on the current point's time value. If the X value of the current point is 1:00, for example, then preview playback starts at one minute from the beginning of the file rather than the beginning of the selection. This lets you preview the point's settings without playing the entire selection.

To save a shape, use the Presets controls.

When performing FFT processing, the sound is processed one block at a time. To smooth out transitions from one block to the next, it is necessary to overlap blocks. The Overlap value controls what percentage the FFT analysis of one block overlaps the next. A high percentage makes the transition between each block more smooth. It also requires more processing time since overlapping samples are recalculated several times. A low percentage results in rougher transitions, but processes much faster. A value of 88% or higher is recommended.

When performing FFT processing, the sound is processed one block at a time. The FFT size value controls the size of these blocks. The number of samples to process is calculated by taking the value as a power of 2. A value of 10 gives 2 to the 10th power, or 1024.

Old License Information

This version of GoldWave requires an ID based license. If you have an old name/password based license, you'll need to request an updated license from the [website](#)

GoldWave Order Form

Please provide the following information:

Full Name (first & last): _____

Address: _____

Country: _____

[Telephone (with Area Code)]: _____

E-mail address: _____

Version you are using: v5.04

GoldWave license: US\$40, Can\$55, UK£25

Payment:

- Check/money order enclosed (payable to GoldWave Inc.)
- VISA credit card (charged in Canadian currency)

VISA number: _____

Expires: ___/___

Cardholder name: _____

Signature: _____

Please mail this form to the address below. Thank you for registering!

GoldWave Inc.
P.O. Box 51
St. John's, NF
CANADA A1C 5H5

Website Links

Company site:

<http://www.goldwave.com>

Ordering information:

<http://www.goldwave.com/gwregister.html>

Frequently asked questions:

<http://www.goldwave.com/faq.html>

Registering

GoldWave is a shareware program. It is not free software. After trying GoldWave, the modest registration fee should seem very reasonable considering all of the great features. To register and support further development, please see the [website](#). You can order securely online or you can fill in the [order form](#) and send it by regular mail. Registration details are given below. If you've already purchased a license, please enter it into the program (close this help window first).

Registration License (US\$40, Can\$55, UK£25)

You will receive a unique ID and License that removes the startup and usage messages and unlocks GoldWave. The same license will work with all future versions of GoldWave. This is equivalent to a lifetime of free updates! All you have to do is download the latest version from the GoldWave website:

<http://www.goldwave.com>

Sending Payment

Checks from banks in the **United States, Canada,** and the **United Kingdom** are welcome. VISA credit card orders are accepted. Other credit cards cannot be accepted at this time, except [online](#).

International postal money orders or **international postal bank draft cheques** are also accepted, but payment must be made in Canadian currency.

Order Now

GoldWave Shareware Version

This application is a **fully functional** shareware version of the GoldWave digital audio editor. Shareware allows you to try a program before you buy it. After you've tried GoldWave, if you decide to keep it, you are required to register it. Please note the usage limit mentioned below.


Getting Started:

- [Playing Sounds](#)
- [Recording Sounds](#)
- [Selecting Part of a Sound](#)

Please check the [Contents](#) for additional information. The [WhatsNew.txt](#) file lists recent changes and the revision history. The [GoldWave.htm](#) file contains the manual, with detailed instructions for using GoldWave.

For the latest information and updates, please refer to the GoldWave website:

<http://www.goldwave.com>



Usage Limit

The upper right status bar displays a command count (unlicensed usage), which gives you a rough idea of how much you use the program. This shareware version is limited to 150 commands each session and 3000 commands total. When the session limit is reached, a reminder message will appear whenever you use a control in the Control window. Exiting and restarting GoldWave will let you use another 150 commands without interruption. The program will stop working when the total command count is reached. By registering, you will receive a license that removes this counter completely.

As shareware, you can give copies of GoldWave to anyone you think might find it useful. You can upload it to Web, BBS or ftp sites and post it to appropriate forums or newsgroups. Magazine and book publishers can include GoldWave on cover and companion CD-ROMs. Before copying, uploading, or posting, please click [here](#).

Only the original GoldWave zip file or self-extracting exe file may be copied, uploaded, or posted. This ensures that everyone will get a complete and working copy. Distributing modified or incomplete copies is a violation of the copyright. Note that GoldWave is not free software and should not be described as such.

