

WinHex 11.26

General Information

[About WinHex](#)
[Using a Hex Editor](#)
[Integer Data Types](#)
[Date Types](#)
[ANSI ASCII/IBM ASCII](#)
[Technical Hints](#)

[Ordering Information](#)
[Floating-Point Data Types](#)
[Checksums](#)
[License Agreement](#)

Working with the Hex Editor

[Start Center](#)
[Entering Characters](#)
[Useful Hints](#)
[Disk Editor](#)

[Options](#)
[Edit Modes](#)
[Scripts](#)
[RAM Editor](#)

[Status Bar](#)
[API](#)

Menu Reference

[File Menu](#)
[Search Menu](#)
[Tools Menu](#)
[File Manager](#)
[Help Menu](#)

[Edit Menu](#)
[Position Menu](#)
[Specialist Tools](#)
[Window Menu](#)
[Context Menu](#)

[View Menu](#)
[Options Menu](#)

Extras

[Conversions](#)
[Data Interpreter](#)
[Position Manager](#)
[Template Editing](#)

[Modify Data](#)
[Disk Cloning](#)
[Backup Manager](#)
[**Data Recovery**](#)

[Wiping and Initializing](#)

WinHex 11.26

© 1995-2004 Stefan Fleischmann

Marketed by X-Ways Software Technology AG, a stock corporation incorporated under the laws of the Federal Republic of Germany.

Postal address: Carl-Diem-Str. 32 • 32257 Bünde • Germany

E-mail address: mail@x-ways.com

Fax: +49-721-151 322 561

First released in 1995, last updated in March 2004.

The following operating systems are supported:

- Windows 95/98/Me
- Windows NT 4.0
- Windows 2000
- Windows XP

Homepage: <http://www.x-ways.net>

Forum: <http://www.winhex.net>

Please find the latest version of this program there.

French translation by Jérôme Broutin (user interface) and Henri Pouzoullic (program help) in January 2000. Revised and updated since by Bernard Leprêtre. Entire Spanish translation by José María Tagarro Martí. Italian translation by Luca Cantarini (user interface). Brazilian Portuguese translation by Heyder Lino Ferreira (user interface).

Cryptography consulting: Alexandre Pukall

ZDNet Software Library Rating: 5 stars (of 5)!

Registered professional users around the world include:

U.S. and German federal law enforcement agencies, U.S. national institutes (e.g. the Oak Ridge National Laboratory in Tennessee), ministries such as the Australian Department of Defence, the Technical University of Vienna, the Technical University of Munich (Institute of Computer Science), the German Aerospace Center, the German federal bureau of aviation accident investigation, Microsoft Corp., Hewlett Packard, Toshiba Europe, Ericsson, Novell Inc., Ontrack Data International Inc., KPMG Forensic, Siemens AG, Siemens Business Services, Siemens VDO AG, Infineon Technologies Flash GmbH & Co. KG, Lockheed Martin, BAE Systems, TDK Corporation, Seoul Mobile Telecom, Visa International, DePfa Deutsche Pfandbriefbank AG, Analytik Jena AG, and many other companies and scientific institutes. Order the [full version](#) now!

The algorithms Pukall Cipher 1 (PC 1) and Pukall Stream Cipher Hash Function are copyright by Alexandre Pukall. Source code available from <http://www.multimania.com/pc1>.

The MD5 message digest is copyright by RSA Data Security Inc.

The "zlib" compression library is copyright by Jean-loup Gailly and Mark Adler. Homepage: <ftp://ftp.cdrom.com/pub/infozip/zlib/zlib.html>

Using a Hex Editor

A hex editor is capable of completely displaying the contents of each file type. Unlike a text editor, a hex editor even displays control codes (e. g. linefeed and carriage-return characters) and executable code, using a two-digit number based on the hexadecimal system.

Consider one byte to be a sequence of 8 bits. Each bit is either 0 or 1, it assumes one of two possible states. Therefore one byte can have one of $2 \cdot 2 \cdot 2 \cdot 2 \cdot 2 \cdot 2 \cdot 2 \cdot 2 = 2^8 = 256$ different values. Since 256 is the square of 16, a byte value can be defined by a two-digit number based on the hexadecimal system, where each digit represents a tetrad or nibble of a byte, i. e. 4 bits. The sixteen digits used in the hexadecimal system are 0-9, A-F.

You can change the value of a byte by changing these digits in the hexadecimal mode. It is also possible to enter the character that is assigned to a certain byte value by a character set (cf. Entering Characters). All kinds of characters are allowed (e.g. letters and punctuation marks). Example: A byte whose decimal value is 65 is displayed as 41 in hexadecimal notation ($4 \cdot 16 + 1 = 65$) and as the letter A in text mode. The ASCII character set defines the capital letter A to have the decimal value of 65.

When editing files of a certain type (for instance executable files), it is essential not to change the file *size*. Moving the addresses of executable code and included data results in severely damaging such files. Please note that changing the contents of a file generally may be the reason for the corresponding application to behave anomalously. It is quite safe to edit text passages in a file. At any rate, it is recommendable to create backup files before editing.

The command "Combined Search" was especially designed for editing files created by computer games to save the game state. If you know the value of a variable in two of such files, you can find out the offset, i. e. the position, at which this data is saved. Example: If two files hold the information that you have 5 resp. 7 points/lives/..., search simultaneously for the hex value 05 in the first and 07 in the second file.

Ordering Information

You may evaluate WinHex free of charge, as long as you need. For regular use and for use as a full version, you need a *base* license (personal, professional, or specialist). If you are going to install WinHex on more than one machine, you will also need *additional* licenses. The full version will save files larger than 200 KB, write disk sectors, edit virtual memory and show no evaluation version reminders. It will reveal its license status on start-up and in the About box.

- Personal licenses are available at a reduced price for non-commercial purposes only, in a non-business, non-institutional, and non-government environment.
- Professional licenses allow usage of the software in *any environment* (at home, in a company, in an organization, or in public administration). Professional licenses provide the ability to execute scripts and to use the WinHex API.
- Specialist licenses in addition to this allow to use the Specialist Tools menu section. Particularly useful for computer forensics and IT security specialists.

Pricing

Personal licenses: EUR 39.90 / US\$ 49 (base license)
 EUR 29.90 / US\$ 37 (each additional license)

Professional licenses: EUR 75.90 / US\$ 93 (base license)
 EUR 45.90 / US\$ 56 (each additional license)

Specialist licenses: EUR 124.90 / US\$ 153 (base license)
 EUR 72.90 / US\$ 89 (each additional license)

Recommended within the European Union: Have your bank transfer the money directly into our company's bank account (see below) and notify us. When transferring from outside of the Euro area, please add EUR 7 / US\$ 9 once. Please specify "WinHex 11.26" and your address when ordering/sending payment/notifying us.

For **online ordering**, please visit the WinHex Internet order page <http://www.x-ways.net/winhex/order.html>. Payment by **credit card** accepted. Fastest option. Somewhat more expensive than stated above.

When your payment is received, you will be sent license codes and instructions how to use them to turn WinHex into the full version. Upgrading to later versions that are released within 15 months (counted from the release of the version you pay for) is free! (probably even more)

X-Ways Software Technology AG
Carl-Diem-Str. 32
32257 Bünde
Germany

Homepage: <http://www.x-ways.net>
E-Mail: mail@x-ways.com
Fax: +49-721-151 322 561

Bank account owner: X-Ways AG
Account No.: 2705390
Bank code No.: 48070024
Bank name: Deutsche Bank PGK
SWIFT/BIC: DEUT DE 3B 492

IBAN: DE28 4807 0024 0270 5390 00

Bank address: Deutsche Bank PGK, Filiale Bünde, Bahnhofstr. 7-9, 32257 Bünde, Germany

Thank you very much for your order!

Integer Data Types

<u>Format/Type</u>	<u>Range</u>	<u>Example</u>
signed 8 bit	-128...127	FF = -1
unsigned 8 bit	0...255	FF = 255
signed 16 bit	-32,768...32,767	00 80 = -32,768
unsigned 16 bit	0...65,535	00 80 = 32,768
signed 32 bit	-2,147,483,648...2,147,483,647	00 00 00 80 = -2,147,483,648
unsigned 32 bit	0...4,294,967,295	00 00 00 80 = 2,147,483,648
signed 64 Bit	$-2^{63} \dots 2^{63}-1$	00 00 00 00 00 00 00 80 = -2^{63}

Unless stated otherwise, multi-byte numbers are stored in little-endian format, meaning that the first byte of a number is the least significant and the last byte is the most significant. This is the common format for computers running Microsoft Windows. Following the little-endian paradigm, the hexadecimal values 10 27 can be interpreted as the hexadecimal number 2710 (decimal: 10,000).

The Data Interpreter is capable of interpreting data as all of the aforementioned integer types.

Floating-Point Data Types

<u>Type</u>	<u>Range</u>	<u>Precision</u>	<u>Bytes</u>
Float (Single)	$\pm 1.5e-45..3.4e+38$	7-8	4
Real	$\pm 2.9e-39..1.7e+38$	11-12	6
Double (Double)	$\pm 5.0e-324..1.7e+308$	15-16	8
Long Double (Extended)	$\pm 3.4e-4932..1.1e+4932$	19-20	10

The type names originate from the C programming language. The corresponding Pascal names are specified in brackets. The Real type exists only in Pascal. The Data Interpreter is capable of translating hex values in an editor window into floating-point numbers of all four types and vice-versa.

In the computer, a floating-point number F is represented by a mantissa M and an exponent E , where $M \times 2^E = F$. Both M and E are signed integer values themselves. The four data types differ in their value ranges (i.e. the number of bits reserved for the exponent) and in their precision (i.e. the number of bits reserved for the mantissa).

On Intel-based systems, calculations upon floating-point numbers are carried out by a math coprocessor while the main processor waits. The Intel 80x87 uses 80-bit precision for calculations, whereas RISC processors often use 64-bit precision.

ANSI ASCII/IBM ASCII

ANSI ASCII is the character set used in Windows applications. It is standardized by the American National Standards Institute. MS-DOS uses the IBM ASCII character set (also called OEM character set). These character sets differ in the second half, containing characters with a ASCII values greater than 127.

It is reasonable to switch the menu option "Use ANSI ASCII" off when viewing or editing files belonging to a DOS program.

Use the "Convert" command of the Edit Menu to convert text files from one character set into the other.

The first 32 ASCII values do not define printable characters, but control codes:

Hex Control Code

0	Null
1	Start of Header
2	Start of Text
3	End of Text
4	End of Transmission
5	Enquiry
6	Acknowledge
7	Bell
8	Backspace
9	Horizontal Tab
A	Line Feed
B	Vertical Tab
C	Form Feed
D	Carriage Return
E	Shift Out
F	Shift In
10	Data Link Escape
11	Device Control 1 (XON)
12	Device Control 2
13	Device Control 3 (XOFF)
14	Device Control 4
15	Negative Acknowledge
16	Synchronous Idle
17	End of Transmission Block
18	Cancel
19	End of Medium
1A	Substitute
1B	Escape
1C	File Separator
1D	Group Separator
1E	Record Separator
1F	Unit Separator

Checksums

A checksum is a characteristic number used for verification of data authenticity. Two files with equal checksums are highly likely to be equal themselves (byte by byte). Calculating and comparing the checksums of a file *before* and *after* a possibly inaccurate transmission may reveal transmission errors. An unaffected checksum indicates that the files are (in all likelihood) still identical. However, a file can be manipulated on purpose in such a way that its checksum remains unaffected. Digests are used instead of checksums in such a case, where malicious (i.e. not mere random) modifications to the original data are to be detected.

In WinHex, checksums are calculated when opening (optional, cf. Security Options) or analyzing (cf. Tools Menu) a file. After modifying files, checksums can be re-calculated by pressing Alt+F2.

The standard checksum is simply the sum of all bytes in a file, calculated either on an 8-bit, a 16-bit, a 32-bit, or a 64-bit accumulator. The CRC (cyclic redundancy code) is based on more sophisticated algorithms, which safer.

Example: If a transmission alters two bytes of a file in such a way that the modifications are countervailing (for instance byte one +1, byte two -1), the standard checksum remains unaffected, whereas the CRC changes.

Technical Hints

Amount of memory used:	1.0 MB
Maximum number of windows:	1000 (Windows NT/2000), 500 (Windows 9x)
Maximum file & disk size:	~ 2000 GB
Max. no. of program instances:	99
Maximum number of positions:	limited by RAM only
Max. reversible keyboard inputs:	65535
Encryption depth:	128 bit
Digest length in backups:	128/256 bit
Character sets supported:	<u>ANSI ASCII</u> , <u>IBM ASCII</u> , EBCDIC (limited)
Offset presentation:	hexadecimal/decimal

- In most cases, the progress display shows the completed percentage of an operation. However, during search and replace operations it indicates the relative position in the current file or disk.
- The user interface looks best if *no* extra large font is used in your Windows system.
- WinHex expects your computer to be running in little-endian mode.
- Search and replace operations generally run fastest with case sensitivity switched on and without wildcards enabled.
- Here are some pieces of information concerning the Master Boot Record of a hard disk, that is editable using the Disk Editor.
- When searching with the option "count occurrences" activated or when replacing without prompting, for a search algorithm there are generally two ways to behave when an occurrence has been found, which in some cases may have different results. This is explained by the following example:

The letters "ana" are searched in the word "banana". The first occurrence has already been found at the second character.

1st alternative: The algorithm continues the search at the third character. So "ana" is found again at the fourth character.

2nd alternative: The three letters found in the word "banana" are skipped. The remaining letters "na" do not contain "ana" any more.

WinHex is programmed in the second manner, since this delivers the more reasonable results when counting or replacing occurrences. (If you continue a search using the F3 key or you choose the replace option "prompt when found", the algorithm follows the first alternative.)

- For further technical information, please consult the WinHex homepage at <http://www.winhex.com>.

Legalities

Copyright © 1995-2004 Stefan Fleischmann. All rights reserved.
Marketed by X-Ways Software Technology AG.

License Agreement

Your use, distribution, or installation of a software product published by X-Ways Software Technology AG indicates your acceptance of this license agreement. If you do not agree to any of the terms, then do not install, distribute or use the product.

A trial version may be only used for evaluation purposes. Purchasing one license authorizes you to install one copy of the full version of the software on a single machine. Additional licenses authorize you to install additional copies of the full version at the same time.

This software, and all accompanying files, data, and materials, are distributed "as is" and with no warranties of any kind, whether express or implied, to the maximum extent permitted by applicable law. The user must assume the entire risk of using the program, knowing in particular that this software is not designed or intended for use in hazardous environments requiring fail-safe performance, where its failure to perform, misuse or inability to use adequately can reasonably be expected to lead to death, personal injury, or severe physical or environmental damage. In no event shall X-Ways Software Technology AG, or its officers, directors, employees, affiliates, contractors, or subsidiaries be liable for any direct, indirect, incidental, consequential, or punitive damages whatsoever arising out of the use or inability to use the software, to the maximum extent permitted by applicable law. Any liability will be limited exclusively to refund of purchase price by X-Ways Software Technology AG.

You may not rent, lease, modify, translate, reverse-engineer, decompile or disassemble the software or create derivative works based on it without prior explicit permission. All rights of any kind in the software product which are not expressly granted in this license agreement are entirely and exclusively reserved to and by X-Ways Software Technology AG.

--

The algorithms Pukall Cipher 1 (PC 1) and Pukall Stream Cipher Hash Function are copyright by Alexandre Pukall. Source code available from <http://www.multimania.com/pc1/>, <http://www.multimania.com/cuisinons/progs/>, and <http://www.freecode.com>.

The "zlib" compression library is copyright by Jean-loup Gailly and Mark Adler. Homepage: <ftp://ftp.cdrom.com/pub/infozip/zlib/zlib.html>

About the program help

This publication is designed to provide accurate and authoritative information in regard to the subject matter covered. However, the author neither offers any warranties or representations nor does he accept any liability with respect to the program or its manual.

No part of this publication may be reproduced, or stored in a database or retrieval system without the prior permission of the author. Any brand names and trademarks mentioned in the program or in this program help are properties of their respective holders and are generally protected by laws.

General Options

1st column:

- At startup, WinHex can optionally **show** the **Start Center** or **restore** the **last window constellation** (all windows with their sizes and the positions as you left them in the precedent WinHex session).
- Specify the number of **recently** opened **documents** to remember and to **list** in the Start Center (255 at max.). Up to 9 of them are also listed at the end of the File menu.
- In addition to *which documents* (file or disk) you had recently opened, WinHex can optionally also **remember** the last editing **positions** and the block (if defined).
- You may have **WinHex** appear in the Windows **context menu**. The shell displays the context menu when the user clicks an object with the right mouse button. WinHex provides menu items for files, folders and disks. If this option is not fully selected, there is no menu item for files.
- The option **Allow multiple program instances** lets you execute WinHex more than once on a single computer at a time. If it is not enabled, WinHex puts the main window of the running instance into the foreground instead of creating a new program instance.
- **Do not update file time** means that WinHex will not change the last write time when a modified file is saved.
- If **Check for surplus sectors** is disabled, WinHex will not try to search for surplus sectors when a physical hard disk is opened. When additional sectors are detected, WinHex will remember them the next time you open the disk. You may enforce a new check by holding the Shift key while opening the disk. Checking for surplus sectors may cause very long delays, strange behavior or even damage to the Windows installation on *some very few* systems. Only under Windows XP surplus sectors are included automatically, which renders this option obsolete.
- By default, **edit windows** are not **opened** in a **maximized** state.
- On a right click, **WinHex** can bring up a special **context menu**, the regular edit menu, or define the end of the current block.
- If you select **Show file icons**, the icons stored in a file are shown in the information column. This increases memory requirements and delays the opening of files. If a file contains no icons, the icon of the file *type* is shown, except this option is not "fully" selected.
- The **ENTER** key can be used to enter up to four two-digit hex values. A useful example is **0x0D0A**, which is interpreted as an end-of-line marker in the Windows world (Unix: 0x0D). The Start Center could then still be opened using SHIFT+ENTER.
- Decide whether you want to use the **TAB key** to switch from text to hexadecimal mode and vice versa or to enter the TAB character (0x09). In any case, TAB+SHIFT can be pressed to switch the current mode.

2nd column:

- Specify the **folder** in which to create **temporary files**.
- Specify the **folder** in which to create **backup files** (.whx).

- Specify the **folder** in which to create **project files** (.prj).
- Specify a path to your favorite **text editor**. WinHex offers you to view the report of [file comparisons](#) using this program.
- Specify a path to your favorite **viewer** (cf. [Tools](#) menu)
- Decide the number of **bytes per line** in an edit window. Common values are 16 or 32 (depending on the screen resolution).
- Decide how many **bytes** shall be displayed in a **group**. Powers of 2 serve best for most purposes.

3rd column:

- **Offsets** can be presented and prompted for in a decimal or **hexadecimal** notation. This setting is valid for the entire program.
- When using the [RAM editor](#) it may be reasonable to have WinHex display **virtual addresses** instead of zero-based offsets. This is always done in hexadecimal notation. The dialog window of the [Goto Offset](#) command will also prompt for virtual addresses.
- If line-by-line scrolling is selected, **page** and sector **separators** may be **displayed**. If this option is enabled partially, only sector separators are displayed.
- **Scrolling** can be done either **line by line** or pagewise.
- Specify how many **lines to scroll** when **rolling** the mouse **wheel** (if available).
- You may select one of several different **dialog window** and **button styles**.
- **Use Windows default colors** should be self-explanatory.
- Select a **color** used as the **background** of the current **block**. You can only change the color if the option "Use Windows default colors" is switched off.
- Select a **color** used as the **background** of every other fixed-length *record*, if [record presentation](#) is enabled.
- You may want WinHex to **hilite modified bytes**, i.e. display altered parts of a file, disk, or memory in a different color, so you can distinguish between original data and changes you have made so far. You may select the hilite color.
- You may choose a **font** for [ANSI ASCII](#) mode. The WinHex font implements the full Windows character set (even characters such as the TM and Euro symbols and diverse quotation marks).
- **Display Windows-styled progress bar** replaces the WinHex progress bar with the typical progress bar common to most Windows programs.

--

Factory settings of *all* options can be restored using the Initialize command of the [Help menu](#).

Entering Characters

In hex mode only hexadecimal characters are to be entered ('0'...'9', 'A'...'F'). In text mode you can enter all kinds of characters: letters, numbers, punctuation marks and special characters (e. g. '»', ']' and '^'). Please use the Windows program charmap.exe to find out key combinations for such characters (e. g. Alt-1-7-5 for '»'). The "WinHex" font even supports the Euro symbol.

Edit Modes

Default edit mode: Modifications to files or disks opened in default edit mode are stored in temporary files. The latter are created dynamically when needed. The menu command "Save" of the File Menu updates the original file or disk.

View mode: Files or disks that are opened in view mode cannot be edited, only viewed. In other words, they are opened write-protected.

In-place edit mode: Please use caution when opening files or disks in in-place edit mode. *All* kinds of modifications (keyboard input, filling/removing the block, writing clipboard data, replacements, ...) are written *to the original file* ("in-place") *without prompting!* It is not necessary to save the file manually after having modified it. Instead, the modifications are saved lazily and automatically, at latest when closing the edit window. However, you may use the Save command to ensure the buffer is flushed at a given time.

The in-place edit mode is preferable if the data transfer from the original to the temporary file and vice-versa, which is obligatory in default edit mode for certain operations, consumed too much time or disk space. This may be the case when opening very large files or when modifying huge amounts of data. Since usually no temporary files are needed in in-place edit mode, this edit mode is generally faster than the default edit mode. The in-place edit mode is the only mode available when using the RAM editor.

Hint: Even in in-place edit mode the creation of a temporary file is unavoidable when altering the file *size*.

Status Bar

The status bar displays the following information about a file:

1. Number of current page and total number of pages (disk editor: sectors)
2. Current position (offset)
3. Decimal translation of the hex values at the current position
4. Beginning and end of the current block (if currently defined)
5. Size of current block in bytes (ditto)

Click the status bar cells in order to...

1. Move to another page/sector,
2. Move to another offset,
3. Define the integer type for decimal translation and
4. Define the block.

Right-click the status bar in order to copy pieces of information from the status bar into the clipboard.

Right-clicking the 2nd status bar field permits switching between absolute (default) and relative offset presentation.

Right-clicking the 3rd status bar field also permits copying the four hex values at the current position in reverse order into the clipboard. This is useful for following pointers.

Useful Hints

- Use the mouse buttons as follows to define the block (if the context menu is switched off):
 - Double-clicking left sets the block beginning.
 - Single-clicking right sets the block end.
 - Double-clicking the right button clears the block.
 - You may want to define the block using the keyboard (Shift+arrow keys or Alt+1 and Alt+2).
 - Use the TAB key to switch between hexadecimal and text mode.
 - Use the Ins key to switch between insert and overwrite mode.
 - Ctrl+Q closes all windows.
 - Enter displays the Start Center.
 - Ctrl+Enter displays the Window Manager.
 - ESC aborts the current operation if any, otherwise clears the block, dismisses an active dialog or template window.
 - PAUSE stops or continues the current operation.
 - F11 repeats the last Go To Offset command. Ctrl+F11 works in the opposite direction (from the current position).
 - Alt++ is a variant of the Go To Offset command specifically to jump a certain number of sectors *down*.
 - Alt+- is another variant specifically to jump a certain number of sectors *up*.
 - Shift+F7 switches between three character sets.
 - (Shift+)Alt+F11 repeats the last Move Block command.
 - Alt+F2 recalculates the auto-hash (checksum or digest) after a file was modified.
 - Alt+Left and Alt+Right allow for switching between records within a template (just as the "<" and ">" buttons). Alt+Home and Alt+End access the first and the last record, respectively.
 - Alt+G moves the cursor in the edit window to the current template position and closes the template window.
 - Ctrl+F9 opens the Access button menu (disk edit windows only)
- WinHex accepts filenames specified in the command line, and is drag-and-drop capable.
 - Use scripts to make your work with WinHex more efficient.
 - You can specify the name of a script as a command line parameter.
 - "Invalid input": After dismissing this error message box, the blinking cursor indicates what parameter provided by you is invalid and needs to be corrected.
 - Switch from hexadecimal to decimal offset presentation by clicking the offset numbers.
 - If a screen resolution of 800×600 or more is provided you can increase or decrease the editor window and the information column at the right by clicking and pulling the bottom borders.
 - Try clicking the status bar cells (left and right mouse button).

Disk Editor

The Disk Editor, that is part of the Tools menu, allows you to access floppy and hard disks below file system level. Disks consist of sectors (commonly units of 512 bytes). You may access a disk either logically (i. e. controlled by the operating system) or physically (controlled by the BIOS). On most computer systems you can even access CD-ROM and DVD media.

Opening a *logical drive* means opening a contiguous formatted part of a disk (a partition) that is accessible under Windows as a drive letter. It's also called a "volume". WinHex relies on Windows being able to access the drive. Opening a *physical disk* means opening the entire medium, as it is attached to the computer, e.g. a hard disk including *all* partitions. It could also be called the "raw device". The disk normally does not need to be properly formatted in order to open it that way.

Usually it is preferable to open a logical drive instead of a physical disk, because more features are provided in this case. For example, "clusters" are defined by the file system, the allocation of clusters to files (and vice versa) is known to WinHex, "free space" and "slack space" have a meaning. Only if you need to edit sectors outside a logical drive (e.g. the master boot record), if you wish to search something on several partitions of a hard disk at the same time, or if a partition is damaged or formatted with a file system unknown to Windows, so Windows is unable to make it accessible as a drive letter, you would open the physical disk instead. Via the menu that appears when clicking the "Access" button, you may also open individual partitions from within a physical disk.

Directory Browser

Questions & Answers

Please note the following limitations:

- Under Windows NT and its successors administrator rights are needed to access hard disks.
- Replace functions are not available.
- WinHex cannot *write* to CD-ROM or DVD.
- The disk editor cannot operate on remote (network) drives.

Edit free space on drive (Windows 95/98/Me)

Under Windows 95/98/Me, it is possible to edit the currently unused space on a logical disk. The aforementioned limitations do not apply in this case. WinHex creates a file which uses the complete free space on the selected drive. You can edit this file in in-place mode. The integrity of data in the used parts of the drive *cannot be affected* hereby.

You can use this function to recover unintentionally deleted data which has not yet been overwritten by new files. Search for the data, mark it as the current block and copy it. Of course, data that has been deleted by WinHex using the Delete irreversibly command cannot be found in unused parts of a drive any more.

Save Sectors: To be used analogously to the Save command for files. Part of the File menu. Writes all modifications to the disk. Please note that, depending on your changes, this may severely damage the integrity of the disk data. If the corresponding undo option is enabled, a backup of the concerned sectors is created, before they are overwritten. *This command is only available in the full version.*

Here are some pieces of information concerning the Master Boot Record of a hard disk, that is editable

using the disk editor.

File Menu

New: This command is used to create a file. The file is initialized with zero bytes and principally opened in default edit mode. You have to specify the desired file size.

Open: Lets you open one or more files. You may choose an edit mode in case it is not predetermined in the Tools menu.

Save: Saves the currently displayed file with all modifications to the disk. In in-place edit mode, using this command is not necessary. When using the disk editor, this command is named "Save Sectors".

Save As: Saves the currently displayed file under a different name.

Make Backup Copy/Make Disk Backup

Load Backup: Select a backup file (.whx file) whose contents (either a file or disk sectors) you would like to restore.

Backup Manager

Execute: Executes the current file if executable, or otherwise the associated program.

Print

Properties: Lets you edit the size, the time stamp and attributes of a file (under Windows NT as well of a directory). Valid attributes are: A (archive), S (system), H (hidden), R (read-only). After entering new values in any area (size, time or attributes), simply press the Enter key, so the modifications take effect.

Open Folder: This command is used open several files that meet special requirements at a time. Select a folder in which to open files. Subfolders are browsed optionally. You may specify a series of file masks (e. g. "w*.exe;x*.dll"). There is also a switch that permits opening only those files that contain a certain text or certain hex values. The standard search dialogs are displayed upon request for this purpose. If WinHex is not set up to work as a viewer or in-place editor (this can be done in the Tools menu), you may choose an edit mode.

Save Modified Files: All files which have been changed are written to the disk.

Save All Files: All files that have not been opened in view mode are written to the disk.

Exit: Use this command to end WinHex. You will be prompted to save any modifications to files and disks.

Edit Menu

Undo: Reverses the last modification, in case the corresponding undo option was activated.

Cut: Removes the current block from the file and puts it into the clipboard. The data following the block is pulled to the former block beginning.

Copy Block/All/Sector:

- **Normally:** Copies the current block/the entire file/the current sector into the clipboard. The contents of the clipboard can be pasted or written later.

- **Into New File:** Copies the data directly into a new file (not via the clipboard). For instance, this command can be used to recover a lost file from disk sectors.

- **Hex Values:** Copies the data as concatenated hex values.

- **Editor Display:** Copies the data as text, formatted as if it was displayed in the hex editor, i. e. with an offset, a hex and a text column.

- **C/Pascal Source:** Copies the data as C/Pascal-formatted source code into the clipboard.

Paste Clipboard: Inserts the clipboard contents at the current position of a file. The file data following this position is moved forward.

Write Clipboard: Copies the clipboard contents to the current file at the current position. The data at this position is *overwritten*. If the end of the file is encountered, the file size is increased so that the clipboard contents finds place.

Paste Clipboard Into New File: Creates a new file of the clipboard contents.

Empty Clipboard: This command is used to free the memory used by the clipboard.

Remove: Deletes the current block from the file. The data following the block is pulled to the former block beginning. The clipboard is not affected by this command. If the block is equally defined in all open files (i.e. it begins and ends at the same offsets), this command can even be applied to all open files at the same time.

Paste Zero Bytes: Use this command to insert zero bytes at the current position of a file.

Define Block: This function is accessible from the menu and the status bar. A dialog box lets you specify the desired block limits. This command can also be applied to all open files.

Select All: Defines the beginning and the end of the current file as its block limits.

Convert

Modify Data

Fill Block/File/Disk Sectors

Search Menu

Find Text: This command is used to search for a specified string of up to 50 characters in the current file, disk or RAM section (cf. [Search Options](#)).

Find Hex Values: This command is used to search for a sequence of up to 50 two-character hex values (cf. [Search Options](#)).

Replace Text: Use this command to replace occurrences of a specified string with another string (each of up to 50 characters), cf. [Replace Options](#).

Replace Hex Values: Functions exactly as the Replace Text command, but is applied to a sequence of hex values (50 at max.), cf. [Replace Options](#).

Combined Search: Provides a complex search mechanism. In the current and in a second file a common offset is searched, where either file contains the specified respective hex values.

Integer Value: Enter an integer (within the limits of the signed 64-bit [integer data type](#)). This function searches data in the current file, which can be interpreted as this integer.

Floating-Point Value: Enter a floating-point number (e. g. $12.34 = 0.1234 * 10^2 = 0.1234E2$) and select a floating-point data type. This function searches data in the current file, which can be interpreted as this floating-point value.

Text Passages: Use this command to look for a sequence of letters (a-z, A-Z), digits (0-9) and/or punctuation marks. It is useful for instance if you intend to translate text passages hidden somewhere in a file with executable code.

Set the sensitivity of the search by specifying how long a character sequence must be to be recognized. Click "Tolerate Unicode characters" in order to force the algorithm to accept zero bytes between two characters.

Continue Global Search: This command is used to continue a global search operation (i.e. a search operation applied to all opened files) in the next file.

Continue Search: Lets you continue a search operation in the current file at the current position.

Position Menu

Go To Offset: Moves the current position to the specified offset. Normally this is done relative to the beginning of the file (offset 0). You can also move the cursor relative to the current position (forward or backward) or from the end of the file (backward). An offset can be specified in bytes (default), words (2 bytes), doublewords (4 bytes), records (if defined), or sectors. Press F11 to repeat the last position movement.

Go To Page/Sector: Browses to the specified page, sector, or cluster. Please note that the data area on FAT drives starts with cluster #2.

Go To FAT Entry/FILE Record: Jump to a certain entry in the file allocation table on a FAT drive or to a certain FILE record in the master file table on an NTFS drive, respectively.

Move Block: Moves the current block selection (not the data within the block) forward or backward. Specify the distance in bytes. Press Alt+F11 to repeat the last block movement, press Shift+Alt+F11 to reverse the movement. This command may facilitate editing a file that consists of homogeneous records of a fixed length.

WinHex keeps a history of your offset jumps within a document and allows to go **back** and **forward** in the chain later.

Go To...

Beginning Of File: Display the first page of the current file and moves the current position to offset 0.

End Of File: Displays the last page of the current file and moves the current position to the last byte (offset=file size-1).

Beginning Of Block: Moves the current position to the beginning of the current block.

End Of Block: Moves the current position to the end of the current block.

Mark Position: Marks the current position and thus enables you to find it again later.

Delete Marker: Removes the marker from the screen.

Go To Marker: Moves the current position to the marker set by Mark Position.

Position Manager

Window Menu

Window Manager: Displays all windows and provides "instant window switching" functionality. You may also close windows and save files.

Save Arrangement As Project: Writes the current window constellation into a project file. From the Start Center you will then be able to load the project and restore editing positions in each document at any time, to conveniently continue your work right where you left it or to begin your work in case of a recurring task.

Close All: Closes all windows and thus all open files, disks and RAM sections.

Close All Without Prompting: Closes all windows and thus all opened files and disks without giving you the opportunity to save your modifications.

Cascade/Tile: Arranges the windows in the aforementioned way.

Minimize All: Minimizes all windows.

Arrange Icons: This command arranges all minimized windows.

Tools Menu

Disk Editor

List Clusters: Available for FAT and NTFS drives. On FAT drives, this command relies on a recent drive map as generated by the Scan Cluster Chains (Again) command. WinHex searches clusters that are assigned to a file or directory you specify. To make this work with a directory, *type in* the directory name and do not select it in the folder list. The found clusters are listed in a small separate window. You may click a list item to browse to that cluster number. Try the context menu to copy the listed clusters off the drive into a new file or to copy the list itself to a text file.

Scan Cluster Chains Again: Available for FAT and NTFS drives. WinHex traverses all cluster chains and thereby generates a drive map. This enables WinHex to display for each sector which file or directory it is allocated to. The complete listing of deleted files on NTFS drives in the directory browser depends on this, too. It is recommended to invoke this command again after file operations on a drive to keep the information displayed by WinHex up to date. Cf. security options.

Initialize Free Space: Confidential information is possibly stored in currently unused parts of a drive as a result of normal delete, copy and save actions. Free space on a drive can be initialized for security reasons. This effectively overwrites all data in unused parts of the disk and makes it impossible to recover this data.

Initialize Slack Space: Overwrites slack space (the unused bytes in the respective last clusters of all cluster chains, beyond the actual end of a file) with zero bytes. This may be used in addition to "Initialize Free Space" to securely wipe confidential data on a drive or to minimize the space a compressed disk backup (like a WinHex backup) requires. Close any running or resident program that may write to the disk prior to using this command.

Initialize MFT Records: On NTFS drives, WinHex can clear all currently unused \$Mft (Master File Table) file records, as they may still contain names and fragments of files previously stored in them.

Clone Disk

File Recovery by Name

File Recovery by Type

Set Disk Parameters: Using this command on a physical disk, you may override the number of cylinders, heads, and sectors per track as recognized by WinHex. This can be useful to access surplus sectors at the end of the disk (in case they were not detected by WinHex), or to adjust the CHS coordinate system to your needs. Use this command on a logical drive to override the total number of clusters WinHex detects on that drive. This can prove useful when examining huge DVDs, which are detected as 2 GB media under Windows 9x.

RAM Editor

Invoke Text Editor: Executes an external text editor (selected in the General Options dialog). Opens the currently open file or currently defined block in that program. If you alter the file or block using the text editor, WinHex can adopt the changes afterwards.

Invoke Viewer: Executes an external file viewing program (such as Quick View Plus etc., selected in the General Options dialog). Opens the current file or block in that program.

Invoke X-Ways Trace: Available only if X-Ways Trace is installed. This software can analyze the Internet Explorer's index.dat history file and the Windows recycle bin's info2 files.

Calculator: Runs the Windows calculator "calc.exe". Switching to scientific mode is highly recommended.

Hex Converter: Enables you to convert hexadecimal numbers into decimal numbers and vice versa. Simply type in the number and press ENTER.

Analyze Block/File/Disk: Scans the data within the current block/the entire file/the entire disk and counts the occurrences of each byte value (0...255). The result is graphically displayed by proportional vertical lines. The number of occurrences and the percentage are displayed for each byte value when moving the mouse over the corresponding vertical line.

Use this command for instance to identify data of unknown type. Audio data, compressed data, executable code etc. produce characteristic graphics. The 32-bit standard checksum and the CRC32 of the selected data are also displayed. Use the context menu of the window to switch zero byte consideration on or off, to *print* the analysis window, or to *export* the analysis to a text file.

Calculate Hash: Calculates one of the following checksums/digest of the entire current file, disks, or the currently selected block: 8-bit, 16-bit, 32-bit, 64-bit checksum, CRC16, CRC32, MD5, SHA-1, SHA-256, or PSCHF.

Options Menu

General Options

Undo Options

Security & Safety Options

Data Interpreter Options

Use As Viewer: If you use WinHex simply for viewing files and you do not need the possibility to edit them, you can switch on this menu option. All files will be opened in view mode.

In-Place Editor: All files are opened in in-place mode, i. e. all changes are done directly in the original file.

Character set: Lets you switch between the ANSI-ASCII, IBM-ASCII, and EBCDIC character for display and keyboard input. You may also use Shift+F7. EBCDIC (originating from IBM mainframes) is currently not supported by the print command.

File Manager

Execute: Lets you select a file to execute. If the file itself is not executable, it is opened by the application it is associated with.

Split: This command creates several destination files using the contents of a single source file. Specify a split offset for each destination file. The source file is not affected by this function.

Concatenate: Select several source files that are to be copied into one destination file. The source files are not affected.

Unify: Select two source files and one destination file. The bytes/words from the source files will be written alternately into the destination file. The first byte/word originates from the source file that was specified first. Use this function to create a file with odd and even bytes/words originating from separate files (e.g. in EPROM programming).

Dissect: Select a source file and two destination files. The bytes/words from the source files will be written alternately into the destination files. The first byte/word will be transferred to the destination file that was specified first. Use this function to create two separate files each containing either the odd or the even bytes/words of the original file (e.g. in EPROM programming).

Compare: This command is used to compare two edit windows (files or disks) byte by byte. Decide whether different or identical bytes shall be reported. You may indicate how many bytes to compare. If desired, the operation can abort automatically after having found a certain number of differences or identical bytes. The report is stored as a text file, whose size might otherwise grow dramatically. The comparison starts at the respective offsets specified for each edit window. These offsets may differ, such that e.g. the byte at offset 0 in file A is compared to the byte at offset 32 in file B, the byte at offset 1 with the one at offset 33, etc. When you select an edit window for comparison, the current position will automatically be entered in the "From offset" box. There is yet another compare function in WinHex: you may also compare edit windows visually and synchronize scrolling in these windows (see [View menu](#)).

Copy: Copies a file.

Move: Use this command to move and/or rename an existing file. The source file is deleted.

Wipe Securely: This command is used to erase the contents of one or more files irrevocably, such that they cannot be restored by WinHex itself or other special data recovery software. Each selected file is overwritten according to the current settings, shortened to a length of zero and then deleted. In the full version of WinHex the name entry of the file is erased as well. Even professional attempts to restore the file will be futile. Therefore this command should be applied to files with confidential contents, which is to be destroyed.

Help Menu

Contents: Displays the contents of the program help.

Setup: Lets you switch between the English, the German, the French, the Spanish, the Portuguese, and the Italian user interface.

Initialize: Use this command to restore the default settings of this program.

Uninstall: Use this command to remove WinHex from your system. This works properly even if you did not install WinHex using the setup program.

Online: Opens the WinHex homepage (<http://www.winhex.com>), the support forum (<http://www.winhex.net>), the Knowledge Base (<http://www.winhex.com/winhex/kb/>), or the newsletter subscription page in your browser.

About WinHex: Displays information about WinHex (the program version, your license status, and more).

Printing

Use the "print" command of the File menu to print a file, disk sectors or RAM contents. Define the printing rang via offsets. You may select and set up a printer.

Please choose the character set for printing and accept or change the suggested font size. The recommended font size is calculated as follows: print resolution (e. g. 720 dpi) / 6 (e. g. = 120). If desired you may enter a comment which will be printed at the end.

If you need more flexibility with printing, you can define a block and copy it using "Edit->Copy->Editor Display" as a hex-editor-formatted text into the clipboard. You may paste it in your favorite word processor. It should look perfect in "Courier New", 10 pt.

Block

You can mark a part of an open file as a "block". This part can be manipulated by several function in the edit menu just as selections in other Windows programs. If no block is defined, these functions usually are applied to the whole file.

The current position and size of the block are displayed in the status bar. Double-clicking the right mouse button or pressing the ESC key clears the block.

Useful hints

Modify Data

Use this command to modify the data within the block or within the whole file, in case no block is defined. Either a fixed integer number is *added* to each element of the data, the bits are *inverted*, a constant is XORed with the data (a simple kind of encryption), ORed, or ANDed, bits are shifted logically, or bytes are swapped. By shifting bits, you can simulate inserting or removing single bits at the beginning of the block. You may also shift entire *bytes* (currently to the left only, by entering a negative number of bytes). This is useful if you wish to cut bytes from a very huge file in in-place mode, which would otherwise require the creation of a huge temporary file.

Swap Bytes

This command assumes all data to consist of 16-bit elements (32-bit elements resp.) and swaps high-order and low-order bytes (and high-order and low-order words resp.). Use it in order to convert big-endian into little-endian data and vice versa.

Addition

Specify a positive or negative, decimal or hexadecimal number, which is to be added to each element of the current block. An integer format defines size (1, 2 or 4 bytes) and type (signed or unsigned) of an element.

There are two ways how to proceed if the result of the addition is out of the range of the selected integer format. Either the range limit is assumed to be the new value (I) or the carry is ignored (II).

Example: unsigned 8-bit format

- I. FF + 1 -> FF (255 + 1 -> 255)
- II. FF + 1 -> 00 (255 + 1 -> 0)

Example: signed 8-bit format

- I. 80 - 1 -> 80 (-128 - 1 -> -128)
- II. 80 - 1 -> 7F (-128 - 1 -> +127)

- If you decide to use the first method, WinHex will tell you how often the range limit has been exceeded.
- The second method makes sure the operation is reversible. Simply add -x instead of x based on the same integer format to recreate the original data.
- When using the second method it does not make a difference whether you choose a signed or an unsigned format.

Conversions

WinHex provides the "Convert" command of the Edit menu for easy conversions of different data formats and for encryption and decryption. The conversion can optionally be applied to all opened files instead of only the currently displayed one. The formats marked with an asterisk can only be converted as a whole file, not as a block. The following formats are supported:

- ANSI ASCII, IBM ASCII (two different ASCII character sets)
- EBCDIC (an IBM mainframe character set)
- Lowercase/uppercase characters (ANSI ASCII)
- Binary* (raw data)
- Hex ASCII* (hexadecimal representation of raw data as ASCII text)
- Intel Hex* (=Extended Intellec; hex ASCII data in a special format, incl. checksums etc.)
- Motorola S* (=Extended Exorcisor; ditto)

Please note:

- When converting Intel Hex or Motorola S data, the internal checksums of these formats are not checked.
- Depending on the file size, the smallest possible output subformat is chosen automatically. Intel Hex: 20-bit or 32-bit. Motorola S: S1, S2, or S3.
- When converting from binary to Intel Hex or Motorola S, only memory regions not filled with hexadecimal FFs are translated, to keep the resulting file compact.
- Some conversions can only be applied to whole files.

Encryption/Decryption

It is recommended to specify a combination of at least 8 characters as the encryption key. Do not use words of any language, it is better to choose a random combination of letters, punctuation marks, and digits. Note that encryption keys are case sensitive. Remember that you will be unable to retrieve the encrypted data without the appropriate key. The decryption key you enter is not verified before decrypting.

The encryption algorithm is "Pukall Cipher 1" (PC 1), using a 128-bit key (=the 128-bit digest of the key you specify).

Search Options

Case sensitive: If this option is enabled, WinHex distinguishes between upper and lower case, e.g. so that "Option" is not found in the word "optionally".

Unicode character set: The specified text is searched using the 256 ANSI-ASCII-equivalent Unicode characters, where the high-order byte is 0. The simultaneous search allows to search for the same text at the same time in Unicode and ASCII. For this to work, the checkbox needs to be "half" checked.

You may specify a **wildcard** (one character or a two-digit hex value), which represents one byte. For example this option can be used to find "Speck" as well as "Spock" when searching for "Sp?ck" with the question mark as the wildcard.

Only whole words: The searched string is recognized only, if it is separated from other words, e. g. by punctuation marks or blanks. If this option is enabled, "tomato" is not found in "automaton".

Search direction: Decide whether WinHex shall search from the beginning to the end, or downwards or upwards from the current position.

Condition: Offset modulo $x = y$: The search algorithm accepts search string occurrences only at offsets that meet the given requirements. E. g. if you search for data that typically occurs at the 10th byte of a hard disk sector, you may specify $x=512$, $y=10$. If you are looking for DWORD-aligned data, you may use $x=4$, $y=0$ to narrow down the number of hits.

Search in block only: The search operation is limited to the current block.

Search in all open windows: The search operation is applied to all open edit windows. Press F4 to continue the search in the next window. If "Search in block only" is enabled at the same time, the search operation is limited to the current block in each window.

Count occurrences/Save occurrence positions: Forces WinHex not to show each single occurrence, but to count them. If this option is fully enabled, WinHex will enter all occurrences into the Position Manager.

Search for "non-matches": In "Find Hex Values" you may specify a single hex value with an exclamation mark as a prefix (e.g. !00) to make WinHex stop when it encounters the first byte value that *differs*.

[Search Menu](#)

[Replace Options](#)

[Technical Hints](#)

Replace Options

Prompt when found: WinHex awaits your decision when an occurrence has been found. You may either replace it, continue or abort the search.

Replace all occurrences: All occurrences are replaced automatically.

Case sensitive: The characters that are to be replaced are searched using this option (cf. [Search Options](#)).

Unicode character set: The specified characters are searched and replaced in Unicode format (cf. [Search Options](#)).

You may specify one character/a two-digit hex value as a **wildcard** (cf. [Search Options](#)). This is usually done in the search string.

If the *substitute* contains a wildcard, the character at the relative position in an occurrence will not be changed. Thus, "black" and "block" can be replaced simultaneously with "crack" and "crock" (enter "bl?ck" and "cr?ck").

Only whole words: The searched string is recognized only if it is separated from other words e. g. by punctuation marks or blanks. If this option is enabled, "tomato" is not replaced in "automaton".

Search direction: Decide whether WinHex shall replace from the beginning to the end, or downwards or upwards from the current position.

Replace in block only: The replace operation is limited to the current block.

Replace in all opened files: The replace operation is applied to all files not opened in view mode. If "Replace in block only" is enabled at the same time, the replace operation is limited to the current block of each file.

WinHex is able to replace one string or hex value sequence with another one that has a different length. You will be prompted, which of the following methods shall be applied:

1st method: The data behind the occurrence is moved due to length difference. So the file size is changed. This method must not be applied to certain file types, such as executable files. It is even possible to specify *nothing* as the substitute, which means all occurrences will be *removed* from the file!

2nd method: The substitute is written into the file at the position of the occurrence. If the substitute is shorter than the searched character sequence, the exceeding characters will remain in the file. Otherwise even the bytes behind the occurrence will be overwritten (as far as the end of the file is not reached). The file size is not affected.

[Search Menu](#)

[Search Options](#)

[Technical Hints](#)

Undo Options

The availability of the "Undo" command depends on the following options:

- Specify how many sequential actions are to be reversed by the Undo command. This option does not affect the number of reversible keyboard inputs, which is only limited by the available RAM.
- In order to save time and space on your hard disk, you can specify a file size limit. If a file is larger than this limit, backups will not be created and the Undo command is not available except for keyboard input.
- Automatically created backups for the internal use with the Undo command are deleted by WinHex when closing the file, if the corresponding option is fully selected. If it is partially selected, they are deleted when WinHex terminates.
- Choose for all kinds of editing actions whether they should be reversible or not. In case they should, an internal backup is created before the action takes place.

Position Manager

The Position Manager maintains a list of file or disk offsets and corresponding descriptions. You may enter new positions and edit or delete existing entries. If a special offset in a file is important to you because you have to edit it more than once, you can enter it into the Position Manager. This makes it a lot easier to find it again later, and you do not have to remember it. An appropriate description for instance could be "Data chunk begins here!".

Click the right mouse button in order to see a context menu. The context menu provides additional commands. You may delete, load or save positions, even export the list as HTML. If the position list was changed, it is saved in the file *WinHex.pos* when exiting WinHex.

The position manager window can be minimized, so you may switch between the positions in the selected order by pressing Ctrl+Left and Ctrl+Right.

A complete documentation of the POS file format is available from the WinHex Homepage <http://www.winhex.com>.

Backup Manager

Displays a list of previously created backups. The items can be listed in a chronological or alphabetical order. Choose the backup you would like to restore. When that function completes, the original file or sector contents is shown.

You can restore the backup

- into a temporary file first such that you will still need to save it,
- directly and immediately to the disk, or
- to a new file.

In the case of disk sectors you may also wish to specify a different destination disk or a different destination sector number. It is also possible to only extract a subset of the sectors from the backup. (However, sectors at the beginning of a *compressed* backup cannot be left out during restoration.) If the backup was saved with a checksum and/or a digest, data authenticity is verified before the sectors will be directly written to the disk.

The backup manager also allows to delete backups which you do not need any longer. Backups that were created for internal use by the Undo command can be deleted by WinHex automatically (cf. Undo Options).

Backup files that are maintained by the Backup Manager are located in the folder specified in the General Options dialog. Their filenames are "xxx.whx" where xxx is a unique three-digit identification number. This number is displayed in the last column of the backup manager list.

A complete documentation of the WHX file format is available from the WinHex Homepage <http://www.winhex.com>.

Data Interpreter

The Data Interpreter is a small window that provides "translation services" for the data at the current cursor position. The Data Interpreter Options dialog lets you specify the data types to interpret. These are currently seven integer data types (by default in decimal notation, optionally hexadecimal or octal), the binary format (8 bits of a byte), four floating-point data types, assembler opcodes (Intel), and five date types.

The Data Interpreter is also capable of translating all data types (except assembler opcodes) back into hex values. Double-click a number in the Data Interpreter window, enter a new value and press ENTER. The Data Interpreter will enter the corresponding hex values into the edit window at the current position.

Right-click the data interpreter to bring up a context menu. This will let you switch between big-endian and little-endian translation of integer and floating-point data.

Hints:

Some hex values cannot be translated into floating-point numbers. For these hex values the Data Interpreter displays NAN (**n**ot **a** number).

Some hex values cannot be translated into valid dates. The value ranges of different date types are more or less narrow.

There are redundancies in the Intel instruction set, which show up in the Data Interpreter as duplication of both hex opcodes and mnemonics. Floating-point instructions are generally displayed as F***.

More detailed reference can be found in the Intel Architecture Software Developer's Manual Volume 2: Instruction Set Reference, available in PDF format on the Internet.

RAM Editor

The RAM Editor is part of the Tools menu. It allows examining the virtual memory of a process (i.e. a program that is being executed). All memory pages committed by this process are presented in a continuous block. Unused (free or reserved) pages are ignored by default, but optionally included and displayed with "?" characters. With no such gaps, you may compare memory dumps to files exactly with one another (absolute and virtual addresses are identical), e.g. to examine stack and heap states or observe viruses.

Select one of the listed processes. You may access either the so-called primary memory or the entire memory of this process or one of the loaded modules. The primary memory is used by programs for nearly all purposes. Usually it also contains the main module of a process (the EXE file), the stack, and the heap. The "entire memory" contains the whole virtual memory of a process, including the part of memory that is shared among all processes, except system modules. Under Windows 95/98/Me, system modules are listed optionally in the process tree. System modules are defined as modules that are loaded above the 2 GB barrier (such as kernel32.dll, gdi32.dll). They are shared among all running processes.

Please note the following limitations:

- Caution: Only keyboard input can be undone!
- Virtual memory of 16-bit processes is *partially* accessible under Windows 95/98/Me only.
- Editing is possible in in-place mode only.
- System modules of Windows 95/98/Me can only be *examined* in view mode, *not manipulated*.
- The evaluation version only supports view mode. Order the full version!

The options relevant for the RAM editor are "Check for virtual memory alteration" (security options) and "Virtual addresses" (general options).

Context Menu

The Windows shell displays the context menu when the user clicks an object with the right mouse button. WinHex is present in the context menu only if you enable to corresponding option.

Edit with WinHex: Opens the selected file in WinHex.

Open Folder in WinHex: Lets you open all files of the selected folder in WinHex, just as the Open Special command of the File menu.

Edit Disk: Opens the selected disk in the disk editor of WinHex. If you hold the Shift key, instead of the selected logical drive the corresponding physical disk is opened, if any. (The latter feature is not available under Windows NT.)

WinHex provides its own context menus on the status bar, the Data Interpreter, and in the position manager.

It seems you are still eligible to get this update for free. However, you cannot run this version as a full version using the detected license file "user.txt". You were most probably sent a new one on November 1, 2003 automatically! Please check your e-mail. You may also wish to consult <http://www.x-ways.net/winhex/upgrade.html>. When you ask for assistance by e-mail, please include your full name and address.

Key

Specify a string consisting of 1-16 characters as the encryption/decryption key. The more characters you enter, the safer is the encryption. The key itself is not used for encryption and decryption, instead it is digested to the actual key.

The key is not saved on your hard disk. If the corresponding security option is enabled, the key is stored in an encrypted state in the RAM as long as WinHex is running.

Make Backup Copy/Make Disk Backup

This command provides a dialog window enabling you to create a backup (safety copy) of the current file or of sectors of the current disk (drive imaging). The backup is stored as a .whx file.

When creating a backup of a physical disk or logical drive (so-called drive imaging), you have to specify which sectors to save. By default, all sectors starting with the current position are selected. You may have WinHex split the backup into volumes of a fixed size. Partial backups of 650 MB e.g. are suitable for archiving drive images on CD-R. In order to make the backup as small as possible, it is recommended to initialize unused space before drive imaging. This is because sectors that consist but of zero values barely increase the backup size when compression is enabled.

Hints on disk cloning and disk imaging

If you have WinHex assign a filename for the .whx file automatically, the file will be created in the folder for backups (cf. General Options), named with the next free "slot" according to the Backup Manager's naming conventions ("xxx.whx"), and will be available in the Backup Manager. If you explicitly specify a path and a filename, you can still restore the backup later using the »Load Backup« command, and in case of split backups WinHex will automatically append the volume number to the filenames.

You may specify a textual description of the backup.

The .whx format is able to store a checksum or a digest of the original data, and it optionally provides encryption. The calculation of digests and encryption both slow down the backup creation considerably, so these functions should not be used unless required for security purposes. When restoring a digested backup with no warning showing up in WinHex, you can be sure about the data contained in the backup has not been tampered with!

The encryption algorithm is "Pukall Cipher 1" (PC 1), using a 128-bit key that is digested from the 256-bit concatenation of the 128-bit digest of the key you enter and 128 bits random input. The random input is saved in the .whx file for later decryption.

WinHex makes use of the "Deflate" compression algorithm that is part of the popular general-purpose library *zlib*. This algorithm consists of LZ77 compression and Huffman coding. The compression ratio is the same as ZIP.

The .whx file format is fully documented (cf. the WinHex Homepage <http://www.winhex.com>).

Security & Safety Options

- The **Sector reading cache** accelerates sequential disk access by the disk editor. This option is recommended particularly when scrolling through CD-ROM and floppy disk sectors, since the number of necessary physical accesses is significantly reduced.
- Enabling the option **Inspect clusters automatically** causes WinHex to automatically traverse the cluster chains of a FAT or NTFS drive if such a drive is opened in WinHex and the required drive map does not yet exist. Using the drive map, WinHex is able to display each sector's and cluster's allocation (for storing which file it is used). Use the command "Inspect clusters" of the Tools menu to update the drive map.
- With the option **Keep drive map for next session** enabled, all information on FAT and NTFS drives collected by WinHex remains in the folder for temporary files even when WinHex terminates. WinHex can reuse drive maps during later program runs.
- Use the option **Check for virtual memory alteration** to make sure the RAM editor inspects the structure of virtual memory every time before *reading* from or *writing* to it. If the structure has changed, a possible read error is prevented. Especially under Windows NT the checking may result in a loss of speed. When editing the "entire memory" of a process, WinHex generally *never* checks for alterations, even if this option is enabled.
- A **hash** can be **calculated automatically** for each file when opening it. It is then displayed in the information column at the right. Checksums and digests can also be calculated using the Tools Menu.
- Before modifications to an existing file are saved (i. e. before the **file is updated**), you are prompted for **confirmation**. To inhibit this behavior of WinHex, switch off the corresponding option.
- When manually restoring backups, a **restoration report** is **shown** only in case the backup contains a digest or the backup is corrupt. Optionally, you may have WinHex always display the report **always** after restoration. In this case even the digest will be displayed.
- The **key** that is required for encryption and decryption can be entered in a normal edit box. Optionally, you **enter it blindly** (asterisks are displayed instead of the actual characters). In this case you have to confirm the key in a second edit box to detect typos.
- By default, the encryption **key** is kept in main memory (in an encrypted state) as long as WinHex is running so that you do not have to type it again and again if you use it several times. Possibly you prefer WinHex to erase the key after use.
- Decide whether or not WinHex shall **prompt before executing a script**, or only before executing a script via the command line.

Endian-ness

Microprocessors differ in the position of the least significant byte: Intel®, MIPS®, National Semiconductor, and VAX processors have the least significant byte first. A multi-byte value is stored in memory from the lowest byte (the "little end") to the highest byte. For example, the hexadecimal value 12345678 is stored as 78 56 34 12. This is called the **little-endian format**.

Motorola and Sparc processors have the least significant byte last. A multi-byte value is stored in memory from the highest byte (the "big end") to the lowest byte. For example, the hexadecimal value 12345678 is stored as 12 34 56 78. This is called the **big-endian format**.

Digests

A so-called digest is, similar to a checksum, a characteristic number used for verification of data authenticity. But digests are more than that: digests are strong one-way hash codes.

It is computationally feasible to manipulate any data in such a way that its checksum remains unaffected. Verifying the checksum in such a case would lead to the assumption that the data has not been changed, although it has. Therefore, digests are used instead of checksums if malicious (i.e. not mere random) modifications to the original data are to be detected. It is computationally infeasible to find any data that corresponds to a given digest. It is even computationally infeasible to find two pieces of data that correspond to the same digest.

Of course, random modifications, e. g. caused by an inaccurate transmission, can also be detected when using digests, but checksums serve better for this purpose, because they can be calculated much faster.

WinHex incorporates the widely known 128-bit MD5 message digest, SHA-1, SHA-256, and PSCHF ("Pukall Stream Cipher" hash function).

Date Types

The following date formats are supported by the Data Interpreter:

MS-DOS Date & Time (4 bytes)

The lower word determines the time, the upper word the date. Used by several DOS function calls and by all FAT file systems.

<u>Bits</u>	<u>Contents</u>
0-4	Second divided by 2
5-10	Minute (0-59)
11-15	Hour (0-23 on a 24-hour clock)
16-20	Day of the month (1-31)
21-24	Month (1 = January, 2 = February, etc.)
25-31	Year offset from 1980

Win32 FILETIME (8 bytes)

The FILETIME structure is a 64-bit integer value representing the number of 100-nanosecond intervals since January 1, 1601. Used by the Win32 API.

OLE 2.0 Date & Time (8 bytes)

A floating-point value (more exactly: a double) whose integral part determines the number of days passed since December 30, 1899. The fractional part is interpreted as the day time (e.g. 1/4 = 6:00 a.m.). This is the OLE 2.0 standard date type, e.g. it is used by MS Excel.

ANSI SQL Date & Time (8 bytes)

Two consecutive 32-bit integer values. The first one determines the number of days since November 17, 1858. The second one is the number of 100-microsecond intervals since midnight. This is the ANSI SQL standard and used in many databases (e.g. InterBase 6.0).

UNIX/C Date & Time (4 bytes)

A 32-bit integer value that determines the number of seconds since 1/1/1970. This data type is used in UNIX, DOS C and C++ ("time_t"), and by FORTRAN programs since the 80's. Sporadically defined as the number of *minutes* since 1/1/1970. The Data Interpreter options let you switch between both sub-types.

Java Date & Time (8 bytes)

A 64-bit integer value that specifies the number of milliseconds since January 1, 1970. Principally stored in big endian, which is the typical byte order in Java.

Master Boot Record

The **Master Boot Record** is located at the physical beginning of a hard disk, editable using the Disk Editor. It consists of a **master bootstrap loader code** (446 bytes) and four subsequent, identically structured **partition records**. Finally, the hexadecimal signature 55AA completes a valid Master Boot Record.

The format of a partition record is as follows:

Offset	Size	Description
0	8 bit	A value of 80 designates an active partition.
1	8 bit	Partition start head
2	8 bit	Partition start sector (bits 0-5)
3	8 bit	Partition start track (bits 8,9 in "start sector" as bits 6,7)
4	8 bit	Operating system indicator
5	8 bit	Partition end head
6	8 bit	Partition end sector (bits 0-5)
7	8 bit	Partition end track (bits 8,9 in "end sector" as bits 6,7)
8	32 bit	Sectors preceding partition
C	32 bit	Length of partition in sectors

Operating system indicators: (hexadecimal, incomplete list)

- 00 Empty partition-table entry
- 01 DOS FAT12
- 04 DOS FAT16 (up to 32 MB)
- 05 DOS 3.3+ extended partition
- 06 DOS 3.31+ FAT16 (over 32 MB)
- 07 OS/2 HPFS, Windows NT NTFS, Advanced Unix
- 08 OS/2 v1.0-1.3, AIX bootable partition, SplitDrive
- 09 AIX data partition
- 0A OS/2 Boot Manager
- 0B Windows 95+ FAT32
- 0C Windows 95+ FAT32 (using LBA-mode INT 13 extensions)
- 0E DOS FAT16 (over 32 MB, using INT 13 extensions)
- 0F Extended partition (using INT 13 extensions)
- 17 Hidden NTFS partition
- 1B Hidden Windows 95 FAT32 partition
- 1C Hidden Windows 95 FAT32 partition (using LBA-mode INT 13 extensions)
- 1E Hidden LBA VFAT partition
- 42 Dynamic disk volume
- 50 OnTrack Disk Manager, read-only partition
- 51 OnTrack Disk Manager, read/write partition
- 81 Linux
- 82 Linux Swap partition, Solaris (Unix)
- 83 Linux native file system (ext2fs/xiafs)
- 85 Linux EXT
- 86 FAT16 volume/stripe set (Windows NT)
- 87 HPFS fault-tolerant mirrored partition, NTFS volume/stripe set
- BE Solaris boot partition
- C0 DR-DOS/Novell DOS secured partition
- C6 Corrupted FAT16 volume/stripe set (Windows NT)
- C7 Corrupted NTFS volume/stripe set
- F2 DOS 3.3+ secondary partition

Wiping and Initializing

For securely erasing (shredding) data, and also simply for filling files or disk sectors with certain byte values, WinHex offers the following options:

Fill with hex values: Specify either 1, 2, 3, 4, 5, 6, 12, 15, or 16 two-character hex values, which will be copied repeatedly into the current block, the entire file or all disk sectors, respectively.

Fill with random bytes: Specify a decimal interval (0 to 255 at max.) for random numbers, which will be copied repeatedly into the current block, the entire file or all disk sectors, respectively. The random bytes are Laplace-distributed.

In case in *all* open files either a block or *no* block is defined, this command can optionally be applied to all these files at the same time.

To maximize security, if you wish to totally wipe (sanitize) slack space, free space, unused NTFS records, or an entire media, you may want to apply more than one pass for overwriting disk space (up to three).

According to the Clearing and Sanitization Matrix, the standard outlined in the U.S. Department of Defense (DoD) 5220.22-M operating manual, method "c", a hard disk or floppy disk can be cleared by overwriting (once) all addressable locations with a single character. This is usually the hexadecimal value 0x00, but can be any other value. To sanitize hard disks according to method "d", overwrite all addressable locations with a character, its complement, then a random character, and verify. (This method is not approved by the DoD for sanitizing media that contain *top secret* information.)

The "DoD" button configures WinHex for sanitization, such that it will first overwrite with 0x55 (binary 01010101), then with its complement (0xAA = 10101010), and finally with random byte values.

The "0x00" button configures WinHex for simple initialization, wiping once with zero bytes.

Disk Editor: Questions and Answers

How can I access CD-RW sectors?

DirectCD and PacketCD must not be installed on the Windows system.

How can I access CD-ROM sectors under Windows 9x?

Please make sure the following requirements are met:

1. A Windows driver of the CD-ROM drive must be installed. An MS-DOS driver is not sufficient.
2. The ASPI interface must be installed. Maybe you have to copy the file `wnaspi32.dll` manually into your `Windows\System` directory. The file is to be found on your Windows installation CD. The shareware program WinZip (available from <http://www.winzip.com>) is recommended for extracting files from CAB archives.
3. The CD-ROM drive must support the way WinHex tries to read sectors. Most of modern ATAPI and SCSI drives are suitable.

How can I make WinHex detect an installed PC Card ATA Flash Disk/PCMCIA Drive as a physical disk under Windows 9x?

Windows Control Panel -> System -> Device Manager -> Select your PCMCIA drive -> Click "Properties" and search for an option with name similar to "Int 13h device". The actual way to find this checkbox may vary on different Windows versions. If possible, *enable* this option and reboot your computer.

Template Editing

A template is a dialog box that provides means for editing custom data structures in a more comfortable and error-preventing way than raw hex editing does. Editing is done in separate edit boxes. Changes take effect when pressing the Enter key or when quitting the template after being prompted. The data may originate from a file, from disk sectors, or from virtual memory. Especially when editing databases, you may prefer to define a custom template for ease of access to the records. You will find the command to *print* a template in the system menu.

A template definition is stored in a text file. The template editor enables you to write template definitions and offers syntax checking. A template definition mainly contains variable declarations, that are similar to those in source code of programming languages. The supported data types include all the common integer, floating-point and boolean variants, five date types, hex values, binary, characters, and strings type. Arrays of both single variables and groups of variables can be used. The ability to move freely forwards and backwards within the data makes using templates particularly flexible:

- The same variable may be interpreted and manipulated in several ways.
- Irrelevant data sections can be skipped.

The template manager lists all text files in the WinHex directory that contain template definitions. The title of the template along with a description, the filename, and the date and time of the last modification is shown. Click the Apply button to display a template using the selected template definition for the data in the current editor window at the current position. You may also create a new template definition, delete or edit an existing one.

WinHex comes with several demonstration templates.

Template Definition

A template definition consists of a header and a body.

Header syntax

Variable declarations in the body

Advanced commands the body

Template Definition Header

The header of a template definition has the following format:

```
template "title"  
[description "description"]  
[applies_to (file/disk/RAM)]  
[fixed_start offset]  
[sector-aligned]  
[requires offset "hex values"]  
[big-endian]  
[hexadecimal/octal]  
[read-only]  
[multiple [fixed overall size]]  
// Put any general comments to the template here.  
begin  
    variable declarations  
end
```

Tags in brackets are optional. The order of the tags is irrelevant. Expressions need only be enclosed in inverted commas if they contain space characters. Comments may appear anywhere in a template definition. Characters following a double slash are ignored by the parser.

The keyword "applies_to" must be followed by one and only one of the words file, disk, or RAM. WinHex issues a warning if you are going to use a template on data from a different source.

While by default templates start interpreting the data at the current cursor position when applied, an optional `fixed_start` statement ensures interpretation always starts at the specified absolute offset within the file or disk.

If the template applies to a disk, the keyword "sector-aligned" ensures the template interpretation starts at the beginning of the current sector, regardless of the exact cursor position.

Similar to the "applies_to" statement, the "requires" statement enables WinHex to prevent an erroneous application of a template definition to data that does not match. Specify an offset and a hex-value chain of an arbitrary length that identifies the data for which the template definition was intended. For example, a valid master boot record can be recognized by the hex values 55 AA at offset 0x1FE, an executable file by the hex values 4D 5A ("MZ") at offset 0x0. There may be multiple "applies_to" statements in a template definition header, which are all considered.

The keyword "big-endian" causes all multi-byte integer and boolean variables in the template definition to be read and written in big-endian order (high-order byte first).

The keyword "hexadecimal" causes all integer variables in the template definition to be displayed in hexadecimal notation.

The keyword "read-only" ensures that the template can only be used to examine, but not to manipulate data structures. The edit controls within the template will be grayed out.

If the keyword "multiple" is specified in the header, WinHex allows browsing to neighboring data records while displaying the template. This requires that WinHex has knowledge of the record's size. If it is not specified as a parameter to the "multiple" statement, WinHex assumes the overall size of a template structure (=record) to be the current position at the end of the template interpretation less the base editing position. If this is a variable size, i.e. array sizes or move parameters are determined dynamically by the

value of variables, WinHex cannot browse to precedent data records.

Variable Declarations

The body of a [template definition](#) mainly consists of variable declarations, similar to those in programming languages. A declaration has the basic form

```
type "title"
```

where type can be one of the following:

- int8, uint8 = byte, int16, uint16, int32, uint32, int64,
- [uint_flex](#)
- binary,
- float = single, real, double, longdouble = extended,
- char, char16, string, string16,
- boole8 = boolean, boole16, boole32
- hex,
- DOSDateTime, FileTime, OLEDateTime, SQLDateTime, UNIXDateTime = time_t, JavaDateTime

"title" must only be enclosed in inverted commas if it contains space characters. "title" must not consist only of digits. WinHex does not distinguish between upper and lower case characters in titles. 41 characters are used to identify a variable at most.

type can be preceded by at most one member of each of the following modifier groups:

big-endian	little-endian	(see Endian-ness)
hexadecimal	decimal octal	
read-only	read-write	

These modifiers only affect the immediately following variable. They are redundant if they appear in the header already.

The number at the end of a type name denotes the size of each variable (strings: of each character) in bits. With char16 and string16, WinHex supports Unicode characters and strings. However, Unicode characters other than the first 256 ANSI-equivalent characters are not supported. The maximum string size that can be edited using a template is 8192 bytes.

The types string, string16, and hex require an additional parameter that specifies the number of elements. This parameter may be a constant or a previously declared variable. If it is a constant, it may be specified in hexadecimal format, which is recognized if the number is preceded by 0x.

You may declare arrays of variables by placing the array size in square brackets next to the type or the title. The following two lines declare a dynamically sized ASCII string, whose length depends on the preceding variable:

```
uint8          "len"  
char[len]     "A string"
```

The same could be achieved by the following two declarations:

```
byte          "len"  
string len   "A string"
```

The character "~" can be used as a placeholder for later replacement with the actual array element number (see [Advanced Commands](#)). This does not apply to arrays of char variables, since they are

automatically translated into a string.

Please note that in the current version templates are not able to "calculate", so operators such as "+" and "*" must not be used neither in parameters nor in array size expressions.

Advanced Commands

When enclosed in braces, several variable declarations comprise a block that can be used repeatedly as a whole. Note, however, that blocks must not be *nested* in the current implementation. The "~" character can be used in a variable's name as a placeholder for later replacement with the actual repetition count. The optional "numbering" statement defines where to begin counting (0 by default).

```
numbering 1
{
byte      "len"
string len "String No. ~"
} [10]
```

In this example the actual variable names in the template will be "String No. 1", "String No. 2", ..., "String No. 10". Instead of a constant number of repetitions (10 in this example), you may also specify "unlimited". In that case WinHex will repeat the block until the end of file is encountered.

In order to facilitate reading and navigating the template, you may define groups of variables that are separated by empty space in the dialog box:

```
section    "...Section Title..."
...variable declarations...
endsection
```

The "section", "endsection", and "numbering" statements do not advance the current position in the data to be interpreted.

There are two commands that do not declare variables either, but are explicitly used to change the current position. This can be done to skip irrelevant data (forward movement) or to be able access certain variables more than once as different types (backward movement). Use the "move n" statement to skip n bytes from the current position, where n may be negative. "goto n" browses to the specified absolute position from the beginning of the template interpretation (must be positive).

The following example demonstrates how to access a variable both as a 32-bit integer and as a four-part chain of hex values:

```
int32      "Disk serial number (decimal)"
move -4
hex 4      "Disk serial number (hex)"
```

Disk Cloning

The command "Clone Disk" is part of the Tools menu. This function copies a defined number of sectors from a source to a destination disk (or alternatively from a disk image file or to a disk image file). Both disks must have the same sector size. In order to effectively *duplicate* a drive (i.e. in order to copy all sectors of the drive), enable the appropriate option, so the correct number of sectors is entered automatically. The destination disk must not be smaller than the source disk.

Disk cloning offers options that control the behavior when bad sectors are encountered on the source disk:

- By default, you are notified of the error and prompted for either continuing or aborting the operation. "Log procedure silently" creates a complete log file of the entire operation in the folder for temporary files (filename "Cloning Log.txt"), including a report on unreadable sectors (which cannot be copied), and prevents WinHex from reporting each unreadable sector separately. This is useful e.g. for computer forensics.
- WinHex can either leave the destination sector that corresponds to a damaged source sector unchanged or fill it with an ASCII pattern you specify (e.g. your initials, or something like "BAD "). Leave the pattern edit box blank to fill such sectors with zero bytes. BTW, this pattern is also used to display a bad sector's contents in the disk editor.
- Bad sectors often occur in contiguous groups, and each attempt to read a bad sector usually takes a long time. You may have WinHex avoid such damaged disk areas. When a bad sector is encountered, WinHex can try to skip a number of subsequent sectors you specify (25 by default). This is useful if you wish to accelerate the cloning process and if you do not care about some actually readable sectors not making it to the clone.

Regular disk cloning is not an option if you want to duplicate a disk in a removable drive (e.g. a floppy disk) with only one removable drive present. The correct concept for this application is *disk imaging*, where the data is first stored in an image *file*. The image can then be copied to a different disk. The result is the same as disk cloning.

There are two ways to image a disk:

- If convenience is your primary concern, use the backup functionality. For easy recovery, a backup file includes information on its contents: sector numbers, source disk etc.
- The disk cloning dialog allows copying sectors from a disk into a raw, headerless image file and later vice-versa. Combined with the silent "log file" mode, this is preferable to creating a backup in case of defective sectors on the source disk.

Hint on disk cloning and disk imaging

Cloning or imaging the drive that contains the active Windows installation can produce inconsistent copies. At any rate, please make sure the source drive is not written to during the cloning/imaging/backup/restoration procedure by any other program or by Windows itself. It is recommended to move the TEMP directory to a different drive. The swap file should be created on a different drive, too. Alternatively, completely disabling swapping in the control panel may help as well.

Make sure no other program or service can write to the partition you are going to clone. E.g. check for defragmentation tools running in the background and deactivate them for the duration of the cloning/backup/restoration. Under Windows NT/2000/XP it is recommended to unmount the partition as a logical drive/disk letter, or at least make the logical drive temporarily read-only (NTFS only).

After cloning a logical NTFS drive, you may need to reboot your system or run "chkdsk /f" on the target drive in order to see the new contents in Windows (this clears all of Windows' internal buffers).

Cloning or imaging in WinHex makes exact sector-wise copies. It cannot dynamically change partition sizes or adapt to destination disks larger or smaller than the source disks. This can later be done by PartitionMagic, PartitionStar etc.

Data Recovery

There are four ways how to recover data using WinHex. All require that you open the disk to recover from with the disk editor.

- 1) Automatic recovery of files with given filenames (easiest method)
- 2) Automatic recovery of files of a certain type (does not require a healthy file system)
- 3) File recovery with the Access button or the Directory Browser (advanced access to the mechanism #1)
- 4) Manual data recovery

Important: At any rate, do not use the drive that you wish to recover from for writing data any more! You may inadvertently overwrite lost files, making them unrecoverable. This includes not booting Windows from such a drive any more, as this involves numerous write operations.

Sorry, this version is a free update only for users who purchased WinHex 10.55 or later. Your license codes cannot be used with this version. Please see <http://www.winhex.com/winhex/upgrade.html> on how to upgrade.

Start Center

The so-called Start Center is a dialog window that is optionally displayed at startup and is meant as a simplified control panel for beginning your work. It allows to quickly open files, disks, memory modules, and folders as well as up to 255 recently edited documents (16 by default, left-hand list). These may be files, folders, logical drives or physical disks. When opened again, WinHex restores the last cursor position, the scrolling position, and the block (if defined) of each document, unless the corresponding option is disabled.

From the Start Center you are also able to access *projects* (right-hand top list). A project consists of one or more documents to edit (files or disks). It remembers the editing positions, the window sizes and positions and some display options. By saving a window arrangement as a project you can continue to work in several documents right where you left them, with a single click only. This is especially useful for recurring tasks. When you load a project, all currently opened windows are automatically closed first.

Besides, WinHex automatically saves the window arrangement from the end of a WinHex session as a project, and can re-create it next time at startup. Each project is stored in a .prj file. It can be deleted or renamed right within the Start Center (context menu or Del/F2 key).

Last not least, the Start Center is the place where to manage scripts. You may check, edit, create, rename, and delete scripts using the context menu. To execute a script, double-click it or single-click it and click the OK button.

View Menu

Text Display Only: Hides the hexadecimal data display and uses the full width of the editor window for the ASCII text display.

Hex Display Only: Hides the ASCII text display and uses the full width of the editor window for the hexadecimal data display.

Record Presentation: When editing subsequent data records of the same size (for instance, table entries of a database) you may now have WinHex display every other record with a different background color, as a kind of visual aid. The color can be selected in the General Options dialog. Also, WinHex offers to display the current record number and the offset within that record (relative offset) in the status bar, based the record size and the offset of the first record as specified. If any of the two record features is enabled, the Go To Offset command allows moving the current position in units of the current record size.

Show: The **directory browser** is available for logical drives/partitions opened with the disk editor. The **Data Interpreter** is a small window that provides "translation services" for the data at the current cursor position. The **toolbar** is displayed optionally, too. A **tab control** makes each edit window accessible with a single mouse click only. The **details panel** provides in-depth information on any open object (file, disk, RAM).

Template Manager

Tables: Provides four conversion tables (cf. ANSI ASCII/IBM ASCII).

Lines & Columns

Synchronize Scrolling: Synchronizes up to four tiled windows on identical absolute offsets. Hold the Shift key when enabling this feature to tile the windows horizontally instead of vertically.

Synchronize & Compare: Synchronizes up to four windows and visually displays byte value differences. If no more than two windows are involved, WinHex maintains the initial distance between the offsets of the first shown byte in these windows when scrolling. Not synchronizing on absolute offsets is useful for example when comparing two copies of the file allocation table, which are obviously at different offsets. You may skip to the next or to the previous byte value difference by clicking the extra buttons that are provided in one of the two edit windows.

Refresh View: Redraws the contents of the current edit window. In case the current file was updated by an external program, WinHex offers to dismiss any changes made in WinHex and reload the file from scratch.

Scripts

Most of the functionality of WinHex can be used in an automated way, e.g. to speed up recurring routine tasks or to perform certain tasks on unattended remote computers. The ability to execute scripts other than the supplied sample scripts is limited to owners of a [professional license](#). Scripts can be run from the [Start Center](#) or the command line. While a script is executed, you may press Esc to abort. Because of their superior possibilities, scripts supersede routines, which were the only method of automation in previous versions of WinHex.

WinHex scripts are text files with the filename extension ".whs". They can be edited using any text editor and simply consist of a sequence of commands. It is recommended to enter one command per line only, for reasons of visual clarity. Depending on the command, you may need to specify parameters next to a command. Most commands affect the file or disk presented in the currently active window.

Script commands are case-*insensitive*. Comments may occur anywhere in a script file and must be preceded by two slashes. Parameters may be 255 characters long at most. Where in doubt because hex values, text strings (or even integer numbers) are accepted as parameters, you may use inverted commas (quotation marks) to enforce the interpretation of a parameter as *text*. Inverted commas are *required* if a text string or variable name contains one or more space characters, so that all characters between the inverted commas are recognized as constituting *one* parameter.

Also see: [WinHex API](#)

The following is a description of currently supported script commands, including example parameters.

Create "D:\My File.txt" 1000

Creates the specified file with an initial file size of 1000 bytes. If the file already exists, it is overwritten.

Open "D:\My File.txt"

Open "D:*.txt"

Opens the specified file(s)..

Open C:

Open D:

Opens the specified logical drive.

Open 80h

Open 81h

Open 9Eh

Opens the specified physical media. Floppy disk numbering starts with 00h, fixed and removable drive numbering with 80h, optical media numbering with 9Eh.

Optionally, you may pass a second parameter with the Open command that defines the [edit mode](#) in which to open the file or media ("in-place" or "read-only").

CreateBackup

Creates a backup of the active file in its current state.

CreateBackupEx 0 100000 650 true "F:\My backup.whx"

Creates a backup of the active disk, from sector 0 through sector 1,000,000. The backup file will be split automatically at a size of 650 MB. Compression is enabled ("true"). The output file is specified as the last parameter.

If the backup file should not be split, specify 0 as the third parameter. To disable compression, specify "false". To have the Backup Manager automatically assign a filename and place the file in the folder for

backup files, specify "" as the last parameter.

Goto 0x128

Goto MyVariable

Moves the current cursor position to the hexadecimal offset 0x128. Alternatively, an existing variable (up to 8 bytes large) can be interpreted as a numeric value, too.

Move -100

Moves the current cursor position 100 bytes back (decimal).

Write "Test"

Write 0x0D0A

Write MyVariable

Writes the four ASCII characters "Test" or the two hexadecimal values "0D0A" at the current position (in overwrite mode) and moves the current position forward accordingly (i.e. by 4 bytes). Can also write the contents of a variable specified as the parameter.

Insert "Test"

Functions just as the "Write" command, but in *insert* mode. Must only be used with *files*.

Read MyVariable 10

Reads the 10 bytes from the current position into a variable named "MyVariable". If this variable does not yet exist, it will be created. Up to 16 different variables allowed. Another way to create a variable is the Assign command.

ReadLn MyVariable

Reads from the current position into a variable named "MyVariable" until the next line break is encountered. If the variable already exists, its size will be adjusted accordingly.

Close

Closes the active window without saving.

CloseAll

Closes all windows without saving.

Save

Saves changes to the file or disk in the active window.

SaveAs "C:\New Name.txt"

Saves the file in the active window under the specified path and filename. Specify "?" as the parameter to let the user specify the destination.

SaveAll

Saves changes in all windows.

Exit

Terminates script execution and ends WinHex.

ExitIfNoFilesOpen

Aborts script execution if no files are already opened in WinHex.

Block 100 200

Block "My Variable 1" "My Variable 2"

Defines the block in the active window to run from offset 100 to offset 200 (decimal). Alternatively, existing variables (each up to 8 bytes large) can be interpreted as numeric values.

Block1 0x100

Defines the block beginning to be at the hexadecimal offset 0x100. A variable is allowed as the parameter as well.

Block2 0x200

Defines the block end to be at the hexadecimal offset 0x200. A variable is allowed as the parameter as well.

Copy

Copies the currently defined block into the clipboard. If no block is defined, it works as known from the Copy command in the Edit menu.

Cut

Cuts the currently defined block from the file and puts it into the clipboard.

Remove

Removes the currently defined block from the file.

CopyIntoNewFile "D:\New File.dat"**CopyIntoNewFile "D:\File +MyVariable+.dat"**

Copies the currently defined block into the specified new file, without using the clipboard. If no block is defined, it works as known from the Copy command in the Edit menu. Can copy disk sectors as well as files. The new file will not be automatically opened in another edit window. Allows an unlimited number of "+" concatenations in the parameter. A variable name will be interpreted as an integer if not be larger than 2²⁴ (~16 Mio.). Useful for loops and file recovery.

Paste

Pastes the current clipboard contents at the current position in a file, without changing the current position.

WriteClipboard

Writes the current clipboard contents at the current position in a file or within disk sectors, without changing the current position, by overwriting the data at the current position.

Convert *Param1 Param2*

Converts the data in the active file from one format into another one. Valid parameters are ANSI, IBM, EBCDIC, Binary, HexASCII, IntelHex, and MotorolaS, in combinations as known from the conventional Convert menu command.

Encrypt "My Password"

Encrypts the active file or disk, or selected block thereof, with the specified key (up to 16 characters long) using the PC1 algorithm (128 bit).

Decrypt "My Password"

Decrypts the active file or disk.

Find "John" [*MatchCase MatchWord Down Up BlockOnly SaveAllPos Unicode Wildcards*]**Find 0x0D0A [*Down Up BlockOnly SaveAllPos Wildcards*]**

Searches in the active window for the name John or the hexadecimal values 0x0D0A, respectively, and stops at the first occurrence. Other parameters are optional. By default, WinHex searches the entire file/disk. The optional parameters work as known from usual WinHex search options.

ReplaceAll "John" "Joan" [*MatchCase MatchWord Down Up BlockOnly Unicode Wildcards*]**ReplaceAll 0x0A 0x0D0A [*Down Up BlockOnly Wildcards*]**

Replaces all occurrences of either a string or hexadecimal values in the active file with something else. Can only be applied to a disk if in in-place mode.

IfFound

A boolean value that depends on whether or not the last Find or ReplaceAll command was successful. Place commands that shall be executed if something was found after the IfFound command.

IfEqual MyVariable "constant string"**IfEqual 0x12345678 MyVariable****IfEqual MyVariable MyOtherVariable**

Compares two variables, ASCII strings, or hexadecimal values at the binary level. Comparing two objects with a different length always returns False as the result. If equal, the following commands will be executed.

IfGreater 0x12345678 MyVariable**IfGreater MyVariable MyOtherVariable**

Compares two variables and interprets them as integer values (64-bit signed). Such an integer comparison is not appropriate for comparing strings of different lengths alphabetically. If the first one is greater than the second one, the following commands will be executed.

Else

May occur after IfFound or IfEqual. Place commands that shall be executed if nothing was found or if the compared objects are not equal after the Else command.

EndIf

Ends conditional command execution (after IfFound or IfEqual).

{...

ExitLoop

...}

Exits a loop. A loop is defined by braces. Closing braces may be followed by an integer number in square brackets, which determines the number of loops to execute. This may also be a variable or the keyword "unlimited" (so the loop can only be terminated with an ExitLoop command). Loops must not be nested.

Example of a loop:

```
{ "Loop" }[10] will write the word "Loop" ten times.
```

Label ContinueHere

Creates a label named "ContinueHere"

JumpTo ContinueHere

Continues script execution with the command following that label.

NextObj

Switches cyclically to the next open window and makes it the "active" window. E.g. if 3 windows are open, and window #3 is active, NextObj will make #1 the active window.

ForAllObjDo

The following block of script commands (until **EndDo** occurs) will be applied to all open files and disks.

CopyFile C:\A.dat D:\B.dat

Copies the contents of C:\A.dat into the file D:\B.dat.

MoveFile C:\A.dat D:\B.dat

Moves the file C:\A.dat to D:\B.dat.

DeleteFile C:\A.dat

Surprisingly, deletes C:\A.dat.

InitFreeSpace
InitSlackSpace

Clears free space or slack on the current logical drive, respectively, using the currently set initialization settings. InitSlackSpace switches the drive temporarily to in-place mode, thus saving all pending changes.

Assign MyVariable 12345
Assign MyVariable 0x0D0A
Assign MyVariable "I like WinHex"
Assign MyVariable MyOtherVariable

Stores the specified integer number, binary data, ASCII text, or other variable's contents in a variable named "MyVariable". If this variable does not yet exist, it will be created. Up to 16 different variables allowed. Another way to create a variable is the Read command.

Inc MyVariable

Interprets the variable as an integer (if not larger than 8 bytes) and increments it by one. Useful for loops.

Dec MyVariable

Interprets the variable as an integer (if not larger than 8 bytes) and decrements it by one.

MessageBox "Caution"

Displays a message box with the text "Caution" and offers the user an OK and a Cancel button. Pressing the Cancel button will abort script execution.

ExecuteScript "ScriptName"

Executes another script from within a running script, at the current execution point, e.g. depending on a conditional statement. Calls to other scripts may be nested. When the called script is finished, execution of the original script will be resumed with the next command. This feature can help you structure your scripts more clearly.

Turbo On**Turbo Off**

In turbo mode, most screen elements are not updated during script execution and you are not able to abort (e.g. by pressing Esc) or pause. This accelerates the script by up to 75% if a lot of simple commands such as Move and NextObj are executed in a loop.

Debug

All the following commands must be confirmed individually by the user.

UseLogFile

Error messages are written into the log file "Scripting.log" in the folder for temporary files. These messages are not shown in a message box that requires user interaction. Useful especially when running scripts on unattended remote computers.

CurrentPos**GetSize****unlimited**

are keywords that act as placeholders and may be used where numeric parameters are required. On script execution, CurrentPos stands for the current offset in the active file or disk window and GetSize for its size in bytes. unlimited actually stands for the number 2,147,483,647.

WinHex API

Purpose

The WinHex API (application programming interface) allows to use the advanced capabilities of the WinHex hex & disk editor programmatically from your own C++, Delphi, or Visual Basic programs. In particular, it provides a convenient and simple interface for random access to files and disks.

Requirements

Developing software that uses the WinHex API requires a valid *professional* or *specialist* WinHex license. Additionally, you need import declarations for your programming language of choice, the library file "whxapi.dll", and the API documentation. Please find those files and more detailed information online at <http://www.winhex.com/winhex/api/>.

You may also *distribute* both any software that makes use of the WinHex API and WinHex itself. There are two ways how to distribute WinHex:

1. Distribute the unlicensed WinHex version. For the API to work, your customer has to purchase professional, specialist, or API licenses according to the number of WinHex installations needed.

-or-

2. Recommended: purchase and distribute a special API version of WinHex yourself, which is configured to only provide the API functionality, which cannot be run with the normal user interface, and which is available at a reduced price. You may place your order online at <http://www.winhex.com/winhex/api/>. Volume discount available on request (please specify the number of licenses you are interested in). One WinHex API license needed per end user computer. The product will be licensed to you, *you* will be the actual owner of the licenses, but any of your customers may use them. The end user does not have to take care of anything related to WinHex.

Also see: [Scripts](#)

File Recovery with the Access Button

WinHex offers an advanced way to access its automated file recovery by name, allowing to conveniently undelete files of any type.

If on a logical *NTFS* drive you navigate to a file record (beginning with the signature "FILE"), you may use the Recover command in the Access button's menu to recover the file or directory described in that record. To find a particular file record, search the *NTFS* drive for the filename with the Unicode option enabled or use the directory browser.

Whenever a logical *FAT* drive is open and a cluster is visible that is allocated to a directory (and thus contains directory entries), you may use a command in the Access button menu named "Recover current directory" to replicate that currently displayed directory, with all its files and optionally its nested subdirectories, regardless of whether they are partially still existing or have been deleted. WinHex will save all this in a destination folder you specify (strongly recommended: on a different drive, to avoid overwriting other deleted or lost files). WinHex assumes that the files have not been overwritten and are not fragmented. This is crucial for a successful recovery. The file allocation table is only optionally respected, since it is initialized by the OS in the relevant parts when a file is deleted. You need to carefully check the resulting files for consistency. Unfortunately, Windows 2000 and XP erase the upper 16 bits of the start cluster number when deleting files and directories directly (not via the recycle bin).

Within a cluster with directory entries, you may also point the cursor to a short filename entry (or short directory name) and use another command in the Access button menu to browse to that file or directory, or to recover that specific file or directory only.

Remember, to find the right cluster with the directory entries in the first place, you could simply start with the root directory, use Tools | Disk Tools | List Directory Clusters for a specific existing directory, or search for the short name of a file or directory you lost via text search.

During recovery, WinHex recreates the original hierarchical directory structure and restores the original file dates, times, and attributes. Long filenames are respected instead of the short 8+3 equivalents where possible. The recovery is strictly read-only on the source disk. The data or file system on the source disk will not be altered in any way.

File Recovery by Type

A data recovery function in the Disk Tools menu that searches for those files on any disk or disk image file that can be recognized by a characteristic file header signature (a certain sequence of byte values). Because of this approach, File Recovery by Type does not depend on the existence of functional file system structures. Optionally, only files found in unallocated drive space are recovered (files that presumably have been lost or deleted). A log file about the selected parameters is written to the output directory as well. The resulting files are named according to a pattern you provide ("file~~~~" by default, where the swung dashes are placeholders for an incrementing number). Optionally, recovered files of each type are put into their own subfolder. Note that File Recovery by Type will not produce consistent files in case the original files were stored in a fragmented way (in discontinuous clusters).

Also optionally, a thorough search can be conducted at all offsets, not just at the beginning of clusters. This is necessary when recovering files from backup files or tapes where they are not aligned at cluster boundaries. It also renders this recovery method easier to use because you don't have to care about sector and cluster sizes. This comes at the cost of an increased number of false positives, though, misidentified file signatures occurring randomly on a media, not indicating the beginning of a file.

WinHex comes with various preset file type signatures. You may select multiple file types at the same time for recovery. You may also fully customize the file type definitions and add your own. Click the Customize button to edit the file "File Type Signatures.txt". By default, WinHex opens the file in MS Excel. This is convenient because the file consists of columns separated by tabs. If you edit the file with a text editor, be sure to retain these tabs, as WinHex relies on their presence to properly interpret the file type definitions. To find characteristic file header signatures, open several files of a certain type in WinHex and look for common byte values near the beginning of the file at identical offset. After editing the file you need to exit the dialog window and use the File Recovery by Type menu command again to see the changes in the file type list. WinHex will ignore everything beyond the 16th byte in a header or footer signature, after the 19th character in a file type description, and after the 11th character in a file type extension. The maximum number of supported file types is 256.

If no file footer is specified, WinHex will extract the files it finds at the fixed size specified in the dialog window (usually preferable). Otherwise WinHex will search for corresponding footers which mark the end of the file, but will not search further after the file header than the number of bytes specified in the dialog window as the maximum file size.

For example, to extract all JPEG image files, WinHex searches the hexadecimal values FFD8FF as the file header signature (typed as 0xFFD8FF in the file type definition file to indicate a hexadecimal as opposed to an ASCII signature). The header offset is 0 because the aforementioned signature always occurs at that offset within the file and within the file's first cluster, right at the beginning. Unless you know a footer that is safe to trust (e.g. FFD9 is a valid footer for JPEG files, but is not safe, meaning it may also occur randomly in the image data, not only at the end of a file), it is recommended to recover with a fixed file size (the usual size of your JPG files or more), without a footer. Usually it does no harm to recover with a "too big" size, since their corresponding application programs can tell from the file format where the actual end of file is.

Specialist Tools Menu

Specialist license only.

Gather Free Space: Traverses the currently open logical drive and gathers all unused clusters in a destination file you specify. Useful to examine data fragments from previously existing files that have not been deleted securely. Does not alter the source drive in any way. The destination file must reside on another drive.

Gather Slack Space: Collects slack space (the unused bytes in the respective last clusters of all cluster chains, beyond the actual end of a file) in a destination file. Each occurrence of slack space is preceded by line break characters and the cluster number where it was found (as ASCII text). Otherwise similar to Gather Free Space. Works with FAT12, FAT16, FAT32, and NTFS drives. WinHex cannot access slack space of files that are compressed or encrypted at the file system level.

Gather Inter-Partition Space: Captures all space on a physical hard disk that does not belong to any partition in a destination file, for quick inspection to find out if something is hidden there or left from a prior partitioning.

Gather Text: Recognizes text according to the parameters you specify and captures all occurrences from a file, a disk, or a memory range in a file. This kind of filter is useful to considerably reduce the amount of data to handle e.g. if a computer forensics specialist is looking for leads in the form of text, such as e-mail messages, documents, etc. The target file can easily be split at a user-defined size. This function can also be applied to a file with collected slack space or free space, or to damaged files in a proprietary format than can no longer be opened by their native applications, like MS Word, to recover at least unformatted text.

Simultaneous Search: A parallel search facility, that lets you specify a virtually unlimited list of search terms, one per line. The search terms are either text strings or hex values (specified with a 0x prefix). They are searched simultaneously, and their occurrences can be archived either in the Position Manager, or in a tab-delimited text file, similar to the disk catalog, which can be further processed in MS Excel or any database. WinHex will save the offset of each occurrence, the search term, the name of the file or disk searched, and in the case of a logical drive the cluster allocation as well! (i.e. the name and path of the file that is stored at that particular offset, if any)

That means e.g. a forensic examiner is now able to systematically search multiple hard drives and disk images in a single pass for words like

- drug
- cocaine
- (street synonym #1 for cocaine)
- (street synonym #2 for cocaine)
- (street synonym #3 for cocaine)
- (street synonym #3 for cocaine, alternative spelling)
- (name of dealer #1)
- (name of dealer #2)
- (name of dealer #3)

at the same time! When searching a logical drive and archiving the results, this will narrow down the examination to a list of files upon which to focus. If you do not have WinHex archive the occurrences, you may use the F3 key to continue the search. [Search options](#)

Create Drive Contents Table: Creates a disk "catalog" of existing and deleted files and directories on a logical drive or partition, with user-configurable information such as attributes, all available date & time stamps, size, allocated clusters, hash ([checksum](#) or [digest](#)), alternate data streams (which contain hidden data, on NTFS drives only), etc. Extremely useful to systematically examine the contents of a disk. Allows

to limit the search for files of a certain type using a filename mask (e.g. *.jpg;*.gif). Hash values can only be calculated for existing files. Internal system files and extensive cluster allocation information can only be listed for NTFS volumes if you include deleted files in the table. In the column with cluster allocation information you may also find only a sector in the master file table listed (in which small files are stored directly). Clusters allocated to alternate data streams are listed in this column following the ADS name and a colon.

The result can be output to a tab-delimited text file, which is useful for import and further processed in databases or MS Excel. Sorting by date & time stamps will result in a good overview of what a disk has been used for at a certain time. E.g. the NTFS attribute "encrypted" might quickly reveal what files may turn out to be the most important ones in a forensic analysis.

The result can also be output directly to the [directory browser](#). That means you have an "all files view" of a logical drive or partition in WinHex and can sort by date, filename extension, etc., move to the clusters where a file is stored, recover a file, delete irrelevant items from the list, etc. However, while the directory browser offers a more interactive approach, it shows less detail than the text file output.

Create Directory Contents Table: Works like Create Drive Contents Table, but for a user-selected directory and its subdirectories only.

Media Details Report: Shows information about the currently active disk or file and lets you copy it e.g. into a report you are writing. Most extensive on physical hard disks, where details for each partition and even unallocated gaps between existing partitions are pointed out.

Interpret Image File As Disk: Treats a currently open and active disk image file as either a logical drive or physical disk. This is useful if you wish to closely examine the file system structure of a disk image, extract files, etc. without copying it back to a disk. If interpreted as a physical disk, WinHex can access and open the partitions contained in the image individually as known from "real" physical hard disks. WinHex is even able to interpret *spanned* image files, that is, image files that consist of separate segments of any size. For WinHex to detect a spanned image file, the first segment may have an arbitrary name and a non-numeric extension or the extension ".000". The second segment must have the same base name, but the extension ".001", the third segment ".002", and so on. The DOS cloning tool X-Ways Replica is able to image disks and produce such file segments. This is useful because the maximum image file size supported by FAT16 and FAT32 is 2 GB or 4 GB, respectively.

Bates-number Files: Bates-numbers all the files within a given folder and its subfolders for discovery or evidentiary use. A constant prefix (up to 13 characters long) and a unique serial number are inserted between the filename and the extension in a way attorneys label paper documents for later accurate identification and reference.

Trusted Download: Solves a security problem. When transferring unclassified material from a classified hard disk drive to unclassified media, you need to be certain that it will have no extraneous information in any cluster or sector "overhang" spuriously copied along with the actual file, since this slack space may still contain classified material from a time when it was allocated to a different file. This command copies files in their current size, and no byte more. It does not copy entire sectors or clusters, as conventional copy commands do. Multiple files in the same folder can be copied at the same time.

Highlight Free Space/Slack Space: Displays offsets and data in softer colors (light blue and gray, respectively). Helps to easily identify these special drive areas. Works on FAT and NTFS logical drive and FAT partitions.

Manual Data Recovery

Aside from offering various *automatic data recovery* mechanisms, WinHex is a powerful tool to *manually* recovery data. It is possible to restore lost or deleted files (or more general: data) that have not been physically erased (or overwritten), but merely marked as deleted in the file system (logical deletion).

Open the logical drive where the deleted file resided on using the disk editor. Principally you can **recreate** such **a file by selecting the disk sectors**, that were allocated to the file, as the current **block** and **saving them using** the menu command **Edit | Copy Block | Into New File**. But it may prove difficult to *find* the sectors where the file is still stored in the first place. There are principally two ways to accomplish this:

1. In case you know a snippet of the file you are looking for (e.g. the characteristic signature in the header of a JPEG file or the words "Dear Mr. Smith" in a MS Word document), search it on the disk using the common search commands ("Find Text" or "Find Hex Values"). This is a very simple and safe way, and can be recommended to anyone.
2. In case you only know the filename, you will need some knowledge about the filesystem on the disk (FAT16, FAT32, NTFS, ...) to find traces of former directory entries of the file and thereby determine the number of the first cluster that was allocated to the file. Information on file systems is available in the Knowledge Base on the WinHex web site. The following applies to all FAT variants:

If the directory that *contained* the file (let's call that directory "D") still exists, you can find D on the disk using Tools | Disk Tools | List Directory Clusters. The factory template for FAT directory entries that comes with WinHex will then be helpful to find out the number of the first cluster that was allocated to the deleted file in that directory. Otherwise, if D has been deleted as well, you need to find the contents of D (using the directory entry template) starting with the directory that contained D (possibly the root directory).

Deleted files and directories are marked with the character "å" (hexadecimal: E5) as the first letter in their name.

You may encounter the problem that the file to recover is fragmented, that is, not stored in subsequent contiguous clusters. On FAT drives, the next cluster of a file can be looked up in the file allocation table at the beginning of the drive, but this information is erased when a file is deleted.

File Recovery by Name

There is a very easy-to-use data recovery function in WinHex, part of the the Disk Tools menu. Requires that you have opened a logical drive or a single partition of a physical disk with the disk editor. Works on FAT12, FAT16, FAT32, and NTFS drives. You may specify one or more filename patterns that cover all the files you wish to retrieve, e.g.:

Letter to Mr. Smith.doc

Invoice*.pdf

m*.xls

Image*.gif

*.tif

Please note that files that were moved to the recycle bin prior to permanent deletion are internally renamed by Windows, where only the filename extension remains the same. Unlike File Recovery by Type, this function will also restore the file date & time and its attributes.

Optionally WinHex only recovers files that are explicitly marked as deleted in the file system. It may be wise not to use that option if you are looking for files that got lost other than by normal deletion, e.g. due to file system corruption. In that case you can even switch to files that are *not* marked as deleted. With that setting you will recover only those files that existed at the time when the corruption occurred and no duplicates (like previously existing working copies, temporary files etc.) that were deleted because they were no longer needed.

Alternatively to using the file allocation table of a FAT drive, WinHex can optionally also rely on files not being fragmented, recovering them as a continuous stream of consecutive clusters.

Check "Intercept invalid filenames" to prevent a failure of the recovery because of filenames with characters considered as invalid by the file system. Useful for example if you wish to recover files that had filenames in a non-western language with a western-language Windows version. This option will rename such a file if necessary to ensure that it can be recreated.

On an NTFS drive, if the file you are looking for cannot be found, it may help to enable the "thorough" search. It is not enabled by default because it takes significantly more time.

You must also specify an output folder where to recreate the original file(s). Important: make sure this folder is on a different drive. Specifying a folder on the same drive where you are recovering from could easily overwrite disk space where deleted files reside that you still wish to recover! That way they would be lost forever. It might also lead to a loop, if WinHex repeatedly "recovers" files that it has just recreated.

Surplus Sectors

This term is used in WinHex in the following way:

Surplus sectors on a logical drive are those few sectors at the end that do not add to a full cluster and thus cannot be used by the OS (and thus by no conventional application program either).

Surplus sectors on a physical disk are those sectors at the end that are located outside the regular disk geometry scheme (because they do not add to a full cylinder/header/track entity), which is why they are usually not used by any partition or the operating system (or any conventional application program).

Surplus sectors have nothing to do with "bad" or damaged sectors or sectors a hard disk internally uses as a replacement for sectors found to be faulty.

Flexible Integer Variables

A special variable type supported by templates is `uint_flex`. This type allows to compose an unsigned integer value from various individual bits within a 32-bit (4-byte) range in an arbitrary order and is even more flexible than a so-called bit field in the C programming language.

`uint_flex` requires an additional parameter string in inverted commas that specifies exactly which bits are used in which order, separated by commas. The bit listed first becomes the most significant bit (high value bit) in the resulting integer, and it is not interpreted as a + or - indicator. The bit listed last becomes the least significant bit in the resulting integer.

The bits are counted starting with 0. Bit 0 is the bit that is the least significant bit of the 1st byte. Bit 31 is the most significant bit of the fourth byte. Thus, the definition is based on little-endian philosophy.

For example,

`uint_flex "15,14,13,12,11,10,9,8,7,6,5,4,3,2,1,0" "Standard 16-bit integer"`
is exactly the same as `uint16`, the common unsigned 16-bit integer variable.

`uint_flex "31,30,29,28,27,26,25,24,23,22,21,20,19,18,17,16,15,14,13,12,11,10,9,8,7,6,5,4,3,2,1,0"`
`"Standard 32-bit integer"`
is exactly the same as `uint32`, the common unsigned 32-bit integer variable.

The benefit of `uint_flex`, though, is that the number, the position, and the usage order of all bits can be chosen arbitrarily. For example,

`uint_flex "7,15,23,31" "An unusual 4-bit integer"`

composes a 4-bit integer out of the respective most significant bits of each of the four bytes involved. If these four bytes happen to be `F0 A0 0F 0A = 11110000 10100000 00001111 00001010`, bit 7 is 1, bit 15 is 1, bit 23 is 0, and bit 31 is 0. So the resulting `uint_flex` is `1100 = 1*8 + 1*4 + 0*2 + 0*1 = 12`.

Directory Browser

On logical drives and partitions formatted with FAT12, FAT16, FAT32, or NTFS, WinHex offers a *directory browser*, which resembles the Windows Explorer's right-hand list. It can be disabled or enabled by clicking the checkbox next to the Access button. The directory browser lists existing files and directories first, then deleted files and directories. Compressed files are displayed in blue, encrypted files in green (NTFS only). Right-clicking any item in the directory browser brings up a context menu with commands for opening a file or directory, exploring a directory, locating the beginning of a file or directory on the disk, locating the corresponding directory entry (FAT) or file record (NTFS), listing the allocated clusters in a separate window, and for easily recovering a lost or existing file or directory. The latter can recreate entire directory structures. Double-clicking executes the default action (locating the data, listing clusters, and exploring in the case of a directory). Clicking items in the separate list window allows to navigate to the listed clusters in the disk editor.

On NTFS drives, the directory browser lists all deleted files on the drive of which traces could still be found in a dedicated virtual folder "Lost & Found". These are the same files that are also recoverable using [File Recovery by Name](#) with the "thorough search" option disabled.

The directory browser can also be filled by [Create Drive Contents Table](#).

