

Contents

GeoClock for Windows version 7.0

[What is GeoClock](#)

[Getting Started](#)

[Main Bar](#)

[File](#)

[Edit GEOOn.DAT](#)

[Edir GEOCLOCK.INI](#)

[Make Zoom Up](#)

[Setup](#)

[Exit](#)

[Maps](#)

[World](#)

[Zoom Up](#)

[Zoom Home](#)

[Random](#)

[Map List](#)

[Controls](#)

[Save Settings](#)

[Time Control](#)

[Window Controls](#)

[Options](#)

[Command Entry](#)

[Back](#)

[City/Country](#)

[Lat/Long Lines](#)

[Actions](#)

[Where is](#)

[Distance](#)

[Scripts](#)

[Reset](#)

[HAM radio](#)

[Advanced Topics](#)

[Registration](#)

[What's New](#)

What Is GeoClock

"It's inconceivable that you won't like this program."

-- Jerry Pournelle, BYTE

GeoClock shows the current time (based on your computer's clock) with a high quality map of the earth. The current sun position is displayed, and the parts of the earth in sunlight and twilight are highlighted. This display is automatically updated every few seconds. Local sunrise, sunset, the sun's azimuth and elevation, and times around the world are also displayed. A variety of map backgrounds and other options are available. A color graphics adapter (640x480x16 or better) and a hard disk are required. Both DOS and Windows 3.x versions are included with registration.

GeoClock is distributed as shareware. This means that if you use and enjoy the program, you are expected to register it. See "Ordering GeoClock" for details. The registered version includes the zoom, distance measuring, and city time display functions, and at least 40 maps.

GeoClock
Joseph R Ahlgren
2218 N Tuckahoe St
Arlington VA 22205

Voice 703-241-2661
BBS 703-241-7980
FAX 703-241-5809
CompuServe 70461,2340 (Joe Ahlgren)
Internet jahlgren@capaccess.org

Getting Started

See also:

[Initial Setup](#)

[System Requirements](#)

[Using GeoClock](#)

If you have purchased the registered version of GeoClock for Windows, there is a SETUP program on the distribution disk that installs and customizes GeoClock.

GeoClock is available in both DOS and Windows versions. GeoClock for Windows is distributed in the file GCKWINxx.ZIP (where xx is the version number). This ZIP file has the following files:

GEOCKWIN.EXE (GeoClock for Windows executable file)
GEOCKWIN.HLP (GeoClock for Windows Help file)
USCITY.BIN (US city data base)
WRLDCITY.BIN (world city data base)
GECONFIG.DAT (initial configuration information)
GEOCLOCK.DAT (default map annotation file)
GEOn.DAT (n=1,2,2000, and 2501) (Map annotation files)
MAPn.EGA (n=1,2,2000, and 2501) (Map graphics files)

(The distribution file for GeoClock for DOS is GEOCLKxx.ZIP. This file has all the files listed above, except the first two, plus the special files required for DOS)

In addition, there is an extra file which contains more maps and some additional features:

MAPn.EGA (n=3,4,5)
GEOn.DAT (n=3,4,5)
ZIPCODES.BIN (zip code configuration file)

To set up GeoClock, you must at a minimum unZIP the GCKWINxx.ZIP file to a directory made for GeoClock. If you have a version of GeoClock for DOS, you should place the Windows files in the same directory. You can unZIP other GeoClock files if you have them. If you have a registered version of GeoClock for DOS, you should run the REGISTER program to register the Windows version. At this point you can set up an icon for GEOCKWIN.EXE and run the program. GeoClock will take you through a setup menu the first time you run it.

When GeoClock for Windows runs, it creates several files:

GCWINDEX.BIN (list of maps)
GCWZOOMU.BIN (zoom up control file)
GEOCLOCK.INI (GeoClock for Windows configuration information)

GeoClock does ***NOT*** make any changes to Windows files, or add any DLLs to Windows.

Using GeoClock

GeoClock is available for DOS and for Windows 3.x. Both versions use a similar interface and share most files.

GeoClock for Windows is distributed in the GCKWINxx.ZIP (where xx is the version number). This file contains:

GEOCKWIN.EXE (executable file)
GEOCKWIN.HLP (Windows help file)

If you already have a registered copy of the DOS version or a previous GeoClock for Windows version, unZIP the file into the directory with the prior GeoClock materials, and then run the REGISTER program. If you are installing new a registered version of GeoClock for Windows, execute the SETUP program on the GeoClock for Windows diskette.

After the files have been installed, you can execute GEOCKWIN using the program manager, or by setting up an icon for the program. The first time GEOCKWIN is run, it will automatically take you through the customization and setup procedure.

There are a variety of way to navigate through the maps. The easiest is to click the left mouse button over an area of interest. This displays the highest resolution map containing that point. Clicking the right mouse button displays successively large area maps until the world map is reached. You can also use the Gazetteer function (press W or select Actions| Where Is) to bring up the most detailed map containing a particular city. You can also use the functions in the map menu, including map list, to select a map.

There are a number of functions which can be controlled by a single keystroke:

C Command Entry
D Distance measurement
K Switch back to previous map
L Toggle latitude/longitude display
M Select map from list
N Window Controls
O Major Options
R Reset time, scripts, etc
S Set speed of time passage
T Set Time
U Set Update Interval
W Where Is...
X Exit
Y Toggle between city and country display
0..9 Start script
<space> Terminate script

System Requirements

GeoClock for windows will run on a minimal windows system - VGA, 4 MB RAM, 80286 processor. However, the performance will be extremely poor on such a system. We recommend as a minimum:

486DX33 processor
8 MB RAM
256 color display
800x600 display

Whats New

GeoClock for Windows runs under Windows 3.x. It uses the same files and utility programs as the DOS version, and ordinarily both versions should be installed in the same directory. The primary features in the Windows version that are not available in the DOS version are:

- + Maps may be scaled to any size
- + Runs in the background or foreground
- + Online setup
- + Simplified interaction

The primary features in the DOS version that are not in the Windows version are:

- Advanced zoom and distance functions
- GeoGlobe

The Windows 3.x version has a few limitations due to Windows 3.x characteristics:

- Non-rectangular maps limited to 800x600
- Much slower update times
- Less accurate timing
- Much larger program size.

File

File Menu

Quit

Edit GEO.n.DAT

Edir GEOCLOCK.INI

Setup

Quit

Pressing Q, selecting this menu item, or pressing ESCape twice terminates GeoClock and closes all GeoClock Windows.

Edit DAT files

Annotation and other map display characteristics are controlled by text files. For any particular map (for example, MAP1), there is a corresponding text file (for example, GEO1.DAT) that has the specific custom characteristics for that map. The GECONFIG.DAT and GEOCLOCK.INI files have customization data that applies to all maps. These files ordinarily do not need to be changed by the user, but they may be edited using the menu items. The various commands and their syntax and functions are described in detail in the Commands section of help.

Make Zoom Up Table

In most GeoClock installations, more than one map can serve as the world map (the map at the top of the zoom hierarchy). The menu item allows the user to select the particular map to be used as the world map.

Set Up

GeoClock for Windows must be configured for your particular location. In particular, the time zone of your computer's clock **MUST** be set correctly, or all the times, the sun and moon positions, and the sunlight curve, will be incorrect.

To set up GeoClock, selected the Setup item from the Files menu. (The setup program is run automatically the first time you start GeoClock).

There are three ways to specify your location, which is used to calculate sun rise and set times, and to mark your location on the maps.

1) If you live in the US, the most accurate way is to use the "Init by ZipCode" button. By specifying your 5 digit postal zip code, your location accurate to a few kilometers, and your time zone, will be set. After typing your zip code, you must enter your city name in the box (this area will show ENTER_NAME_FOR_ZIP_CODE_00000). If you get the message INVALID_ZIP_CODE (which can mean that you have a new zip code not in the table GeoClock uses, or a zip code outside the 50 states), you must use one of the other methods.

2) You can use the "Init by LookUp" button. This will allow you to pick your location from about 4000 cities around the world using the GeoClock Gazetteer. Select the "US city" or "World City" radio buttons to determine which data base to use. You can sort by city name or by state/country name. Double click the city you want, or click the OK button when the city is highlighted. If your city does not appear, you should pick the city that is closest and is in the same time zone.

3) You can enter the city and location manually. Type the city name, latitude and longitude in the appropriate boxes. Make sure the latitude and longitude are in the correct format.

You select when your city will be displayed by the "Show City" radio group. If you select "never", your city will only appear on the maps if it happens to be included in the standard data file for that map. If you select "when on map", your city will appear on the map, and your city will be used for showing sun rise and sunset and local time, whenever the city fits on the map displayed. If the city does not fit on the map displayed, the primary city in the standard data file for that map will be used. If you select "always", your city will be displayed on the map if it fits, but will always be used for sun rise and sunset and local time zone information.

Once your city and location are selected, you must set the time zone information. If you use methods 1 or 2, the time zone fields will automatically be filled in. There is usually no reason to change these settings. If you use method 3, it is best to use method 2 to set to a close city in the same time zone, then use method 3 to change to city and location. If you need to change the time zone, use the drop down list to pick the proper zone. The drop down list shows the GeoClock time zone code name, then the name(s) of the standard and summer zones (for example, ET is EDT in the summer, and EST the rest of the year), and the hours from UTC (GMT) for standard and summer time (for ET, -5 and -4). The location time zone is the time zone your location uses. The PC time zone is for the time zone your PC is set to. Usually this is the same as the local zone, but some PC users keep the PC clock on UTC, or on standard time all year, and these users must set the PC time zone to that zone.

When you click OK, this configuration information will be written to the GEOCLOCK.INI file and will be used every time GeoClock starts.

Map Menu

These menu items allow you to select maps in a variety of ways. In addition, clicking the left mouse button on a point on the current map will bring up the most detailed map available containing that point, and clicking the right button will select less detailed maps containing the map displayed, until the world map is reached. (See also [ZOOMFRACT](#)).

[World](#)

[Zoom Up](#)

[Zoom Home](#)

[Random](#)

[Back](#)

[Map List](#)

World

Selecting this menu item changes to the map at the top of the zoom sequence. This is usually a map of the world.

Zoom Up

Selecting this menu item, or clicking on the map with the right mouse button, moves to the next larger map containing the currently displayed map.

Zoom Home

Selecting this menu item switches to the smallest map containing the home town selected for this installation. See [setup](#) .

Random

Selecting this menu item displays a map chosen at random from all available maps. This will always be different from the currently displayed map.

Back

Pressing "K" or selecting this menu item displays the map prior to the current maps (goes back).

Map List

Selecting this menu item, or pressing the "M" key, displays a list of all available maps. The maps are sorted by size, title, or number according to the "Sort Method" radio box. Double clicking an entry, or selecting an entry and then clicking OK, will display the selected map.

Controls

These menu items provide ways to control the appearance of GeoClock.

Save Settings

Time Control

Window Controls

Options

Command Entry

City/Country

Lat/Long Lines

Save Settings

This check item determines whether or not the user settings, such as window sizes and positions, are save between GeoClock runs. The setting information is written to the GEOCLOCK.INI file. To save the current settings, you can toggle the Save Settings button on the Controls|Window Controls menu item.

Command Entry

GeoClock has a large number of commands which may be used to control the display. The most commonly used commands have been implemented on the mneu bar at the top of the screen. You can activate any of these commands by clicking the appropriate menu item (such as Controls|Lat/Long). Many commands can be activate by pressing a single letter (such as "L" for Lat/Long) Other commands (such as SUNANGLE) may be included in the configuration file, in a data file, on the GeoClock command line, or entered interactively by pressing the C (for Command) key while GeoClock is displaying a map.

The commands are described in detail in another section of help.

Time Control

This dialog box allows the current time to be changed (this affects GeoClock time display but not the system time), and also allows the update intervals to be changed.

The first six spin boxes change the current time. The hours are based on a 24 hour clock. Above the hours spin box is an indication of the time zone to which the time corresponds.

The Fgnd Update box allows the GeoClock foreground update interval to be changed. This is the number of seconds that GeoClock will remain idle between screen refreshes while GeoClock is in the foreground. 0 seconds indicates that GeoClock will update continuously. The default value is 5 seconds.

The Bgnd Update box allows the GeoClock background update interval to be changed. This is the number of seconds that GeoClock will remain idle between screen refreshes while GeoClock is in the background. 0 seconds indicates that GeoClock will update continuously. This setting is not recommended because other applications will become sluggish. The default value is 60 seconds.

The Time Rate box determines how much time will appear to pass every time the screen is updated. For example, 24 causes the displayed time to change by 24 hours (1 day) every time the screen is updated. This feature can be used to see how the sun and moon and sunlight curves change over the day or season.

Window Controls

This dialog box controls how GeoClock will be displayed on the screen. The X and Y spin boxes on the right allow the width and height of the map display to be varied. These can be set to 640x480, or 800x600, by clicking the appropriate button.

The radio buttons in the upper left set how GeoClock will respond to window size changes. If "Full Control" is selected, the window may be set to any size. If "4x3 aspect" is selected, the window will be constrained to maintaining a 4x3 aspect ratio, which gives the most accurate map display. If the window size is changed while this button is selected, whichever dimension is changed last will be held, while the other dimension will be changed to maintain 4x3. For example, if the left vertical side is dragged left so that the width is 720 pixels, the height will be changed to 540 pixels.

The radio buttons in the middle left control the window state. Selecting "Maximize" maximizes the window, "Minimize" minimizes the window, and "Normal" restores the window to the last non-maximum non-minimum state. These are equivalent to the maximize, minimize, and restore buttons and system menu choices.

The check box on the left enables or disables the display of the menu bar, title bar, and border of the map window. This display is disabled, the map display will be somewhat larger, but the mouse cannot be used to change window size or position, or select menu items. All hot keys still function in this mode. Therefore, pressing "N" will bring up this dialog box and the bars and borders can be reenabled.

Options

This menu allows you to change to eight most commonly used values in GeoClock. Select the item by clicking the appropriate radio button on the left, then select a new value by clicking the appropriate radio button on the right. You can make the change effective in this run only, or you can make the value the new default value for GeoClock (writing the value to GEOCLOCK.INI) or the value for that map only (writing the value to GEOn.DAT).

Legend controls the data displayed at the bottom of the screen

Display Mode controls how sun shading is displayed

Units controls statute/nautical miles in the distance function

Moon controls the display of the moon symbol and ephemeris data

City Time Format controls showing day ahead/behind with arrows

Year Format selectes between two and four digit year format

Show Seconds controls the display of time seconds

Show Day of Week controls showing the day of week

Month Format controls showing text or number months

City/Country

Pressing "Y" or selecting this menu item toggles between showing city names and country names on the maps.

Lat/Long Lines

Pressing "L" or selecting this menu item toggles between showing or not showing latitude and longitude lines on the maps.

Actions

These selections control special features of GeoClock.

Where is
Distance
Scripts

Where is

GeoClock has a data base with about 4000 cities around the world. Using this dialog box, you can select any one and display the city on the best map containing that place, in addition to finding the current local time, sun rise, and sunset.

The radio boxes on the right control whether to display US or world cities, and whether to sort the cities by city name or country/state name. Pressing a letter key will advance the display to the first city (or country/state) starting with that letter. The selected city will be displayed in the box along with the current local time.

Selecting OK will display that city on the best map GeoClock has containing the city. Selecting Ignore will continue to display the current city. Selecting Cancel will restore the display of the primary city on that map.

Distance

Clicking on this menu item, or pressing D, starts a special two point distance measuring function. One point is fixed and the other is controlled by the mouse. Pressing a mouse button, or pressing ENTER, moves the first point to the current mouse position. At the bottom of the screen, the coordinates of both points, the distance between them, and the azimuths between them are displayed. To exit the distance function, click the reset menu item, or press ESCape.

Scripts

10 scripts can be played by GeoClock. Each script consists of GeoClock command lines (including a map selection command) and optionally a time (by default, 60 seconds). At the end of the specified interval, the next command line in the script is executed. Scripts can be edited and controlled from the Actions|Scripts... menu item.

One way to start a script is to press a number key (0 through 9). The corresponding script file is named GEOSCR0.DAT through GEOSRC9.DAT. Another way to invoke a script is to use the command SCRIPTx, where x is any number. The corresponding script file is GEOSCRx.DAT. If this command is on the command line in GECONFIG.DAT or in GEOCLOCK.INI, that script is executed as soon as GeoClock starts. If not, and if GEOSCR0.DAT exists, it is executed automatically when GeoClock is started. If the script encounters a REPEAT command, the script restarts at the beginning of the file. If the script encounters a HALT command, GeoClock immediately stops and returns to DOS. The script stops when the end of the script file is reached, or any key is pressed.

Example:

```
GEOSCR9.DAT contains:  
MAP1 LINE30 SHOWLL  
MAP2 LINE5  
RANDOM 30 NOLINE  
REPEAT
```

When 9 is pressed, MAP1 with LINE30 and SHOWLL is displayed for 15 seconds. then MAP2 with LINE5 is displayed for 15 seconds, then a randomly selected map is displayed for 30 seconds with NOLINE, and the sequence repeats.

Scripts can also be used as macro keys. For example, if GEOSCR1.DAT contains:
MAPP1

then when 1 is pressed, the next sequential map in map number sequence is displayed. If GEOSCR2.DAT contains:
T+0.0416666667

then when 2 is pressed, the current time is advanced by one hour (1/24 day).

Reset

Pressing "R" or selecting this menu item sets the GeoClock time to the current system time, and changes the update intervals to their default values, and sets the time passage to real time.

Advanced Topics

These topics cover a variety of technical aspects of GeoClock

[About Lat/Long](#)

[Configuring For Your Time Zone](#)

[About Sunrise and Sunset](#)

[About The Terminator](#)

[City Locations on Maps](#)

[Finding Your Latitude and Longitude](#)

[City Name Placement and Time Display](#)

[Ephemeris Data and Accuracy](#)

[Software structure](#)

[Map Generation System](#)

About Time Zones

Time zones are more complicated than most people think. To begin with, they change with longitude, so that the sun is approximately overhead at noon. However, various political decisions based on uniformity, local custom, and how to handle daylight saving time (or summer time), have made time zones very complex. There are a number of changes every year, and countries can and do change their time systems without warning.

Data for all known time zones (about 100, including permutations of daylight saving time) are distributed with GeoClock. They are included in the GEOZONES.DAT file.

To specify a time zone, several items are needed. First, how the time zone relates to the standard time zone must be defined. This zone is variously called Greenwich Mean Time (GMT) or Universal Time Coordinated (UTC) or Zulu Time (Z). US Eastern Standard Time is five hours behind (earlier than) GMT. Next, the dates and times when the zone changes to and from summer time must be defined. US Eastern Time goes to summer time on April 7, 1991 at 0700 GMT, and returns to standard time on October 27, 1991 at 0700 GMT. Finally, names for the time zone and the standard and summer times must be specified. As an example, US Eastern Time from April 1991 to April 1992 is specified by:

```
ZONE ET EST -5 EDT -4 91/04/07:7 91/10/27:7
```

ET is the name the time zone is referred to by all GeoClock commands. The definition states that the zone is called EST and is 5 hours behind GMT, except between 91/04/07 0700 GMT and 91/10/27 0700 GMT, when it is called EDT and is 4 hours behind GMT. A special time zone called ST gives true local sun time.

If the ZONE commands are not for the correct year, GeoClock will automatically update. This update is close but not always correct, and countries' summer time definitions can change. Therefore, I recommend that the ZONE commands be kept current. A GEOZONES.DAT file with current time zone data is available on the GeoClock Bulletin Board.

The PCZONE command sets the relationship between the local time on the PC's clock and GMT, i.e., declares which time zone the PC's clock is in. It takes one parameter - a time zone code, as defined in the ZONE command. For example, if you use Eastern Time, specify: PCZONE ET

This command is best used in the GECONFIG.DAT or GEOCLOCK.INI files.

About Lat/Long

Every point on the Earth's surface has an address. The first part of the address is the latitude, which is the distance north or south of the equator. The second part of the address is the longitude, which is the distance east or west of a line going from the north pole to the south pole through Greenwich, England (this is called the Greenwich meridian). Since the Earth is a sphere, these distances are expressed as angles.

There are several ways to express these angles. The first system was invented by the Babylonians about 5000 years ago. It divides angles into 360 degrees (°), each degree into 60 minutes ('), and each minute into 60 seconds ("). The Washington Monument is 38° 53' 21.5" north of the equator, and 77° 2' 8.0" west of the Greenwich meridian in this system. This location is accurate to about 60 feet, or 0.5 seconds. GeoClock can use this system. For example, the Washington Monument is at 38x53x21.5N 77x2x8.0W

A more modern system gives these same angles as decimal degrees. North latitudes and east longitudes are positive, while south and west are negative. GeoClock can use this system also. It is used for data files distributed with GeoClock. For example, the Washington Monument is at +38.8893 -77.0356

Configuring For Your Time Zone

GeoClock has a comprehensive system for handling all known time zones in the world. The GEOZONES.DAT file contains definitions of all time zones and daylight saving time systems identified to date. You can read or print this file for the complete list.

These definitions include the dates for switching between standard and summer time (for example, 91/04/07 and 91/10/27 for most of the U.S. in 1991), the common names for standard and summer time (for example, EST and EDT), and a codename to refer to the definition (for example, ET). Ordinarily, you should not need to change these definitions. Each time zone is preceded by the keyword ZONE.

To make sure that GeoClock gives the proper sun position, you must tell GeoClock what time zone your PC's clock uses. (For most users, this will be the time zone in which you live.) This is done by using Setup or editing GECONFIG.DAT or GEOCLOCK.INI and adding the proper PCZONE command. This command should be placed in the GECONFIG.DAT or GEOCLOCK.INI file. The format is:

```
PCZONE codename
```

where codename is the codename for the time zone, as listed in the ZONE commands. There should be no other characters on this line.

Some common codenames are:

ET	Eastern Standard/Daylight Time
EST	Eastern Standard Time all year (most of Indiana)
CT	Central Standard/Daylight Time
MT	Mountain Standard/Daylight Time
MST	Mountain Standard Time all year (Arizona)
PT	Pacific Standard/Daylight Time
AKT	Alaska
HST	Hawaii
UKT	United Kingdom, Ireland
+1A	Most of continental Europe
+2A	Eastern Europe
JST	Japan

The GEOSETUP program will prompt you for the time zone code (or supply it automatically if you live in a US zip code area) and place the time zone code in the GECONFIG.DAT or GEOCLOCK.INI files.

About Sunrise and Sunset

GeoClock calculates the sunrise and sunset times for your location. The times are usually within one minute of local newspaper data.

The precise moment of sunrise or sunset is difficult to determine. It depends not only on the position of the Earth and sun, but also on the terrain near you (it appears to rise later from behind a mountain than from the sea), and on the earth's atmosphere. Another complication is that the sun appears quite large, and takes about two minutes to shift position by its own diameter. All these factors together mean that even at sea level, the sun appears to just break above the horizon when it is in reality almost one degree BELOW the horizon.

By default, GeoClock uses the value of 0.833 degrees below the horizon to compute sunrise and sunset. This agrees well with observed times at moderate latitudes and flat terrain. The SUNANGLE parameter, which is the angle GeoClock uses for the sunrise and sunset calculations, can be adjusted to correspond to your local conditions.

About The Terminator

The terminator is the boundary between day and night. Its position changes during the day (it makes a complete circuit around the Earth in one day), and it also changes during the year. Daylight is longer in the northern hemisphere than in the southern hemisphere from about March 21 to September 21, and daylight is longer in the southern than in the northern hemisphere during the rest of the year. You can see the changes by using the time control features of GeoClock.

The terminator more or less divides the Earth into halves: facing the sun and facing away from the sun. Like sunrise and sunset times, the precise location of the terminator is hard to define. By default, GeoClock shows the optical terminator, which corresponds to visual sunrise and sunset. The SUNLIGHT command can be used to control the precise terminator position. If it is set to the same value as SUNANGLE, the terminator position will agree with sunrise and sunset.

GeoClock also shows the twilight terminator. By default, GeoClock uses -6° , which corresponds to the civil definition of twilight: the time when it is so dark that you must use your headlights. The TWILIGHT parameter is used to control the precise definition of this terminator.

City Locations on Maps

GeoClock has great flexibility in displaying cities on the maps. For most maps (e.g., MAP2) there is a corresponding text file (e.g., GEO2.DAT) that contains the customization information for that map. GEOCLOCK.DAT is used for MAP1, and any other map that does not have a corresponding GEO2.DAT file.

The first line of any GEO2.DAT file is the time zone codename that determines which time zone will be used for time display on that map. For example, ET indicates Eastern time, and CT indicates central time. (See "Configuring for Your Time Zone.") This should normally be the time zone codename for the first city listed (the second line of the file). This city is the "primary" city for the map. The rest of the lines in the file specify the names and locations of other cities to be displayed.

The format for display of a city is "Latitude Longitude Name". Either decimal degrees or degrees minutes seconds (DMS) may be used. In the decimal degree format, the minus sign (-) indicates south latitude (south of the equator) and west longitude (in the western hemisphere). For DMS format, separate entries by an "x", and place the direction indicator at the end. For example, 31 degrees 15 minutes west longitude would be 31x15W in DMS, and -31.25 in decimal, while 45 degrees 12 minutes 38 seconds north latitude would be 45x12x38N in DMS and 45.2106 in decimal. Some examples of these lines are:

```
34.00    -118.25  Los Angeles
30x3N    31x15E   Cairo
-26.17   28.03    Johannesburg
27x49N   85x21E   Katmandu Nepal
```

The first city listed in a file is the "primary" city. It is used for the astronomical calculations which are normally shown at the bottom of the map. The sunrise and sunset time, azimuth and elevation to the sun, local time, and the sun's sub point (the point on earth where the sun is directly overhead) can be displayed for this location.

Finding Your Latitude and Longitude

Accurate lat/long are essential for proper display of cities on a map, and also for accurate sunrise and sunset times of a map's "primary" city. An error of one degree of longitude changes sunrise and sunset by four minutes. The easiest way to find a particular latitude and longitude is to look it up in an atlas. The next easiest way is to call your local airport or weather bureau for the information. You can also leave a request for information on the GeoClock Bulletin Board, and you should get a reply in a short time.

City Name Placement and Time Display

For registered users only, additional control over city placement, color, size, and local time display is possible. All are marked by characters appearing after an exclamation point (!) on a city line in GEOn.DAT. This new data consists of an optional string of characters as follows:

- A - show city name Above mark
- B - show city name Below mark
- L - show city name Left of mark
- R - show city name Right of mark
- Y - show city name in color 5 (Yellow by default)
- E - show city name in 8x14 font
- M - show city name in 8x8 font (default)
- S - show city name in 4x8 font
- T - show city name in 4x6 font
- X - show city name in external font (see FONTLOAD command)
- number - show city name in color number (e.g., 6 shows city name in color 6). Color numbers are described in "Color Control."
- N - show a name without a mark. This is particularly useful if you want to name an area, such as the Pacific Ocean
- Z - indicates a country name rather than a city name
- O - display the last symbol defined (see SYMDEF) instead of the normal marker for the city.

After these optional codes, the line may be followed by a space and a time zone code. If included, this specifies that the local time for that city is to be displayed to the right of the city name. If a "*" is included, the name of the time zone will be displayed in addition to the time. THE SPACING OF THESE CHARACTERS IS CRITICAL. For example:

```

      ET
38.90  -77.02  Washington !E
42.65  -73.75  Albany !Y
35.08  -106.65  Albuquerque ! *MT
42.28  -83.75  Ann Arbor !A
33.75  -84.39  Atlanta !0
44.30  -69.76  Augusta
33.52  -86.81  Birmingham ! CT
46.80  -100.78  Bismarck !B6 *CT
```

In this example, Washington will be displayed in the 8x14 font, Albany will be displayed in yellow, Albuquerque will be followed by the local time and MST or MDT as appropriate, Ann Arbor will appear above the marker, Atlanta will be displayed in color 0 (red), Birmingham will appear follow by local (central) time but without a CST or CDT, and Bismarck will be displayed below the marker in color 6 (black) and followed by local time and CST or CDT.

Ephemeris Data and Accuracy

The ephemeris data in GeoClock is calculated using formulas from "Astronomical Formulae for Calculators" (Jean Meeus, Willmann-Bell Inc, Richmond VA). They were calibrated by comparing with data from "Interactive Computer Ephemeris" (ICE) (Nautical Almanac Office, Code FA, US Naval Observatory, Washington, DC 20392). For a period of 400 days including 1991, the maximum and RMS latitude errors are 0.0047383 and 0.0019377 degrees, while the maximum and RMS longitude errors are 0.0131104 and 0.0053660 degrees. This accuracy is approximately four times better than the method used in GeoClock 4.2 and earlier, and should provide better accuracy for past and future years.

The terminator is shown as the locations where the sun's center is a specified angle above the horizon, ignoring atmospheric effects. For 0 degrees, the sunrise occurs earlier and the sunset occurs later than the terminator indicates. The sun rise and sun set times are also computed as the times that the sun's center is a specified angle above or below the horizon. The default value, -0.8333, corresponds to the normal definition of sun rise and set (as printed in newspapers and almanacs), where the visible top edge of the sun just breaks the horizon.

Software structure

GeoClock for Windows is written entirely in 16-bit Delphi 1.0, with a very small amount on inline assembly for speed in some of the main loops. Much of the code was directly transported from the DOS version, and it took only 3 months from buying the compiler to the first working version of GeoClock for Windows. As a fourth generation language, it is hard to estimate the number of lines in a Delphi program, but there are about 1.3 million bytes in the source code, including the data structures that support the Windows, menus, and forms.

GeoClock for DOS is written entirely in Turbo Pascal version 7.0, except for the mouse interface routines and a few inline sections required for speed. It has approximately 19000 lines of source code. It uses 8 byte reals for most calculations, and thus relies on the 80x87 emulation package for systems without a math co-processor. It uses a custom graphics package which provides access to special hardware features (such as independent control of screen planes, fast fill, and preserving the graphics memory during text display) that are not available in the EGAVGA.BGI driver.

Map Generation System

The maps used for the GeoClock program were produced by a custom data base and software system. This system consists of a highly compressed vectorized map data base and a set of programs to convert the data into custom maps. The data bases are used. The primary data base is a PC conversion of World Data Bank II. It contains approximately 5.7 million vectors covering coastlines, islands, lakes, rivers, and similar geologic features, together with political boundary data. It covers the entire earth, and included features are accurate to approximately 600 meters. World Data Bank II was converted to this custom PC format by an ad hoc program which took advantage of specific features of both data bases. In its operational form, the PC data base uses approximately 0.84 bytes per vector, and in archival form takes approximately 0.5 bytes per vector. The data base is therefore easily stored and manipulated on an AT class PC.

A secondary data base is a PC conversion of 1979 1:2 Million Digital Line Graph data base from USGS. It includes highway and railroad data in addition to much more detailed physical and political features, and contains about 8.3 million vectors covering the 50 states, compressed to about 13 MB (1.6 bytes per record) on the PC.

A third data base is a PC conversion of the 1992 "Digital Chart of the World", made by digitizing 1:1 Million ONC charts (and some other paper sources). The extracted the data (highway, railroad, coastlines, islands, lakes, rivers, and streams) contains about 30 million vectors and compressed to about 50 MB on the PC.

A graphics tablet and several custom programs are used to add features than were not contained in the original data bases, for example, the borders of the countries of the former USSR.

Custom maps are generated by using two programs. The first, MAPGEN, reads the appropriate parts of the map data base and produces separation files of the required feature data as EGA, VGA, or 800x600 raster images. Rectangular, polar, orthoscopic, azimuthal-equidistant, and Lambert projections may be used in forming these separation files. Depending on complexity and scale, this process takes between 30 and 300 seconds on an AT with a co-processor. The second, MOVIE, allows the user to process the separation files to select the features and colors for the final map, including filling areas. This program also writes the map in a rasterized compressed format with headers and trailers so that it may be easily used as background data for other programs (for example, the GeoClock program).

Both these programs, and the converted data bases, are proprietary and not yet available to the general public. World Data Bank II is available from National Technical Information Center, Springfield, VA, for about \$1000 on 5 reels of tape. Both the 1:2,000,000 DLG data base (\$30 on one CD-ROM) and the Digital Chart of the World (\$200 on 4 CD-ROMs) are available from the US Geological Survey (Earth Science Information Center) in Reston VA.

Commands

GeoClock has a large number of commands which may be used to control the display. The most commonly used commands have been implemented in an Icon Bar, which is displayed at the top of the screen. A mouse device may be used to activate any of these commands simply by moving the mouse controlled cursor to the appropriate icon and clicking on it with the left mouse key. The commands consisting of a single letter (such as S) are activated by pressing that letter. The other commands (such as MAP) may be included in the configuration file, in a data file, on the GeoClock command line, or entered interactively by pressing the C (for Command) key while GeoClock is displaying a map.

The available commands are listed alphabetically below. (For a list by command type, see [Commands By Type](#)) More detailed information is available in other sections of Help.

<u>BLANK</u>	Sunlight highlighting is not used
<u>BORDERn</u>	Control window border
<u>CALL</u>	Specify initial call sign
<u>CITY</u>	Display city names
<u>CLINE</u>	Clear all specific latitude/longitude lines
<u>COLOR</u>	Set color (out of 64)
<u>COUNTRY</u>	Display country names
<u>Country/City</u>	Toggle between city and country display
<u>DARK</u>	No sunlight is displayed
<u>DATAFILE</u>	Select extension for data files
<u>DATECHANGEn</u>	Control display of next/previous date
<u>DRAWCIRCLE</u>	Draw circle on map
<u>DRAWFCIRCLE</u>	Draw a filled circle on map
<u>DRAWLINE</u>	Draw line on map
<u>DST</u>	Control Daylight Saving Time
<u>EPHEMERISdisp</u>	Control display of ephemeris data
<u>F</u>	Set rate of time passage
<u>FAST</u>	Use reduced accuracy but faster calculations
<u>FCOLOR</u>	Set map frame color
<u>FONTE</u>	Set default font to 8x14
<u>FONTM</u>	Set default font to 8x8
<u>FONTs</u>	Set default font to 4x8
<u>FONTT</u>	Set default font to 4x6
<u>FONTX</u>	Set default font to external font
<u>FONTLOAD</u>	Loads an external font
<u>FORCEMARK</u>	Always display location markers for cities
<u>FULL</u>	City, sun rise/set, local time, sun position legend
<u>GINCLUDE (or GI)</u>	Global include data file
<u>GLINC</u>	Set longitude line increment
<u>GLSPEC</u>	Specific longitude line
<u>GRID</u>	Display GeoClock Selected lat/long lines
<u>HALT</u>	Terminate script and return to Windows
<u>HAM</u>	Activate HAM features
<u>HAMCD</u>	Specify option HAM CDROM data base
<u>HAMDB</u>	Specify HAM data base maximum speed configuration
<u>HAMDBX</u>	Specify HAM data base minimum memory configuration
<u>HIDELL</u>	Do not show Latitude/Longitude values
<u>HTA</u>	Display specified city as primary city on all maps
<u>HTN</u>	Do not display specified city on any maps
<u>HTS</u>	Display specified city as primary city on local maps
<u>INCLUDE (or I)</u>	Include data file
<u>LIGHT</u>	All sunlight is displayed

<u>LINE</u>	Set lat/long line increment
<u>LINEPERM</u>	Make TLSPEC and GLSPEC lines permanent
<u>LLCOLOR</u>	Set color and style of lat/long lines and labels
<u>MAP</u>	Select MAP from list
<u>MAPCENTERn</u>	Center world map on longitude n
<u>MAPMINUSn</u>	Selects the previous sequential map using sort
<u>MAPPLUSn</u>	Selects the next sequential map using sort method n
<u>MAPn</u>	Changes to MAP number n
<u>MARK</u>	Display location markers for cities.
<u>MARKLIMIT</u>	Control display of cities close to HTA/HTS city
<u>MOONdisp</u>	Control display of moon
<u>NAUTICAL</u>	Display distances in nautical miles
<u>NOCITY</u>	Do not display city names
<u>NODAY</u>	Does not show display the day of the week
<u>NOGRID</u>	Do not display GeoClock selected lat/long lines
<u>NOHAM</u>	Deactivate HAM features
<u>NOHT</u>	Same as HTN
<u>NOLINE</u>	Do not display latitude/longitude lines
<u>NOMARK</u>	Do not display location markers
<u>NOMONTH</u>	Show month number rather than name
<u>NONE</u>	No legend
<u>NORMAL</u>	Normal Display
<u>NOSECONDS</u>	Shows time to last minute
<u>PALETTE</u>	Specify Windows color
<u>PCZONE</u>	Specify PC time zone
<u>Quit</u>	Terminate GeoClock
<u>REM</u>	Remark remainder of line is ignored
<u>REPEAT</u>	Start script over from first line
<u>RESIZEn</u>	Control window resizing
<u>SCRIPT</u>	Invoke a specific script
<u>SHOWDAY</u>	Show day of week
<u>SHOWLL</u>	Show Latitude/Longitude values
<u>SHOWMONTH</u>	Show month name rather than number
<u>SHOWSECONDS</u>	Show time to nearest second
<u>SLOW</u>	Use high accuracy but slower calculations
<u>STATUTE</u>	Display distances in statute miles
<u>SUN</u>	City, sun rise/set, local time legend
<u>SUNANGLE</u>	Sun rise/set definition
<u>SUNLIGHT</u>	Terminator definition
<u>SYMBOL</u>	Displays an external symbol
<u>SYMDEF</u>	Load an external symbol definition
<u>SIZE</u>	Control size state of window
<u>T</u>	Set new time
<u>TEXT</u>	Display text on all maps
<u>TEXTBG</u>	Set text background color
<u>TIME</u>	Local time only legend
<u>TLINC</u>	Set latitude line increment
<u>TLMASK</u>	Twilight area pattern
<u>TLSPEC</u>	Specific latitude line
<u>TWILIGHT</u>	Twilight terminator definition
<u>UWIN</u>	Set update times
<u>VECTOR (or V)</u>	Continue a line
<u>WINDOW</u>	Set window size and position
<u>WINSET</u>	specifies that the GeoClock program has been initialized
<u>YEAR2</u>	Show 2 digit year

YEAR4

ZONE

ZOOMFRACT

Show 4 digit year

Define time zone

Set screen active area for zoom

Commands By Type

Sun and Moon Display

<u>BLANK</u>	Sunlight highlighting is not used
<u>DARK</u>	No sunlight is displayed
<u>LIGHT</u>	All sunlight is displayed
<u>MOONdisp</u>	Control display of moon
<u>NORMAL</u>	Normal Display
<u>SUNANGLE</u>	Sun rise/set definition
<u>SUNLIGHT</u>	Terminator definition
<u>TLMASK</u>	Twilight area pattern
<u>TWILIGHT</u>	Twilight terminator definition

Windows controls

<u>BORDERn</u>	Control window border
<u>RESIZEn</u>	Control window resizing
<u>SIZE</u>	Control size state of window
<u>WINDOW</u>	Set window size and position
<u>WINSET</u>	specifies that the GeoClock program has been initialized

HAM radio

<u>CALL</u>	Specify initial call sign
<u>HAM</u>	Activate HAM features
<u>HAMCD</u>	Specify option HAM CDROM data base
<u>HAMDB</u>	Specify HAM data base maximum speed configuration
<u>HAMDBX</u>	Specify HAM data base minimum memory configuration
<u>NOHAM</u>	Deactivate HAM features

Map Annotation

<u>CITY</u>	Display city names
<u>COUNTRY</u>	Display country names
<u>Country/City</u>	Toggle between city and country display
<u>DATAFILE</u>	Select extension for data files
<u>FORCEMARK</u>	Always display location markers for cities
<u>GINCLUDE (or GI)</u>	Global include data file
<u>HTA</u>	Display specified city as primary city on all maps
<u>HTN</u>	Do not display specified city on any maps
<u>HTS</u>	Display specified city as primary city on local maps
<u>INCLUDE (or I)</u>	Include data file
<u>MARK</u>	Display location markers for cities.
<u>MARKLIMIT</u>	Control display of cities close to HTA/HTS city
<u>NOCITY</u>	Do not display city names
<u>NOHT</u>	Same as HTN
<u>NOMARK</u>	Do not display location markers

Lat/Long lines

<u>CLINE</u>	Clear all specific latitude/longitude lines
<u>GLINC</u>	Set longitude line increment
<u>GLSPEC</u>	Specific longitude line
<u>GRID</u>	Display GeoClock Selected lat/long lines
<u>HIDELL</u>	Do not show Latitude/Longitude values
<u>LINE</u>	Set lat/long line increment
<u>LINEPERM</u>	Make TLSPEC and GLSPEC lines permanent
<u>NOGRID</u>	Do not display GeoClock selected lat/long lines
<u>NOLINE</u>	Do not display latitude/longitude lines

<u>SHOWLL</u>	Show Latitude/Longitude values
<u>TLINC</u>	Set latitude line increment
<u>TLSPEC</u>	Specific latitude line
Screen Display	
<u>COLOR</u>	Set color (out of 64)
<u>FCOLOR</u>	Set map frame color
<u>LLCOLOR</u>	Set color and style of lat/long lines and labels
<u>PALETTE</u>	Specify Windows color
<u>TEXTBG</u>	Set text background color
Time Display	
<u>DATECHANGEn</u>	Control display of next/previous date
<u>DST</u>	Control Daylight Saving Time
<u>F</u>	Set rate of time passage
<u>NODAY</u>	Does not show display the day of the week
<u>NOMONTH</u>	Show month number rather than name
<u>NOSECONDS</u>	Shows time to last minute
<u>PCZONE</u>	Specify PC time zone
<u>SHOWDAY</u>	Show day of week
<u>SHOWMONTH</u>	Show month name rather than number
<u>SHOWSECONDS</u>	Show time to nearest second
<u>T</u>	Set new time
<u>YEAR2</u>	Show 2 digit year
<u>YEAR4</u>	Show 4 digit year
<u>ZONE</u>	Define time zone
Drawing	
<u>DRAWCIRCLE</u>	Draw circle on map
<u>DRAWFCIRCLE</u>	Draw a filled circle on map
<u>DRAWLINE</u>	Draw line on mapn
<u>SYMBOL</u>	Displays an external symbol
<u>SYMDEF</u>	Load an external symbol definition
<u>TEXT</u>	Display text on all maps
<u>VECTOR (or V)</u>	Continue a line
System Control	
<u>FAST</u>	Use reduced accuracy but faster calculations
<u>NAUTICAL</u>	Display distances in nautical miles
<u>Quit</u>	Terminate GeoClock
<u>REM</u>	Remark remainder of line is ignored
<u>SLOW</u>	Use high accuracy but slower calculations
<u>STATUTE</u>	Display distances in statute miles
<u>UWIN</u>	Set update times
<u>ZOOMFRACT</u>	Set screen active area for zoom
Fonts	
<u>FONTE</u>	Set default font to 8x14
<u>FONTM</u>	Set default font to 8x8
<u>FONTS</u>	Set default font to 4x8
<u>FONTI</u>	Set default font to 4x6
<u>FONTX</u>	Set default font to external font
<u>FONTLOAD</u>	Loads an external font
Legend	
<u>FULL</u>	City, sun rise/set, local time, sun position legend

<u>NONE</u>	No legend
<u>SUN</u>	City, sun rise/set, local time legend
<u>TIME</u>	Local time only legend
Scripts	
<u>HALT</u>	Terminate script and return to Windows
<u>REPEAT</u>	Start script over from first line
<u>SCRIPT</u>	Invoke a specific script
Map Selection	
<u>MAP</u>	Select MAP from list
<u>MAPCENTERn</u>	Center world map on longitude n
<u>MAPMINUSn</u>	Selects the previous sequential map using sort
<u>MAPPLUSn</u>	Selects the next sequential map using sort method n
<u>MAPn</u>	Changes to MAP number n

Sun and Moon Display Commands

<u>BLANK</u>	Sunlight highlighting is not used
<u>DARK</u>	No sunlight is displayed
<u>LIGHT</u>	All sunlight is displayed
<u>MOONdisp</u>	Control display of moon
<u>NORMAL</u>	Normal Display
<u>SUNANGLE</u>	Sun rise/set definition
<u>SUNLIGHT</u>	Terminator definition
<u>TLMASK</u>	Twilight area pattern
<u>TWILIGHT</u>	Twilight terminator definition

Windows controls Commands

<u>BORDERn</u>	Control window border
<u>RESIZEn</u>	Control window resizing
<u>SIZE</u>	Control size state of window
<u>WINDOW</u>	Set window size and position
<u>WINSET</u>	specifies that the GeoClock program has been initialized

HAM radio Commands

<u>CALL</u>	Specify initial call sign
<u>HAM</u>	Activate HAM features
<u>HAMCD</u>	Specify option HAM CDROM data base
<u>HAMDB</u>	Specify HAM data base maximum speed configuration
<u>HAMDBX</u>	Specify HAM data base minimum memory configuration
<u>NOHAM</u>	Deactivate HAM features

Map Annotation Commands

<u>CITY</u>	Display city names
<u>COUNTRY</u>	Display country names
<u>Country/City</u>	Toggle between city and country display
<u>DATAFILE</u>	Select extension for data files
<u>FORCEMARK</u>	Always display location markers for cities
<u>GINCLUDE (or GI)</u>	Global include data file
<u>HTA</u>	Display specified city as primary city on all maps
<u>HTN</u>	Do not display specified city on any maps
<u>HTS</u>	Display specified city as primary city on local maps
<u>INCLUDE (or I)</u>	Include data file
<u>MARK</u>	Display location markers for cities.
<u>MARKLIMIT</u>	Control display of cities close to HTA/HTS city
<u>NOCITY</u>	Do not display city names
<u>NOHT</u>	Same as HTN
<u>NOMARK</u>	Do not display location markers

Lat/Long lines Commands

<u>CLINE</u>	Clear all specific latitude/longitude lines
<u>GLINC</u>	Set longitude line increment
<u>GLSPEC</u>	Specific longitude line
<u>GRID</u>	Display GeoClock Selected lat/long lines
<u>HIDELL</u>	Do not show Latitude/Longitude values
<u>LINE</u>	Set lat/long line increment
<u>LINEPERM</u>	Make TLSPEC and GLSPEC lines permanent
<u>NOGRID</u>	Do not display GeoClock selected lat/long lines
<u>NOLINE</u>	Do not display latitude/longitude lines
<u>SHOWLL</u>	Show Latitude/Longitude values
<u>TLINC</u>	Set latitude line increment
<u>TLSPEC</u>	Specific latitude line

Screen Display Commands

<u>COLOR</u>	Set color (out of 64)
<u>FCOLOR</u>	Set map frame color
<u>LLCOLOR</u>	Set color and style of lat/long lines and labels
<u>PALETTE</u>	Specify Windows color
<u>TEXTBG</u>	Set text background color

Time Display Commands

<u>DATECHANGE</u> n	Control display of next/previous date
<u>DST</u>	Control Daylight Saving Time
<u>F</u>	Set rate of time passage
<u>NODAY</u>	Does not show display the day of the week
<u>NOMONTH</u>	Show month number rather than name
<u>NOSECONDS</u>	Shows time to last minute
<u>PCZONE</u>	Specify PC time zone
<u>SHOWDAY</u>	Show day of week
<u>SHOWMONTH</u>	Show month name rather than number
<u>SHOWSECONDS</u>	Show time to nearest second
<u>T</u>	Set new time
<u>YEAR2</u>	Show 2 digit year
<u>YEAR4</u>	Show 4 digit year
<u>ZONE</u>	Define time zone

Drawing Commands

<u>DRAWCIRCLE</u>	Draw circle on map
<u>DRAWFCIRCLE</u>	Draw a filled circle on map
<u>DRAWLINE</u>	Draw line on mapn
<u>SYMBOL</u>	Displays an external symbol
<u>SYMDEF</u>	Load an external symbol definition
<u>TEXT</u>	Display text on all maps
<u>VECTOR (or V)</u>	Continue a line

System Control Commands

<u>FAST</u>	Use reduced accuracy but faster calculations
<u>NAUTICAL</u>	Display distances in nautical miles
<u>Quit</u>	Terminate GeoClock
<u>REM</u>	Remark remainder of line is ignored
<u>SLOW</u>	Use high accuracy but slower calculations
<u>STATUTE</u>	Display distances in statute miles
<u>UWIN</u>	Set update times
<u>ZOOMFRACT</u>	Set screen active area for zoom

Fonts Commands

<u>FONTE</u>	Set default font to 8x14
<u>FONTM</u>	Set default font to 8x8
<u>FONTS</u>	Set default font to 4x8
<u>FONTI</u>	Set default font to 4x6
<u>FONTX</u>	Set default font to external font
<u>FONTLOAD</u>	Loads an external font

Legend Commands

<u>FULL</u>	City, sun rise/set, local time, sun position legend
<u>NONE</u>	No legend
<u>SUN</u>	City, sun rise/set, local time legend
<u>TIME</u>	Local time only legend

Scripts Commands

<u>HALT</u>	Terminate script and return to Windows
<u>REPEAT</u>	Start script over from first line
<u>SCRIPT</u>	Invoke a specific script

Map Selection Commands

<u>MAP</u>	Select MAP from list
<u>MAPCENTERn</u>	Center world map on longitude n
<u>MAPMINUSn</u>	Selects the previous sequential map using sort
<u>MAPPLUSn</u>	Selects the next sequential map using sort method n
<u>MAPn</u>	Changes to MAP number n

BLANK

See [Sun and Moon Display Commands](#)

BLANK Highlighting is not used
This does not perform any highlighting. This is appropriate for some specialized maps
which use more than 7 colors.

Border

See [Windows controls Commands](#)

BORDERn Control border

BORDER1 causes all window borders to be hidden, including all four border lines, the top menu, the title bar, and the system control items such as the minimize, maximize, and system control menu.

BORDER0 displays all these items.

CALL

See [HAM radio Commands](#)

CALL Specify initial call sign

This command allows the initial call sign, when a HAM map is brought up, to be specified. For example, GEOCLK MAP9009 CALL=K3NA will cause the HAM package to be activated with K3NA data displayed. The last displayed call sign will be displayed after switching away from and then back to a HAM map.

CITY

See [Map Annotation Commands](#)

CITY Display city names. The city names and locations are contained in the corresponding GEO*.DAT file. The name is usually displayed to the right of the location, but the name may be moved if it does not fit. The location can be controlled by the user, and local time can be added (see Advanced Topics).

CLINE

See [Lat/Long lines Commands](#)

CLINE Clear all specific latitude/longitude lines

CLINE removes all non-permanent special lines from the display. CLINE1 removes all line including permanent lines.

COLOR

See [Screen Display Commands](#)

COLOR Set color

The COLOR command provides a way to change the GeoClock default colors. The format is:
COLORnddb

where n is the feature number (0-7), dd is the color value for the non-sunlit feature, and bb is the color value for the sunlit feature (n+8). The easiest way to get the proper values is to use the CSET menu. The proper COLOR commands to produce the colors as modified by CSET are given on the right hand side of the CSET menu. For example, for the color values given in the CSET example, the command is COLOR22062.

COUNTRY

See [Map Annotation Commands](#)

COUNTRY Display country names

Supporting the above capability is a control character used after the ! in GEO entries: Z. Any city (or entry in the GEO.DAT file) with a !Z is not displayed unless the COUNTRY command has been given. CITY reverts back to normal display, and cities with the !Z are not displayed. In the data files included, this capability is used to toggle between normal display of cities and times, and display of country names.

Country/City

See [Map Annotation Commands](#)

Country/City Toggle between city and country display
Selecting this menu item, or pressing Y, toggles between display of city names and country names.

DARK

See [Sun and Moon Display Commands](#)

DARK No sunlight is displayed
This does not highlight any of the screen, and does not display the sun symbol.

DATAFILE

See [Map Annotation Commands](#)

DATAFILE Select extension for data files

This command sets the extension to be used for GEOn files. By default, it is DAT (the previous default). This allows multiple sets of GEOn files to be used with the maps. If the extension does not exist, then DAT is used. For example, DATAFILE XYZ would first check GEOn.XYZ, and if it does not exist, then check GEOn.DAT, and if that did not exist, check GEOCLOCK.DAT.

DATECHANGEn

See [Time Display Commands](#)

DATECHANGEn Control display of next/previous date

If n is 0, the date is not indicated. If n is 1, the local time shows a ":" if the local date is the same as the current date, it shows an up-arrow if the local date is one day ahead of the current date, and it shows a down-arrow if the local date is one day behind the current date.

DRAWCIRCLE

See [Drawing Commands](#)

DRAWCIRCLE Draw circle on map

DRAWCIRCLE latcenter longcenter latrad longrad color draws an ellipse centered at (latcenter, longcenter) and with latitude (vertical) radius latrad and with longitude (horizontal) radius longrad, and with color. The command operates ONLY when contained in a GEOn.DAT file that is processed for the map. Color is the color in which the line will be drawn. If omitted, color defaults to 5, which is displayed as yellow. Example:

```
DRAWCIRCLE 38.9 -77.0 10 20 6
```

draws an oval centered on Washington DC that is 10 degrees from the center to the northernmost point, and 20 degrees from the center to the easternmost point, and in color 6. Alternatively, the form: DRAWCIRCLE latcenter longcenter -radius 0 color can be used. This draws a circle of the specified radius (in kilometers) in the specified color around the specified center point. For example:

```
DRAWCIRCLE 38.9 -77.0 -100 0 6
```

draws a 100 km circle in color 6 around Washington DC. The negative sign in front of the radius, and the 0 after the radius, are required to ensure compatibility with the older system.

DRAWFCIRCLE

See [Drawing Commands](#)

DRAWFCIRCLE Draw a filled circle on map

DRAWFCIRCLE has the same syntax as DRAWCIRCLE, except that the circle or ellipse drawn is solid rather than outlined.

DRAWLINE

See [Drawing Commands](#)

DRAWLINE Draw line on map

DRAWLINE lat1 long1 lat2 long2 color draws a line between (lat1, long1) and (lat2, long2) on the current map. Color is the color in which the line will be drawn. See "Color Control" for an explanation of the use of color. If omitted, color defaults to 5 (yellow). Example:

```
DRAWLINE 38.9 -77.0 34.0 -118.3 0
```

draws a line between Washington DC and Los Angeles in color 0. The DRAWLINE command cannot be issued from the Command level. It operates ONLY when contained in a GEO*.DAT file that is processed for the map, or in a text file that is appended to a map with the INCLUDE command.

DST

See [Time Display Commands](#)

DST Control Daylight Saving Time

The method GeoClock uses to handle summer time when current data is not available in GECONFIG.DAT or GEOCLOCK.INI is close, but not perfect. This command specifies for which years the GeoClock computed correction is to be applied. By default, GeoClock does not use summer time before 1980. DST is used to change this date. The syntax is:

DST year1 year2

Year1 is the earliest year in which to use summer time under the current specification, and year2 is the latest year in which to use summer time. If year2 is omitted, there is no upper limit. For example, DST 1950 specifies that summer time is to be used from 1950 on, while DST 1985 1995 specifies that summer time is to be used only between 1985 and 1995.

EPHEMERISdisp

See [System Control Commands](#)

EPHEMERISdisp Control display of ephemeris data with the Distance function. If disp is 0 or omitted, only coordinates and distances are displayed with the distance function. If disp is 1, the current local time and time zone are displayed, along with the sun rise, sun set, sun azimuth, and sun elevation, for the selected point.

F

See [Time Display Commands](#)

Fn makes the rate of time passage n hours per iteration. It is the equivalent of the rate of time item in the time control menu, but can be used in scripts and from the command line.

FAST

See [System Control Commands](#)

FAST Use reduced accuracy but faster calculations
Forces GeoClock to use a faster but slightly less accurate algorithm for drawing the sunlit area. This is the default for systems without an 80x87.

FCOLOR

See [Screen Display Commands](#)

FCOLOR Set map frame color

FCOLORn sets the color of the frame around the map display to n. The default value is 15 (white). A value of 0 through 15 frames the map in that color. Any other value (for example, -1) does not display any frame.

FONT_E

See [Fonts Commands](#)

FONT-E Set default font to 8x14. This font size is used for city and time display on the maps unless it is overridden by an !E, M, S, or T on the corresponding line in GEO*.DAT.

FONT_M

See [Fonts Commands](#)

FONT-M * Set default font to 8x8

FONT_S

See [Fonts Commands](#)

FONT-S Set default font to 4x8

FONT_T

See [Fonts Commands](#)

FONT-T Set default font to 4x6

FONT_X

See [Fonts Commands](#)

FONT-X Set default font to external font

FONTLOAD

See [Fonts Commands](#)

FONTLOAD Loads an external font

FONTLOAD filename loads the external font specified by <filename> The format of the external font file is:

Byte 0 horizontal character width in bits (w)

Byte 1 vertical character height in bits (h)

Byte 2 first character in table (c1)

Byte 3 last character in table (c2)

Bytes 4 through $4+(c2-c1+1)*h*\text{entier}((w+7)/8)$ character bits If the requested character is not in the c1..c2 range, the character is displayed as c1.

FORCEMARK

See [Map Annotation Commands](#)

FORCEMARK Always display location markers for cities, regardless of the presence of the "N" flag.

FULL

See [Legend Commands](#)

FULL * City, sun rise/set, local time, sun position legend GeoClock can display a time legend at the bottom of the screen. FULL displays the full range of time and sun-related information on the legend. This includes primary city name, its time and date, including local time zone name, and sunrise and sunset time. (The time zone is the one specified in the corresponding GEO*.DAT file.) It shows sunrise and sunset times for the primary city, the sun's subpoint coordinates, and the azimuth and elevation of the sun from the primary city. The format of the time and date can be controlled with other commands (see "Time, Zone, and Format Control").

GINCLUDE

See [Map Annotation Commands](#)

GINCLUDE (or GI) Global include data file

The command works the same as include above, except that the file is included on all maps. Ordinarily, the GINCLUDE command would be in GECONFIG.DAT file, but it can be on the command line (using the @ character) or in response to P or C. The command is canceled by GINCLUDE or GI with no file name specified. If both GI and I are active on the same map, both files will be processed.

GLINC

See [Lat/Long lines Commands](#)

GLINC Set longitude line increment

TLINC and GLINC allow the spacing between latitude and longitude lines to be set independently. For example, TLINC 15 and GLINC 30 set the latitude spacing to 15 degrees, and the longitude spacing to 30 degrees.

GLSPEC

See [Lat/Long lines Commands](#)

GLSPEC Specific longitude line

TLSPEC and GLSPEC allow specific latitude and longitude lines to be displayed. For example, TLSPEC -67 draws a latitude line at 67 degrees south (the Antarctic circle). Up to 20 of these special lines can be specified.

GRID

See [Lat/Long lines Commands](#)

GRID Display GeoClock Selected lat/long lines

This command overrides all the other Lat/Long commands and display GeoClock selected lines. It is equivalent to LINE, TLINCx, GLINCy, and SHOWLL, where x and y are selected by GeoClock on a map by map basis.

HALT

See [Scripts Commands](#)

HALT Terminate script and return to DOS

HAM

See [HAM radio Commands](#)

HAM Activate HAM features

This command activates the HAM features on azimuthal-equidistance maps. A good place for this command is in the GEOn.DAT file corresponding to your HAM map.

HAMCD

See [HAM radio Commands](#)

HAMCD Specify option HAM CD-ROM data base
HAMCD file specifies that the BuckMaster HamCall CD-ROM is loaded and should be used to obtain extra information about US call signs. If the file parameter is missing, all online local CD-ROM drives will be checked for the data base. This will almost always correctly identify the CD, but you may specify the complete path to the data base (for example, HAMCD D:\HAM0\HAMCALL.129) if GeoClock cannot automatically locate this data base. When a call sign is parsed, the CD will be checked first. If the call is not found, the GeoClock HAM data base (see below) will be used.

HAMDB

See [HAM radio Commands](#)

HAMDB Specify HAM data base - maximum speed configuration HAMDB file loads the HAM call sign data base from file the named file. Only the first occurrence of this command in a GeoClock execution is effective (i.e., the data base will not be reloaded or changed). A good place for this command is in the GEOn.DAT file corresponding to your HAM map. The HAM data base and other required files are an extra cost option in GeoClock.

HAMDBX

See [HAM radio Commands](#)

HAMDBX Specify HAM data base - minimum memory configuration HAMDBX file specifies the file with the HAM data base. Whenever a call sign needs to be analyzed, the data base is loaded into temporary memory, and the memory is released after analysis. This slows the analysis slightly, but requires about 60Kb less RAM. If you are shelling to GeoClock from another program and get Error 203 messages when you use the HAM features, placing this command in GECONFIG.DAT may solve the problem.

HIDELL

See [Lat/Long lines Commands](#)

HIDELL * Do not show Latitude/Longitude values

HTA

See [Map Annotation Commands](#)

HTA Display specified city as primary city on all maps
HTA/Lat/Long/ZoneCode/CityName forces the specified city to be the primary city on all maps. HTA with no home town specified forces the display of a previously specified home town. It overrides the first and second lines in every GOn.DAT file, and thus is a shortcut method to configure GeoClock for your city. For example, HTA/38.90/-77.03/ET/Washington forces Washington to be the primary city on all maps, and displays ET (Eastern Time) for all ephemeris data. HTA is an acronym from Home Town Always.

HTN

See [Map Annotation Commands](#)

HTN Do not display specified city as primary city on any maps

HTN/Lat/Long/ZoneCode/CityName forces the specified city to be the primary city on all maps, but prevents it from being displayed as the primary city. HTN with no parameters does not change any previously defined city, but does prevent it from being displayed. HTN is an acronym from Home Town Never.

HTS

See [Map Annotation Commands](#)

HTS Display specified city as primary city on maps containing it
HTS/Lat/Long/ZoneCode/CityName It works identically to HTA, except that it uses the
specified city only if the city appears on the map. HTS with no parameters use a previously
defined home town, but display it only if the city appears on the maps. For example,
HTS/38.90/-77.03/ET/Washington would force Washington to be the primary city on MAP2
(US - 48 States), but not on MAP5 (Europe). HTS is an acronym for Home Town Showing.

INCLUDE

See [Map Annotation Commands](#)

INCLUDE (or I) Include data file

When contained in a GEOn.DAT file, INCLUDE <file> suspends reading from the file being processed, and processes all commands in the <file>. When all commands in that file have been processed, reading resumes from the original file. INCLUDE may be nested up to ten levels. INCLUDE may also be used in response to the "P" command. In this case, the named file will be included at the end of the GEOn.DAT file for the map currently displayed. The effect of the INCLUDE command will be negated when a new map is selected or a new file is specified with INCLUDE. The INCLUDE command can be abbreviated by I (i.e., I DATELINE). An include file can be set on the command line or in a script by using the @ character as a separator (e.g., GEOCLK MAP1 I@dateline). This syntax is not allowed in data files or in response to P or C.

LIGHT

See [Sun and Moon Display Commands](#)

LIGHT All sunlight is displayed
This highlights the entire screen, and does not display the sun symbol. This often provides a better display of details of small-area maps, on which terminator display may be unimportant, e.g., city maps.

LINE

See [Lat/Long lines Commands](#)

LINE Set lat/long line increment and display lines This command enables latitude and longitude lines on the display, and sets the spacing between the lines. For example, LINE15 draws latitude and longitude 15 degrees apart.

LINEPERM

See [Lat/Long lines Commands](#)

LINEPERM Make TLSPEC and GLSPEC lines permanent
LINEPERM makes all currently defined TLSPEC and GLSPEC lines permanent, i.e., they will be displayed on all maps. If TLSPEC and GLSPEC commands are followed by LINEPERM in GECONFIG.DAT, these lines will be permanent. A similar sequence in a GEON.DAT file will make these lines permanent. CLINE1 clear all permanent lines.

LLCOLOR

See [Screen Display Commands](#)

LLCOLOR Set color and style of lat/long lines and labels This command takes two parameters **LLCOLOR a/b.** a is the color number for the lat/long lines (the default is 6). b is the color number for the lat/long line labels (the default value is 7). If a is negative, the lines will overwrite all map features, while if a is positive it will only overwrite colors 1, 2, 3 (water, land, and land/water).

MAP

See [Map Selection Commands](#)

MAP Select MAP from list

This command works identically to F. If it is included on the GeoClock command line (for example, GEOCLK MAP), the selection menu will appear before the program starts.

MAPCENTERn

See [Map Selection Commands](#)

MAPCENTERn Center world map on longitude n

Centers any rectangular projection world map on longitude n (more or less). For example, MAPCENTER-77 centers the world map on Washington. It does not have any effect on non-rectangular projection or non-world maps. Like FCOLOR, this command does not take effect immediately if used in the GEOn.DAT files (except GEOCLOCK.DAT) or scripts, but does work correctly in GECONFIG.DAT, the command line, and "P".

MAPMINUSn

See [Map Selection Commands](#)

MAPMINUSn Selects the previous sequential map using sort method n. This command chooses the previous sequential map using the sort method described in MAPPLUSn.

MAPPLUSn

See [Map Selection Commands](#)

MAPPLUSn Selects the next sequential map using sort method n. This command chooses the next map in sequence. If n is 1, it chooses the next high map number. If n is 2, it chooses the next map in alphabetical order. If n is some other number, it chooses the next map in coverage area. If n is missing, it uses the method last selected in the "M"aplist or "F"indMap function.

MAPn

See [Map Selection Commands](#)

MAPn Changes to MAP number n

This command displays a specific map. For example, MAP5 displays map number 5. If this command is included in GECONFIG.DAT or GEOCLOCK.INI, the map specified will appear as the first map displayed.

MARK

See [Map Annotation Commands](#)

MARK Display location markers for cities.

MARKLIMIT

See [Map Annotation Commands](#)

MARKLIMIT Control display of cities close to HTA/HTS city This sets the minimum distance from the home town city that a city must be to be displayed. For example, MARKLIMIT5 means that any mark within 5 pixels x and y of the home town mark will not be displayed. The distances can be set independently, e.g., MARLIMIT5/10 means x of 5 and y of 10. The default is -1, or no restriction.

MOONdisp

See [Sun and Moon Display Commands](#)

MOONdisp Control display of moon

If disp is 0 or omitted, no moon is displayed. If disp is 1, a moon symbol is displayed with approximate phase information over the correct sub-point. If disp is 2, the text moon illumination fraction is displayed with the moon symbol. If disp is 3, the symbol, illumination, lat, long, azimuth, and elevation are all displayed. If disp is increased by 4, the moon is displayed using the calendar convention (i.e., the moon looks like the symbol in printed calendars). For example, if disp is 6, the moon symbol is displayed using the calendar convention, and the moon illumination fraction is displayed in text.

NAUTICAL

See [System Control Commands](#)

NAUTICAL Display distances in nautical miles

NOCITY

See [Map Annotation Commands](#)

NOCITY * Do not display city names

NODAY

See [Time Display Commands](#)

NODAY * Does not show display the day of the week.

NOGRID

See [Lat/Long lines Commands](#)

NOGRID * Do not display GeoClock Selected lat/long lines. This command negates the GRID command.

NOHAM

See [HAM radio Commands](#)

NOHAM Deactivate HAM features

NOHT

See [Map Annotation Commands](#)

NOHT (same as HTN) Do not display specified city as primary city on any maps
HTN/Lat/Long/ZoneCode/CityName forces the specified city to be the primary city on all maps, but prevents it from being displayed as the primary city. HTN with no parameters does not change any previously defined city, but does prevent it from being displayed. HTN is an acronym from Home Town Never.

NOLINE

See [Lat/Long lines Commands](#)

NOLINE * Do not display latitude/longitude lines
NOLINE removes all latitude/longitude lines from the display.

NOMARK

See [Map Annotation Commands](#)

NOMARK * Do not display location markers.

NOMONTH

See [Time Display Commands](#)

NOMONTH * Show month number rather than name.

NONE

See Legend Commands

NONE No legend

NORMAL

See [Sun and Moon Display](#)

NORMAL * Normal Display

This highlights the sunlit area and displays the sun symbol at the sun's subpoint.

NOSECONDS

See [Time Display Commands](#)

NOSECONDS Shows time to last minute
This command shows time to the last minute (1991/05/01 12:14)

Palette

See [Screen Display Commands](#)

`PALe/r/g/b` sets the RGB value for a GeoClock color. `e` is the palette position (corresponding to the DOS version), `r` is the red value (0-255), `g` is the green value, and `b` is the blue value. For example `PAL2/128/64/0` sets position 2 (dark land) to red=128, green=64, blue=0 (dark brown).

Default colors in GeoClock are as follows:

palette posit	color	use
-----	-----	-----
0	red	Political Bdy (dark)
1	blue	Water (dark)
2	dark green	Land (dark)
3	green	Land/Water Bdy (dark)
4	black	Text Background (dark)
5	yellow	Aux Text Color (dark)
6	black	Lat/Long Lines (dark)
7	white	Frame and Text
8	bright red	Political Bdy (sunlit)
9	light blue	Water (sunlit)
10	green	Land (sunlit)
11	light green	Land/Water Bdy (sunlit)
12	black	Text Background (sunlit)
13	yellow	Aux Text and Sun (sunlit)
14	black	Lat/Long Lines (sunlit)
15	white	Frame and Text

The EGA graphics adapter provides for the simultaneous display of 16 colors from a palette of 64. The VGA graphics adapter provides for the simultaneous display of 16 colors from a palette of 262144. Most programs use the default palette, which roughly corresponds to the colors provided by the CGA in text mode. In order to make the map display the most attractive, the EGA/VGA/SVGA version of GeoClock for DOS does not use this standard palette. Instead, the 16 colors that can be displayed simultaneously are used to represent 16 features displayed by GeoClock. The first eight numbers are for features not in sunlight, and the second eight are for features that are in sunlight.

In Windows systems supporting at least 256 colors, GeoClock for Windows can use the full palette. In 16 color systems (VGA), GeoClock does not have access to all available colors and the display will be somewhat less pleasing.

PCZONE

See [Time Display Commands](#)

PCZONE Specify PC time zone

The PCZONE command sets the relationship between the local time on the PC's clock and GMT, i.e., declares which time zone the PC's clock is in. It takes one parameter - a time zone code, as defined in the ZONE command. For example, if you use Eastern Time, specify:

```
PCZONE ET
```

This command is best used in the GECONFIG.DAT or GEOCLOCK.INI files, and it must follow the ZONE command that it references.

Quit

See [System Control Commands](#)

Quit Quit GeoClock and return to Windows

Selecting this menu item, or pressing ESCape twice terminates GeoClock and closes all GeoClock Windows.

REM

See [System Control Commands](#)

REM Remark - remainder of line is ignored
Remarks can be used within *.DAT files for additional documentation of the various text files
you may change to customize GeoClock maps.

REPEAT

See [Scripts Commands](#)

REPEAT Start script over from first line

Resize Control

See [Windows controls Commands](#)

RESIZE n Control window resizing

RESIZE1 forces all window resizing, including dragging the window border, to keep the 4x3 aspect ratio all GeoClock maps use. RESIZE0 allows full control of the window size.

SCRIPT

See [Scripts Commands](#)

SCRIPT Invoke a specific script

SCRIPTx invokes script x (i.e., the file GEOSCRx.DAT). x may be any number. This is especially useful from the command line. Note that if GEOSCR0.DAT exists, it is automatically invoked when GeoClock starts unless the SCRIPTx command is in the GECONFIG.DAT or GEOCLOCK.INI file or on the command line.

SHOWDAY

See [Time Display Commands](#)

SHOWDAY Show day of week

This command displays the day of the week (1991/05/01 WED 12:14:45). As in SHOWMONTH, the default is the standard 3 letter English abbreviation, but other names can be specified:

SHOWDAY SUN MON TUE WED THU FRI SAT

SHOWLL

See [Lat/Long lines Commands](#)

SHOWLL Show Latitude/Longitude values

This command labels all the latitude and longitude lines displayed. The labels appear on the top and left edges of the display. The labels may overlap other data. Optionally, SHOWLL can control which axis are labeled: SHOWLLn

n and 1 = 0 show left latitude

n and 2 = 0 show right latitude

n and 4 = 0 show top longitude

SHOWMONTH

See [Time Display Commands](#)

SHOWMONTH Show month name rather than number (91 MAY 01 12:14:45). The standard 3 letter English abbreviations are used by default. The text for the month names can be specified by giving the 12 strings to be used for the 12 months. For example:
SHOWMONTH JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC

SHOWSECONDS

See [Time Display Commands](#)

SHOWSECONDS * Show time to nearest second

This command shows time to the nearest second (1991/05/01 12:14:45).

SLOW

See [System Control Commands](#)

SLOW Use high accuracy but slower calculations

Forces GeoClock to use the high accuracy algorithm for drawing the sunlit area. This is the default for systems with an 80x87. On systems with an 80x87, the difference in speed between SLOW and FAST is negligible, while on those systems without an 80x87, FAST is approximately twice the speed of SLOW. These options do not effect polar, orthoscopic, or azimuthal-equidistance maps.

STATUTE

See [System Control Commands](#)

STATUTE * Display distances in statute miles

SUN

See [Legend Commands](#)

SUN City, sun rise/set, local time legend

SUNANGLE

See [Sun and Moon Display Commands](#)

SUNANGLE Sun rise/set definition

SUNANGLE angle sets the elevation angle of the sun used to compute sunrise and set. The default is -0.8333 degree, which corresponds to the sun just breaking the horizon, considering refraction effects. This parameter does not affect the terminator line calculations.

SUNLIGHT

See [Sun and Moon Display Commands](#)

SUNLIGHT Terminator definition

SUNLIGHT angle specifies the sun's elevation angle for the terminator. The default is -0.8333, which corresponds to apparent sunrise and sunset, when the edge of the sun is just visible. 0 corresponds to the geometric terminator, which divides the earth into two equal halves.

SYMBOL

See [Drawing Commands](#)

SYMBOL Displays an external symbol

SYMBOL name lat long displays the symbol referred to by <name> (defined by a previous SYMDEF command) centered on lat long. This symbol is drawn before any city names or times are drawn, so the symbol can be overwritten by this data.

SYMBOL filename lat long displays the symbol defined in <filename> centered on lat long. This symbol is drawn before any city names or times are drawn, so the symbol can be overwritten by this data.

SYMBOL filename name lat long displays the symbol defined in <filename> and named <name> centered on lat long. This symbol is drawn before any city names or times are drawn, so the symbol can be overwritten by this data. <filename> is assumed to have more than one SYMBOL in one file, see SYMDEF.

SYMDEF

See [Drawing Commands](#)

SYMDEF Load an external symbol definition

SYMDEF filename loads the external symbol specified by <filename>. The format of the external file is:

Initial Byte	length	Meaning
0	2	Number of pixels in the x direction (nx)
2	2	Number of pixels in the y direction (ny)
4	2	x pixel corresponding to the symbol center
6	2	y pixel corresponding to the symbol center
8	8	Name of symbol (trailing spaces)
10	nx*ny	Color of pixel (going horizontally from 1 to nx, then vertically from 1 to ny). 0-15 displays as that color. 16-255 is transparent.

Multiple symbol definitions can be included in a single file by concatenating the above structure.

Size

See [Windows controls Commands](#)

SIZE Control size state of window
SIZE0 allows normal window size
SIZE1 forces the window to Maximized
SIZE2 forces the window to Minimized

T

See [Time Display Commands](#)

T Set new time

Pressing the T key prompts you for a new display time in six spin boxes (year month day hour minute second). This does not change your PC's clock. All times in GeoClock use the 24 hour format. If this command is used on the command line or in a DAT file, the included data is interpreted as year month day hour minute second. The data must be given with no extra characters, and exactly two digits per item. Missing data is set to 2000/01/01 00:00:00. For example, T9205151207 is taken as 1992/05/15 12:07:00. A four digit year (between 1000 and 2999) is allowed. When used on the command line or in a DAT file, the data may have a + or - followed by a number. With this format, the current virtual time is incremented or decremented by the specified number of days. For example, T+30 increments the time by 30 days, while T-0.25 decrements the time by 1/4 day = 6 hours.

TEXT

See [Drawing Commands](#)

TEXT Display text on all maps

TEXTx/y/font/color/bg*text No spaces before the * are allowed. x is the horizontal coordinate of the starting pixel for the string (if negative, from the right of the screen), y is the vertical coordinate of the starting pixel (if negative, from the bottom of the screen, font is 0 for 8x14, 1 for 4x6, 2 for 8x8, 3 for 4x8, and 4 for the Xfont. color is the color number for the text, and bg is the background color (-1 means transparent). The text itself can be anything. The underscore (_) is interpreted as a space.

TEXTBG

See [Screen Display Commands](#)

TEXTBG Set text background color

TEXTBGn changes the text background color number to n. The default value is 4.

TIME

See [Legend Commands](#)

TIME Local time only legend

TLINC

See [Lat/Long lines Commands](#)

TLINC Set latitude line increment

TLMASK

See [Sun and Moon Display Commands](#)

TLMASK Twilight area pattern

TLMASK n specifies the fraction (in 16ths) of halftoning for twilight display. 4 is the default, which gives 1/4 light and 3/4 dark for the twilight area. You may have to experiment with this value to get the best display for your monitor. A value of 4 may give a better effect, particularly if you wish to emphasize the terminator relatively to the twilight line.

TLSPEC

See [Lat/Long lines Commands](#)

TLSPEC Specific latitude line

TWILIGHT

See [Sun and Moon Display Commands](#)

TWILIGHT Twilight terminator definition

TWILIGHT angle specifies the sun's elevation angle for the twilight terminator. The default is 0. -6.00 corresponds to civil twilight, -12 corresponds to nautical twilight, and -18 corresponds to astronomical twilight. If this angle is greater than or equal to the SUNLIGHT parameter, the twilight area is not displayed.

UWIN

See [System Control Commands](#)

UWIN Set the update time intervals

UWINf/b sets the update intervals (the time that GeoClock relinquishes control to Windows before the next screen refresh). f is the interval in seconds when GeoClock is in the foreground, and g is the interval in seconds when GeoClock is in the background. The defaults are 1 second for foreground, and 60 seconds for background.

VECTOR

See [Drawing Commands](#)

VECTOR (or V) Continue a line

VECTOR latx longx draws a line starting at the position of the last DRAWLINE or VECTOR, to (latx,) using the color specified in the last DRAWLINE. For example, if the following lines immediately follow the line in the DRAWLINE example:

```
VECTOR 41.83 -87.75
```

```
VECTOR 38.67 -90.25
```

a line from Los Angeles to Chicago to St, Louis will be drawn in color 0. The VECTOR command may be abbreviated by V (i.e., V 41.83 -87.75).

Window

See [Windows controls Commands](#)

WINDOWn/xp/yp/xs/ys

WINDOW allows all GeoClock Windows to be set to special sizes and positions

n=1 specifies the main map window

n=2 specifies the Where Is (Gazetteer) window

n=3 specifies the MapList window

n=4 specifies the About Box window

n=5 specifies the Command Entry window

n=6 specifies the Data File Edit window

n=7 specifies the Registration window

n=8 specifies the Scripts window

n=9 specifies the SetUp window

n=10 specifies the TimeSet window

n=11 specifies the Window Controls window

n=12 specifies the Zip Code window

n=13 specifies the Options window

xp is the screen relative horizontal position of the upper left corner

yp is the screen relative vertical position of the upper left corner

xs is the width in pixels

ys is the height in pixels

For example, WINDOW1/0/0/400/300 places the map window in the upper left corner of the screen, and makes the map area 400x300 pixels.

Ordinarily, the user will not have to enter this command directly. These are written automatically to the GEOCLOCK.INI file when Save Settings is invoked. When save settings is used, comments are automatically added to make clear which windows are effected. For example,

WindowMain1/0/0/400/300.

Winsetup

See [Windows controls Commands](#)

WINSET specifies that the GeoClock program has been initialized for local conditions. If this statement does not appear in GEOCLOCK.INI, GeoClock will start with the Setup window. WINSET will be written to the GEOCLOCK.INI file automatically after GeoClock is set up.

YEAR2

See [Time Display Commands](#)

YEAR2 * Show 2 digit year (e.g., 91/05/01 12:14:45)

YEAR4

See [Time Display Commands](#)

YEAR4 Show 4 digit year (e.g., 1991/05/01 12:14:45)

ZONE

See [Time Display Commands](#)

ZONE Define time zone

This command defines a time zone: it relates the time zone to the standard time zone (variously called Greenwich Mean Time (GMT) or Universal Coordinated Time (UTC) or Zulu Time (Z)); it specifies the dates and times when the zone changes to and from summer time; and it names the time zone and the standard and summer times. As an example, U.S. Eastern Time is specified by:

```
ZONE ET EST -5 EDT -4 91/04/07:7 91/10/27:7
```

ET is the name the time zone is referred to by all GeoClock commands. The definition states that the zone is called EST and is 5 hours behind GMT, except between 91/04/07 0700 GMT and 91/10/27 0700 GMT, when it is called EDT and is 4 hours behind GMT.

If the offset to GMT is 100 or larger, the time zone will give true local sun time (i.e., the sun is at its highest elevation at exactly 12:00 every day). A special time zone named ST (for sun-time) is defined in the GEOZONES.DAT file for this zone.

If the ZONE commands are not for the correct year, GeoClock will automatically update them by changing each date to the closest date in the correct year which falls on the same day of the week.

ZOOMFRACT

See [System Control Commands](#)

ZOOMFRACT Set screen active area for zoom

This command sets the size of the active area on the map for zoom to prevent zoom to areas too close to the screen edge, and to allow map to map lateral zooming.

ZOOMFRACT1.0 allows zooming to any area on the screen. ZOOMFRACT0.95, for example, does not allow zooming closer to the edge than 5% of the screen dimensions. This parameter also affects the Where function, ensuring that the selected city is not too close to the edge of the map. One consequence of this is that clicking near the edge of the map will bring up the highest resolution map containing that point but not near the edge, so the zoom function can be used to navigate laterally through the maps.

HAM radio features

The HAM package is an add-in to the registered version of GeoClock. It supports a variety of features to support HAM, SWL, and DX operators, and includes a custom Azimuthal-Equidistant (Great Circle) projection map centered on your location.

[HAM package features](#)

[Starting the HAM package](#)

[BuckMaster CDRom](#)

[Call Sign Analysis](#)

[Use of other GeoClock features](#)

[Twilight zone definition](#)

[HAM data base](#)

[HAM package support](#)

HAM package features

The GeoClock HAM package activates several new features of particular interest to amateur radio operators and short-wave listeners. These include:

Azimuthal-Equidistant (Great Circle) maps.

Day, night, and twilight zone display:

-Twilight zone parameters can be set to indicate boundaries of sun illumination on the F- and D-layers of the ionosphere.

Amateur radio call sign analysis (based on a user-maintainable call sign data base). When a call sign (or prefix) is entered, the following information is displayed:

- Remote station location
- short and long great circle path
- short and long path azimuth and range
- remote station (reciprocal) azimuth
- UTC, local, and remote station local time
- DXCC and WAE country identifications
- CQ and ITU zones
- Continent, area, and location names

The package has three major components: a custom Azimuthal-Equidistant map centered on your station; a call sign data base, and a utility program to process the text call sign data base into the GeoClock form. Your registered copy of GeoClock will use this data base to overlay HAM data on the custom map.

The custom Azi-Equi map centered on your location is named MAP9009.EGA. A custom GEO9009.DAT file is also provided to control the display of HAM data.

If the optional BuckMaster HamCall CD-ROM is online, the GeoClock HAM package will use the CD-ROM to provide very accurate coordinates and headings for US call signs in the data base.

These features are provided in addition to the other features of GeoClock.

Starting the HAM package

To start the HAM package, enter "GEOCLK MAP9009" at the DOS prompt. The program will start with your custom map and an indication of the sun and terminator locations. In the present release, ham features are activated only on the custom map.

TIP: Edit your GECONFIG.DAT file with an ASCII text file editor and add the command "MAP 9009" as the last line of this file. You will now be able to start the GeoClock program by simply entering GEOCLK at the DOS prompt. GeoClock will then start up automatically with your custom map displayed.

You should see a color Azi-Equi map displayed on your screen against a black background. Your location at the center of the map is shown with a cross symbol. Around the edge of the map are tick marks for every 10 degrees of azimuth. In the bottom right corner, your name, call sign, and location will be displayed. In the bottom left corner two clock lines will be displayed: GMT clock and local time at your location. The format of clock information can be tailored to suit your taste in clock style. See the "commands" section of the help system.

In a few seconds (depending on the speed of your computer), the current sunlight, night, and twilight zones will be displayed. A yellow "sun" will appear at the current sun subpoint (i.e., the spot on Earth where the sun is currently directly overhead). GeoClock will continue to adjust the display to keep up with real time, at a rate dictated by the processing power of your computer. The date/time of the present display is shown on the clocks in the lower left corner.

Note: The rate of updates can be slower (approximately half as fast for the worst case) whenever the boundaries of the twilight zone approach the edges of the Azi-Equi map. This is because a larger number of calculations are required in order to accurately display the twilight zone boundary around the map edge. GeoClock automatically adjusts to this condition in order to insure that the map display remains accurate.

BuckMaster CDROM

If your computer has a CD-ROM drive, and the BuckMaster HamCall CD-ROM is on line, GeoClock can use the database on the CD-ROM to provide very accurate locations (within a few km) and bearing for US call signs in the Data Base. In addition, the name and home town of the owner of the call sign is displayed when the call sign is keyed in. This feature is activated automatically if the HAMCD command is in GECONFIG.DAT. If the CD-ROM drive is on a network or otherwise non-standard, that command can be used to specify the exact path and file name of the data base.

The CD-ROM can be obtained from GeoClock or directly from the publisher for \$50:

BuckMaster Publishing
Rt 4 Box 1630
Mineral VA 23117
Voice: 703-894-5777
FAX: 703-894-9141

Call Sign Analysis

To activate call sign analysis, simply begin to type in the letters and numbers of the amateur radio call sign of interest. When the first key is depressed, a window pops open and the call sign you are typing is displayed in the window. Backspace and cursor keys may be used to correct any typing errors. When the call sign has been completely entered, press the RETURN key.

To abort call sign entry, press the ESCape key. To clear the call sign display, press any letter, then BACKSPACE and RETURN.

You do not need to enter an entire call sign. GeoClock will operate on call sign prefixes. However, GeoClock contains over 1,700 entries in its call sign analysis database. By entering a complete call sign, you will frequently benefit from more precise location information.

Call signs containing "/" may be entered directly from the keyboard; e.g., FR5ZD/E, KN3T/KH6, HB0/DL7FT and SP9PBE/6.

Once a call sign has been entered, GeoClock displays the following information:

- a. a cross "mark" at the location of the station is added to the map. The location chosen is the most accurate location known to the database.
- b. the local time at that distance location is added to the bottom left corner of the screen. This is the third clock time, labelled "mark:". This time is continually updated, along with all the other clocks on the screen. Rules for local daylight savings (summer) time are applied.
- c. short and long great circle paths from your location to the distance "mark" are displayed on the map. If you look carefully, you will see the long path has a yellow color. (On an Equi-Az map, the long path is obvious: it is the path which crosses the edge of the map.) In addition, the left side of the screen shows the following for both short and long paths:
 - azimuth (direction) from your location to the mark.
 - azimuth from the mark to your location.
 - distance in miles and kilometers.
- d. on the left side of the screen, additional information about the call sign is shown:
 - DXCC country: standard prefix and country name.
 - WAE country: standard prefix and country name.
 - area: state, region, or ooblast within the country for this particular call sign. For USSR ooblasts, the ooblast number is also shown.
 - mark: the city or geographical spot which is displayed on the map and used for distance and bearing calculations.
 - CQ zone(s) for the area named above.
 - ITU zone(s) for the area named above.

To erase the information, press the minus (-) key.

Use of other GeoClock features

Most of the GeoClock commands and features described in the other sections of HELP are available while using the HAM package. In addition to real time operation, GeoClock can be instructed to operate at other dates and times, and to operate at accelerated rates. Distances and great circle directions can be determined between any locations on the globe. There are many commands which allow you to customize the type and style of information displayed on GeoClock. You should take time to read the remaining GeoClock help sections to learn about these additional capabilities. These will help you get the most out of your GeoClock system.

GeoClock also includes many additional maps of the world, polar regions, continents, oceans, and individual countries. These additional maps allow you to zoom in on specific areas on interest in the globe; e.g., twilight zone crossings of Africa, etc.

While using your custom map and ham features, you can enter these other GeoClock commands by holding down the SHIFT key while pressing the appropriate letter. For example, pressing SHIFT and T (for Time) allows you to change the date/time used to calculate the displayed day, night, and twilight zones.

Note: The SHIFT key must be used. The CAPS LOCK key and caps-lock status is ignored. Any keys pressed without the SHIFT will be interpreted as characters for a call sign.

GeoClock supports two commands which are specific to ham features.

The HAMDB command specifies the name of the call sign database to be used. This command should be in the GECONFIG.DAT file. For example, HAMDB HAM.HDB specifies that HAM.HDB contains the call sign data base. This database MUST be in the format produced by GENHAMDB, not in text format. Only the first use of HAMDB in a given run has effect - the data base cannot be changed while GeoClock is executing.

The second command, HAM, specifies that the HAM features are to be activated. The best place to this command is in the GEO9009.DAT file corresponding to your Azimuthal-Equidistant (Azi-Equi) map. In the current release of GeoClock, the HAM features may only be used when the Azi-Equi map is displayed. NOHAM deactivates the HAM features.

Twilight zone definition

One of the strengths of GeoClock is the ability for you to use the TWILIGHT and SUNLIGHT commands to determine the boundaries of the day zone, twilight zone, and night zone. You can set these boundaries to any value desired.

The value is the offset, in degrees, of the zone boundary from the edge of the (geometric) sunlight part of the earth. Typical values of interest for shortwave operating include:

- SUNLIGHT = -6.596 Boundary where sun starts/stops illuminating the D-layer. This controls absorption on the lower frequency shortwave radio bands.
- TWILIGHT = -14.165 Boundary where sun starts/stops illuminating the F-layer. These values are based on average D- and F- layer heights. They define the Ionospheric Gray Line: a twilight zone where shortwave radio signals can pass through the D-layer without absorption. Within this zone signals will encounter an illuminated F- layer whose ionization level will be normally enhanced over that found in the night zone.

Other common values for these commands include:

- SUNLIGHT = -0.833 Sunset/sunrise at sea level, taking into account the bending of light through the Earth's atmosphere and the apparent width of the sun.
- TWILIGHT = -6 Boundary of civil (legal) twilight, where it is bright enough to work outdoors.
- TWILIGHT = -12 Boundary of nautical twilight, where it is bright enough to see the horizon. One can take navigational sightings with a sextant in this zone.
- TWILIGHT = -18 Boundary of astronomical twilight, where sunlight on the upper atmosphere interferes with the use of telescopes by astronomers.

To use the same values for twilight definition on all maps, enter these commands in the GECONFIG.DAT file. To specify values for each particular map, the commands should appear in the GEO*.DAT file (where "*" represents the map number; e.g., GEO9009.DAT for your custom Equi-Az map).

HAM data base

Analysis of amateur radio call signs is driven by information contained in the ham database. The database consists of three files:

-- HAM42B.DAT: An ASCII text file containing information described below. The "42B" in the name indicates the version number of the database: "42" indicates that this database was prepared to support GeoClock version 4.2, and "B" indicates this is the second release of the database for this GeoClock version. You may have received a more recent version number.

-- GENHAMDB.EXE: An executable utility which converts the ASCII text file into a binary format used by GeoClock for call sign analysis. Database validation is also performed by this utility.

-- HAM.HDB: The binary format produced by the GENHAMDB.EXE utility program.

HAM42B.DAT

The text form of the call sign data base consists of lines specifying key data about a group of call signs. Each line consists of 11 data items:

1. CallPattern - the leading characters of the call sign group. For example, PY signifies all call signs beginning with the characters PY.

Wildcard characters are used in describing call sign patterns as follows:

-- represents any single digit; i.e., 0, 1, 2, ... 9.

@ -- represents any single alphabetic character; i.e., A, B, ... Z.

? -- represents any single character, either alphabetic or numeric.

* -- represents any string of characters.

For example, PY#Z* represents any call sign beginning with PY, followed by any single digit, then the letter Z, and then anything else. PY0ZZ would match this pattern.

All characters are interpreted as upper case. This file has been created in lower case. If you add entries of your own, you may wish to make them upper case so that you can easily recognize your own additions for future maintenance and debugging purposes.

2. HamLat - the latitude of the location corresponding to this call sign. This may be in decimal degrees (-15.146 for 15.146 degrees South), or in degrees/minutes/seconds ("15 8 45.6S"). If the latter format is used, the latitude must be enclosed in quote marks.

3. HamLong - the longitude of the location corresponding to this call sign. This may be in decimal degrees (-15.146 for 15.146 degrees West), or in degrees/minutes/seconds ("15 8 45.6W"). If the latter format is used, the latitude must be enclosed in quote marks.

4. HamTimeZone - the time zone code for local time for this call sign group. For example, ET stands for US Eastern time. The time zone acronyms are defined in the GEOZONES.DAT file.

5. HamCQzone - the CQ zone for this call sign group. If the zone has imbedded spaces, it must be enclosed in quotes; e.g., "3 4 5".

6. HamITUzone - the ITU zone for this call sign group. If the zone has imbedded spaces, it must be enclosed in quotes.

7. HamContinent - the continent for this call sign group. NA, SA, AF, EU, AS, AN, and OC may be used as abbreviations.

8. DXCCprefix - the standard DXCC call sign prefix designation for this CallPattern. The DXCC country identification for this CallPattern is determined by this prefix.
9. AreaName - the name of the area within a country which is covered by this CallPattern; e.g., state, ooblast, region, or other political subdivision. This must be enclosed by quotes.
10. MarkName - the name of the specific place used to represent this call sign group. Ordinarily this should correspond to the latitude, longitude and time zone specified above. If the MarkName is missing, the AreaName is used. This must be enclosed by quotes.
11. WAEprefix - the standard WAE call sign prefix designation for this CallPattern. The WAE country identification for this CallPattern is determined by this prefix. If omitted, it is assumed that the WAE country is the same as the DXCC country.

NOTE -- Items enclosed in quotes must be separated from one another by at least one space. All items must be contained on a single line.

Another type of line in the text call sign data base specifies equivalences in call signs. For example, ZY* =PY* specifies that any call sign starting with ZY should be treated as if it started with PY; i.e., ZY5EG can be processed as if the call was PY5EG.

Through appropriate combinations of "equates" and wildcards, the database and analysis algorithm is capable of accurately determining the location of any call sign heard on the air, including special prefixes.

Mobile call signs (K3NA/MM, for instance) will be processed but not result in a location display on the map, since the exact location of the station is not predictable in advance.

You may add additional entries to the HAM42B.DAT (or later versions) file with a simple ASCII file editor, following the conventions outlined above.

Any line beginning with a space in column 1 is interpreted as a comment. You can see a typical comment line in the first line of the HAM42B.DAT file, where columns are named for your convenience.

After the HAM42B.DAT file has been modified, it must be converted into a format which can be processed by the GeoClock program. The program GENHAMDB.EXE does this conversion. To start the program, enter at the DOS prompt: GENHAMDB (filename). Example: GENHAMDB HAM42B.DAT

Conversion processing can take several minutes, depending on the speed of your computer. The GENHAMDB utility provides you with a cryptic status of the current state of the conversion process.

When conversion is completed, GENHAMDB prompts you for a name for the converted file. The normal convention is to use the name HAM.HDB. If you do not specify a name, GENHAMDB will assume HAM.HDB.

NOTE -- GeoClock is initially configured to look for the database under the name HAM.HDB. To change this, you must modify the GEO9009.DAT file with an ASCII file editor. The command line HAMDB specifies the name of the .HDB file to use when your custom map is displayed. For simplicity, you may wish to always tell GENHAMDB to name its output as HAM.HDB.

After writing the .HDB file to disk, GENHAMDB allows you to test the database without

running GeoClock. You will be prompted for a call sign. GENHAMDB takes the call sign given and looks it up in the data base, and displays the data base entry, including a summary of the equivalences used in the analysis. You can test as many call signs as you wish before exiting the program.

Note -- You will also see other numbers displayed along with the data base entry. These other numbers are used by the GeoClock software developers in order to debug errors.

To exit GENHAMDB, enter an empty call sign (i.e., just press the RETURN key).

If you wish to conduct further tests on the HAM.HDB file, simple re-enter GENHAMDB by typing the following command at the DOS prompt:

```
GENHAMDB HAM.HDB /D
```

where "HAM.HDB" is the name of the .HDB binary file to be tested. GENHAMDB takes note of the "/D" debug switch on the command line, skips the database construction phase, and prompts you to enter test call signs.

Support

The call sign data base included with the HAM version of GeoClock was developed by Eric Scace, K3NA. This is also a copyrighted software product. You may use the database for any other software which you have developed for your personal use (e.g., contesting software, QSL card processing programs, etc). However, the database can not be incorporated into any software product which is sold or distributed as shareware without prior permission.

Questions, comments, additional data and corrections to the ham database are welcomed! These can be sent to Eric via the GeoClock RBBS, or by other means to:

Eric L. Scace K3NA
10701 Five Forks Road
Frederick MD 21701

home: +1-301-293-2448
work: +1-703-689-6556
fax: +1-703-689-5036
telex: +23-740-0368 ERIC UC
X400 e-mail: C:USA A:Telemail O:Sprintmail
FN: Eric SN: Scace MI: L.
amateur radio BBS: K3NA @K3NA

Call Sign Analysis Algorithm

Matching Algorithm (ALG-2):

1. Use ALG-1 on the input string.
2. If input string does not contain a "/", done
3. If there was no match, go to step 7
4. If the match after the / is exact, done
5. If the end string is /A, /M, or /P, done
6. If the end string is a single numeric, replace the first non-leading numeric in the string before the /. If ALG-1 produces a match, done.
7. If the string exactly matches one of the */ entries, use that entry
8. Use the shorter of the strings before and after the / (after if equal) and apply ALG-1

ALG-1:

1. Find the most stringent straight match on the input string
2. Find the most stringent equate match. If none, go to 4
3. Make the substitutions, and find the most stringent straight match (Can be done recursively up to a maximum limit.)
4. If only one match was found, done
5. If both a straight and substitution match were found, use the more stringent.

Registration

GeoClock is distributed as shareware. This means that if you use and enjoy the program, you are expected to register it. See "Ordering GeoClock" for details. Registering your copy makes continued improvement and support for GeoClock possible. Furthermore, the registered version includes the zoom, distance measuring, and city time display functions, plus many additional maps. You also get access to additional map files from the GeoClock Bulletin Board System.

See Also:

[Why Register?](#)

[Registration Form](#)

[Updates](#)

[Available Maps](#)

[BBS](#)

[Special Pricing](#)

[Ordering GeoClock](#)

Why Register?

Also see [Registration Form](#)

There are several important reasons you should register your copy of GeoClock:

You make continued improvement and support of the program possible

You receive MANY more maps

Your copy will display local times next to the city names

Your copy will start immediately with map display, rather than pausing at the about box

You can register new versions GeoClock free

You will be notified of new versions and products

You will be able to download special maps and utilities from the GeoClock BBS

If you have already purchased a registered version of GeoClock, you can update to a new registered version of GeoClock, including the windows version, by obtaining the shareware version (from a BBS, shareware catalog, CompuServe or other online service, or by mail), copying the new files over your existing GeoClock installation, and running the REGISTER.EXE program supplied when you purchase your original registered version of GeoClock.

Registration Form

Also see [Why Register?](#)

You can print (or save to a file) a completed order form by filling out the registration menu (under Help|Register on the main menu bar, or by pressing the register button on the about box.

The various check boxes select the options available with GeoClock. The top right box, GeoClock Registration, is required unless you already have purchased GeoClock. If this box is not checked, you must enter your registration number. This will be filled in already if you are running a registered copy of GeoClock.

The next five check boxes are for the various extra map sets.

The next check box is for the HAM package. If you want the HAM package, you must fill in your call sign (enter "none" if you don't have one), and your latitude and longitude. If you don't know your latitude and longitude, and live outside the 50 US states, you can enter the name of the nearest large city instead. If you live inside the US, the latitude/longitude is not necessary - we can get it from your zip code.

The next check box is for the BuckMaster HamCall CD-ROM. If you have the HAM package, this CD-ROM will greatly improve the accuracy of GeoClock calculations for US call signs. This CD-ROM is available from many sources.

Finally, you can order the Spinning Globe program. This program works much better under DOS and Windows standard mode than it does under Windows in the 386 mode, OS/2, and Windows NT.

In the box on the upper left, enter your name and shipping address. We use post office first class mail for deliveries in the US, and post office air mail for deliveries outside the US.

In the next box, choose your payment method. We accept checks (payable in US dollars and drawn on US banks), VISA, and MasterCard. We do not accept purchase orders or CODs. Money orders mailed separately (especially from France) have not proved reliable and should not be used. If you choose a credit card, you must fill in the card number and expiration date boxes.

If you live outside the US, Canada, and APO/FPO addresses, check the air mail shipping box.

To check the order, click the Validate button. Any erroneous data will be highlighted in red. In addition, the total price will be displayed. When the order is correct, press the Print button (to print the order form) or File button (to save the order form to the file ORDERGEO.TXT in the GeoClock directory).

Updates

If you have registered an older version of GeoClock, you can register a new version without cost. Just unLZH the files from the newest shareware version of GeoClock and run the REGISTER.EXE program that was included on your original distribution disks. The latest version is always available from the GeoClock computer bulletin board system (BBS).

Available Maps

GeoClock includes a large number of maps. All these maps have border data for the former USSR, former Czechoslovakia, and former Yugoslavia as of the release date of this version. While the specific maps included change from time to time to reflect changing interests, the following maps are currently included with registration:

Africa	Australia & NZ	British Isles
Canada	Caribbean	Europe
Far East	Former USSR	Japan
Meso America	Mexico	Middle East
N America	New York City (2)	North Pole
S America	SW Asia/India	South Pacific
South Pole	United States (2)	US Regional (13)
View-From-Space (6)	World (3)	

These basic maps are also available in 800x600 resolution.

There are four supplemental map sets providing detailed coverage of every country in the world, the US states, and the Canadian Provinces.

North America has approximately 50 maps, including the 50 US states and the Canadian provinces.

Europe has approximately 40 maps, including all the countries of the former USSR.

Middle East / Asia / Pacific has approximately 35 maps.

Africa / South America has approximately 35 maps including Central America and the Caribbean.

The maps distributed are changed from time to time to reflect changing interests. The GeoClock Bulletin Board always has all the maps available to registered users.

About the GeoClock Bulletin Board

A free computer Bulletin Board System (BBS) provides support for users of GeoClock. It always has the latest version of the program available for downloading. In addition, it provides a forum for all interested parties to exchange programs and information concerning GeoClock and high quality mapping for the IBM PC.

Everyone is welcome to use this BBS, but registered GeoClock users have access to certain special files and have higher access limits. HAM package owners also have access to the latest version of the HAM data base. Please have your registration number handy when you log on for the first time. Except for these special files, the messages and files on the board are available to everyone. Your comments and suggestions are welcome.

You need a modem (1200, 2400, 9600 v.32, 14400 v.32bis) and terminal emulation software (such as ProComm or CrossTalk) for your PC to access the BBS. The BBS uses N-8-1 communications. The BBS number is 703-241-7980. This is a Washington DC metro area number. GeoClock is also available from many Shareware catalogs, computer bulletin boards, and CompuServe (CSID 70461,2340).

GeoClock 7.0 special pricing

License for multiple users at a single site (for LAN use, estimate the number of LAN users of GeoClock):

Number	Price
1	\$ 35/User
2-9	\$ 30/User
10-20	\$ 25/User
21-40	\$ 20/User
41+	\$ 15/User

Site licenses, corporate licenses, educational licenses, and other large quantity licenses are available. Contact GeoClock directly (voice 703-241-2661, FAX 703-241-5809) for details.

SVGA basic map set - \$10.

Supplemental Map Sets: \$ 20 for one, \$30 for two, \$35 for three, \$40 for all four ordered at the same time. Available sets:

- Basic (included with GeoClock registration)
- North America
- Europe
- Asia/Pacific
- South America/Africa/Middle East

Spinning Globe: \$15

HAM radio support package: \$ 30

Custom maps - \$30 for rectangular projection maps covering at least 120,000 square miles (at least 300 miles North to South) outside the US, or at least 800 square miles (25 miles North to South) within the US. Other projections and sizes by negotiation.

Custom modifications to GeoClock - by negotiation. Custom modifications can generally be made on a fixed price basis after agreement to specifications.

The supplemental maps and HAM package can be used by each registered user without additional charge. The supplemental map sets contain detailed maps of all individual countries in the areas listed above. GEO*.DAT files accompany each country(s) map(s) and provide both city and country data.

In all cases, the purchaser must make all required copies from the supplied master copy, and must protect the software the same way the purchaser protects its own proprietary software to ensure that the license is not violated.

Terms: Payment must be by VISA, MasterCard, or check in advance. Purchase Orders are accepted only for unlimited site licenses and custom programming. No CODs.

Ordering GeoClock 7.0

Registration of GeoClock includes a copy of the latest version of the program, a large set of maps (the basic set described in "Available Maps"), a file with the names and locations of many world cities for customizing the maps, a "starter set" of map overlay files, and an installation program for automatic set-up on a hard disk. Updates to the program are available to registered users at no charge from the GeoClock BBS.

The supplemental map sets(North America; Europe; Middle East, Asia & Pacific; South America & Africa), and the HAM package, can be ordered with the initial registration or later. Custom maps and quantity license agreements are available. Write for details.

Orders paid by cash or check are accepted by mail. VISA and MasterCard orders may be made by mail, voice, FAX, or electronically via the GeoClock BBS.

Purchase orders, and checks drawn on or payable to banks outside the USA, are not accepted. International postal money orders mailed separately have not proved reliable and should be avoided. In all cases, specify whether 5.25" (1.2MB) or 3.5" (1.44MB) disks are required.

- \$35 GeoClock registration (DOS and Windows versions), programs, and basic map set
- \$5 Extra for international air mail and handling
- \$10 SVGA basic map set
- \$20 One supplemental map set
- \$30 Two supplemental map sets
- \$35 Three supplemental map sets
- \$40 All four supplemental map sets
- \$30 HAM package (include your call sign and QTH)
- \$15 Spinning Globe program
- \$50 BuckMaster HamCall CD-ROM

You can also order the basic GeoClock registered version (\$35) via CompuServe's SWREG (search for the keyword GEOCLOCK)

GeoClock 2218 N Tuckahoe St, Arlington VA 22205-1964
Voice: 703-241-2661 (normal business hours)
BBS: 703-241-7980 (24 hours)
FAX: 703-241-5809 (24 hours)
CompuServe: 70461,2340
Internet: jahlgren@capaccess.org

