

```

//*****
//*  MACRO: CHNGFNT.WCM
//*  PURPOSE: Globally change font face and color in a Presentations show.
//*****
Application (Presentations; "Presentations"; Default; "EN")
//*****
//*  VARIABLE INITIALIZATION
//*  Because of dialog updating, many flags are used in macro!
//*****
OnError(fError)
WM_SYSCOMMAND:=274
Doitf:=0    // User created text flag
Doitc:=0// User created color flag
Doitx:=0    // Template objects flag
x1:=80w// Next 4 are for routine DoitFonts
y1:=9500w
x2:=600w
y2:=8900w
Declare TitleRGB[]={0;0;0}    // Next 6 are color arrays
Declare SubRGB[]={0;0;0}
Declare BulletRGB[]={0;0;0}
Declare UserRGB[]={0;0;0}
Declare LayRGB[]={0;0;0}
Declare BackRGB[]={0;0;0}
vLay:=0 // Next 17 are flags
vBack:=0
vShow:=0
ccTitle:=0
ccSub:=0
ccBullet:=0
ccUser:=0
ccLay:=0
ccBack:=0
vTitle:=0
vSub:=0
vBullet:=0
xUser:=0
xLay:=0
xBack:=0
xxLay:=0
xxBack:=0
Popup1:="Title" // Next 19 strings for dialog/font
fontx:=""
colorx:=""
Combo1:="-NO CHANGE-"
Color1:="-NO CHANGE-"
cTitle:="-NO CHANGE-"
cSub:="-NO CHANGE-"
cBullet:="-NO CHANGE-"
cUser:="-NO CHANGE-"
cLay:="-NO CHANGE-"
cBack:="-NO CHANGE-"
qTitle:="-NO CHANGE-"
qSub:="-NO CHANGE-"
qBullet:="-NO CHANGE-"
qUser:="-NO CHANGE-"
qLay:="-NO CHANGE-"
qBack:="-NO CHANGE-"
qLayOnly:="-NO CHANGE-"
qNone:="-NO CHANGE-"
vBold:=0    // Next 3 are font appearance flags
vItalic:=0

```

```

vUnder:=0
vBulletColor:=0 // Flag for bullet color
vHelp:="Change Title Layouts in Layout Editor." // QuickHelp variable
vFound:=0 // SelectChart() flag
vIndex:=18 // Number of Index's for Hard Coded font list.
vMin:=0
/*****
/* HARD CODED FONT LIST/COLOR ARRAY
/* (DO NOT REMOVE "-NO CHANGE-" from list)
*****/
FontCnt:=EnvNextFontFace(1)
FontCnt:=FontCnt + 1
Declare (FontInfo[FontCnt])
FontCount := 0
WaitMsgInit ()
WaitMsgDisplay ("Getting fonts list...")
For (Count; 1; Count <= FontCnt; Count + 1)
    WaitMsgDisplay ("Getting fonts "+Count+" of "+FontCnt+"...")
    FontInfo[Count]:=EnvNextFontFace(0)
    FontCount := FontCount + 1
EndFor
FontInfo[FontCount] := "-NO CHANGE-"

DECLARE Colors[11] // Color list array
a:=1
FOREACH(vC;{"-NO CHANGE-";"Black"; "Blue"; "Cyan"; "Gray (Dark)";"Gray (Light)"; "Green"; "Magenta"; "Red";
"Yellow";"White"})
    Colors[a] := vC
    a := a + 1
endfor
if(EnvCurrentMode = 1)
    BEEP
    MESSAGEBOX(vStatus; "Change Font Macro - Error"; "Presentations must be in Slide Show mode."; IconStop!)
    Quit
endif
WaitMsgHide ()
WaitMsgDestroy ()
/*****
/* DIALOG CREATION
*****/
DialogDefine(100; 50; 50; 285; 175; Percent!|Cancel!;"Change Font Macro")
DialogAddText(100; 1997; 8; 3; 100; 15; 1; "&Text Element:")
DialogAddText(100; 1998; 120; 3; 100; 15; 1; "Font face:")
DialogAddText(100; 1999; 180; 3; 100; 15; 1; "Font color:")
DialogAddListBox(100; 2001; 10; 17; 105; 80; Unsorted!; Popup1)
DialogAddListItem(100; 2001; "Title")
DialogAddListItem(100; 2001; "Subtitle")
DialogAddListItem(100; 2001; "Bullet/Text Chart")
DialogAddListItem(100; 2001; "Text Area/Line")
DialogAddListItem(100; 2001; "Text Area/Line (Layouts)")
DialogAddListItem(100; 2001; "Text Area/Line (Backgrounds)")
DialogAddListItem(100; 2001; "Layout Items Only")
DialogAddListItem(100; 2001; "Change All")
DialogAddHLine(100; -1; 8; 90; 200)
DialogAddText(100; 2002; 8; 95; 50; 13; 1; "&Font face:")
DIALOGADDTTEXT(100; 55; 8; 106; 80;10;1;"Updating filenames ...")
DialogAddComboBox(100; 2003; 8; 106; 100; 100; Droplist!|Sorted!; Combo1; 0)
DialogAddText(100; 2010; 130; 95; 100; 13; 1; "F&ont color:")
DialogAddComboBox(100; 2011; 130; 106; 65; 100; Droplist!; Color1; 0)
for(x; 1; x<=11; x+1)
    DialogAddListItem(100; 2011; Colors[x])
endfor

```

```

DialogAddCheckBox(100; 2004; 8; 125; 28; 13; "Bo&ld"; xBold)
DialogAddCheckBox(100; 2005; 45; 125; 28; 13; "I&talic"; xItalic)
DialogAddCheckBox(100; 2006; 8; 140; 50; 13; "&Underlined"; xUnder)
DialogAddCheckBox(100; 2007; 125; 125; 90; 13; "Ch&ange color of bullets"; vBulletColor)
DialogAddGroupBox(100; -2; 220; 80; 53; 70; "QuickHelp")
DialogAddText(100; 11; 223; 89; 47; 58; 1; vHelp)
DialogAddText(100; 300; 120; 17; 55; 8; 1; qTitle) // Update fonts being used
DialogAddText(100; 301; 120; 25; 55; 8; 1; qSub)
DialogAddText(100; 302; 120; 33; 55; 8; 1; qBullet)
DialogAddText(100; 303; 120; 41; 55; 8; 1; qUser)
DialogAddText(100; 304; 120; 49; 55; 8; 1; qLay)
DialogAddText(100; 305; 120; 57; 55; 8; 1; qBack)
DialogAddText(100; 400; 180; 17; 50; 8; 1; cTitle) // Update color being used
DialogAddText(100; 401; 180; 25; 50; 8; 1; cSub)
DialogAddText(100; 402; 180; 33; 50; 8; 1; cBullet)
DialogAddText(100; 403; 180; 41; 50; 8; 1; cUser)
DialogAddText(100; 404; 180; 49; 50; 8; 1; cLay)
DialogAddText(100; 405; 180; 57; 50; 8; 1; cBack)
DialogAddHLine(100; 649; 5; 156; 200)
DialogAddCheckBox(100; 650; 8; 160; 210; 13; "Minimi&ze Corel Presentations for faster changes"; vMin)
DialogAddPushButton(100; "Ok"; 235; 10; 40; 13; 1; " OK ")
DialogAddPushButton(100; "Cancel"; 235; 27; 40; 13; 0; " Cancel ")
DialogAddPushButton(100; "Help"; 235; 48; 40; 13; 0; " &Help ")
DialogLoad(100; "Presentations")
RegionShowWindow("100.CancelBttn"; Hide!)
RegionEnableWindow("100.2004";Disable!)
RegionEnableWindow("100.2005";Disable!)
RegionEnableWindow("100.2006";Disable!)
RegionEnableWindow("100.2007";Disable!)
DialogShow(100; "Presentations";Looper@)
//*****
RegionShowWindow("100.2003"; Hide!)
RegionShowWindow("100.55"; Show!)
for(x; 1; x<(FontCount+1); x+1)
    RegionAddListItem("100.2003"; FontInfo[x])
    REGIONSETWINDOWTEXT("100.55"; "Loading fonts "+x+" of "+FontCnt)
endfor
RegionShowWindow("100.55"; Hide!)
RegionShowWindow("100.2003"; Show!)
RegionSelectListItem("100.2003"; "-NO CHANGE-")
//*****
xCan:=1
CallBackWait()
DialogDestroy(100)
IF(vMin = 1)
    PRActivate ()
    ApplicationMinimize ()
ENDIF
WaitMsgInit ()
WaitMsgDisplay ("")
if(xCan=1)AND(Doitx=1))
    Call(Doit)
endif
if((Doitf=1)OR(Doitc=1))
    vShow:=1
    Call(DoitFonts)
    vShow:=0
endif
if(xxLay=1)
    vLay:=1
    Call(DoitFonts)
    EditSlides()

```

```

    vLay:=0
endif
if(xxBack=1)
    vBack:=1
    Call(DoitFonts)
    EditSlides()
    vBack:=0
endif
WaitMsgHide ()
WaitMsgDestroy ()
IF(vMin = 1)
    ApplicationRestore ()
    PRActivate ()
ENDIF
Quit
/**
/** LOOPER CALLBACK: This will update the dialog and flags as needed.
/**
label(Looper)
if(Looper[5]=273)
    switch(Looper[3])
        caseof"Ok":
            DialogDismiss("100";"Ok")
            CallBackResume()
        caseof"Cancel":
            DialogDestroy(100)
            QUIT
        caseof"CancelBttn":
            DialogDestroy(100)
            QUIT
        caseof"Help":
            Call(Help)
        caseof"2003":
            Combo1 = REGIONGETSELECTEDTEXT("100.2003")
            if(Combo1 <> "-NO CHANGE-")
                RegionEnableWindow("100.2004";Enable!)
                RegionEnableWindow("100.2005";Enable!)
                RegionEnableWindow("100.2006";Enable!)
            else
                RegionEnableWindow("100.2004";Disable!)
                RegionEnableWindow("100.2005";Disable!)
                RegionEnableWindow("100.2006";Disable!)
            endif
            for(x; 1; x<(FontCount+1); x+1)
                if(Combo1 = FontInfo[x])
                    fontx:=FontInfo[x]
                    lseton()
                endif
            endfor
        caseof"2011":
            Color1 = REGIONGETSELECTEDTEXT("100.2011")
            for(x; 1; x<12; x+1)
                if(Color1 = Colors[x])
                    colorx:=Colors[x]
                    cseton()
                endif
            endfor
        caseof"2001":
            Popup1 = REGIONGETSELECTEDTEXT("100.2001")
            if(Popup1 = "Title")
                RegionSelectListItem("100.2003"; qTitle)
                RegionSelectListItem("100.2011"; cTitle)
            endif
        endfor
    endif
endif

```

```

        vHelp:="Change Title Layouts in Layout Editor."
        RegionSetWindowText("100.11";vHelp)
        RegionEnableWindow("100.2007";Disable!)
    endif
if(Popup1 = "Subtitle")
    RegionSelectListItem("100.2003"; qSub)
    RegionSelectListItem("100.2011"; cSub)
    vHelp:="Change Subtitle Layouts in Layout Editor."
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Disable!)
endif
if(Popup1 = "Bullet/Text Chart")
    RegionSelectListItem("100.2003"; qBullet)
    RegionSelectListItem("100.2011"; cBullet)
    vHelp:="Change Bullet/Text Charts in Layout Editor."
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Enable!)
endif
if(Popup1 = "Text Area/Line")
    RegionSelectListItem("100.2003"; qUser)
    RegionSelectListItem("100.2011"; cUser)
    vHelp:="Change User Created Text in Slide Editor."
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Disable!)
endif
if(Popup1 = "Text Area/Line (Layouts)")
    RegionSelectListItem("100.2003"; qLay)
    RegionSelectListItem("100.2011"; cLay)
    vHelp:="Change User Created Text in Layout Editor."
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Disable!)
endif
if(Popup1 = "Text Area/Line (Backgrounds)")
    RegionSelectListItem("100.2003"; qBack)
    RegionSelectListItem("100.2011"; cBack)
    vHelp:="Change User Created Text in Background Editor."
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Disable!)
endif
if(Popup1 = "Layout Items Only")
    RegionSelectListItem("100.2003"; qLayOnly)
    vHelp:="Change Title's, Subtitle's, and Bullet/Text Charts in Layout Editor"
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Enable!)
endif
if(Popup1 = "Change All")
    RegionSelectListItem("100.2003"; qNONE)
    vHelp:="Change All Text in Slide Show. (See help for non-applicable objects)"
    RegionSetWindowText("100.11";vHelp)
    RegionEnableWindow("100.2007";Enable!)
endif
caseof"2004":
    xBold = RegionGetCheck("100.2004")
    if(xBold = 1)
        vBold:=1
    else
        vBold:=0
    endif
caseof"2005":
    xItalic = RegionGetCheck("100.2005")
    if(xItalic = 1)
        vItalic:=1

```

```

        else
            vItalic:=0
        endif
    caseof"2006":
        xUnder = RegionGetCheck("100.2006")
        if(xUnder = 1)
            vUnder:=1
        else
            vUnder:=0
        endif
    endswitch
else
    if(WM_SYSCOMMAND = Looper[5])
        DialogDismiss("100","Cancel")
        xCan:=0
        Dsply:=0
        Doitf:=0
        xxLay:=0
        xxBack:=0
    endif
endif
return
/*****
/* ROUTINE: DOIT
/* DESCRIPTION: Go into layout editor, and change layout object fonts
*****/
label(Doit)
WaitMsgDisplay ("Changing Layout Objects... ")
EditLayouts ()
OnNotFound Call(nothing)
for(x; 1; x<=EnvNumberofLayouts(); x+1)
    ShowLayout(x) // Change Layout
    SelectTextChart(0) // SelectTitle
    if(vFound = 0) // Check if Title exists
        BulletChartAttrStart()
        if(vTitle = 1)
            SetLevelFont(0; qTitle; ; 1; vItalic; vUnder; ;)
        endif
        if(ccTitle = 1)
SetLevelPattern(0;Solid!;TitleRGB[1];TitleRGB[2];TitleRGB[3];0;0;0;255;255;255;255;255;255;0;0; ClosedFilled!)
        endif
        BulletChartAttrEnd(Chart!)
        UnSelectAllObjects()
    endif
    SelectTextChart(1) // Select Subtitle
    if(vFound = 0) // Check if Subtitle exists
        BulletChartAttrStart()
        if(vSub = 1)
            SetLevelFont(0; qSub; ; vBold; vItalic; vUnder; ;)
        endif
        if(ccSub = 1)
SetLevelPattern(0;Solid!;SubRGB[1];SubRGB[2];SubRGB[3];0;0;0;255;255;255;255;255;255;0;0; ClosedFilled!)
        endif
        BulletChartAttrEnd(Chart!)
        UnSelectAllObjects()
    endif
    SelectTextChart(2) // Select Text/Bullet
    if(vFound = 0) // Check if Bullet or Text chart exists
        BulletChartAttrStart()
        if(vBullet = 1)
            for(y; 0; y<6; y+1)
                SetLevelFont(y; qBullet; ; vBold; vItalic; vUnder; ;)
            endfor
        endif
    endif
endif

```

```

        endfor
    endif
    if(ccBullet = 1)
        for(z; 0; z<6; z+1)
SetLevelPattern(z,Solid!,BulletRGB[1];BulletRGB[2];BulletRGB[3];0;0;0;255;255;255;255;255;255;0;0;ClosedFilled!)
        if(vBulletColor = 1)
            SetBulletColor ((z+1); BulletRGB[1];BulletRGB[2];BulletRGB[3])
        endif
        endfor
    endif
    BulletChartAttrEnd(Chart!)
    UnSelectAllObjects()
endif
vFound:=0
endifor
EditSlides ()
return
/*****
/* ROUTINE: LSETON
/* DESCRIPTION: Updates the font face, and font flags.
*****/
label(lseton)
Popup1 = RegionGetSelectedText("100.2001")
if(Popup1 = "Title")
    if(fontx = "-NO CHANGE-")
        vTitle:=0
    else
        Doitx:=1
        vTitle:=1
    endif
    qTitle:=fontx
    RegionSetWindowText("100.300";fontx)
endif
if(Popup1 = "Subtitle")
    if(fontx = "-NO CHANGE-")
        vSub=0
    else
        Doitx:=1
        vSub:=1
    endif
    qSub:=fontx
    RegionSetWindowText("100.301";fontx)
endif
if(Popup1 = "Bullet/Text Chart")
    if(fontx = "-NO CHANGE-")
        vBullet:=0
    else
        Doitx:=1
        vBullet:=1
    endif
    qBullet:=fontx
    RegionSetWindowText("100.302";fontx)
endif
if(Popup1 = "Text Area/Line")
    if(fontx = "-NO CHANGE-")
        xUser:=0
        Doitf:=0
    else
        xUser:=1
        Doitf:=1
    endif
    qUser:=fontx

```

```

    RegionSetWindowText("100.303";fontx)
endif
if(Popup1 = "Text Area/Line (Layouts)")
    if(fontx = "-NO CHANGE-")
        xxLay:=0
        xLay:=0
    else
        xxLay:=1
        xLay:=1
    endif
    qLay:=fontx
    RegionSetWindowText("100.304";fontx)
endif
if(Popup1 = "Text Area/Line (Backgrounds)")
    if(fontx = "-NO CHANGE-")
        xxBack:=0
        xBack:=0
    else
        xxBack:=1
        xBack:=1
    endif
    qBack:=fontx
    RegionSetWindowText("100.305";fontx)
endif
if(Popup1 = "Layout Items Only")
    if(fontx = "-NO CHANGE-")
        vTitle:=0
        vSub:=0
        vBullet:=0
        Doitx:=0
    else
        vTitle:=1
        vSub:=1
        vBullet:=1
        Doitx:=1
    endif
    qTitle:=fontx
    qSub:=fontx
    qBullet:=fontx
    qLayOnly:=fontx
    RegionSetWindowText("100.300";fontx)
    RegionSetWindowText("100.301";fontx)
    RegionSetWindowText("100.302";fontx)
endif
if(Popup1 = "Change All")
    if(fontx = "-NO CHANGE-")
        Doitx:=0
        Doitf:=0
        xxLay:=0
        xxBack:=0
        vTitle:=0
        vSub:=0
        vBullet:=0
        xUser:=0
        xLay:=0
        xBack:=0
    else
        Doitx:=1
        Doitf:=1
        xxLay:=1
        xxBack:=1
        vTitle:=1

```



```

        vSub:=1
        vBullet:=1
        xUser:=1
        xLay:=1
        xBack:=1
    endif
    qTitle:=fontx
    qSub:=fontx
    qBullet:=fontx
    qUser:=fontx
    qLay:=fontx
    qBack:=fontx
    qLayOnly:=fontx
    qNONE:=fontx
    for(k; 0; k<6; k+1)
        l:=NumStr(k;;)
        RegionSetWindowText("100.30"+l;fontx)
    endfor
endif
return
/*****
/* ROUTINE: CSETON
/* DESCRIPTION: Updates the font color, and color flags.
*****/
label(cseton)
Color1 = RegionGetSelectedText("100.2011")
if(Popup1 = "Title")
    if(colorx = "-NO CHANGE-")
        ccTitle:=0
    else
        Doitx:=1
        ccTitle:=1
    endif
    cTitle:=colorx
    TitleRGB[]=ConvertColor(cTitle; TitleRGB[])
    RegionSetWindowText("100.400";colorx)
endif
if(Popup1 = "Subtitle")
    if(colorx = "-NO CHANGE-")
        ccSub:=0
    else
        Doitx:=1
        ccSub:=1
    endif
    cSub:=colorx
    SubRGB[]=ConvertColor(cSub; SubRGB[])
    RegionSetWindowText("100.401";colorx)
endif
if(Popup1 = "Bullet/Text Chart")
    if(colorx = "-NO CHANGE-")
        ccBullet:=0
    else
        Doitx:=1
        ccBullet:=1
    endif
    cBullet:=colorx
    BulletRGB[]=ConvertColor(cBullet; BulletRGB[])
    RegionSetWindowText("100.402";colorx)
endif
if(Popup1 = "Text Area/Line")
    if(colorx = "-NO CHANGE-")
        ccUser:=0

```

```

        Doitc:=0
    else
        ccUser:=1
        Doitc:=1
    endif
    cUser:=colorx
    UserRGB[]=ConvertColor(cUser; UserRGB[])
    RegionSetWindowText("100.403";colorx)
endif
if(Popup1 = "Text Area/Line (Layouts)")
    if(colorx = "-NO CHANGE-")
        ccLay:=0
        xxLay:=0
    else
        ccLay:=1
        xxLay:=1
    endif
    cLay:=colorx
    LayRGB[]=ConvertColor(cLay; LayRGB[])
    RegionSetWindowText("100.404";colorx)
endif
if(Popup1 = "Text Area/Line (Backgrounds)")
    if(colorx = "-NO CHANGE-")
        ccBack:=0
        xxBack:=0
    else
        ccBack:=1
        xxBack:=1
    endif
    cBack:=colorx
    BackRGB[]=ConvertColor(cBack; BackRGB[])
    RegionSetWindowText("100.405";colorx)
endif
if(Popup1 = "Layout Items Only")
    if(colorx = "-NO CHANGE-")
        ccTitle:=0
        ccSub:=0
        ccBullet:=0
    else
        Doitx:=1
        ccTitle:=1
        ccSub:=1
        ccBullet:=1
    endif
    cTitle:=colorx
    cSub:=colorx
    cBullet:=colorx
    RegionSetWindowText("100.400";colorx)
    RegionSetWindowText("100.401";colorx)
    RegionSetWindowText("100.402";colorx)
    TitleRGB[]=ConvertColor(cTitle; TitleRGB[])
    SubRGB[]=ConvertColor(cSub; SubRGB[])
    BulletRGB[]=ConvertColor(cBullet; BulletRGB[])
endif
if(Popup1 = "Change All")
    if(colorx = "-NO CHANGE-")
        Doitx:=0
        Doitf:=0
        xxLay:=0
        xxBack:=0
        ccTitle:=0
        ccSub:=0
    endif
endif

```

```

        ccBullet:=0
        ccUser:=0
        ccLay:=0
        ccBack:=0
    else
        Doitx:=1
        Doitf:=1
        xxLay:=1
        xxBack:=1
        ccTitle:=1
        ccSub:=1
        ccBullet:=1
        ccUser:=1
        ccLay:=1
        ccBack:=1
    endif
    cTitle:=colorx
    cSub:=colorx
    cBullet:=colorx
    cUser:=colorx
    cLay:=colorx
    cBack:=colorx
    for(k; 0; k<6; k+1)
        l:=NumStr(k,;)
        RegionSetWindowText("100.40"+l;colorx)
    endfor
    TitleRGB[]=ConvertColor(cTitle; TitleRGB[])
    SubRGB[]=ConvertColor(cSub; SubRGB[])
    BulletRGB[]=ConvertColor(cBullet; BulletRGB[])
    UserRGB[]=ConvertColor(cUser; UserRGB[])
    LayRGB[]=ConvertColor(cLay; LayRGB[])
    BackRGB[]=ConvertColor(cBack; BackRGB[])
endif
return
/*****
/*  ROUTINE: DOITFONTS
/*  DESCRIPTION: Change Text Area/Line in either Slide Editor, Layout      Editor, or Background Editor.
*****/
label(Doitfonts)
if(vLay = 1)
    EditLayouts()
    vNum:=EnvNumberofLayouts()
endif
if(vBack = 1)
    EditBackground()
    vNum:=EnvNumberofBackgrounds()
endif
if(vShow = 1)
    SlideShowSlide()
    ShowSlide(1)
    vNum:=EnvNumberofSlides()
endif
WaitMsgDisplay ("Changing Text Areas and/or Lines... ")
for(h; 1; h<(vNum+1); h+1)
    for(j; 1; j<3; j+1)
        if(j=1)
            TextBoxCreate ()
            AddTextBox (x1;y1;x2;y2)
        endif
        if(j=2)
            TextLineCreate ()
            AddTextBox (x1;y1;x1;y1)

```

```

endif
Type (" ")
TextEditExit ()
UnselectAllObjects()
BeginSelect()
ObjectPointSelect (x1;y1;No!)
SelectLikeObjects()
if(vLay = 1)
    if(xLay =1)
        SetFontFace(qLay; ; vBold; vItalic; vUnder; ; ; TT!)
        RealizeFontChanges()
    endif
    if(ccLay = 1)
        ObjectSetFillForeground(LayRGB[1]; LayRGB[2]; LayRGB[3];0)
    endif
endif
if(vBack = 1)
    if(xBack = 1)
        SetFontFace(qBack; ; vBold; vItalic; vUnder; ; ; TT!)
        RealizeFontChanges()
    endif
    if(ccBack = 1)
        ObjectSetFillForeground(BackRGB[1]; BackRGB[2]; BackRGB[3];0)
    endif
endif
if(vShow = 1)
    if(xUser = 1)
        SetFontFace(qUser; ; vBold; vItalic; vUnder; ; ; TT!)
        RealizeFontChanges()
    endif
    if(ccUser = 1)
        ObjectSetFillForeground(UserRGB[1]; UserRGB[2]; UserRGB[3];0)
    endif
endif
UnselectAllObjects()
BeginSelect()
ObjectPointSelect (x1;y1;No!)
DeleteObjects()
ENDFOR
if(vLay = 1)
    LayoutNext()
endif
if(vBack = 1)
    BackgroundNext()
endif
if(vShow = 1)
    SlideNext()
endif
endif
Return
/*****
/*      ROUTINE: ConvertColor
/*      DESCRIPTION: Converts Colors to RGB values
/*****
Function ConvertColor(vColor; vRGB[]) // 1=RED, 2=GREEN, 3=BLUE
vRGB[1]:=0
vRGB[2]:=0
vRGB[3]:=0
if(vColor = "Black")
    // No change needed
endif
if(vColor = "White")

```

```

        vRGB[1]:=255
        vRGB[2]:=255
        vRGB[3]:=255
endif
if(vColor = "Red")
    vRGB[1]:=255
endif
if(vColor = "Blue")
    vRGB[3]:=255
endif
if(vColor = "Green")
    vRGB[2]:=255
endif
if(vColor = "Cyan")
    vRGB[2]:=255
    vRGB[3]:=255
endif
if(vColor = "Magenta")
    vRGB[1]:=255
    vRGB[3]:=255
endif
if(vColor = "Yellow")
    vRGB[1]:=255
    vRGB[2]:=255
endif
if(vColor = "Gray (Light)")
    vRGB[1]:=191
    vRGB[2]:=191
    vRGB[3]:=191
endif
if(vColor = "Gray (Dark)")
    vRGB[1]:=124
    vRGB[2]:=124
    vRGB[3]:=124
endif
Return(vRGB[])
EndFunc
/*****
//      ERROR ROUTINES
//*      DESCRIPTION: All error routines are located here.
/*****
label(nothing)
vFound:=1
return
label(fError)
MESSAGEBOX(vStatus; "ERROR"; "An error has occurred, ending macro. NOTE: Macro must be executed from slide editor.";
IconStop!)
Quit
/*****
//*      ROUTINE: HELP
//*      DESCRIPTION: Help message for macro.
/*****
Label(Help)
MessageBox(vStatus;"About the Change Font Macro";"Font settings will be changed throughout the slide show. The following will
not be changed: data and organization charts, text objects grouped with any other objects, and text with special effects such as
contour, explode, Quick3D, or QuickWarp. "; IconQuestion!)
Return
/*****
//      Wait Message Procedures
/*****
PROCEDURE WaitMsgInit ()
DialogDefine ("WaitMsg"; 50; 50; 150; 36; 16; "Please Wait")

```

```
DialogAddText ("WaitMsg"; "WaitText"; 8; 14; 144; 16; 1; "")
DialogLoad ("WaitMsg"; "Presentations")
Return
ENDPROC
```

```
PROCEDURE WaitMsgDisplay (Text)
RegionSetWindowText ("WaitMsg" + ".WaitText"; Text)
DialogShow ("WaitMsg";; WaitDlgCallBack)
ENDPROC
```

```
PROCEDURE WaitDlgCallBack ()
If (WaitDlgCallBack[5] = 274 And WaitDlgCallBack[6] = 61536)
    Assert (CancelCondition!)
EndIf
ENDPROC
```

```
PROCEDURE WaitMsgHide ()
DialogDismiss ("WaitMsg"; "WaitText")
ENDPROC
```

```
PROCEDURE WaitMsgDestroy ()
DialogDestroy ("WaitMsg")
ENDPROC
```