

LogOffServer Method (Application Object)

The **LogOffServer** method logs off an SQL server or ODBC data source. Use this method when you have logged on to the data source using **LogOnServer**.

Syntax

```
object.LogOffServer DLLName, ServerName, _DatabaseName,  
UserID, Password
```

Parameters

DLLName - Specifies the name of the DLL for the server or password protected non-SQL table you want to log on to, for example "PDSODBC.DLL". Note that the DLLName must be enclosed in quotes. DLL names have the following naming convention: PDB*.DLL for standard (non-SQL) databases, PDS*.DLL for SQL/ODBC databases.

ServerName - Specifies the log on name for the server used to create the report.* (For ODBC, use the data source name.) This value is case-sensitive.

DatabaseName (Optional) - Specifies the name for the database used to create the report.*

UserID (Optional) - Specifies the User ID number necessary to log on to the server.*

Password (Optional) - Specifies the password necessary to log on to the server.

**When you pass an empty string ("") for this parameter, the program uses the value that's already set in the report. If you want to override a value that's already set in the report, use a non-empty string (i.e., "Server A").*

Remarks

If you try to log off a server that is still in use (i.e., there is an object variable still in focus that holds reference to a report that requires being logged on to the server to access data) you will be unable to log off. This will apply to every object that comes from the **Report** Object, as they all hold reference to the report through their respective Report properties.