
Macintosh II Two-Page Monochrome Video Card and Expansion Kit





Overview

The Apple® Macintosh® IITwo-Pagel Monochrome Video Card providestheinterfacebetween the Apple Two-Page Mono-chrome Monitor and the Macintosh II computer. It allows for true grayscaling, displaying as many as four levelsofgrayatthesametime.

The optional Macintosh II **VideoCardExpansionKitcan** increasethedisplaycapabilitiesof yourAppleTwo-PageMonochromeMonitorto16graylevels.

Features

· Up to four shades of gray atone time Optional 4-bit expansion kit Adjustabledisplaymodes

NuBus™compatible

Offerstruegray-scalingfor

Benefits

- enhancing graphics, scanned images, and documents.
- Increases the display capability to 16 gray
- Lets you use the computer's Control Panel toselect2,4,or16graylevels.
- PlugsintoanyMacintoshIIslot.
- Isself-configuring.
- RS-170capability Providesinterlaced video output compatible withmanytypesofvideoequipment.



MacintoshIITwo-PageMonochrome VideoCardandExpansionKit

Product Details	Software-selectable display modes Using the Control Panel desk accessory, you can set the Macintosh II Two-Page Monochrome Video Card to display 1 or 2 bits per pixel. This provides, respectively, 2 or 4 gray levels on the Apple Two-Page Monochrome Monitor.	The ability to set a two-level displayensures that monochromatic Macintoshapplications can operate as quickly as possible. Optional 4-bit upgrade The Macintosh II Two-Page Monochrome Video Cardhasa display capability of 2 bits per pixel. Upgrading this to a 4-bit-per-	pixeldisplaywiththe Video Card Expansion Kitlets you view up to 16 gray levels on your monitor's screen simultaneously. The upgrade consists of eight video RAM chips, which fit into sockets on the Macintosh II Two-Page Monochrome Video Card.
System Requirements	TousetheMacintoshIITwo-Page MonochromeVideoCard,you need:	AMacintosh II personal computer with an available NuBus stot	
Technical Specifications	Interface NuBus-plugsintoany Macintosh II slot Output signals Modes: RGB (analog) and gray scale Video: RS-343 standard and RS-170 timing-standard interlaced video	Sync:separatesync,negative-going,TTL Connector D-style with three internal coaxial connectors and 10 pins Display modes 1 or 2 bits per pixel (2 or 4 graylevels)	Upgradable to 4 bits per pixel (16 gray levels) with the Macintosh II Video Card Expansion Kit Rasterrates Vertical: 75 hertz Horizontal: 68.7 kilohertz Dot clock: 100 megahertz Power consumption 10 watts
Ordering Information	Macintosh II Two-Page Monochrome Video Card	OrderNo.M0260	With your order, you'llreceive: MacintoshIITwo-Page Monochrome Video Card Extended ADB keyboard cable Limited warranty statement
	Macintosh II Video Card Expansion Kit*	OrderNo.M0213	With your order, you'll receive: Expansion kit-eight video RANdrips Limited warranty statement *Dealer in stallation is required.