

Click a folder icon to expand or collapse a list of topics for an item. To expand or collapse all folders, click the icon in the title of this topic. Read **Basics** if you are new to WinSight or new to this version of WinSight. If you need information on using the Help system, return to the Help menu and choose Using Help.



<u>Basics:</u> Overview of features; concepts you'll need to know for working with WinSight.



Tasks: Information on using WinSight.



Menu Commands: A list of WinSight menus.



Click a folder icon to expand or collapse a list of topics for an item. To expand or collapse all folders, click the icon in the title of this topic. Read **Basics** if you are new to WinSight or new to this version of WinSight. If you need information on using the Help system, return to the Help menu and choose Using Help.



<u>Basics:</u> Overview of features; concepts you'll need to know for working with WinSight.

- Getting Started
- Messages WinSight Tracks
- WinSight Views



Tasks: Information on using WinSight.

- Tracing Messages
- Using the Find Window Mode
- Using the Keyboard with WinSight
- Using the Messages Menu to Trace

Messages

- Using the Mouse with WinSight
- Using the Spy Menu to Display

Window Details

- Using the Start! and Stop! Menu
- Using the Tree Menu to Display the

Window Tree View

Using the View Menu to Display

WinSight Views



Menu Commands: A list of WinSight menus.

- Control Menu
- Spy Menu
- View Menu
- Tree Menu
- Messages Menu
- Stop! and Start! Menu
- Help Menu

Click a folder icon to expand or collapse a list of topics for an item. To expand or collapse all folders, click the icon in the title of this topic. Read **Basics** if you are new to WinSight or new to this version of WinSight. If you need information on using the Help system, return to the Help menu and choose Using Help.

- Basics: Overview of features; concepts you'll need to know for working with WinSight.
 - Getting Started
 - Messages WinSight Tracks
 - WinSight Views
- <u>Tasks:</u> Information on using WinSight.
- Menu Commands: A list of WinSight menus.

Click a folder icon to expand or collapse a list of topics for an item. To expand or collapse all folders, click the icon in the title of this topic. Read **Basics** if you are new to WinSight or new to this version of WinSight. If you need information on using the Help system, return to the Help menu and choose Using Help.

- <u>Basics:</u> Overview of features; concepts you'll need to know for working with WinSight.
- <u>Tasks:</u> Information on using WinSight.
 - Tracing Messages
 - Using the Find Window Mode
 - Using the Keyboard with WinSight
 - Using the Messages Menu to Trace

Messages

- Using the Mouse with WinSight
- Using the Spy Menu to Display

Window Details

- Using the Start! and Stop! Menu
- Using the Tree Menu to Display the

Window Tree View

Using the View Menu to Display

WinSight Views

Menu Commands: A list of WinSight menus.

Click a folder icon to expand or collapse a list of topics for an item. To expand or collapse all folders, click the icon in the title of this topic. Read **Basics** if you are new to WinSight or new to this version of WinSight. If you need information on using the Help system, return to the Help menu and choose Using Help.

- Basics: Overview of features; concepts you'll need to know for working with WinSight.
- <u>Tasks:</u> Information on using WinSight.



Menu Commands: A list of WinSight menus.

- Control Menu
- Spy Menu
- View Menu
- Tree Menu
- Messages Menu
- Stop! and Start! Menu
- Help Menu



Basics

WinSight gives you debugging information about window classes, windows, and messages. Using WinSight, you can study how any application creates classes and windows and monitor how windows send and receive messages.

WinSight uses three views to study applications:

- Window Tree view
- Class List view
- Message Trace view

WinSight is a passive observer: it intercepts and displays information about messages but does not prevent messages from getting to applications.

To watch windows sending and receiving messages, you can use WinSight to do the following:

- <u>Find</u> the window(s) you want to watch
- Trace the messages that get sent

What you need to know to begin using WinSight

Choose one of these topics for more information:

Getting Started

Messages WinSight Tracks

WinSight Views



Tasks

Choose one of these topics for information about using WinSight:

Tracing Messages

Using the Find Window Mode

Using the Keyboard with WinSight

Using the Messages Menu to Trace Messages

Using the Mouse with WinSight

Using the Spy Menu to Display Window Details

Using the Start! and Stop! Menu

Using the Tree Menu to Display the Window Tree View

Using the View Menu to Display WinSight Views



Getting Started

See Also

To start WinSight, double-click the WinSight icon.

The first time you start WinSight, it displays the Window Tree view.

When you exit, WinSight saves your configuration. If you open all three views and exit WinSight, the next time you start it, all three views will be displayed.

See Also WinSight Views

Using the Mouse with WinSight

Here is a list of actions with mouse and menu equivalents.

Action	With the mouse	With menus		
Select an item	Click			
Select multiple items	Ctrl+click			
Toggle highlighted item	Shift+click			
Show details of item	Double-click	Spy <u>Open Detail</u>		
Expand one level	Click on <+>	Tree Expand One Level		
Expand branch	Right-click on <+>	Tree Expand Branch		
Collapse branch	Click on <->	Tree CollapseBranch		
You can also use the mouse to resize the WinSight window or the panes.				

Using the Keyboard with WinSight

Here is a list of actions with keyboard and menu equivalents.

Action	With the keyboard	With menus
Select an item	Up or Down arrow	
Select multiple items	Ctrl+Shift Up or Down	
	arrow	
Move selection bar	Ctrl+Up or Down arrow	
Toggle highlighted item	Spacebar	
Expand one level	+	Tree Expand One Level
Expand branch	*	Tree Expand Branch
Expand tree completely	Ctrl+*	Tree Expand All
Collapse branch	-	Tree Collapse Branch

The right and left arrows scroll horizontally.

Use Tab or F6 to move the focus between panes. Use Shift+Tab or Shift+F6 to switch the focus in the opposite direction.

Using WinSight

See Also

WinSight gives you debugging information about window classes, windows, and messages. You can study how any application creates classes and windows, and monitor how windows send and receive messages.

WinSight uses three views to study applications:

- Window Tree view
- Class List view
- Message Trace view

WinSight is a passive observer: it intercepts and displays information about messages but does not prevent messages from getting to applications.

To watch Windows sending and receiving messages, you can use WinSight to

- Find the window(s) you want to watch
- Trace the messages that get sent.

See Also

WinSight Views

Find Window Mode

See Also

Find Window mode allows you to monitor how specific windows send and receive messages. To enter Find Window mode choose Spy|Find Window.

Note: All other applications are suspended while you are in Find Window mode.

Selecting Windows

In Find Window mode, you can select windows in one of two ways:

- Move the mouse into the boundaries of a window object. A thick border appears around that window object, and the corresponding window name is highlighted in the <u>Window Tree view</u>.
- Use the cursor keys to select windows from the Window Tree view. When you hightlight a window name, WinSight puts a thick border around the corresponding window object.

To leave Find Window mode, click the mouse button, or press Escape. This removes the border from the screen but leaves the current window selected in the Window Tree view.

If you press Enter or double-click the highlighted window in the Window Tree view, you will see the Detail window.

See Also

Tracing Messages

Tracing Messages

See Also

When you monitor how windows or classes send and receive messages, you are tracing the patterns of these messages.

By default WinSight traces all messages and displays them in the Message Trace view.

You can trace messages in one of three ways:

- Choose Messages|Selected Classes or Messages|Selected Windows, then shift-click to select the classes (in the <u>Class List view</u>) or windows (in the <u>Window Tree view</u>) you want to trace.
- Choose Messages|All Windows to select all the messages sent to windows.
- Choose Messages|Options, then select any or all of the ten groups of messages.

Choose <u>Stop!</u> or Messages|Trace Off to control when WinSight stops tracing messages. The Message Trace view remains visible.

To resume tracing, choose one of the following menu commands:

- Start!
- Messages|Selected Classes
- Messages|Selected Windows
- Messages|All Windows

See Also
Finding Windows
Messages Menu
Messages Winsight Traces



WinSight Menu Commands

Here is a list of the menus and menu commands in WinSight. The menus are listed in the order they appear.

Control Menu

Restore

Move

<u>Size</u>

Minimize

Maximize

Close

Switch to

Spy Menu

Open Detail

Find Window

<u>Exit</u>

View Menu

Class List

Window Tree

Message Trace

Split Horizontal

Split Vertical

Tree Menu

Expand One Level

Expand Branch

Expand All

Collapse Branch

Messages Menu

Trace Off

Selected Classes

Selected Windows

All Windows

Clear

Options...

Stop! and Start!

Help Menu

Index

Finding Windows

Tracing Messages

Menu Commands

Keyboard

Mouse

Using Help

About WinSight



Spy Menu

Use the Spy menu to display more details for a window, locate the window for which you want to trace messages, or exit WinSight.

The Spy menu commands are:

Open Detail

Find Window

<u>Exit</u>

Spy | Open Detail

Choose Spy|Open Detail to display more detail about the selected class or window.

Use this command to open the $\underline{\text{Detail window}}$. The information in the window depends on the current active view, indicated by the dotted rectangle.

Spy | Find Window

Choose Spy|Find Window to locate the window for which you want to trace messages. Use this command to enter <u>Find Window mode.</u>

Spy | Exit

Choose Spy|Exit to exit WinSight.



View Menu

Choose the View menu to select a $\underline{\text{view}}$ and how WinSight displays it, either horizontally or vertically.

The View commands are:

Class List

Window Tree

Message Trace

Split Horizontal

Split Vertical

WinSight Views

See Also

WinSight can display three views within its main window:

- Class List
- Window Tree
- Message Trace

The Window Tree view is the initial default view, but you can use the $\underline{\text{View menu}}$ to open or close any of these views.

When you exit WinSight, WinSight saves your current desktop configuration.

WinSight automatically tiles the views within the main window, however, you can resize them.

See Also

Tree Menu

View | Class List

Choose the View|Class List command to display the Class List view.

If the Class List view is displayed, choosing this command hides the view.

Note: The term "class" refers to the class name with which the window class was registered with Windows via the RegisterClass API function. It does not refer to C++ classes.

Class List View

See Also

The Class List view displays all the currently registered window classes.

The format for the classes in the Class List view is:

Class (Module) Function Styles

You can see more information about a window class in the <u>Detail window</u> by doing one of the following:

- Double-clicking the window class in the Class List view.
- Selecting the window class and press Enter.
- Selecting the window class and choose Spy|Open Detail.

See Also

Tree Menu View|Class List WinSight Views

View | Window Tree

Choose View|Window Tree to display the Window Tree view.

If the Window Tree view is displayed, choosing this command hides the view.

Window Tree View

See Also

The Window Tree view displays the hierarchy of windows on the desktop.

Use this display to do the following:

- Determine what windows are actually present.
- See the status of windows, including hidden windows.
- See which windows are receiving messages.
- Select the windows you want to trace messages for.

The format for the classes in the Window Tree view is:

Tree Handle {Class} Module Position "Title"

You can see more information about a window in the <u>Detail window</u> by doing one of the following:

- Double-click the window item in the view.
- Select the window item and press Enter.
- Select the window item and choose Spy|Open Detail.

See Also
Finding Windows
Tree Menu
View|Window Tree
WinSight Views

Detail Window

See Also

The Detail window displays the class name, executable module, and other information about the selected window or class.

See Also
Class List View
Window Tree View

View | Message Trace

Choose the View|Message Trace command to display the <u>Message Trace view</u>. If the Message Trace view is displayed, choosing this command hides the view.

Message Trace View

See Also

The Message Trace view displays information about messages received by selected windows or windows classes.

SendMessage messages are shown twice, once when they are sent and again when they return.

Dispatched messages are shown only once, since their return value is meaningless. The message display is indented to show how messages are nested within other messages.

The format for the messages in the Message Trace window is:

Handle "Title"-or-{Class} Message Status ...

Win32 Messages

Winsight checks if the task whose messages are being traced is a Win32 task. If so, it displays **[Win32]** immediately after the window handle on traced messages. These messages, however, are displayed in Win16 message format.

See Also View|<u>Message Trace</u> <u>WinSight Views</u>

View | Split Horizontal

Choose View|Split Horizontal to stack the $\underline{\text{views}}$ on top of one another.

View | Split Vertical

Choose View|Split Vertical to display the $\underline{\text{views}}$ side by side.

Class

The name of the window class.

Some predefined Windows classes have numeric names and are shown with the number and a name.

Module

The name of the executable module (.EXE or .DLL) that registered the class or created the window.

Function

The address of the class window function.

Styles

A list of the CS_ styles for the class. The names are the same as the CS_ definitions in WinTypes, except that the CS_ is removed and the name is in mixed case.

Tree

The lines and diamonds on the left of the view show the window tree structure. Each window is connected to its parent, siblings, and children.

Handle

The window handle returned by CreateWindow.

Position

The window's position.

If the window is hidden, the text "(hidden)" is displayed.

If the window is visible, the window coodinates are given as (xBegin,yBegin)-(xEnd,yEnd). Top-level windows use their own screen coordinates. Child windows use coordinates within the parent window client area.

Title

The window title or text, returned by GetWindowText or a WM_GETTEXT message. If the title is the null string, the quotation marks are omitted.

If the title is a null string in the Message Trace window, the class name is displayed in curly braces.

Message

The message name defined in WINDOWS.H.

Known undocumented Windows messages are shown in lower case.

Unknown message numbers (user-defined) are shown in one of the following formats:

- WM_USER+0xXXXX if they are greater than or equal to WM_USER
- WM_0xXXXX if they are less than WM_USER.

Registered message numbers (from RegisterWindowsMessage) are shown with their registered name in single quotation marks.

Status

One or more of the following items may be reported:

Dispatched The message was received via DispatchMessage

Sent [from XXXX] The message was received via SendMessage. If it was sent from another window,

"from XXXX" gives that window's handle. If it was sent from the same window receiving it, this is shown with "from self." If it was sent from Windows itself, the

"from" phrase is omitted.

Returns The message was received via SendMessage and is now returning.

...

Additional information specific to each message.

If a "returning message", the return value, either in numeric form, or more specific information for messages such as WM_GETTEXT.

If a "sent and dispatched message", the message parameters. WinSight interprets the parameters to give a readable display. If a message has associated data structures, those structures are included in the display.



Tree Menu

Choose the Tree menu to display, expand, or collapse window entries in the Window Tree view.

The diamonds on the left of the Class List and Window Tree windows invert color momentarily when the window receives a message. They also show if the window class has any children:

- The window has no children.
- The window has children, but they are hidden. To expand and see the children, click on the diamond, or select the window and press
- ①. To expand to show all levels of child windows, select a window and right-click.
- The window has children, and they are visible. To hide the children again, click the diamond, or select the parent window and press



The Tree menu commands are:

Expand One Level

Expand Branch

Expand All

Collapse Branch

Tree | Expand One Level (+)

See Also

Choose Tree|Expand One Level to expand an entry one level in the Window Tree view.

A plus sign in the diamond (+) next to an entry indicates that the window has children, but they are hidden.

See Also
Tree|Collapse Branch
Tree|Expand All
Tree|Expand Branch

Tree | Expand Branch (*)

See Also

Choose Tree|Expand Branch to expand an entire branch in the Window Tree view.

A plus sign in the diamond (+) next to an entry indicates that the window has children, but they are hidden.

See Also Tree|Collapse Branch

Tree|Expand All

Tree|Expand One Level

Tree | Expand All (Ctrl+*)

See Also

Choose Tree|Expand All to expand all branches that are collapsed in the Window Tree view.

A plus sign in the diamond (•) next to an entry indicates that the window has children, but they are hidden.

See Also

Tree|Collapse Branch

Tree|Expand Branch

Tree|Expand One Level

Tree | Collapse Branch (-)

See Also

Choose Tree|Collapse Branch to collapse an entire branch in the Window Tree view.

A minus sign in the diamond (🗢) next to an entry indicates that the window's children are currently hidden.

See Also
Tree|Expand All
Tree|Expand Branch
Tree|Expand One Level

Messages Menu

See Also

Choose the Messages menu to select the types of messages you want to trace for the selected window(s).

You can configure WinSight to trace messages by:

- Window
- Window class
- Message type
- A combination of these

The Messages menu commands are:

Trace Off

Selected Classes

Selected Windows

All Windows

Clear

Options...

See Also Messages WinSight Traces

Messages | Selected Classes

Choose Messages|Selected Classes to trace messages going to a particular class.

This command is active only if you select a class in the Class List view.

Changing the selection in the Class List view will immediately change which windows have messages traced.

Choose Messages|Selected Classes to open the Message Trace view when it is hidden.

Messages | Selected Windows

Choose Messages|Selected Windows to trace messages going to a particular window.

This command is active only if you select a window in the Window Tree view.

Changing the selection in the Window Tree view will immediately change which windows have messages traced.

Choose Messages|Selected Windows to open the Message Trace view when it is hidden.

Messages | All Windows

Choose Messages|All Windows to trace all messages, regardless of what is selected in the <u>Window Tree view</u> or the <u>Class List view</u>.

Choose Windows|All Windows to open the Message Trace view when it is hidden.

Messages | Trace Off

Choose Messages|Trace Off to turn off message tracing. The Message Trace view remains visible.

Tracing resumes when you choose one of the following menu commands:

- Messages|<u>Selected Classes</u> Messages|<u>Selected Windows</u>
- Messages All Windows

You can also use Stop! to turn off message tracing.

Messages | Clear

Choose Messages|Clear to clear all messages in the Message Trace view.

Messages | Options...

Choose Messages|Options... to open the Message Trace Options dialog box.

Use the Messages Trace Options dialog box to choose the types of messages you want to trace.

Messages to Trace check boxes

Use the $\underline{\text{Messages to Trace check boxes}}$ and the $\underline{\text{Individual Messages List Box}}$ to choose which messages to trace.

Interpret and Hex Values check boxes

Use the Interpret and Hex Values check boxes to determine the message display format.

Log File check box

Use the <u>Log File check box</u> to log traced messages.

Messages to Trace Check Boxes

See Also

Use the Messages to Trace check boxes on the Message Trace Options dialog box to choose the types of messages to trace.

You can configure WinSight to trace any of the following:

- All messages
- Subgroups of messages
- Individual messages
- A combination of groups and individual messages

All Messages

The All Messages checkbox allows you to select or deselect all ten subgroups of messages.

When All Messages is selected, all messages in the Individual Messages Display Box are highlighted. The All Messages checkbox is dimmed when the list box is used to either select or deselect an individual message.

Message Subgroups

To select specific <u>types of messages</u>, uncheck All Messages and check individual message groups. Checking the All Messages checkbox also turns on these checkboxes. Unchecking the All Messages checkbox turns off previously selected subgroup checkboxes.

When a subgroup is selected, the messages in that subgroup are highlighted in the Individual Messages Display Box. The subgroup checkbox is dimmed when the list box is used to either select or deselect an individual message in that group.

"Other" checkbox

The "Other" checkbox allows tracing of all messages that WinSight does not know about, such as unknown WM_USER+xxxx and registered messages. This checkbox must be on for these messages to be traced. Checking the All Messages checkbox also turns on this checkbox.

Individual Messages List Box

The Individual Messages List Box displays all of the messages that WinSight knows about. It is here that individual messages are selected or deselected. The All Messages checkbox and corresponding subgroup checkboxes are dimmed to indicate when individual messages are selected or deselected.

See Also

Messages|Options

Mouse Messages

See Also

Check Mouse on the Message Trace Options dialog box to trace mouse messages.

The mouse messages that WinSight traces are:

WM_HSCROLL

WM_LBUTTONDBLCLK

WM_LBUTTONDOWN

 ${\sf WM_LBUTTONUP}$

WM_MBUTTONDBLCLK

WM_MBUTTONDOWN

WM_MBUTTONUP

WM_MOUSEACTIVATE

WM_MOUSEMOVE

WM_RBUTTONDBLCLK

WM_RBUTTONDOWN

WM_RBUTTONUP

WM_SETCURSOR

WM_VSCROLL

Window Messages

See Also

Check Window on the Message Trace Options dialog box to trace window messages.

The window messages that WinSight traces are (those messages in lowercase are undocumented Windows messages):

WM_ACTIVATE

WM ACTIVATEAPP

WM_CANCELMODE

WM_CHILDACTIVATE

WM CLOSE

WM_CREATE

WM_CTLCOLOR

WM_DESTROY

WM_ENABLE

WM_ENDSESSION

WM ERASEBKGND

WM_GETDLGCODE

WM GETMINMAXINFO

WM_GETTEXT

WM_GETTEXTLENGTH

WM ICONERASEBKGND

WM_KILLFOCUS

WM_MOVE

WM PAINT

wm_painticon

WM_QUERYDRAGICON

WM QUERYENDSESSION

WM QUERYNEWPALETTE

WM_QUERYOPEN

WM QUIT

WM_SETFOCUS

WM SETFONT

WM_SETREDRAW

WM SETTEXT

WM_SHOWWINDOW

WM SIZE

WM_WINDOWPOSCHANGED

WM_WINDOWPOSCHANGING

Input Messages

See Also

Check Input on the Message Trace Options dialog box to trace input messages.

The input messages that WinSight traces are (those messages in lowercase are undocumented Windows messages):

WM_CHAR

WM CHARTOITEM

WM_COMMAND

WM_DEADCHAR

WM KEYDOWN

WM_KEYUP

WM_KEYLAST

WM MENUSELECT

WM_MENUCHAR

WM PARENTNOTIFY

WM SYSCHAR

WM_SYSKEYDOWN

WM SYSKEYUP

WM_SYSDEADCHAR

WM_TIMER

WM_VKEYTOITEM

sm_yomichar

Notification Control Messages

BN_CLICKED

BN_DOUBLECLICKED

BN CLOSEUP

BN_DBLCLK

BN_DROPDOWN

BN EDITCHANGE

CBN_CLOSEUP

CBN DBLCLK

CBN DROPDOWN

CBN EDITCHANGE

CBN_EDITUPDATE

CBN ERRSPACE

CBN_KILLFOCUS

CBN SELCHANGE

CBN_SELENDCANCEL

CBN SELENDOK

CBN_SETFOCUS

EN CHANGE

EN_ERRSPACE

EN_HSCROLL

EN_KILLFOCUS

EN_MAXTEXT

EN_SETFOCUS

EN_UPDATE

EN_VSCROLL

LBN_DBLCLK

LBN_ERRSPACE

LBN_KILLFOCUS

LBN_SELCANCEL

LBN_SELCHANGE

LBN_SETFOCUS

System Messages

See Also

Check System on the Message Trace Options dialog box to trace system messages.

The system messages that WinSight traces are:

WM_COMPACTING

WM_DEVMODECHANGE

WM_ENTERIDLE

WM_FONTCHANGE

WM_NULL

WM_PALETTECHANGED

WM_PALETTEISCHANGING

WM_POWER

WM_QUEUESYNC

WM_SPOOLERSTATUS

WM_SYSCOLORCHANGE

WM_SYSCOMMAND

WM_TIMECHANGE

WM_WININICHANGE

Pen Messages

See Also

Check Pen on the Message Trace Options dialog box to trace pen messages.

The pen messages that WinSight traces are:

WM_RCRESULT

WM_HOOKRCRESULT

WM_GLOBALRCCHANGE

WM_SKB

WM_HEDITCTL

Initialization Messages

See Also

Check Initialization on the Message Trace Options dialog box to trace initialization messages.

The initialization messages that WinSight traces are:

WM_INITDIALOG

WM_INITMENU

WM_INITMENUPOPUP

Clipboard Messages

See Also

Check Clipboard on the Message Trace Options dialog box to trace initialization messages.

The clipboard messages that WinSight traces are:

WM_ASKCBFORMATNAME

WM_CHANGECBCHAIN

WM_CLEAR

WM_COPY

WM_CUT

WM_DESTROYCLIPBOARD

WM_DRAWCLIPBOARD

WM_HSCROLLCLIPBOARD

WM_PAINTCLIPBOARD

WM_PASTE

WM_RENDERALLFORMATS

WM_RENDERFORMAT

WM_SIZECLIPBOARD

WM_UNDO

WM_VSCROLLCLIPBOARD

DDE Messages

See Also

Check DDE on the Message Trace Options dialog box to trace dynamic data exchange messages.

The DDE messages that WinSight traces are:

WM_DDE_ACK

WM_DDE_ADVISE

WM_DDE_DATA

WM_DDE_EXECUTE

WM_DDE_INITIATE

WM_DDE_POKE

WM_DDE_REQUEST

WM_DDE_TERMINATE

WM_DDE_UNADVISE

Non Client Messages

See Also

Check Non Client on the Message Trace Options dialog box to trace non client messages.

The non client messages that WinSight traces are:

WM_NCACTIVE

WM_NCCALCSIZE

WM_NCCREATE

WM_NCDESTROY

WM_NCHITTEST

WM_NCLBUTTONDBLCLK

WM_NCLBUTTONDOWN

WM_NCLBUTTONUP

WM_NCMBUTTONDBLCLK

WM_NCMBUTTONDOWN

WM_NCMBUTTONUP

WM_NCMOUSEMOVE

WM_NCPAINT

WM_NCRBUTTONDBLCLK

WM_NCRBUTTONDOWN

WM_NCRBUTTONUP

Controls Messages

See Also

Check Controls on the Message Trace Options dialog box to trace control messages.

The control messages that WinSight traces are:

BM_GETCHECK

BM_GETSTATE

BM_SETCHECK

BM_SETSTATE

BM_SETSTYLE

CB ADDSTRING

CB_DELETESTRING

CB_DIR

CB_FINDSTRING

CB FINDSTRINGEXACT

CB_GETCOUNT

CB GETCURSEL

CB_GETDROPPEDCONTROLRECT

CB_GETDROPPEDSTATE

CB_GETEDITSEL

CB GETEXTENDEDUI

CB_GETITEMDATA

CB GETITEMHEIGHT

CB GETLBTEXT

CB_GETLBTEXTLEN

CB_INSERTSTRING

CB_LIMITTEXT

CB_RESETCONTENT

CB SELECTSTRING

CB_SETCURSEL

CB_SETEDITSEL

CB SETEXTENDEDUI

CB_SETITEMDATA

CB_SETITEMHEIGHT

CB_SHOWDROPDOWN

DM_GETDEFID

DM_SETDEFID

EM_CANUNDO

EM_EMPTYUNDOBUFFER

EM_FMTLINES

EM_GETFIRSTVISIBLELINE

EM_GETHANDLE

EM_GETLINE

EM_GETLINECOUNT

EM_GETMODIFY

- EM_GETPASSWORDCHAR
- EM_GETRECT
- **EM_GETSEL**
- EM_GETWORDBREAKPROC
- **EM LIMITTEXT**
- EM_LINEFROMCHAR
- **EM_LINEINDEX**
- **EM_LINELENGTH**
- **EM LINESCROLL**
- EM_REPLACESEL
- EM_SETHANDLE
- **EM_SETMODIFY**
- EM_SETPASSWORDCHAR
- EM_SETREADONLY
- **EM SETRECT**
- EM_SETSEL
- **EM_SETRECTNP**
- EM_SETTABSTOPS
- EM_SETWORDBREAK
- EM_SETWORDBREAKPROC
- EM_UNDO
- LB_ADDSTRING
- LB_DELETESTRING
- LB_DIR
- LB_FINDSTRING
- LB_FINDSTRINGEXACT
- LB_GETCARETINDEX
- LB_GETCOUNT
- LB GETCURSEL
- LB_GETHORIZONTALEXTENT
- LB_GETITEMDATA
- LB_GETITEMHEIGHT
- LB_GETITEMRECT
- LB_GETSEL
- LB_GETSELCOUNT
- LB_GETSELITEMS
- LB_GETTEXT
- LB_GETTEXTLEN
- LB_GETTOPINDEX
- LB_INSERTSTRING
- LB_RESETCONTENT
- LB_SELECTSTRING
- LB_SELITEMRANGE
- LB_SETCARETINDEX

LB_SETCOLUMNWIDTH

LB_SETCURSEL

LB_SETHORIZONTALEXTENT

LB_SETITEMDATA

LB_SETITEMHEIGHT

LB_SETSEL

LB_SETTABSTOPS

LB_SETTOPINDEX

STM_GETICON

STM_SETICON

Multimedia Messages

See Also

Check Multimedia on the Message Trace Options dialog box to trace multimedia messages.

The multimedia messages that WinSight traces are:

MM_JOY1MOVE

MM_JOY1BUTTONDOWN

MM_JOY1BUTTONUP

MM_JOY1ZMOVE

MM_JOY2MOVE

MM_JOY2BUTTONDOWN

MM_JOY2BUTTONUP

MM_JOY2ZMOVE

MM_MCINOTIFY

MM_MIM_CLOSE

MM_MIM_DATA

MM_MIM_ERROR

MM_MIM_LONGDATA

MM_MIM_LONGERROR

MM_MIM_OPEN

MM_MOM_CLOSE

MM_MOM_DONE

MM_MOM_OPEN

MM_WIM_CLOSE

MM_WIM_DATA

MM_WIM_OPEN

MM_WOM_CLOSE

MM_WOM_DONE

MM_WOM_OPEN

Other Messages

See Also

Check Other on the Message Trace Options dialog box to trace other types of messages.

The other messages that WinSight traces are (those messages in lowercase are undocumented Windows messages):

wm alttabactive

wm_begindrag

WM_COMMNOTIFY

WM_COMPAREITEM

wm convertrequest

wm_convertresult

WM_DELETEITEM

wm_dragloop

wm_dragmove

wm_dragselect

WM DRAWITEM

WM_DROPFILES

wm dropobject

wm_entermenuloop

wm_entersizemove

wm exitmenuloop

wm_exitsizemove

wm_filesyschange

WM GETFONT

wm_gethotkey

wm_isactiveicon

wm Ibtrackpoint

WM MDIACTIVATE

WM_MDICASCADE

WM MDICREATE

WM_MDIDESTROY

WM MDIGETACTIVE

WM_MDIICONARRANGE

WM_MDIMAXIMIZE

WM_MDINEXT

WM MDIRESTORE

WM_MDISETMENU

WM MDITILE

WM_MEASUREITEM

WM NEXTDLGCTL

wm_nextmenu

wm querydropobject

wm_queryparkicon

wm_setvisible

wm_sethotkey wm_sizewait wm_syncpaint wm_synctask WM_SYSTEMERROR wm_systimer wm_testing

Interpret and Hex Values Check Boxes

See Also

The Interpret and Hex Values check boxes determine the format of the Message Trace view display.

Turn the Interpret Values check box on to interpret message parameters and return values in a readable format.

Turn the Hex Values check box on to display message parameters as Hex Values of wParam and IParam, and also return Values as Hex.

See AlsoMessages|Options

Log File Check Box

See Also

Check Log File to log trace messages to a file.

Enter a file name in the input box below the check box. If the file already exists, messages are appended to the end of the file.

To stop logging messages to the file, turn off the Log File check box.

See AlsoMessages|Options

Messages WinSight Tracks

See Also

The messages that WinSight tracks are listed under the following group headings.

Click a group to see the corresponding list of messages tracked by WinSight.

Mouse

<u>Window</u>

<u>Input</u>

<u>System</u>

<u>Pen</u>

Initialization

Clipboard

<u>DDE</u>

Non Client

Control

MultiMedia

<u>Other</u>

See Also

Messages|Options

Stop! and Start! Menu

See Also

Use the Stop! and Start! menu to turn off or on real-time updating in WinSight.

All views are kept current as classes are registered, windows are created and destroyed, and messages are received.

This command is a toggle. When you choose Stop! to suspend activity, the command changes to Start!. When you choose Start! to resume activity, the command changes to Stop!.

Using Stop! allows you to study a particular situation. It also removes the overhead of having WinSight update itself constantly.

You can also use Messages Trace Off to stop message tracing.

See Also Tracing Messages

Help Menu

The Help menu provides access to online Help, which comes up in a special Help window. One-line menu hints also appear on the status line at the bottom of the screen whenever you select a menu command.

The Help menu commands are:

<u>Index</u>

Finding Windows

Tracing Messages

Menu Commands

Keyboard

Mouse

Using Help

About WinSight

Help | Index (F1)

The WinSight online Help has a <u>contents screen</u> that summarizes the organization and contents of the Help system.

To access the Help system from the index, choose one of the highlighted words or pictures on the contents: click it or Tab to it and then press Enter.

For more information on how to use a Help system under Windows, choose the $\text{Help}|\underline{\text{Using Help}}$ menu command.

Help | Finding Windows

The Help|Finding Windows command displays help on locating windows.

Help | Tracing Messages

The Help|Tracing Messages command displays help on tracing messages.

Help | Menu Commands

Help|Menu Commands displays help on WinSight menus.

Help | Keyboard

The Help|Keyboard command displays help on the <u>keyboard</u>.

Help | Mouse

The Help|Mouse command displays help on the <u>mouse</u>.

Help | Using Help

The Help|Using Help command displays information on how to use the WinSight Help system (or any other Help system under Windows).

Help | About

The About command displays a dialog box that shows copyright and version information. Click OK or Enter to close the About dialog box.

Control Menu

The WinSight Control-menu box is on the far left of the title bar. Click it once or press Alt+Spacebar to display the menu.

The commands that appear on this menu affect the WinSight desktop.

The WinSight Control menu commands are:

Restore

<u>Move</u>

<u>Size</u>

Minimize

<u>Maximize</u>

Close

Switch To

Control | Restore

The Restore command returns the WinSight desktop window to its previous size.

This command is available only if the WinSight desktop window is <u>maximized</u> or <u>minimized</u>.

Control | Move

The Move command moves the WinSight desktop window with your keyboard.

Use the arrow cursor keys to move it, and press Enter when you finish.

You cannot use this command if the WinSight desktop is maximized.

You can also move the window by dragging its title bar to the desired position.

Control | Size

The Size command changes the size of the WinSight desktop window with your keyboard.

Use the arrow cursor keys to move the window borders. Press Enter when you are satisfied with the window size.

Size is available only if the WinSight desktop is not maximized.

Control | Minimize

The Minimize command turns the WinSight desktop into the WinSight icon.

You can choose this command only if the WinSight desktop window is not minimized.

Control | Maximize

The Maximize command zooms the WinSight desktop to fill your entire screen.

You can choose this command only if the WinSight desktop window is not maximized.

Control | Close

The Close command closes the WinSight desktop and unloads WinSight from memory. You can also click the Control-menu box in the upper left corner to close the window.

Control | Switch To

The Switch To command displays the $\underline{\text{Task List}}$ dialog box where you can switch from one application to another and rearrange application windows.

Task List Dialog Box

Use the Task List dialog box to switch to another application and rearrange application windows.

Task List list box

The Task List list box displays all open applications. To choose the application you want, double-click it.

From the keyboard, follow these steps:

- 1 Press the Up or Down arrow keys to reach the application you want.
- 2 Press Enter to choose it.
- 3 Switch to the application and rearrange windows with Action Buttons.

Action Buttons

Use the Action buttons to switch to another application and rearrange application windows.

- With the mouse, click the action button you want.
- With the keyboard, press Tab to go to the action button, then press Enter.

Switch To

The Switch To button switches to another application in the list box.

End Task

The End Task button closes the selected application in the list box.

Cascade

The Cascade button arranges the application windows in an overlap style.

Tile

The Tile button arranges the application windows in a tile fashion (side-by-side).

Arrange Icons

The Arrange Icons button evenly spaces the icons across the bottom of the desktop.