

*Popup Xtra castmember functions:*

**setMenu (member memberID, string menuText)**

*set the text of the menu definition*

**getMenu (member memberID)**

*get the text of the current menu*

**clearMenu (member memberID)**

*clear the entire menu definition*

**refreshMenu (member memberID)**

*refresh the menu definition based on the current setting for the menuField property*

**redraw(member memberID)**

*redraws the sprite on the stage which should be called whenever the palette changes*

**appendItem (member memberID, string menuText, string menuSpec)**

*append a menu item to the menu definition*

**insertItem (member memberID, string menuText, string menuSpec)**

*insert a menu item in the menu definition*

**deleteItem (member memberID, string menuSpec)**

*delete a menu item from the menu*

**disableItem (member memberID, string menuSpec)**

*disable a menu item in the menu definition*

**enableItem (member memberID, string menuSpec)**

*enable a menu item in the menu definition*

**getItem (member memberID, string menuSpec)**

*get the menu item stored in a specific place in the menu definition*

**setItem (member memberID, string menuSpec, string menuText)**

*set the menu item stored in a specific place in the menu definition*

**clearMarks (member memberID)**

*clear all marks stored for the selected menu items*

**setBackcolor (member memberID, indexValue or rgbValue)**

*set the background color of the menu and sprite*

**setForecolor** (member memberID, indexValue or rgbValue)  
set the foreground color of the menu and sprite

**setItemMark** (member memberID, string menuspec, integer markType)  
set the item mark stored for the specified menu item

**setItemStyle** (member memberID, string menuspec, integer styleCode)  
(Macintosh only)  
set the style appearance of a specific menu item of the menu

**getBackcolor** (member memberID)  
returns the indexed background color value

**getForecolor** (member memberID)  
returns the indexed foreground color value

**getItemMark** (member memberID, string menuspec)  
returns the item mark for the specified menu item

**getItemStyle** (member memberID, string menuspec) (Macintosh only)  
returns the style appearance of a specific menu item of the menu