

RAM Upgrade: Only 60ns, 72-pin, SIMMs may be used.

12 MB - Apple 4MB SIMM pre-installed along with 8MB of RAM soldered on the motherboard.

16 MB - Install an additional 4MB SIMM. [For best print quality when printing legal size documents].

20 MB - Install an additional 8MB SIMM.

24 MB - Remove the base 4MB SIMM and install two 8MB SIMMs *OR* one 16MB SIMM.

28 MB - Remove the base 4MB SIMM and install one 4MB SIMM and one 16MB SIMM.

32 MB - Remove the base 4MB SIMM and install one 8MB SIMM and one 16MB SIMM.

40 MB - Remove the base 4MB SIMM and install two 16MB SIMMs.

Page Description Language / Emulation:
PostScript® level 2.

Print Engine:
30MHz AMD 29030 RISC processor with an Engine life of 300,000 pages monochrome, 150,000 pages color.

Speed:
12 pages per minute for monochrome. 3 pages per minute for color.
1 page per minutes for transparencies. Actual Speed depends on image complexity.

Print Quality:
True 600-dpi resolution.
Color PhotoGrade, Apple's technology standard enhanced 600-dpi imaging.
200-lines per inch.

Fonts:
Apple Font Library: 64 fonts total.
39 fonts in ROM from the following font families: ITC Avant Garde Gothic, ITC Bookman, Courier, Helvetica, Helvetica Narrow, Helvetica Condensed, New Century Schoolbook, Palatino, Symbol, Times, ITC Zapf Chancery, and ITC Zapf Dingbats. 64 fonts on Macintosh disk from the following font families: Chicago, Delphian, ITC Garamond

Narrow, Geneva, Helvetica Black, Helvetica Compressed, Lubalin Graph, Lucida Bright, Machine, Monaco, Nadianne, New York, Old English Text, Onyx, Oxford, Swing, and Zeal. Any TrueType or PostScript (Type 1) fonts.

Interfaces:

Simultaneous connection to Ethernet, LocalTalk and bidirectional parallel interfaces.

Simultaneous support for AppleTalk, Novell Netware IPX, and TCP/IP networking protocols.

Internal and external SCSI ports for optional hard disk font storage.

Expandability:

Supports optional large-capacity internal and external hard disks for additional font storage.

Paper Capacities:

Standard:

250-sheet feeder, 100 sheet multipurpose tray

Optional:

250-sheet universal feeder.

Print Materials:

Media: 16- to 28-lb. (60 to 90 g/m²) bond.

Paper: U.S. letter, U.S. legal, A4, B5.

Most letterhead and colored stock.

Use only Apple Color LaserWriter 12/600 PS transparencies.

Power Requirements:

U.S. and Japan: 100 to 120 VAC, 50 to 60 Hz.

Europe and Australia: 220 to 240 VAC, 50 Hz.

Power Consumption:

Operating: 110/120V, 535W; 220/240V, 524W average.

Standby: 110/120V, 215W; 220/240V, 238W average.

Energy-saving mode: 42W (complies with EPA Energy Star)