

**Supported System Software: 7.1.1, 7.5, 7.5.1, 7.5.3**

**SCSI: none**

**Serial Ports: 1**

**Sound Output: mono 8 bit.**

**ADB: see below**

**Ethernet: see below**

**Machine Gestalt ID: 102**

**Minutiae:**

**Apple sometimes advertises this as a 66 MHz machine, since the clock speed is doubled inside the processor chip. However, all I/O to the processor is done at 33 MHz.**

**9" active matrix LCD - 4 bit (16 grays) Display.**

**Has a 152-pin PDS (Processor Direct Slot) connector for connecting to the Duo Docking Bars. Newer Technology makes the following Docking Bars:**

**Part # 7MD-S ----- SCSI MicroDock w/ ADB**

**Part # 7MD-F ----- Floppy MicroDock w/ ADB**

**Part # 7MB-P ----- PC Card MicroDock w/ ADB**

**Part # 7MD-E ----- Ethernet MicroDock w/ ADB**

**Part # 7MD-C ----- Color MicroDock w/ Audio & ADB**

**Part # 7UD16SC --- 16sc UltraDock w/ SCSI, Color, Floppy, Audio & ADB**

**Part # 7UD16SCE -- 16sce UltraDock w/ SCSI, Color, Ethernet, Floppy, Audio & ADB**

**Original Enabler: PowerBook enabler v2.0**

**Serial Port with the phone icon supports synchronous modems, with handshaking on both the output and input.**

**Has 1 MB ROM.**