XPM Manual

The **X** **P**ix**M**ap Format

Version : 3.2g

April 26th 1993

Arnaud Le Hors
lehors@sophia.inria.fr

© BULL 1990-93

Copyright restrictions

Copyright 1990-93 GROUPE BULL

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of GROUPE BULL not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. GROUPE BULL makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

GROUPE BULL disclaims all warranties with regard to this software, including all implied warranties of merchantability and fitness, in no event shall GROUPE BULL be liable for any special, indirect or consequential damages or any damages whatsoever resulting from loss of use, data or profits, whether in an action of contract, negligence or other tortious action, arising out of or in connection with the use or performance of this software.

Acknowledgements

I want to thank my team partner and friend Colas Nahaboo who proposed me this project, and who actively participates to its design. I also want to thank all the users who help me to improve the library by giving feed back and sending bug reports.

Arnaud Le Hors
KOALA Project – BULL Research c/o INRIA
2004 route des Lucioles – 06565 Valbonne Cedex – FRANCE

Support

You can mail any question or suggestion relative to **XPM** by electronic mail to `lehors@sophia.inria.fr`. There is also a mailing list, please mail requests to `xpm-talk-request@sophia.inria.fr` to subscribe. You can find the latest release by anonymous ftp on avahi.inria.fr (138.96.24.30) or export.lcs.mit.edu (18.30.0.238), and also an archive of the mailing list on avahi.

Table of Contents

1 Introduction 1

2 The XPM Format 1

3 The XPM Library 4

- 3.1 The XPM types 4
- 3.2 Functions to deal with XPM files 6
- 3.3 Functions to deal with XPM data 9
- 3.4 Functions to deal with XPM files and data 11
- 3.5 Functions to deal with XPM buffers 12
- 3.6 Functions to deal with XPM files and buffers 13
- 3.7 Miscellaneous functions 14

1 Introduction

First, Why another image format? We (Koala team at Bull Research, France) felt that most images bundled with X applications will be small "icons", and that since many applications are color-customizable, existing image formats such as gif, tiff, iff, etc... were intended for big images with well-defined colors and so weren't adapted to the task. So **XPM** was designed with these criterions in mind:

- be editable by hand (under emacs, vi...). Color pixmap editors aren't available everywhere.
- be includable in C code. It is unreasonable to load 1000 pixmap files on each start of an application.
- be a portable, mailable ascii format.
- provide defaults for monochrome/color/grayscale renderings.
- provide overriding of colors. This way if the user wants your application to be bluish instead of greenish, you can use the SAME icon files.
- allow comments to be included in the file.
- compression must be managed apart of the format.

2 The XPM Format

The **XPM** format presents a C syntax, in order to provide the ability to include **XPM** files in C and C++ programs. It is in fact an array of strings composed of six different sections as follows:

```
/* XPM */ static char* <variable_name>[] = {
<Values>
<Colors>
<Pixels>
<Extensions>
};
```

The words are separated by a white space which can be composed of space and tabulation characters.

The `<Values>` section is a string containing four or six integers in base 10 that correspond to: the pixmap width and height, the number of colors, the number of characters per pixel (so there is no limit on the number of colors), and, optionally the hotspot coordinates and the **XPMEXT** tag if there is any extension following the `<Pixels>` section.

```
<width> <height> <ncolors> <cpp> [<x_hotspot> <y_hotspot>] [XPMEXT]
```

The `Colors` section contains as many strings as there are colors, and each string is as follows:

```
<chars> {<key> <color>}+
```

Where `<chars>` is the `<chars_per_pixel>` length string (not surrounded by anything) representing the pixels,

<color> is the specified color, and <key> is a keyword describing in which context this color should be used. Currently the keys may have the following values:

m	for mono visual
s	for symbolic name
g4	for 4-level grayscale
g	for grayscale with more than 4 levels
c	for color visual

Colors can be specified by giving the colorname, a # followed by the RGB code in hexadecimal, or a % followed by the HSV code (not implemented). The symbolic name provides the ability of specifying the colors at load time and not to hard-code them in the file. Also the string **None** can be given as a colorname to mean "transparent". Transparency is handled by providing a masking bitmap in addition to the pixmap.

The <Pixels> section is composed by <height> strings of <width> * <chars_per_pixel> characters, where every <chars_per_pixel> length string must be one of the previously defined groups in the <Colors> section.

Then follows the <Extensions> section which must be labeled, if not empty, in the <Values> section as previously described. This section may be composed by several <Extension> subsections which may be of two types:

- one stand alone string composed as follows:

  ```
  XPMEXT <extension-name> <extension-data>
  ```

- or a block composed by several strings:

  ```
  XPMEXT <extension-name>
  <related extension-data composed of several strings>
  ```

Finally, if not empty, this section must end by the following string:

```
XPMENDEXT
```

To avoid possible conflicts with extension names in shared files, they should be prefixed by the name of the company. This would ensure unicity.

Below is an example which is the XPM file of a plaid pixmap. This is a 22x22 pixmap, with 4 colors and 2 characters per pixel. The hotspot coordinates are (0, 0). There are symbols and default colors for color and monochrome visuals. Finally there are two extensions.

```
/* XPM */
static char * plaid[] = {
/* plaid pixmap
 * width height ncolors chars_per_pixel */
"22 22 4 2 0 0 XPMEXT",
/* colors */
"   c red    m white  s light_color ",
"Y  c green  m black  s lines_in_mix ",
"+  c yellow m white  s lines_in_dark ",
"x          m black  s dark_color ",
/* pixels */
"x   x   x x x   x   x x x x x x + x x x x x ",
"  x   x   x   x   x   x x x x x x x x x x x ",
"x   x   x x x   x   x x x x x x + x x x x x ",
"  x   x   x   x   x   x x x x x x x x x x x ",
"x   x   x x x   x   x x x x x x + x x x x x ",
"Y Y Y Y Y x Y Y Y Y + x + x + x + x + x + x + ",
"x   x   x x x   x   x x x x x x + x x x x x ",
"  x   x   x   x   x   x x x x x x x x x x x ",
"x   x   x x x   x   x x x x x x + x x x x x ",
"  x   x   x   x   x   x x x x x x x x x x x ",
"x   x   x x x   x   x x x x x x + x x x x x ",
"          x           x   x   x Y x   x   x ",
"          x             x   x   Y   x   x   ",
"          x           x   x   x Y x   x   x ",
"          x             x   x   Y   x   x   ",
"          x           x   x   x Y x   x   x ",
"x x x x x x x x x x x x x x x x x x x x x x ",
"          x           x   x   x Y x   x   x ",
"          x             x   x   Y   x   x   ",
"          x           x   x   x Y x   x   x ",
"          x             x   x   Y   x   x   ",
"          x           x   x   x Y x   x   x "
"XPMEXT ext1 data1",
"XPMEXT ext2",
"data2_1",
"data2_2",
"XPMENDEXT"
};
```

3 The XPM Library

The XPM library provides a set of Xlib-level functions which allows to deal with images, pixmaps, XPM file, data (included XPM file), and buffer (XPM file in memory) in many ways.

The following sections describe these functions and how to use them.

3.1 The XPM types

To provide a simple interface all these functions take, in addition to their main arguments such as the display, a structure called **XpmAttributes**. This structure may be considered as composed of two different groups of members. The first one is composed of attributes to pass data such as colormap and visual and attributes to retrieve returned data such as pixmap's width and height. The second group provides a way to rewrite an **XPM** file without losing information such as comments, color defaults and symbolic names which may exist in the original file (i.e. the **XpmInfo** structure in **XPM 2**). The **XpmAttributes** structure is defined as follows:

```
typedef struct {
    unsigned long valuemask;        /* Specifies which attributes are defined */
    Visual *visual;                 /* Specifies the visual to use */
    Colormap colormap;              /* Specifies the colormap to use */
    unsigned int depth;             /* Specifies the depth */
    unsigned int width;             /* Returns the width of the created pixmap */
    unsigned int height;            /* Returns the height of the created pixmap */
    unsigned int x_hotspot;         /* Returns the x hotspot's coordinate */
    unsigned int y_hotspot;         /* Returns the y hotspot's coordinate */
    unsigned int cpp;               /* Specifies the number of char per pixel */
    Pixel *pixels;                  /* List of used color pixels */
    unsigned int npixels;           /* Number of pixels */
    XpmColorSymbol *colorsymbols;   /* Array of color symbols to override */
    unsigned int numsymbols;        /* Number of symbols */
    char *rgb_fname;                /* RGB text file name */
    unsigned int nextensions;       /* Number of extensions */
    XpmExtension *extensions;       /* Array of extensions */
    /* Infos */
    int ncolors;                    /* Number of colors */
    char ***colorTable;             /* Color table pointer */
    char *hints_cmt;                /* Comment of the hints section */
    char *colors_cmt;               /* Comment of the colors section */
    char *pixels_cmt;               /* Comment of the pixels section */
```

```
    unsigned int mask_pixel;        /* Transparent pixel's color table index */
    /* Color Allocation Directives */
    unsigned int exactColors;       /* Only use exact colors for visual */
    unsigned int closeness;         /* Allowable RGB deviation */
    unsigned int red_closeness;     /* Allowable red deviation */
    unsigned int green_closeness;   /* Allowable green deviation */
    unsigned int blue_closeness;    /* Allowable blue deviation */
    int color_key;                  /* Use colors from this color set */
} XpmAttributes;
```

The valuemask is the bitwise inclusive OR of the valid attribute mask bits. If the valuemask is zero, the attributes are ignored and not referenced. And default values are taken for needed attributes which are not specified.

The colorTable is a two dimensional array of strings, organized as follows:

colorTable[color#][0] points to the character string associated to the color.
colorTable[color#][1] points to the symbolic name of the color.
colorTable[color#][2] points to the default color for monochrome visuals.
colorTable[color#][3] points to the default colXor for 4-level grayscale visuals.
colorTable[color#][4] points to the default color for other grayscale visuals.
colorTable[color#][5] points to the default color for color visuals.

Comments are limited to a single comment string by section. If more exist in the read file, then only the last comment of each section will be stored.

To get information back while writing out to a file, you just have to set the mask bits **XpmReturnInfos** to the valuemask of an **XpmAttributes** structure that you pass to the **XpmReadFileToPixmap** function while reading the file, and then give the structure back to the **XpmWriteFileFromPixmap** function while writing.

To allow overriding of colors at load time the **XPM** library defines the **XpmColorSymbol** structure which contains:

```
typedef struct {
    char *name;         /* Symbolic color name */
    char *value;        /* Color value */
    Pixel pixel;        /* Color pixel */
} XpmColorSymbol;
```

To override default colors at load time, you just have to pass, via the **XpmAttributes** structure, a list of **XpmColorSymbol** elements containing the desired colors to the **XpmReadFileToPixmap** or **XpmCreatePixmapFromData XPM** functions. These colors can be specified by giving the color name in the value member or directly by giving the corresponding pixel in the pixel member. In the latter case the value member must be set to **NULL** otherwise the given pixel will not be considered.

In addition, is is possible to set the pixel for a specific color **value** at load time by setting the color name to NULL, and setting the value and pixel fields appropriately. For example, by setting the color name to NULL, the value to “red”

and the pixel to 51, all symbolic colors that are assigned to “red” will be set to pixel 51. It is even possible to specify the pixel used for the transparent color “none” when no mask is required.

To pass and retrieve extension data use the **XpmExtension** structure which is defined below:

```
typedef struct {
        char *name;             /* name of the extension */
        unsigned int nlines;    /* number of lines in this extension */
        char **lines;           /* pointer to the extension array of strings */
} XpmExtension;
```

To retrieve possible extension data stored in an **XPM** file or data, you must set the mask bits **XpmReturnExtensions** to the valuemask of an **XpmAttributes** structure that you pass to the read function you use. Then the same structure may be passed the same way to any write function if you set the mask bits **XpmExtensions** to the valuemask.

3.2 Functions to deal with XPM files

To create an image from an **XPM** file, use **XpmReadFileToImage**.

int XpmReadFileToImage(*display, filename, image_return, shapeimage_return, attributes*)
Display **display;*
char **filename;*
XImage ***image_return;*
XImage ***shapeimage_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
filename	Specifies the file name to use.
image_return	Returns the image which is created.
shapeimage_return	Returns the shape mask image which is created if any.
attributes	Specifies the location of an **XpmAttributes** structure to get and store information.

The **XpmReadFileToImage** function reads in a file in the **XPM** format. If the file cannot be opened, **XpmReadFileToImage** returns **XpmOpenFailed**. If the file can be opened but does not contain valid **XPM** data, it returns **XpmFileInvalid**. If insufficient working storage is allocated, it returns **XpmNoMemory**.

If the passed **XpmAttributes** structure pointer is not **NULL**, **XpmReadFileToImage** looks for the following attributes: **XpmVisual**, **XpmColormap**, **XpmDepth**, **XpmColorSymbols**, **XpmExactColors**, **XpmCloseness**, **XpmRGBCloseness, XpmReturnPixels**, **XpmReturnExtensions**, **XpmReturnInfos**, and sets the **XpmSize** and possibly the **XpmHotspot** attributes when returning.

XpmReadFileToImage allocates colors, as read from the file or possibly overridden as specified in the **XpmColorSymbols** attributes. The colors are allocated using the color settings for the visual specified by the **XpmColorKey** attribute, which has the value **XPM_MONO, XPM_GRAY4, XPM_GRAY,** or **XPM_COLOR**. If the **XpmColorKey** attribute is not set it is determined by examining the type of visual.

If no default value exist for the specified visual, it first looks for other defaults nearer to the monochrome visual type and secondly nearer to the color visual type. If the color which is found is not valid (cannot parse it), it looks for another default one according to the same algorithm.

If allocating a color fails, and the **closeness** attribute is set, it tries to find a color already in the colormap that is closest to the desired color, and uses that. If no color can be found that is within **closeness** of the Red, Green and Blue components of the desired color, it reverts to trying other default values as explained above. For finer control over the closeness requirements of a particular icon, the **red_closeness**, **green_closeness**, and **blue_closeness** attributes may be used instead of the more general **closeness** attribute.

The RGB components are integers within the range 0 (black) to 65535 (white). A closeness of less than 10000, for example, will cause only quite close colors to be matched, while a closeness of more than 50000 will allow quite dissimilar colors to match. Specifying a closeness of more than 65535 will allow any color to match, thus forcing the icon to be drawn in color no matter how bad the colormap is. The value 40000 seems to be about right for many situations requiring reasonable but not perfect matches. With this setting the color must only be within the same general area of the RGB cube as the desired color.

If the **exactColors** attribute is set it then returns **XpmColorError**, otherwise it creates the images and returns XpmSuccess. If no color is found, and no close color exists or is wanted, and all visuals have been exhausted, **XpmColorFailed** is returned.

XpmReadFileToImage returns the created image to image_return if not **NULL** and possibly the created shapemask to shapeimage_return if not **NULL**. If required it stores into the **XpmAttributes** structure the list of the used pixels and possible comments, color defaults and symbols.

When finished the caller must free the images using **XDestroyImage**, the colors using **XFreeColors**, and possibly the data returned into the **XpmAttributes** using **XpmFreeAttributes**.

In addition on systems which support such features **XpmReadFileToImage** deals with compressed files by forking an **uncompress** or **gzip** process and reading from the piped result. It assumes that the specified file is compressed if the given file name ends by '.Z' or '.z'. In case the file name does not end so, **XpmReadFileToImage** first looks for a file of which the name is the given one followed by '.Z' or '.z'; then if such a file does not exist, it looks for the given file (assumed as not compressed). And if instead of a file name **NULL** is passed to **XpmReadFileToImage**, it reads from the standard input.

To create a pixmap from an **XPM** file, use **XpmReadFileToPixmap**.

int XpmReadFileToPixmap(*display, d, filename, pixmap_return, shapemask_return, attributes*)
Display **display;*
Drawable *d;*
char **filename;*
Pixmap **pixmap_return;*
Pixmap **shapemask_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
d	Specifies which screen the pixmap is created on.
filename	Specifies the file name to use.

pixmap_return	Returns the pixmap which is created.
shapemask_return	Returns the shapemask which is created, if any.
attributes	Specifies the location of an **XpmAttributes** structure to get and store information.

The **XpmReadFileToPixmap** function creates X images using **XpmReadFileToImage** and thus returns the same errors. In addition on success it then creates the related pixmaps, using **XPutImage**, which are returned to pixmap_return and shapemask_return if not **NULL**, and finally destroys the created images using **XDestroyImage**.

When finished the caller must free the pixmaps using **XFreePixmap**, the colors using **XFreeColors**, and possibly the data returned into the **XpmAttributes** using **XpmFreeAttributes**.

To write out an image to an **XPM** file, use **XpmWriteFileFromImage**.

XpmWriteFileFromImage writes out an image to an **XPM** file.

int XpmWriteFileFromImage(*display, filename, image, shapeimage, attributes*)
Display **display;*
char **filename;*
XImage **image;*
XImage **shapeimage;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
filename	Specifies the file name to use.
image	Specifies the image.
shapeimage	Specifies the shape mask image.
attributes	Specifies the location of an **XpmAttributes** structure containing information.

The **XpmWriteFileFromImage** function writes an image and its possible shapeimage out to a file in the **XPM** format. If the file cannot be opened, it returns **XpmOpenFailed**. If insufficient working storage is allocated, it returns **XpmNoMemory**. If no error occurs then it returns **XpmSuccess**.

If the passed **XpmAttributes** structure pointer is not **NULL**, **XpmWriteFileFromImage** looks for the following attributes: **XpmColormap**, **XpmSize**, **XpmHotspot**, **XpmCharsPerPixel**, **XpmRgbFilename**, **XpmInfos** and **XpmExtensions**.

If the **XpmSize** attributes are not defined **XpmWriteFileFromImage** performs an **XGetGeometry** operation. If the filename contains an extension such as ".xpm", in order to get a valid C variable name, the dot character is replaced by an underscore '_' when writing out. If the **XpmInfos** attributes are defined it writes out possible stored information such as comments, color defaults and symbol. Finally if the **XpmRgbFilename** attribute is defined, **XpmWriteFileFromImage** searches for color names in this file and if found writes them out instead of the rgb values.

In addition on systems which support such features if the given file name ends by '.Z' or '.z' it is assumed to be a compressed file. Then, **XpmWriteFileFromImage** writes to a piped **compress** or **gzip** process. And if instead of a file name **NULL** is passed to **XpmWriteFileFromImage**, it writes to the standard output.

To write out a pixmap to an **XPM** file, use **XpmWriteFileFromPixmap**.

int XpmWriteFileFromPixmap(*display, filename, pixmap, shapemask, attributes*)
Display **display;*
char **filename;*
Pixmap *pixmap;*
Pixmap *shapemask;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
filename	Specifies the file name to use.
pixmap	Specifies the pixmap.
shapemask	Specifies the shape mask pixmap.
attributes	Specifies the location of an **XpmAttributes** structure containing information.

The **XpmWriteFileFromPixmap** function uses **XGetImage** to get from the given pixmaps the related X images which are passed to **XpmWriteFileFromImage**. Finally **XpmWriteFileFromPixmap** destroys the created images using **XDestroyImage**. The **XpmWriteFileFromPixmap** function returns the same errors that **XpmWriteFileFromImage** returns.

3.3 Functions to deal with XPM data

An **XPM** data is an array of character strings which may be obtained by simply including an **XPM** file into a C program.

To create an image from an **XPM** data, use **XpmCreateImageFromData**.

int XpmCreateImageFromData(*display, data, image_return, shapeimage_return, attributes*)
Display **display;*
char ***data;*
XImage ***image_return;*
XImage ***shapeimage_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
data	Specifies the location of the data.
image_return	Returns the image which is created.
shapeimage_return	Returns the shape mask image which is created if any.
attributes	Specifies the location of an **XpmAttributes** structure to get and store information, or **NULL**.

The **XpmCreateImageFromData** function allows you to include in your C program an **XPM** file which was written out by functions such as **XpmWriteFileFromImage** or **XpmWriteFileFromPixmap** without reading in the file.

XpmCreateImageFromData exactly works as **XpmReadFileToImage** does and returns the same way. It just reads data instead of a file. Here again, it is the caller's responsibility to free the returned images, the colors and possibly the

data returned into the **XpmAttributes** structure.

To create a pixmap from an **XPM** data, use **XpmCreatePixmapFromData.**

int XpmCreatePixmapFromData(*display, d, data, pixmap_return, shapemask_return, attributes*)

Display **display;*
Drawable *d;*
char ***data;*
Pixmap **pixmap_return;*
Pixmap **shapemask_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
d	Specifies which screen the pixmap is created on.
data	Specifies the location of the data.
pixmap_return	Returns the pixmap which is created.
shapemask_return	Returns the shape mask pixmap which is created if any.
attributes	Specifies the location of an **XpmAttributes** structure to get and store information, or **NULL**.

The **XpmCreatePixmapFromData** function creates X images using **XpmCreateImageFromData** and thus returns the same errors. In addition on success it then creates the related pixmaps, using **XPutImage**, which are returned to pixmap_return and shapemask_return if not **NULL**, and finally destroys the created images using **XDestroyImage**.

Do not forget to free the returned pixmaps, the colors, and possibly the data returned into the **XpmAttributes** structure whence done.

In some cases, one may want to create an **XPM** data from an image in order to be able to create another image from this data using the **XpmCreateImageFromData** function later on. To do so use **XpmCreateDataFromImage**.

int XpmCreateDataFromImage(*display, data_return, image, shapeimage, attributes*)

Display **display;*
char ****data_return;*
XImage **image;*
XImage **shapeimage;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
data_return	Returns the data which is created.
image	Specifies the image.
shapeimage	Specifies the shape mask image.
attributes	Specifies the location of an **XpmAttributes** structure containing information.

The **XpmCreateDataFromImage** function exactly works as **XpmWriteFileFromImage** does and returns the same way. It just writes to a single block malloc'ed data instead of to a file. It is the caller's responsibility to free the data, using **XpmFree** when finished.

XpmCreateDataFromPixmap creates an **XPM** data from a pixmap.

int XpmCreateDataFromPixmap(*display, data_return, pixmap, shapemask, attributes*)
Display **display;*
char ***data_return;*
Pixmap *pixmap;*
Pixmap *shapemask;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
data_return	Returns the data which is created.
pixmap	Specifies the pixmap.
shapemask	Specifies the shape mask pixmap.
attributes	Specifies the location of an **XpmAttributes** structure containing information.

The **XpmCreateDataFromPixmap** function uses **XGetImage** to get from the given pixmaps the related X images which are passed to **XpmCreateDataFromImage**. Finally **XpmCreateDataFromPixmap** destroys the created images using **XDestroyImage**. **XpmCreateDataFromPixmap** returns the same errors that **XpmCreateDataFromImage** returns.

3.4 Functions to deal with XPM files and data

To directly tranform an **XPM** file to and from an **XPM** data array, without requiring an open X display, use **XpmReadFileToData** and **XpmWriteFileFromData**.

XpmReadFileToData allocates and fills an **XPM** data array from an **XPM** file.

int XpmReadFileToData(*filename, data_return*)
char **filename;*
char ***data_return;*

filename	Specifies the file name to read.
data_return	Returns the data array created.

XpmReadFileToData returns **XpmOpenFailed** if it cannot open the file, **XpmNoMemory** if insufficient working storage is allocated, **XpmFileInvalid** if this is not a valid **XPM** file, and **XpmSuccess** otherwise. The allocated data returned by **XpmReadFileToData** should be freed with **XpmFree** when done.

XpmWriteFileFromData writes an **XPM** data array to an **XPM** file.

int XpmWriteFileFromData(*filename, data*)
char **filename;*
char ***data;*

filename	Specifies the file name to write.

data Specifies the data array to read.

XpmReadFileToData returns **XpmOpenFailed** if it cannot open the file, **XpmFileInvalid** if this is not a valid **XPM** data, and **XpmSuccess** otherwise.

3.5 Functions to deal with XPM buffers

An **XPM** buffer is a character string which may be obtained by simply making the exact copy of an **XPM** file into memory.

To create an image from an **XPM** buffer, use **XpmCreateImageFromBuffer**.

int XpmCreateImageFromBuffer(*display, buffer, image_return, shapeimage_return, attributes*)
Display **display;*
char **buffer;*
XImage ***image_return;*
XImage ***shapeimage_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
buffer	Specifies the location of the buffer.
image_return	Returns the image which is created.
shapeimage_return	Returns the shape mask image which is created if any.
attributes	Specifies the location of an **XpmAttributes** structure to get and store information, or **NULL**.

The **XpmCreateImageFromBuffer** works the same way as **XpmReadFileToImage**, it just parses the buffer instead of the file. Be aware that the feature provided on some systems by **XpmReadFileToImage** to deal with compressed files is not available here.

To create a pixmap from an **XPM** buffer, use **XpmCreatePixmapFromBuffer**.

int XpmCreatePixmapFromBuffer(*display, d, buffer, pixmap_return, shapemask_return, attributes*)
Display **display;*
Drawable *d;*
char **buffer;*
Pixmap **pixmap_return;*
Pixmap **shapemask_return;*
XpmAttributes **attributes;*

display	Specifies the connection to the X server.
d	Specifies which screen the pixmap is created on.
buffer	Specifies the location of the buffer.
pixmap_return	Returns the pixmap which is created.
shapemask_return	Returns the shape mask pixmap which is created if any.

attributes Specifies the location of an **XpmAttributes** structure to get and store information, or **NULL**.

The **XpmCreatePixmapFromBuffer** function works the same way as **XpmReadFileToPixmap**, it just calls **XpmCreateImageFromBuffer** instead of **XpmReadFileToImage**.

To create an **XPM** buffer from an image, use **XpmCreateBufferFromImage**.

int XpmCreateBufferFromImage(*display, buffer_return, image, shapeimage, attributes*)
Display **display;*
char ***buffer_return;*
XImage **image;*
XImage **shapeimage;*
XpmAttributes **attributes;*

display Specifies the connection to the X server.

buffer_return Returns the buffer which is created.

image Specifies the image.

shapeimage Specifies the shape mask image.

attributes Specifies the location of an **XpmAttributes** structure containing information.

The **XpmCreateBufferFromImage** works as **XpmWriteFileFromImage**, it just writes to a malloc'ed buffer instead of to a file. The caller should free the buffer using **XpmFree** when finished.

XpmCreateBufferFromPixmap creates an **XPM** buffer from a pixmap.

int XpmCreateBufferFromPixmap(*display, buffer_return, pixmap, shapemask, attributes*)
Display **display;*
char ***buffer_return;*
Pixmap *pixmap;
Pixmap *shapemask;
XpmAttributes **attributes;*

display Specifies the connection to the X server.

buffer_return Returns the buffer which is created.

pixmap Specifies the pixmap.

shapemask Specifies the shape mask pixmap.

attributes Specifies the location of an **XpmAttributes** structure containing information.

The **XpmCreateBufferFromPixmap** function works as **XpmWriteFileFromPixmap**, it just calls **XpmCreateBufferFromImage** instead of **XpmWriteFileFromImage**. Once again, the caller should free the buffer using **XpmFree** when finished.

3.6 Functions to deal with XPM files and buffers

As a convenience, the **XpmReadFileToBuffer** and **XpmWriteFileFromBuffer** are provided to copy a file to a buffer and to write a file from a buffer. Thus for instance one may decide to use **XpmReadFileToBuffer**, **XpmCreatePixmapFromBuffer**, and **XpmFree** instead of **XpmReadFileToPixmap**. On some systems this may lead to a performance improvement but it uses more memory.

XpmReadFileToBuffer allocates and fills a buffer from a file.

int XpmReadFileToBuffer(*filename, buffer_return*)
    char **filename;*
    char ***buffer_return;*

filename	Specifies the file name to read.
buffer_return	Returns the buffer created.

XpmReadFileToBuffer returns **XpmOpenFailed** if it cannot open the file, returns **XpmNoMemory** if insufficient working storage is allocated, and **XpmSuccess** otherwise. The allocated buffer returned by **XpmReadFileToBuffer** should be freed with **XpmFree** when done.

XpmWriteFileFromBuffer writes a buffer to a file.

int XpmWriteFileFromData(*filename, data*)
    char **filename;*
    char **buffer;*

filename	Specifies the file name to write.
buffer	Specifies the buffer to read.

XpmReadFileTobuffer returns **XpmOpenFailed** if it cannot open the file, and **XpmSuccess** otherwise.

3.7 Miscellaneous functions

To free possible data stored into an **XpmAttributes** structure use **XpmFreeAttributes**.

int XpmFreeAttributes(*attributes*)
    XpmAttributes **attributes;*

attributes Specifies the structure to free.

The **XpmFreeAttributes** frees the structure members which have been malloc'ed: the pixels list and the infos members (comments strings and color table).

To dynamically allocate an **XpmAttributes** structure use the **XpmAttributesSize** function.

int XpmAttributesSize()

The **XpmAttributesSize** function provides application using dynamic libraries with a safe way to allocate and then

refer to an **XpmAttributes** structure, disregarding whether the **XpmAttributes** structure size has changed or not since compiled.

To free data possibly stored into an array of **XpmExtension** use **XpmFreeExtensions**.

int XpmFreeExtensions(*extensions, nextensions*)
    XpmExtension **extensions;*
    int *nextensions;*

extensions Specifies the array to free.

nextensions Specifies the number of extensions.

This function frees all data stored in every extension and the array itself. Note that **XpmFreeAttributes** call this function and thus most of the time it should not need to be explicitly called.

To free any data allocated by an **Xpm** function use the XpmFree function.

int XpmFree(*ptr*)
    char **ptr;*

ptr Specifies the data to free.

The current distribution of the Xpm library uses the standard memory allocation functions and thus **XpmFree** is nothing else than a define to the standard **free**. However since these functions may be redefined in specific environment it is wise to use **XpmFree**.

Index of Functions

XpmAttributesSize 14
XpmCreateBufferFromImage 13
XpmCreateBufferFromPixmap 13
XpmCreateDataFromImage 10
XpmCreateDataFromPixmap 10
XpmCreateImageFromBuffer 12
XpmCreateImageFromData 9
XpmCreatePixmapFromBuffer 12
XpmCreatePixmapFromData 10
XpmFree 15
XpmFreeAttributes 14
XpmFreeExtensions 15
XpmReadFileToBuffer 14
XpmReadFileToData 11
XpmReadFileToImage 6
XpmReadFileToPixmap 7
XpmWriteFileFromBuffer 14
XpmWriteFileFromData 11
XpmWriteFileFromImage 8
XpmWriteFileFromPixmap 8