Index

Numerics

32-bit address space
  See address space, 32-bit
64-bit address space
  See address space, 64-bit
64-bit mode 24

A

address exception 9
address space
  32-bit 14–18
    embedding in 64-bit 20
    kseg0 17
    kseg1 18
    kseg2 17
    kuseg 16
    segments of 15
    virtual mapping 16
  64-bit 18–24
    cache-controlled 22
    segments of 18–24
    sign extension 20
    virtual mapping 20
    xkseg 22
    xksseg 22
    xkuseg 21
  bus virtual 12
  data transfer between 192
  device address 4
  kernel 17, 22
    map to user 25
  locking in memory 125
  memory address 5
  physical 4–5, 199
  supervisor 22
  user process 16, 21
addressing 3–28
alternate console 247
ASSERT macro 252
audio not covered 77
Audio/Serial Option (ASO) 45
authorized binary interface (ABI) 170

B

*bdevsw*table 137
block device 45
  combined with character 55, 147
  driver must be MP-aware 141
  used when mounting filesystem 277
  versus character 33
buffer (buf_t)
  See data types, *buf_t*
bus adapter
  translates addresses 12
bus virtual address 12

C

cache 13–14, 581
  64-bit access 22
  alignment of buffers 201
  coherency 14
  control functions 200
  device access always uncached 10
  primary 7
  secondary 7
cache algorithm 23
cdevsw table 137
Challenge/Onyx
  directing interrupts 312
  DMA engine in 303
  IO4 board 313, 581–584
  limit on VME DMA space 331
  no uncached memory 27
  VME address windows 329
  VME bus address mapping in 306
  VME bus numbers 315
  VME design constraints 321
  VME hardware 313–323
character device 45
  combined with block 55, 147
  used with *mkfs* 276
  versus block 34
COFF file format not supported 228
command
  See IRIX commands
compiler options
  32-bit 230
  64-bit 231
  for loadable driver 238
  for network driver 397
compiler variables 229
configuration files 38–40
  /dev/MAKEDEV 227, 241
  /etc/inittab 247
  /etc/rc2.d 36
  /etc/rc2/S23autoconfig 239
  /usr/cpu/sysgen/IPnnboot 233
  /usr/lib/X11/input/config 40
  /var/sysgen/boot 39, 232
  /var/sysgen/Makefile.kernio 228
  /var/sysgen/master.d 38, 226, 232, 233–235
    dependencies 234
    example 278
    format 233, 238
    stubs 235
    variables 235
  /var/sysgen/master.d/mem 26
  */var/sysgen/mtune/** 39
  /var/sysgen/system 39, 232
    example 278
  /var/sysgen/system/irix.sm 63, 67
    for debugging 245
    for SCSI 356
  */var/sysgen/system/irix.sm*VME devices 311
configuration flags 234
configuring a driver
  loadable 237–240
  nonloadable 232–237
CPU 5–14
  device access 10
  IP26 27
  memory access by 6
  model number from inventory 31
  processors in 5
  type numbers 5
  watchpoint registers 259
Crimson
  VME bus address mapping in 306

D

D_MP flag 141, 174
D_MT flag 142

D_OLD flag 142, 146
D_WBACK flag 141
Data Link Provider Interface (DLPI) 391
data transfer 192–195
data types
  summary table 565
  buf_t 154, 183–185
    BP_ISMAPPED 184
    displaying 268
    for syncronization 175
    functions 199
    interrupt handling 166
    management 217
  cred_t 148, 203
  dev_t 35, 147, 180
  struct dsconf 88
  struct dsreq 82, 88
    ds_flags 83
    ds_msg 87
    ds_ret 85
    ds_status 87
  edt_t 145
  iovec_t 182
  lock_t 185, 206
  major_t 34, 180
  minor_t 35, 180
  mrlock_t 185, 212
  mutex_t 185, 208
  struct pollhead 155
  proc_t (not available) 203
  struct scsi_request 363, 368
  struct scsi_target_info 360
  sema_t 185
  sleep_t 210
  sv_t 185, 220
  uio_t 152, 182, 194
  __userabi_t 171
  vhandl_t 159, 196
debugging kernel 243–248
device access 10
device address 4
device number
  See major device number, minor device number
device special file 32–37
  /dev/dsk 36
  /dev/ei 114, 124
  /dev/kmem 25
  /dev/mem 25, 26
  /dev/mmem 26
  */dev/scsi/** 78–81
  */dev/tty** 45
  */dev/vme/** 125
  as normal file 33
  defining 227–228
  EISA mapping 68
  for user-level interrupt 124
  inode contents 33
  multiple names for 37
  name format 36, 79
  VME mapping 63
device special file*/dev/kmem* 26
digital media not covered 77
DIrect Memory Access (DMA)
  cache control 581
Direct Memory Access (DMA) 11, 52–53
  buffer alignment for 201
  cache control 200
  DMA engine for VME bus 303
  EISA bus slave 446
  EISA bus-master 444
  GIO bus 521
  IO4 hardware problem 581
  maximum size 202
  setting up 198–202
  user-level 70–76
  user-level SCSI 85
  VME bus 302, 305
disk volume header 244, 275
driver
  compiling 229–231, 397

configuring 232–240
debugging 243–269
examples
EISA 447–508
GIO bus 528–538
network 401–423
RAM drive 271–294
SCSI bus 370–374
VME 334–347
flag constant 140–142, 237, 542
initialization 143–145
lower half 54
prefix 136, 232
in master.d 38
process context 202
registration 239
types
GIO bus 511–538
types of xxxv, 41–57
block 45
character 45
EISA bus 427–508
kernel-level xxxv, 26, 45–57
layered 55
loadable 57
network 389–423
process-level xxxv
pseudo-device 51
SCSI bus 369–370
STREAMS xxxv, 46
upper half 54
in multiprocessor 172, 173
user-level 25, 41–45
See also entry points
See also loadable driver
driver debugging
alternate console 247
breakpoints 257
circular buffer output 250
lock metering 246
memory display 260
multiprocessor 253
setsym use 247
stopping during bootstrap 254
symbol lookup 256
symbols 245
symmon use 252
system log output 249
driver operations 46–53
DMA 52
ioctl 48
mmap 50
open 46
read 49
write 49
dslib library 90–103
function summary 90
data transfer options 85
doscsireq() 93
ds_ctostr() 95
ds_vtostr() 95
dsclose() 92
dsopen() 92
filldsreq() 93
fillg0cmd() 94
fillg1cmd() 94
inquiry12() 96
modeselect15() 96
modesense1a() 97
read08() 98
readcapacity25() 99
readextended28() 98
releaseunit17() 100
requestsense03() 100
reserveunit16() 100
senddiagnostic1d() 101
testunitready00() 102
write0a() 102
writeextended2a() 102
dsreq driver 78
data transfer options 85

DS_ABORT 89
DS_CONF 88
DS_RESET 90
exclusive open 81
flags 83
return codes 85
scatter/gather 85
struct dsconf 88
struct dsreq 82–88
ds_flags 83
ds_msg 87
ds_ret 85
ds_status 87

E

EISA bus 427–508
address mapping 434
address spaces 430
allocate DMA channel 444
allocate IRQ 442–443
byte order 431
card slots 434
configuring 435–438
DMA to bus master 444–445
example driver 447
interrupts 430, 435
kernel services 439–447
locked cycles 431
mapping into user process 42
overview 428–433
PIO bandwidth 69
PIO mapping 439–441
product identifier ??–433
product indentifier 431–??
request arbitration 430
user-level PIO 67–70
ELF object format 228
entry points
summary table 138, 564
close 149–150, 159, 544
devflag 140–142, 237
edtinit 144, 239, 517
halt 168
info 542
init 144, 239, 543
interrupt 163–166, 519
ioctl 150–151, 170
map 159–161
mmap 161–162
mversion 237
open 146–149, 543
mode flag 148
type flag 147
poll 155–157
and interrupts 166
print 169
read 152–153
size 149, 169
start 145, 239, 543
strategy 154
and interrupts 166
called from read or write 153
design models 217
unload 159, 167–168, 240
unmap 162
usage 139
write 152–153
example driver 271, 334, 370, 401, 447, 528
execution model 170–171
external interrupt 43, 114–119
generate 114
input is level-triggered 115
pulse widths 116
set pulse widths 117
user-level handler 127

F

fixed PIO map 328
fmodsw table 137
function
  See IRIX functions, kernel functions

G

GIO bus 511–538
  address space mapping 513
  configuring 514
  edtinit entry point 517
  example driver 528–538
  form factors 512
  interrupt handler 519
  kernel services 515–517
  memory parity checking with 526
  varieties of 512

H

hardware inventory 29–32
  adding entries to 32
  contents 30
  hinv displays 30
  network driver use 396
  software interface to 31
header files
  summary table 185
  dslib.h 90
  for network drivers 393
  sgidefs.h 25
  sys/cmnerr.h 249
  sys/debug.h 252
  sys/file.h 148
  sys/immu.h 197
  sys/major.h 34
  sys/open.h 147
  sys/param.h 183
  sys/poll.h 155
  sys/region.h 161
  sys/scsi.h 355
  sys/sema.h 185
  sys/sysmacros.h 34, 35, 197
  sys/types.h 25, 34, 35, 180
  sys/uio.h 182
  sys/var.h 39

I

idbg debugger 245–247, 262–269
  command line use 263
  command syntax 264–269
  configuring in kernel 246
  display I/O status 267
  display process data 265
  interactive mode 262
  invoking 262
  loading 262
  lock meter display 267
  log file output 263
  memory display 265
ide PROM monitor 244
include file
  See header files
INCLUDE statement 144, 236, 239
initialization 143–145
inode 33, 47
interrupt 54
  and strategy entry point 166
  associating to a driver 163
  concurrent with processing 172
  enabled during initialization 143
  latency 165
  on multiprocessor 165
  See also user-level interrupt (ULI)

inventory
See hardware inventory
IO4 board 313
multiple DMA problem 581–584
IP26 CPU 27
IPL statement 312
IRIX commands
autoconfig 232, 236, 247
dvhtool 244–245
hinv 30
and MAKEDEV 36, 227
for CPU type 6
install 37, 227, 241
lboot 39
builds switch tables 137
driver prefix with 136
loads SCSI driver 356
mkfs 276
mknod 37, 227, 241
ml 57, 241
mount 48, 146, 277
nvram 248
prtvtoc 275
setsym 247
systune 39, 240, 250
max DMA size 202
switch table size 137
umount 149
uname 6
versions 244
IRIX functions
close() 149
endinvent() 31
getinvent() 31
getpagesize() 21
ioctl() 43, 44, 48, 127
kmem_alloc() 54
mmap() 26, 50, 158–159
EISA PIO 68
VME PIO 64
mpin() 125
munmap() 162
open() 46, 146
with dsreq driver 81
pio_badaddr() 327
plock() 125
poll() 155–156
read() 49, 52
setinvent() 31
syslog() 249
test_and_set() 129
ULI_block_intr() 129
ULI_register_ei() 127
ULI_register_vme() 127
ULI_sleep() 124, 128
ULI_wakeup() 128
write() 49, 52

J

jag (SCSI-to-VME adapter) 356
jag (SCSI-toVME) adapter 80

K

kernel address space
driver runs in 26
mapping to user space 25
kernel execution model 170
kernel functions
summary table 566
add_to_inventory() 32
badaddr() 195
bcopy() 193
biodone() 166, 218
bioerror() 166
biowait() 218
bp_mapin() 200

brelse() 190
bzero() 193
cmn_err() 249–251
  buffer output 250
  system log output 249
copyin() 151, 193
copyout() 151, 193
cvsema() 177
dki_dcache_inval() 201
dki_dcache_wb() 27, 201
dma_map() 331, 445
dma_mapaddr() 331, 445
dma_mapalloc() 330, 445
drv_getparm() 203
drv_priv() 148, 203
drvhztousec() 215
drvusectohz() 215
eisa_dmachan_alloc() 444
eisa_ivec_alloc() 442
fasthzto() 215
flushbus() 201
fubyte() 194
geteblk() 190
getemajor() 34, 181
geteminor() 181, 360
getinvent() 6
getnextpg() 200
getrbuf() 190
initnsema() 177
initnsema_mutex() (not supported) 223
ip26_enable_ucmem() 28
ip26_return_ucmem() 28
itimeout() 156, 215
kern_malloc() (obsolete) 187
kmem_alloc() 17, 187
kmem_zalloc() 189
makedevice() 181
phalloc() 155, 189
phfree() 167, 189
physiock() 141, 153
pio_baddr() 441
pio_bcopyin() 328, 441
pio_bcopyout() 328, 441
pio_map_alloc() 447
pio_mapaddr() 328
pio_mapalloc() 326, 440
pio_mapfree() 167
pio_wbadaddr() 328
pollwakeup() 156, 166
pptophys() 200
printf() 251
psema() 177, 223
ptob() 21
rmalloc() 191
rmallocmap() 191
rmfree() 191
setgioconfig() 516
setgiovector() 515
sleep() 219
splhi()
  denigrated 213
  meaningless 172
splnet()
  ineffective 397
splvme()
  useless 176
subyte() 194
timeout() 215
uiomove() 194
uiophysio() 153
untimeout() 215
userabi() 170
v_getaddr() 196
v_gethandle() 196
v_mapphys() 160, 196
vme_ivec_alloc() 333
vme_ivec_free() 334
vme_ivec_set() 333

vsema() 177, 223
vt_gethandle() 161, 163
wakeup() 219
kernel mode of processor 8
kernel panic
address exception 9
moving data 192
kernel switch tables 137
kernel-level driver xxxv, 45–57, 135–177
structure of 136

L

layered driver 55
lboot
See IRIX commands
libc reentrant version 123
loadable driver 57
and switch table 137
autoregister 143
compiler options 238
configuring 237
initialization 143
loading 239
master.d 238
mversion entry 237
not in miniroot 57
registration 239
unloading 240
loading a driver 239
lock metering support 246, 267
locking
See mutual exclusion
locking memory 125
lower half of driver 54

M

major device number 34, 180
available numbers 34
block vs. character 34
dynamic allocation 241
external versus internal 181
for STREAMS clone 552, 553
in */dev/scsi* 80
in inode 33
in master.d 38, 233
in variables in master.d 235
indexes switch table 137
input to open 47
range of 34
selecting 226
/dev/MAKEDEV 35–37, 78, 180, 227, 241
adding to */dev/scsi* 81
master.d configuration files
See configuration files,*/var/sysgen/master.d*
memory 3–28
memory address
cached 17
physical 5, 259, 434
uncached 18
memory allocation 187–191
memory display 260
memory mapping 25–26, 158–163
miniroot
no loadable drivers 57
minor device number 35, 180
encoding 35
external versus internal 181
for STREAMS clone driver 552, 553
in */dev/scsi* 80
in inode 33
input to open 47, 147
selecting 227

multiprocessor
  block driver must support 141
  converting to 176
  driver design for 171–177, 547
  driver flag D_MP 141, 174
  drivers for 56
  interrupt handling on 165
  network drivers in 396–??
  nonMP driver on CPU 0 141, 174
  splhi useless in 172
  synchronizing upper-half code 173
  uniprocessor assumptions invalid 171
  uniprocessor drivers use CPU 0 56
  using symmon in 253
mutex locks 207
mutual exclusion 204, 205–214
  basic locks 206–207
  in multiprocessor drivers 172
  in network driver 398–400
  mutex locks 207
  priority inheritance 208
  reader/writer locks 211
  semaphore 223
  sleep locks 209

N

names of devices 33, 36, 79
network 389
  based on 4.3BSD 392
  driver interfaces 392–396
  example driver 401
  header files 393
  multiprocessor considerations 396
  overview 390
  STREAMS protocol stack 391
network driver
  debugging 269
  must be MP-aware 141
Network File System (NFS) 391

P

page size
  I/O 197
  macros 197
  memory 21, 197
parity check with GIO 526
pipe semantics 549
prefix 38, 136, 232
primary cache 7
priority inheritance 208
priority level functions 213
privilege checking 203
process 202–203
  display data about 265
  handle of 203
  sending signal to 203
  table of in kernel 265
process-level driver xxxv
processor
  kernel mode 8
  types 5
  user mode 8
Programmed I/O (PIO) 10, 61
  address maps for 325–329
  EISA bus 67–70, 439
  GIO bus 519
  VME bus 62–66, 302, 305
pseudo-device driver 51
putbuf circular buffer 250, 265

R

RAM drive 271
raw device
  See character device
reader/writer locks 211
reentrant C library 123
registration of loadable driver 239

S

sash standalone shell 244
SCSI bus 351–386
  adapter error codes 378
  adapter number 79, 359
  adapter type number 359, 376
  command
    Inquiry 96, 360
    Mode Select 96
    Mode Sense 97
    Read 98
    Read Capacity 99
    Request Sense 100
    Reserve Unit 100
    Send Diagnostic 101
    Test Unit Ready 102
    Write 102
  display request structure 267
  driver 369–370
  error messages 377–386
  example driver 370–374
  hardware support overview 352
  host adapter 353
    functions of 357
    intialization 375
    number of 355
    overview 375
    purpose 354
    scsi_abort() 368
    scsi_alloc() 361
    scsi_command() 363
    scsi_free() 362
    scsi_info() 360
    scsi_reset() 369
    vectors to 358, 376
  kernel overview 353
  LUN 79, 356
  message string tables 378
  sense codes 379
  target ID 79
  target number 356
  user-level access 43, 77–103
  See also dsreq driver
secondary cache 7
sector unit macros 197
semaphore 222–224
  for mutual exclusion 223
  for waiting 224
sign extension of 32-bit addresses 20
signal 203
SIGSEGV 9
Silicon Graphics
  developer program xxxvii
  FTP server xxxvii
  VME bus hardware 300
  WWW server xxxvii
64-bit address space
  See address space, 64-bit
64-bit entries *see*Numbers
sleep locks 209
socket interface 391
stray VME interrupt 334
STREAMS 541–561
  function summary 554
  clone driver 552–553
  close entry point 544
  debugging 268
  display data structures 268

driver xxxv
extended poll support 549
module_info structure 542
multiprocessor design 547
multithreaded monitor 547
open entry point 543
put functions 544
service scheduling 550
srv functions 545
streamtab structure 542
supplied drivers 550
STREAMS protocol stack 391
structure of driver 136
switch table 137
symmon debugger 244–245, 252–261
breakpoints 257
command syntax 255–256
how invoked 253
in multiprocessor 253
in uniprocessor 253
invoking at bootstrap 254
memory display 260
prompt 253
symbol lookup 256
virtual memory commands 259
watchpoint register use 259
synchronization variable 220
SysAD bus parity checks 526
sysgen files
See configuration files
system console
alternate 247
system log display 249
systune
See IRIX commands

T

terminal as console 247
The 269
32-bit entries *see* Numbers
tick 215
time unit functions 215
TLI interface 391
Translate Lookaside Buffer (TLB) 7
Translation Lookaside Buffer (TLB) 8
maps kernel space 22
maps kuseg 17
number of entries in 9

U

udmalib 70–76
dma_allocbuf() 71
dma_mkparms() 72
dma_start() 73
uncached memory access
32-bit 18
64-bit 22
do not map 160
IP26 27
none in Challenge 27
uniprocessor
converting driver 176
using symmon 253
unloading a driver 240
upper half of driver 54
upper half of of driver 172, 173
USE statement 144, 236
user mode of processor 8

user-level DMA 70–76
user-level driver 41–45
user-level interrupt (ULI) 44, 121–132
  and debugging 123
  external interrupt with 127
  initializing 124
  interrupt handler function 122–124
  registration 126
  restrictions on handler 122
  ULI_block_intr() function 129
  ULI_register_ei() function 127
  ULI_register_vme() function 127
  ULI_sleep() function 124, 128
  ULI_wakeup() function 128
  VME interrupt with 127
user-level process 41

V

variables in master.d 235
VECTOR statement 163, 236, 239
  edtinit entry point 144
  EISA kernel driver 436
  EISA PIO 67
  for SCSI host adapter 356
  GIO bus 514
  use of ctlr= 147
  use of probe= 437
  VME devices 311
  VME PIO 63
vfssw table 137
virtual memory 7, 8–10
  32-bit mapping 16
  64-bit mapping 20
  debug display of 259
  page size 21
virtual page number (VPN)
  32-bit 16
VME bus 297–347
  adapter number 80
  bus address spaces 299, 304–309
    mapping 304
  bus cycles 300
  bus numbers in Challenge 315
  configuring 310
  DMA engine 303
  DMA to
    address maps 330–331
    addresses 308
    addressing in Challenge 308
    addressing in Crimson 308–309
  example driver 334
  hardware
    Challenge 313–323
    design constraints 321
    DMA cycle 302
    interrupt priority 321
    overview 300–303
    PIO cycle 302
    relation to system bus 301
  history 298
  interrupt levels 300
  interrupt vector 332
  jag adapter 80
  kernel services 325–347
  mapping into user process 42
  master device 299
  PIO to
    address maps 325–329
    addresses 305
    addressing in Challenge 306
    addressing in Crimson 306
    bandwidth 66
    fixed, unfixed maps 328

slave device 299
stray interrupt cause 334
user-level DMA 43, 70–76
user-level DMA bandwidth 73
user-level interrupt handler for 127
user-level PIO 62–66
VME Cache Controller (VMECC) 315–317
VMEbus Channel Adapter Module (VCAM) board 313, 315
volatile keyword 123
volume header 244, 275

W

waiting 204, 214–222
for a general event 218
for an interrupt 217
for memory 216
semaphore 224
synchronization variables 220
time units 215
timed events 215