



#126: Sub(Launching) from a High-Level Language

Revised by: Rich Collyer & Mark Johnson
Written by: Rick Blair & Jim Friedlander

April 1989
May 1987

Note: Developer Technical Support takes the view that launching and sublaunching are features which are best **avoided** for compatibility (and other) reasons, but we want to make sure that when it is absolutely necessary to implement it, it is done in the safest possible way.

This Technical Note discusses the “safest” method of calling `_Launch` from a high-level language that supports inline assembly language with the option of launching or sublaunching another application.

Changes since August 1988: Incorporated Technical Note #52 on calling `_Launch` from a high-level language, changed the example to offer a choice between launching or sublaunching, added a discussion of the `_Launch` trap under MultiFinder, and updated the MPW C code to include inline assembly language.

The Segment Loader chapter of *Inside Macintosh* II-53 states the following about the `_Launch` trap:

“The routines below are provided for advanced programmers; they can be called only from assembly language.”

While this statement is technically true, it is easy to call `_Launch` from any high-level language which supports inline assembly code, and this Note provides examples of calling `_Launch` in MPW Pascal and C.

Before calling `_Launch`, you need to declare the inline procedure, which takes a variable of type `pLaunchStruct` as a parameter. Since the compiler pushes a pointer to this parameter on the stack, you need to include code to put this pointer into A0. The way to do this is with a `MOVE.L (SP)+, A0` instruction, which is `$205F` in hexadecimal, so the first word after `INLINE` is `$205F`. This instruction sets up A0 to contain a pointer to the filename and 4(A0) to contain the configuration parameter, so the last part of the inline is the `_Launch` trap itself, which is `$A9F2` in hexadecimal. The configuration parameter, which is normally zero, determines whether the application uses alternate screen and sound buffers. Since not all Macintosh models support these alternate buffers, you should avoid using them unless you have a specific circumstance which requires them.

The Finder does a lot of hidden cleanup and other tasks without user knowledge; therefore, it is best if you do not try to replace the Finder with a “mini” or try to launch other programs and have them return to your application. In the future, the Finder may provide better integration for applications, and you will circumvent this if you try to act in its place by sublaunching other programs.

If you have a situation where your application **must** launch another and have it return, and where you are not worried about incompatibility with future System Software versions, there is a “preferred” way of doing this which fits into the current system well. System file version 4.1 (or later) includes a mechanism for allowing a call to another application; we term this call a “sublaunch.” You can perform a sublaunch by adding a set of simple extensions to the parameter block you pass to the `_Launch` trap.

`_Launch` and MultiFinder

Under MultiFinder, a sublaunch behaves differently than under the Finder. The application you sublaunch becomes the foreground application, and when the user quits that application, the system returns control to the next frontmost layer, which will not necessarily be your application.

If you set both high bits of `LaunchFlags`, which requests a sublaunch, your application will continue to execute after the call to `_Launch`. Under MultiFinder, the actual launch (and suspend of your application) will not happen in the `_Launch` trap, but rather after a call or more to `_WaitNextEvent`.

Under MultiFinder, `_Launch` currently returns an error if there is not enough memory to launch the desired application, if it cannot locate the desired application, or if the desired application is already open. In the latter case, that application will **not** be made active. If you attempted to launch, MultiFinder will call `_SysBeep`, your application will terminate, and control will be given to the next frontmost layer. If you attempted to sublaunch, control will return to your application, and it is up to you to report the error to the user.

Currently, `_Launch` returns an error in register D0 for a sublaunch, and you should check it for errors (`D0<0`) after any attempts at sublaunching. If `D0>=0` then your sublaunch was successful.

You should refer to the *Programmer's Guide to MultiFinder* (APDA) and Macintosh Technical Notes #180, MultiFinder Miscellanea and #205, MultiFinder Revisited: The 6.0 System Release, for further discussion of the `_Launch` trap under MultiFinder.)

Working Directories and Sublaunching With the Finder

Putting aside the compatibility issue for the moment, the only problem sublaunching creates under the **current** system is one of Working Directory Control Blocks (WDCBs). Unless the application you are launching is at the root directory or on an MFS volume, you must create a new WDCB and set it as the current directory when you launch the application.

In the example which follows, the new working directory is opened (allocated) by Standard File and its `WDRefNum` is returned in `reply.vRefNum`. If you do not use Standard File and cannot assume, for instance, that the application was in the blessed folder or root directory, then you must open a new working directory explicitly via a call to `_OpenWD`. You should give the new WDCB a `WDProcID` of 'ERIK', so the Finder (or another shell) would know to deallocate when it saw it was allocated by a “sublaunchee.”

Although the sublaunching process is recursive (i.e., programs which are sublaunched may, in turn, sublaunch other programs), there is a limit of 40 on the number of WDCBs which can be created. With this limit, you could run out of available WDCBs very quickly if many programs were playing the shell game or neglecting to deallocate the WDCBs they had created. Make sure you check for **all** errors after calling `_PBOpenWD`. A `tmWDOErr` (-121) means that all available WDCBs have been allocated, and if you receive this error, you should alert the user that the sublaunch failed and continue as appropriate.

Warning: Although the example included in this Note covers sublaunching, Developer Technical Support strongly recommends that developers **not** use this feature of the Launch trap. This trap will change in the not-too-distant future, and when it does change, applications which perform sublaunching **will** break. The only circumstance in which you could consider sublaunching is if you are implementing an integrated development system and are prepared to deal with the possibility of revising it every time Apple releases a new version of the System Software.

MPW Pascal

{It is assumed that the Signals are caught elsewhere; see Technical Note #88 for more information on the Signal mechanism}

```
{the extended parameter block to _Launch}
TYPE
  pLaunchStruct = ^LaunchStruct;
  LaunchStruct = RECORD
    pfName      : StringPtr;
    param       : INTEGER;
    LC          : PACKED ARRAY[0..1] OF CHAR; {extended parameters:}
    extBlockLen : LONGINT; {number of bytes in extension = 6}
    fFlags      : INTEGER; {Finder file info flags (see below)}
    launchFlags : LONGINT; {bit 31,30=1 for sublaunch, others reserved}
  END; {LaunchStruct}

FUNCTION LaunchIt(pLaunch: pLaunchStruct): OSErr; {< 0 means error}
  INLINE $205F, $A9F2, $3E80;
{ pops pointer into A0, calls Launch, pops D0 error code into result:
MOVE.L  (A7)+,A0
_Launch
MOVE.W  D0,(A7)  ; since it MAY return }

PROCEDURE DoLaunch(subLaunch: BOOLEAN); {Sublaunch if true and launch if false}

  VAR
    myLaunch      : LaunchStruct;    {launch structure}
    where         : Point;           {where to display dialog}
    reply         : SFReply;         {reply record}
    myFileTypes   : SFTYPEList;      {we only want APPLs}
    numFileTypes  : INTEGER;
    myPB          : CInfoPBRec;
    dirNameStr    : str255;

  BEGIN
    where.h := 20;
    where.v := 20;
    numFileTypes:= 1;
    myFileTypes[0]:= 'APPL';          {applications only!}
    {Let the user choose the file to Launch}
    SFGetFile(where, '', NIL, numFileTypes, myFileTypes, NIL, reply);
```

```

IF reply.good THEN BEGIN
    dirNameStr:= reply.fName;    {initialize to file selected}

{Get the Finder flags}
    WITH myPB DO BEGIN
        ioNamePtr:= @dirNameStr;
        ioVRefNum:= reply.vRefNum;
        ioFDirIndex:= 0;
        ioDirID:= 0;
    END; {WITH}
    Signal(PBGetCatInfo(@MyPB,FALSE));
{Set the current volume to where the target application is}
    Signal(SetVol(NIL, reply.vRefNum));

{Set up the launch parameters}
    WITH myLaunch DO BEGIN
        pfName := @reply.fName;    {pointer to our fileName}
        param := 0;                {we don't want alternate screen or sound buffers}
        LC := 'LC';                {here to tell Launch that there is non-junk next}
        extBlockLen := 6;          {length of param. block past this long word}
        {copy flags; set bit 6 of low byte to 1 for RO access;}
        fFlags := myPB.ioFlFndrInfo.fdFlags; {from GetCatInfo}

{Test subLaunch and set LaunchFlags accordingly}
        IF subLaunch THEN
            LaunchFlags := $C0000000          {set BOTH high bits for a sublaunch}
        ELSE
            LaunchFlags := $00000000;          {Just launch then quit}
        END; {WITH}

{launch; you might want to put up a dialog which explains that
the selected application couldn't be launched for some reason.}
        Signal(LaunchIt(@myLaunch));
    END; {IF reply.good}

END; {DoLaunch}

```

MPW C

```
typedef struct LaunchStruct {
    char        *pfName;           /* pointer to the name of launchee */
    short int    param;
    char        LC[2];              /*extended parameters:*/
    long int     extBlockLen;        /*number of bytes in extension == 6*/
    short int    fFlags;            /*Finder file info flags (see below)*/
    long int     launchFlags;       /*bit 31,30==1 for sublaunch, others reserved*/
} *pLaunchStruct;

pascal OSErr LaunchIt( pLaunchStruct pLnch) /* < 0 means error */
    = {0x205F, 0xA9F2, 0x3E80};

/* pops pointer into A0, calls Launch, pops D0 error code into result:
    MOVE.L    (A7)+,A0
    _Launch
    MOVE.W    D0,(A7)    ; since it MAY return */

OSErr DoLaunch(subLaunch)
    Boolean        subLaunch;       /* Sublaunch if true and launch if false
    */
{ /* DoLaunch */
    struct LaunchStruct myLaunch;
    Point          where;           /*where to display dialog*/
    SFReply        reply;           /*reply record*/
    SFTYPEList     myFileTypes;     /* we only want APPLs */
    short int      numFileTypes=1;
    HFileInfo      myPB;
    char           *dirNameStr;
    OSErr          err;

    where.h = 80;
    where.v = 90;
    myFileTypes[0] = 'APPL';        /* we only want APPLs */
    /*Let the user choose the file to Launch*/
    SFGetFile(where, "", nil, numFileTypes, myFileTypes, nil, &reply);

    if (reply.good)
    {
        dirNameStr = &reply.fName; /*initialize to file selected*/

        /*Get the Finder flags*/
        myPB.ioNamePtr= dirNameStr;
        myPB.ioVRefNum= reply.vRefNum;
        myPB.ioFDirIndex= 0;
        myPB.ioDirID = 0;
        err = PBGetCatInfo((CInfoPBPtr) &myPB,false);
        if (err != noErr)
            return err;

        /*Set the current volume to where the target application is*/
        err = SetVol(nil, reply.vRefNum);
        if (err != noErr)
            return err;

        /*Set up the launch parameters*/
        myLaunch.pfName = &reply.fName; /*pointer to our fileName*/
        myLaunch.param = 0;              /*we don't want alternate screen
                                         or sound buffers*/
    }
}
```

```

/*set up LC so as to tell Launch that there is non-junk next*/
    myLaunch.LC[0] = 'L'; myLaunch.LC[1] = 'C';
    myLaunch.extBlockLen = 6;          /*length of param. block past
                                        this long word*/
/*copy flags; set bit 6 of low byte to 1 for R0 access:*/
    myLaunch.fFlags = myPB.ioFlFndrInfo.fdFlags; /*from _GetCatInfo*/
/* Test subLaunch and set launchFlags accordingly */
if ( subLaunch )
    myLaunch.launchFlags = 0xC0000000; /*set BOTH hi bits for a sublaunch
*/
else
    myLaunch.launchFlags = 0x00000000; /* Just launch then quit */

    err = LaunchIt(&myLaunch); /* call _Launch */
    if (err < 0)
    {
        /* the launch failed, so put up an alert to inform the user */
        LaunchFailed();
        return err;
    }
    else
        return noErr;
} /*if reply.good*/
} /*DoLaunch*/

```

Further Reference:

- *Inside Macintosh*, Volumes I-12, II-53, & IV-83, The Segment Loader
- *Programmer's Guide to MultiFinder* (APDA)
- Technical Note #129, _SysEnviron: System 6.0 and Beyond
- Technical Note #180, MultiFinder Miscellanea
- Technical Note #205, MultiFinder Revisited: The 6.0 System Release