

CFG_CONFCONFIG

COLLABORATORS

	TITLE : CFG_CONFCONFIG		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		November 11, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	CFG_CONFCONFIG	1
1.1	main	1
1.2	ConfActive	1
1.3	ConfName	2
1.4	ConfAccess	2
1.5	PrivateList	2
1.6	PrivateFiles_XX	3
1.7	BadFileList	3
1.8	BadFiles_XX	3
1.9	Upload_XX	3
1.10	Download_XX	4
1.11	MaxDIZLines	4

Chapter 1

CFG_CONFCONFIG

1.1 main

Description:

The HBBS:Conferences/<ConfDir>/ConfConfig file defines the setting for the conference in which this file exists, there needs to be one in each conference otherwise you will get some error messages.

Options:

ConfActive=<boolean>	More...
ConfName=<string>	More...
ConfAccess=<numeric>	More...
PrivateList=<path>	More...
PrivateFiles_XX=<path>	More...
BadFileList=<path>	More...
BadFiles_XX=<path>	More...
Upload_XX=<path>	More...
Download_XX=<path>	More...
MaxDIZLines=<numeric>	More...

1.2 ConfActive

ConfActive=<boolean>

E.G.

ConfActive=TRUE

Default = FALSE

This option must be set to TRUE if you want the conference to appear to any user or any door on the system, setting this to false totally disables

the conference and all references to it!

1.3 ConfName

ConfName=<string>

E.G.

ConfName="New Users!"

No Default, Must be set!

This option defines the name for the conference. You may include colour sequences in this string.

1.4 ConfAccess

ConfAccess=<numeric>

E.G.

ConfAccess=10

No Default, Must be set!

This option defines the minimum access level required before a user can access the conference. If the user has not got enough access then this conference won't show up on any conference lists generated by the system

1.5 PrivateList

PrivateList=<string>

E.G.

PrivateList=HBBS:Conferences/NewUsers/FileLists/PrivateList

No Default, Must Be Set!

This option specifies the file list to be used when files are uploaded privately to the sysop. This option is available so that if you require you can have one global Private list and Private directory for all your conferences which makes it a hell of a lot easier to find private files!

NOTE: This directory differs from /X in that bad uploads DO NOT go in this directory! See BadFiles_XX and BadFileList

1.6 PrivateFiles_XX

PrivateFiles_XX=<path>

E.G.

PrivateFiles_1=HBBS:Conferences/NewUsers/Private/
PrivateFiles_2=DH2:PrivateOverflow/

No Default, Must be set!

These options specify the Private paths to be used when a user uploads a file privately to the sysop. PrivateFiles_1 gets filled first much in the same way as UploadPath_1 gets filled...

1.7 BadFileList

BadFileList=<path>

E.G.

BadFileList=HBBS:Conferences/NewUsers/FileLists/BadFiles

No Default, Must Be Set!

This option specifies the file list that gets created when a user uploads a bad/corrupt file. (or duplicate).

1.8 BadFiles_XX

BadFiles_XX=<path>

E.G.

BadFiles_1=HBBS:Conferences/NewUsers/BadFiles/
BadFiles_2=DH2:BadFilesOverflow/

No Default, Must Be Set!

These options specifies the directories to store bad, corrupt or duplicate uploads from users.

1.9 Upload_XX

Upload_XX=<path>

E.G.

Upload_1=DH2:Files/Amiga/

```
Upload_2=DH1:Files/Amiga/  
Upload_3=DH0:Files/Amiga/
```

No Default, Must Be Set!

This options specifies the paths to store uploaded files for the conference, files are uploaded into the paths in the other specified, when there is no space on the drive specified by Upload_1 uploads will go into upload_2 and so on, when there is less free space than specified by MinFreeSpace in HBBS:BBSGlobal a script is run in which you may chose to delete/backup old files..

1.10 Download_XX

Download_XX=<path>

E.G.

```
Download_1=DH0:Files/Amiga/  
Download_2=DH1:Files/Amiga/  
Download_3=DH2:Files/Amiga/
```

No Default, Must Be Set!

These options tell the bbs where to look for filenames flagged by the user for downloading, note that when a file flagged the bbs remembers in which conference the file was flagged, so when the user goes to download the files the bbs will search the paths specified in the conference the file was flagged, so there is no need to specify all download paths for each conference anymore!. Also the user will be informed if they don't have enough upload credits in the conference the file was flagged in if you are using conference accounting.

Also note that the paths above should be specified in reverse order to those specified in uploads_xx as the newer files would be stored in the last upload_xx path. This is not a must be the user does not have to wait so long if you stick to this convention.

1.11 MaxDIZLines

MaxDIZLines=<numeric>

E.G.

```
MaxDIZLines=10
```

Default = 12

This option specifes how many lines may be used for the description of each file that has been uploaded. If a description contains more lines than this they will not be added to the filelist. This option may be overridden for each type of files using the HBBS:System/FileID/<ext>

files.