



DataDirect ODBC InterBase Driver

[Logon to InterBase](#)

[InterBase ODBC Setup](#)

[Copyright](#)

Copyright 1995 INTERSOLV Inc. All rights reserved. INTERSOLV is a registered trademark, and DataDirect is a trademark of INTERSOLV, Inc. Other company or product names mentioned herein may be trademarks or registered trademarks of their respective companies.

Configuring an InterBase Data Source

Data Source Name: A string that identifies this InterBase data source configuration in ODBC.INI. Examples include "Accounting" or "InterBase-Serv1."

Description: An optional long description of a data source name. For example, "My Accounting Database" or "InterBase on Server #1."

Database Name: The name of the database to which you want to connect by default.

The following values are optional:

Database List: The list of databases that will be available in the logon dialog box. Separate the list with commas.

Default User Name: The default user name used to connect to your InterBase database. This ID is case-sensitive. Your ODBC application may override this value or you may override this value in the logon dialog box.

Lock Time Out: A value that specifies whether InterBase should wait for a lock to be freed before raising an error when processing a Select...For Update Of statement. Values can be -1 (wait forever) or 0 (don't wait). The default is -1.

Translate: Displays the Select Translator dialog box to allow you to perform a translation of your data from one character set to another. Choose the INTERSOLV OEM ANSI translator to translate your data from the IBM PC character set to the ANSI character set.

Logon to InterBase

Database Name: Enter the name of the InterBase tables you want to access (case-sensitive).

User Name: Enter your User Name (case-sensitive).

Password: Enter your password for the system (case-sensitive).

