

SAN ANTONIO
SIGGRAPH
2002

Measuring Simplification Error

Jonathan Cohen
Computer Science Department
Johns Hopkins University
<cohen@cs.jhu.edu>
<http://www.cs.jhu.edu/~cohen>



What I'll Talk About

- Introduction
- Geometric Error
- Attribute Error
- Hybrid Simplification



Why Measure Error?

- Guide simplification process
 - Making better choices produces better simplifications
- Know quality of results
 - Object-space error bounds describes quality
- Know when to show a particular LOD
 - Which LOD for a given screen-space error
- Balance quality for large environments
 - What error bound for a given polygon count



Ford Bronco Model



Triangles
: 41,855
27,970
20,922
12,939
8,385
4,766

courtesy of Division and Viewpoint

SAN ANTONIO
SIGGRAPH
2002



What I'll Talk About


- Introduction
- Geometric Error
- Attribute Error
- Hybrid Simplification



Geometric Error Measures

- Promote accurate 3D shape preservation
- Also preserves screen-space shape
 - Silhouettes
 - Pixel coverage

Bunny and Bronco Simplification






Classifying Geometric Error Metrics

- Vertex-Vertex Distance
- Vertex-Plane Distance
- Point-Surface Distance
- Surface-Surface Distance




Vertex-Vertex Distance



- $E = \max(\|v_3 - v_1\|, \|v_3 - v_2\|)$
- Appropriate during topology changes
 - Rossignac and Borrel 93
 - Luebke and Erikson 97
- Loose for topology-preserving collapses




Vertex-Plane Distance



- Store set of planes with each vertex
 - Error based on distance from vertex to planes
 - When vertices are merged, merge sets
- Ronfard and Rossignac 96
 - Store plane sets, compute max distance
- *Error Quadratics* - Garland and Heckbert 96
 - Store quadratic form, compute sum of square distances




Point-Surface Distance



- Used in Hoppe 93 and 96
- Map point set to closest points on simplified surface
- Compute sum of square distances



Surface-Surface Distance



- Bound maximum distance between input and simplified surfaces
 - Tolerance Volumes - Guéziec 96
 - Simplification Envelopes - Cohen/Varshney 96
 - Hausdorf Distance - Klein 96
 - Mapping Distance - Bajaj/Schikore 96, Cohen et al. 97



Vertex-Vertex \neq Surface-Surface



- Error is zero at vertices and exterior edges
- Error is non-zero everywhere else
 - not captured by vertex-vertex or vertex-plane metrics




Memoryless Simplification

- Lindstrom/Turk 98
- No measure of error from original mesh
 - *Incremental* rather than total error
- Preserve volume and area as simplification progresses
- Low error demonstrated after-the-fact
 - Metro - Cignoni et al. 96



Screen-space Geometric Error





Geometric Error Observations

- Vertex-vertex and vertex-plane distance
 - Fast
 - Low error shown after-the-fact, but not guaranteed by metric
- Cannot guarantee quality without surface-surface distance bound
- Hoppe's point-surface approximates one-sided surface-surface
- Good error measures useful at run-time
 - 3D average or maximum error distance



What I'll Talk About

- Introduction
- Geometric Error
- Attribute Error
- Hybrid Simplification



Attribute Error Metrics

- Attributes include colors, normals, and texture coordinates
- Promote accuracy of final pixel colors



Classifying Attribute Error Metrics

- Vertex-Vertex Distance
- Vertex-Plane Distance
- Point-Surface Distance
- Surface-Surface Distance



Vertex-Vertex Distance

- GAPS point clouds - Erikson/Manocha 98
 - Measure sum of square distances from vertex to its constituent vertices (area-weighted)
 - Used for colors, normals, and texture coordinates
 - Stored as 5 floats for 3D attributes (e.g. rgb)
- Normal cones
 - Luebke/Erikson 97, Xia et al. 97



Vertex-Plane Distance

- Higher-dimensional error quadrics
 - Garland and Heckbert 98
 - Vertices live in higher-dimensional position + attribute space
 - Planes defined in this space
- Multiple attribute quadrics
 - Hoppe 99
 - Decouples affects of position and attributes
 - Reduces storage and computational complexity



Point-Surface Distance

- Extension of geometric point-surface distance
 - Hoppe 96
- Geometric correspondences found between original surface samples and simplified surface
- Sum of square attribute distances minimized
- Used primarily for vertex colors



Surface-Surface Distance

- Bajaj / Schikore 96
 - Geometric projections provide local mappings
 - Maximum distance of scalar attributes measured over surface



Screen-space Attribute Error

- Texture coordinates work like geometric error
 - Cohen et al. 98
- Normal error controls dynamic refinement around highlights
 - Xia et al. 97, Klein 98
 - Doesn't allow more simplification as objects recede
- Color control?



What I'll Talk About

- Introduction
- Geometric Error
- Attribute Error
- Hybrid Simplification



Hybrid Simplification

- Integrates multi-resolution polygon and point rendering into single hierarchy
 - Based on *Multi-triangulation* data structure of DeFloriani et al '97
- Optimizes hierarchy based on primitives for a given error bound
- full paper - *IEEE Visualization 2001*
<http://www.cs.jhu.edu/~cohen/publications.html>



Simplification Operations


- Polygon simplification (edge collapse)
- Point replacement
 - replace a triangle with fewer than κ points
 - choose points to cover triangle
 - error: triangle error + point radius
- Point simplification
 - merge points (using octree)
 - error: max triangle error + point radius




Polygons versus Points

- Each has measurable rendering performance on a given platform
 - Perhaps based on combination of transform rate and fill rate
- Measure ratio of performance, κ
 - how many points equals a polygon
- Optimize LOD creation to minimize primitive count for given error bound


Bunny Model Varying Kappa (log scale)



Bunny Model Varying Tau (log scale)




Bronco Model Varying Tau (log scale)






Bunny - 1,2,3,4% object-space deviation





Bunny - 5 pixels of deviation





Hybrid Armadillo





Conclusions

- Variety of approaches to bounding object and attribute space errors
- Screen-space geometric error known
- Screen-space texture error known
- Screen-space color and normal error still have room for improvement
 - Employ bounds on color and normal deviation at run-time
 - Guarantee appearance, but simplify more as objects recede
 - Texture and normal map approach requires parameterization, texture management, and advanced shading functions

References

- Bajaj, Chandrajit and Daniel Schikore. Error-bounded Reduction of Triangle Meshes with Multivariate Data. *SPIE*. vol. 2656. 1996. pp. 34-45.
- Cohen, Jonathan, Dinesh Manocha, and Marc Olano. Simplifying Polygonal Models using Successive Mappings. Proceedings of IEEE Visualization '97. pp. 395-402.
- Cohen, Jonathan, Marc Olano, and Dinesh Manocha. Appearance-Preserving Simplification. Proceedings of ACM SIGGRAPH 98. pp. 115-122.
- Cohen, Jonathan, Amitabh Varshney, Dinesh Manocha, Gregory Turk, Hans Weber, Pankaj Agarwal, Frederick Brooks, and William Wright. Simplification Envelopes. Proceedings of SIGGRAPH 96. pp. 119-128.
- DeFloriani, Leila, Paola Magillo, and Enrico Puppo. Building and Traversing a Surface at Variable Resolution. Proceedings of IEEE Visualization '97. pp. 103-110.
- Erikson, Carl and Dinesh Manocha. GAPS: General and Automatic Polygonal Simplification. Proceedings of 1999 ACM Symposium on Interactive 3D Graphics. pp. 79-88.

References

- Garland, Michael and Paul Heckbert. Simplifying Surfaces with Color and Texture using Quadric Error Metrics. Proceedings of IEEE Visualization '98. pp. 263-269, 542.
- Garland, Michael and Paul Heckbert. Surface Simplification using Quadric Error Bounds. Proceedings of SIGGRAPH 97. pp. 209-216.
- Guéziec, André. Surface Simplification with Variable Tolerance. Proceedings of Second Annual International Symposium on Medical Robotics and Computer Assisted Surgery (MRCAS '95). pp. 132-139.
- Hoppe, Hugues. Progressive Meshes. Proceedings of SIGGRAPH 96. pp. 99-108.
- Hoppe, Hugues. View-Dependent Refinement of Progressive Meshes. Proceedings of SIGGRAPH 97. pp. 189-198.
- Hoppe, Hugues, Tony DeRose, Tom Duchamp, John McDonald, and Werner Stuetzle. Mesh Optimization. Proceedings of SIGGRAPH 93. pp. 19-26.
- Hoppe, Hugues H. New Quadric Metric for Simplifying Meshes with Appearance Attributes. Proceedings of IEEE Visualization '99. pp. 59-66.

References

- Klein, Reinhard, Gunther Liebich, and Wolfgang Straßer. Mesh Reduction with Error Control. Proceedings of IEEE Visualization '96.
- Lindstrom, Peter and Greg Turk. Fast and Memory Efficient Polygonal Simplification. Proceedings of IEEE Visualization '98. pp. 279-286, 544.
- Luebke, David and Carl Erikson. View-Dependent Simplification of Arbitrary Polygonal Environments. Proceedings of SIGGRAPH 97. pp. 199-208.
- Ronfard, Remi and Jarek Rossignac. Full-range Approximation of Triangulated Polyhedra. Computer Graphics Forum. vol. 15(3). 1996. pp. 67-76 and 462.
- Rossignac, Jarek and Paul Borrel. Multi-Resolution 3D Approximations for Rendering. Modeling in Computer Graphics. Springer-Verlag 1993. pp. 455-465.
- Xia, Julie C., Jihad El-Sana, and Amitabh Varshney. Adaptive Real-Time Level-of-Detail-Based Rendering for Polygonal Models. IEEE Transactions on Visualization and Computer Graphics. vol. 3(2). 1997. pp. 171-183.