

# Upgrading To Rumpus 4.1

**For users of earlier versions of Rumpus upgrading to the latest release.**

## **Upgrading From Rumpus 3.X**

Rumpus version 4 marks a significant break from earlier versions of Rumpus, with completely revised methods of storing preferences and settings. Unfortunately, this means that upgrading from a previous version is not a simple matter of dropping in the updated Rumpus application, but we are sure that you will find moving to Rumpus 4 worth the effort.

When upgrading to Rumpus 4, launch the new version and complete the Setup Assistant exactly as you would if you were installing Rumpus for the first time. Next, take a few minutes to review the options available on the “FTP Settings” and “Web Settings” windows, adjusting these preferences as needed for your environment. Also, use the “Folder Sets” and “Upload Notices” windows to re-create these settings as well.

User accounts can be imported from Rumpus 3.X. Open the “Install Server” window, click the “Import Users” button and select the Rumpus 3.X “Rumpus User Database” file from your previous version’s “Rumpus Prefs” folder. Your user accounts will be loaded, converted to the new format, and saved automatically. Of course, we strongly recommend that you review all user accounts to confirm that the user Home Folders and other security options are set correctly.

To have the Rumpus server daemon started automatically when your server starts up, open the “Install Server” window and check the “Start Rumpus Service At System Startup” checkbox. When first upgrading from Rumpus 3.5, you may need to first uncheck the box, deleting the old Rumpus 3.5 startup script, and then check the box again to create the newer Rumpus 4 startup script.

We at Maxum understand that moving to Rumpus 4 may require some reconfiguration for many people (especially those with a large number of Upload Notice definitions or Folder Sets). However, the changes put in place for version 4 will, in fact, minimize difficulty in updating Rumpus in the future, as the new settings format is more in line with the Mac OS X (Unix) method of handling server management files. It is always our goal to preserve your investment in Rumpus, and we thank you for your continued support.

## **Upgrading From Rumpus 4.0**

To upgrade from an earlier version of Rumpus 4, simply replace your older Rumpus control application with the new one found in the Rumpus package. Next, launch the Rumpus control application and stop

the server, if it is running. Open the "Install Server" window and click the "Update Rumpus" button to install the newer version of the Rumpus server daemon. Finally, close the "Install Server" window, and click "Start Server" to resume service. Rumpus 4 user accounts, upload notices, and all other preferences and settings will be preserved automatically.

### **A Special Note On WFM Template Customization**

In order to simplify WFM processing and template syntax, the following "WEBFILES" template tags used in Rumpus 4.0 and before have been deprecated. Rumpus 4.1 will no longer process these tags, but simple substitutions are available.

<WEBFILES_USERNAME>	(use <WEBFILES_VAR Username>)
<WEBFILES_USERLOGINS>	(use <WEBFILES_VAR UserLogins>)
<WEBFILES_USERBYTESDOWN>	(use <WEBFILES_VAR UserBytesDown>)
<WEBFILES_USERBYTESUP>	(use <WEBFILES_VAR UserBytesUp>)
<WEBFILES_USERFILESDOWN>	(use <WEBFILES_VAR UserFilesDown>)
<WEBFILES_USERFILESUP>	(use <WEBFILES_VAR UserFilesUp>)
<WEBFILES_PI_SCRIPT>	(include javascript as needed)
<WEBFILES_PI_SUBMIT>	(include javascript as needed)
<WEBFILES_PI_CLOSE>	(include javascript as needed)
<WEBFILES_PI_CLOSE_SCRIPT>	(include javascript as needed)

Progress indicator scripts are now included or excluded from the default templates using the <WEBFILES\_JAVA\_ENABLED> and <WEBFILES\_JAVA\_DISABLED> condition tags. If your custom template uses these deprecated tags to embed a progress indicator, replace the tags with javascripts shown below.

#### *WEBFILES\_PI\_SCRIPT*

```
<SCRIPT LANGUAGE="JavaScript">
function sendFile() {
document.forms[0].submit();
window.open("/Rumpus.ProgressIndicator",
"ProgressIndicator",
"toolbar=no,location=no,directories=no,
status=no,menubar=no,scrollbars=no,
resizable=no,copyhistory=no,width=440,
height=280");
}
</SCRIPT>
```

*WEBFILES\_PI\_SUBMIT*

```
ONCLICK='JavaScript:sendFile()'
```

*WEBFILES\_PI\_CLOSE\_SCRIPT*

```
<SCRIPT LANGUAGE="JavaScript">
function closeProgressInd() {
var newreference = window.open("", "ProgressIndicator");
newreference.close();
}
</SCRIPT>
```

*WEBFILES\_PI\_CLOSE*

```
ONLOAD='JavaScript:closeProgressInd()'
```