

## Intuition and Workbench

```

/*
 * textclass.c Copyright (C) 1991 Commodore-Amiga, Inc. All Rights Reserved Worldwide
 * Written by David N. Junod
 * Compiled with SAS/C 5.10a LC -cfast -ms -v (must be linked with classface.o and
 * hookface.o)
 * The image structure as used by this class:
 *
 * struct Image {
 *     SHORT LeftEdge;
 *     SHORT TopEdge;
 *     SHORT Width;
 *     SHORT Height;
 *     SHORT Depth;
 *     USHORT *ImageData;
 *     UBYTE PlanePick;
 *     UBYTE PlaneOnOff;
 *
 *     struct Image *NextImage;
 * };
 *
 * -----Maintained by boopsi (must be set to CUSTOMIMAGEDDEPTH).
 * -----Pointer to a NULL terminated text string
 * -----We use this for the foreground color
 * -----We use this for the background color
 *
 * struct Image *NextImage; <-----Pointer to the next image. Handled by DrawImage(). };
 */
#include <exec/types.h>
#include <exec/libraries.h>
#include <intuition/intuition.h>
#include <intuition/classes.h>
#include <intuition/ghooks.h>
#include <intuition/gadgetclass.h>
#include <intuition/mageclass.h>
#include <intuition/screens.h>
#include <graphics/gfx.h>
#include <graphics/gfxmacros.h>
#include <libraries/gadtools.h>
#include <utility/tagitem.h>
#include <clib/macros.h>
#include <clib/exec_protos.h>
#include <clib/intuition_protos.h>
#include <clib/graphics_protos.h>
#include <clib/utility_protos.h>
#include <string.h>

extern struct Library *SysBase, *DOSBase;
extern struct Library *IntuitionBase, *GfxBase, *UtilityBase;

/*
 * Because we are dealing with imageclass objects, the data structure that makes up the
 * object is an intuition image structure.
 */
#define IM(o) ((struct Image *) (o))

#define MYCLASSID NULL
#define SUPERCLASSID (IMAGECLASS)

Class
IntmyTextLabelClass(VOID);
freemyTextLabelClass(Class *cl);
ULONG
___savesd
dispatchmyTextLabel(Class *cl, Object *o, struct opset *msg);
getmyTextLabelAttrs(Class *cl, Object *o, struct opset *msg);
drawmyTextLabel(Class *cl, Object *o, struct ImpDraw *msg);
atexExtent(struct RastPort *, STRPTR, LONG, struct TextExtnt *);
getLabelKeyStroke(STRPTR label);
getContentsExtent(Class *cl, Object *o, struct DrawInfo *drinfo);
static VOID
getContentsExtent(Class *cl, Object *o, struct DrawInfo *drinfo);

/* Prototypes of functions from classface.o */
DOMETHOD(Object *o, ULONG methodID, ...);
DOSUPERMETHOD(Class *cl, Object *o, ULONG methodID, ...);
COERCEMETHOD(Class *cl, Object *o, ULONG methodID, ...);
DM(OBJCLASS *cl, Object *o, Msg msg);
DSM(CLASS *cl, Object *o, Msg msg);
SetSuperAttrs(Class *cl, Object *o, ULONG data, ...);

```

## Page IV - 53

## Writing a Boopsi Image Class

```

struct LocalObjData
{
    /* Font to use */
    struct TextFont *Lod_Font;
    /* The key that is underlined */
    WORD Lod_Key;
};

/* DrawMode */
Lod_Mode;
UBYTE

Class
IntmyTextLabelClass(VOID)
{
    ULONG hookEntry(); /* from hookface.o */
    Class *cl;
    if (cl = MakeClass(MYCLASSID,
                      SUPERCLASSID,
                      sizeof(struct LocalObjData), 0))
    {
        /* Fill in the callback hook */
        cl->cl_dispatcher.h_Entry = hookEntry;
        cl->cl_dispatcher.h_SubEntry = dispatchmyTextLabel;
    }
    /* Return a pointer to the class */
    return (cl);
}

ULONG
freemyTextLabelClass(Class *cl)
{
    /* Try to free the public class */
    return ((ULONG) FreeClass(cl));
}

/* The SAS "___savesd" flag tells the SAS compiler to put
 * the data storage address + 32/66 into Arg.
 */
ULONG
___savesd
dispatchmyTextLabel(Class *cl, Object *o, Msg msg)
{
    struct LocalObjData *Lod;
    Object *newobj;
    ULONG retval;

    switch (msg->MethodID)
    {
        case OM_NEW:
            /* Pass up to the superclass... */
            if (newobj = (Object *) DSM(cl, o, msg))
            {
                struct DrawInfo *drinfo;
                struct DrawInfo *drinfo;

                /* Get the DrawInfo */
                drinfo = (struct DrawInfo *) GetRastData(SYSIA_DrawInfo, NULL, attrs);

                /* Get the instance data */
                Lod = INSTR_DATTR(cl, newobj);

                /* Establish defaults */
                IM(newobj)->PlanePick = 1;
                Lod->Lod_Mode = JAMI;

                /* Set the attributes */
                setmyTextLabelAttrs(cl, newobj, (struct opset *) msg);

                /* Get the bounding rectangle of the label */
                getContentsExtent(cl, newobj, drinfo);
                retval = (ULONG) newobj;
            }
            break;
    }
}

```

```

case OM_GET:
    retval = getmyTextLabelAttr(cl, o, (struct opGet *) msg);
    break;

case OM_UPDATE:
case OM_SET:
    /* Do the superclass first */
    retval = DSM(cl, o, msg);

    /* Call our set routines */
    retval += setmyTextLabelAttrs(cl, o, (struct opSet *) msg);
    break;

case IM_DRAW:          /* draw the label */
case IM_DRAWFRAME:    /* drawmyTextLabel() will take care of
                       extra framing info */
    retval = drawmyTextLabel(cl, o, (struct impDraw *) msg);
    break;

/* Let the superclass handle everything else */
default:
    retval = (ULONG) DSM(cl, o, msg);
    break;
}

return (retval);
}

/* Set attributes of an object */
ULONG
setmyTextLabelAttrs(Class * cl, Object * o, struct opSet * msg)
{
    struct localObjData *lod = INST_DATA(cl, o);
    struct TagItem *tags = msg->ops_AttrList;
    struct TagItem *tstate;
    struct TagItem *tag;
    ULONG          tidata;

    /* process rest */
    tstate = tags;
    while (tag = NextTagItem(&tstate))
    {
        tidata = tag->ti_Data;
        switch (tag->ti_Tag)
        {
            case IA_FGPen:
                IM(o)->PlanePick = (UBYTE) tidata;
                break;

            case IA_BGPen:
                IM(o)->PlaneOnOff = (UBYTE) tidata;
                break;

            /* Must be a TextFont pointer. */
            case IA_Font:
                /* Set the font */
                lod->lod_Font = (struct TextFont *) tidata;
                break;

            /* Drawing mode to use */
            case IA_Mode:
                lod->lod_Mode = (UBYTE) tidata;
                break;

            case IA_Data:
                IM(o)->ImageData = (USHORT *) tidata;
                lod->lod_Key = GetLabelKeystroke((STRPTR) tidata);
                break;
        }
    }

    return (1L);
}

```

```

/* Inquire attributes of an object */
ULONG
getmyTextLabelAttr(Class * cl, Object * o, struct opGet * msg)
{
    struct localObjData *lod = INST_DATA(cl, o);

    switch (msg->opg_AttrID)
    {
        case IA_Font:
            *msg->opg_Storage = (ULONG) lod->lod_Font;
            break;

        case IA_Mode:
            *msg->opg_Storage = (ULONG) lod->lod_Mode;
            break;

        /* Let the superclass try */
        default:
            return ((ULONG) DSM(cl, o, msg));
    }

    return (1L);
}

ULONG
drawmyTextLabel(Class * cl, Object * o, struct impDraw * msg)
{
    struct localObjData *lod = INST_DATA(cl, o);
    STRPTR          label = (STRPTR) IM(o)->ImageData;
    struct DrawInfo *di = msg->imp_DrInfo;
    struct RastPort *rp = msg->imp_RPort;
    struct TextFont *tf = NULL;
    WORD           len = strlen(label);
    WORD           left, top;
    WORD           height = 0;
    WORD           width = 0;
    WORD           i;

    /* Clear the key */
    lod->lod_Key = NULL;

    /* Get a pointer to the font to use */
    if (!(tf = lod->lod_Font) && di)
    {
        tf = di->dri_Font;
    }

    /* Make sure we have font pointer */
    if (tf)
    {
        /* Set the font */
        SetFont(rp, tf);
    }

    /* Figure out our coordinates */
    top = msg->imp_Offset.Y + IM(o)->TopEdge + rp->TxBaseline;
    left = msg->imp_Offset.X + IM(o)->LeftEdge;

    /* See if we have frame information. */
    if (msg->MethodID == IM_DRAWFRAME)
    {
        /* Center the text inside the frame. */
        width = msg->imp_Dimensions.Width;
        height = msg->imp_Dimensions.Height;
        top += ((height - IM(o)->Height) > 0) ? ((height - IM(o)->Height) / 2) : 0;
        left += ((width - IM(o)->Width) > 0) ? ((width - IM(o)->Width) / 2) : 0;
    }

    /* Set the colors */
    SetAPen(rp, IM(o)->PlanePick);
    SetBPen(rp, IM(o)->PlaneOnOff);

    /* Set the drawing mode */
    SetDrMd(rp, lod->lod_Mode);

    /* Move to the start */
    Move(rp, left, top);
}

```



```

/*
 * example.c Copyright (C) 1991 Commodore-Amiga, Inc. All Rights Reserved Worldwide
 * Written by David N. Junod
 *
 * Compiled with SAS/C 5.10a LC -cfist -ms -v (must be linked with
 * texticlass.o, classface.o and hookface.o)
 */

#include <exec/types.h>
#include <exec/libraries.h>
#include <intuition/intuition.h>
#include <intuition/classes.h>
#include <intuition/classusr.h>
#include <intuition/cghooks.h>
#include <intuition/gadgetclass.h>
#include <intuition/imageclass.h>
#include <graphics/gfx.h>
#include <graphics/gfxmacros.h>
#include <libraries/gadtools.h>
#include <utility/tagitem.h>
#include <clib/macros.h>
#include <clib/exec_protos.h>
#include <clib/dos_protos.h>
#include <clib/intuition_protos.h>
#include <clib/graphics_protos.h>
#include <clib/utility_protos.h>
#include <string.h>

extern struct Library *SysBase, *DOSBase;
struct Library *IntuitionBase, *GfxBase, *UtilityBase;

Class          *initmyTextLabelClass(VOID);
ULONG          freemyTextLabelClass(Class * cl);

VOID
main(VOID)
{
    Class          *cl;
    struct Image   *im;
    struct Window  *win;
    struct RastPort *rp;
    UWORD          top, left, height;

    /* Make sure we're at least using Version 2.0 */
    if (IntuitionBase = OpenLibrary("intuition.library", 36))
    {
        GfxBase = OpenLibrary("graphics.library", 36);
        UtilityBase = OpenLibrary("utility.library", 36);

        /* Open a window, without system gadgets or IDCMP events */
        if (win = OpenWindowTags(NULL,
                                WA_Left, 10,
                                WA_Top, 10,
                                WA_Width, 320,
                                WA_Height, 100,
                                TAG_DONE))
        {
            /* Cache the pointer to the RastPort */
            rp = win->RPort;

            /* Cache the upper-left coordinates of the window */
            top = win->BorderTop + INTERHEIGHT;
            left = win->BorderRight + INTERWIDTH;

            /* Cache the height of the font */
            height = rp->TxHeight + INTERHEIGHT;

            /* Initialize the custom image class. */
            if (cl = initmyTextLabelClass())
            {
                /* Create a new image structure, using the given string. */
                if (im = NewObject(cl, NULL,
                                   IA_Data, (ULONG) "Line _1",
                                   TAG_DONE))
                {
                    /* Paint using the provided text string. */
                    DrawImageState(rp, im, left, top,

```

```

                                IDS_NORMAL, NULL);

                    /* Replace the text string, and paint it. */
                    im->ImageData = (USHORT *) "Line _2";
                    DrawImageState(rp, im, left, top + height,
                                   IDS_NORMAL, NULL);

                    /* Replace the text string, and paint it. */
                    im->ImageData = (USHORT *) "Line _3";
                    DrawImageState(rp, im, left, top + (height * 2),
                                   IDS_NORMAL, NULL);

                    /* Free the image. */
                    DisposeObject(im);
                }

                /* Free the image class. */
                freemyTextLabelClass(cl);
            }

            Delay(250);
            CloseWindow(win);
        }

        CloseLibrary(UtilityBase);
        CloseLibrary(GfxBase);
        CloseLibrary(IntuitionBase);
    }
}

```

