

```

/* ListDir.c - Amiga Mail simple ExAll() example.
lc -cfis -v -d0 -b0 -j73 ListDir.c
blink from ListDir.o to ListDir lib lib:amiga.lib ;if you don't have pragmas
quit
*
* Pure code if pragmas are used.
* Tuesday, 16-Jul-91 16:21:14, Ewout
*
* Compiled with SAS/C 5.10a
*/

#include <exec/memory.h>
#include <dos/dosextens.h>
#include <dos/rdargs.h>
#include <dos/exall.h>

#include <clib/exec_protos.h>
#include <clib/dos_protos.h>

/* undef PRAGMAS if you don't have them */
#define PRAGMAS
#undef PRAGMAS
#ifdef PRAGMAS
#include <pragmas/exec_pragmas.h>
#include <pragmas/dos_pragmas.h>
#else
struct ExecBase *SysBase;
struct DosLibrary *DOSBase;

#endif

/* Bufferize to receive filenames in */
#define BUFFERSIZE 512

VOID main(VOID);

VOID main(VOID)
{
#ifdef PRAGMAS
struct DosLibrary *DOSBase;
#endif

struct RDArgs *readargs;
LONG rargs[2];
struct ExAllControl *excontrol;
struct ExAllData *ead, *buffer;
UBYTE *source;
BPTR sourcelock;
BOOL exmore;
LONG error;

#ifdef PRAGMAS
/* set up SysBase */
SysBase = (*(struct Library **) 4);
#endif

/* Fail silently if < 37 */
if (DOSBase = (struct DosLibrary *) OpenLibrary("dos.library", 37))
{
if (readargs = ReadArgs("DIRECTORY/A", rargs, NULL))
{
source = (UBYTE *) rargs[0];

if (buffer = AllocMem(BUFFERSIZE, MEMF_CLEAR))
{
if (sourcelock = Lock(source, SHARED_LOCK))
{
if (excontrol = AllocDosObject(DOS_EXALLCONTROL, NULL))
{
excontrol->eac_LastKey = 0;

```

```

do
{
exmore = ExAll(sourcelock,
buffer,
BUFFERSIZE,
ED_NAME,
excontrol);

error = IoErr();
if ((exmore == NULL &&
(error != ERROR_NO_MORE_ENTRIES)))
break;

if (excontrol->eac_Entries == 0)
continue;

ead = buffer;
do
{
/* Check for CTRL-C */
if (SetSignal(0L, SIGBREAKF_CTRL_C) &
SIGBREAKF_CTRL_C)
{
error = ERROR_BREAK;
exmore = FALSE;
break;
}

rargs[0] = (LONG) ead->ed_Name;
VFPrintf(Output(), "%s\n", rargs);

ead = ead->ed_Next;
} while (ead);
} while (exmore);

if (error != ERROR_NO_MORE_ENTRIES)
PrintFault(error, NULL);

FreeDosObject(DOS_EXALLCONTROL, excontrol);
}
else
PrintFault(ERROR_NO_FREE_STORE, NULL);

Unlock(sourcelock);
}
else
PrintFault(IoErr(), source);

FreeMem(buffer, BUFFERSIZE);
}
else
PrintFault(ERROR_NO_FREE_STORE, NULL);
FreeArgs(readargs);
}
else
PrintFault(IoErr(), NULL);
CloseLibrary((struct Library *) DOSBase);
}
}

```

```

/* ListDir2.c AmigaMail seconds ExAll() example.
lc -cfis -v -d0 -b0 -j73 ListDir2.c
blink from ListDir2.o to ListDir2 lib lib:amiga.lib ;if you don't have pragmas
quit
*
* Pure code if pragmas are used.
* Tuesday, 16-Jul-91 16:21:14, Ewout
*
* Compiled with SAS/C 5.10a
*/
#include <exec/memory.h>
#include <dos/dosextns.h>
#include <dos/rdargs.h>
#include <dos/exall.h>
#include <utility/hooks.h>

#include <clib/exec_protos.h>
#include <clib/dos_protos.h>
#include <clib/utility_protos.h>

/* undef PRAGMAS if you don't have them */
#define PRAGMAS
#undef PRAGMAS
#ifdef PRAGMAS
#include <pragmas/exec_pragmas.h>
#include <pragmas/dos_pragmas.h>
#include <pragmas/utility_pragmas.h>
#else
struct ExecBase *SysBase;
struct DosLibrary *DOSBase;
struct Library *UtilityBase;

#endif

/* Bufferize to receive filenames in */
#define BUFFERSIZE 512

VOID          main(VOID);
UWORD         StrLen(UBYTE *);

/* SAS/C specific, use asm stub otherwise */
#define ASM __asm
#define REG(x) register __## x
BOOL ASM ExAllHook(REG(a0) struct Hook * hook,
                  REG(a1) struct ExAllData * data,
                  REG(a2) LONG * datatype);

VOID
main(VOID)
{
#ifdef PRAGMAS
    struct DosLibrary *DOSBase;
    struct Library *UtilityBase;
#endif

    struct RDArgs *readargs;
    LONG          rargs[4];
    struct ExAllControl *excontrol;
    struct ExAllData *ead, *buffer;
    struct Hook      exallhook;
    UBYTE           *pattern, *parsebuffer;
    BPTR           sourcelock;
    BOOL           exmore;
    COUNT          i;
    LONG           parselength, type, error;

#ifdef PRAGMAS
    /* set up SysBase */
    SysBase = (*(struct Library **) 4);
#endif

    /* Fail silently if < 37 */
    if (DOSBase = (struct DosLibrary *) OpenLibrary("dos.library", 37))
    {

```

```

UtilityBase = DOSBase->dl_UtilityBase;

rargs[1] = 0L;
rargs[2] = 0L;
if (readargs = ReadArgs("PATTERN/A,DIRS/S,FILES/S", rargs, NULL))
{
    pattern = (UBYTE *) rargs[0];

    /*
    * If DIRS or files not specified or both, accept
    * both files and directories
    */
    if (rargs[1] == rargs[2])
        type = 0;
    else
    {
        /* Accept only directories */
        if (rargs[1])
            type = 1;
        /* Accept only files */
        else
            type = -1;
    }

    parselength = StrLen(pattern) * 3;
    if (parsebuffer = AllocMem(parselength, MEMF_CLEAR))
    {

        /* Make pattern uppercase for possible character classes */
        i = 0;
        while (pattern[i])
            pattern[i] = ToUpper(pattern[i++]);

        if ((ParsePatternNoCase(pattern, parsebuffer, parselength)) != -1)
        {
            if (buffer = AllocMem(BUFFERSIZE, MEMF_CLEAR))
            {
                sourcelock =
                    ((struct Process *) FindTask(NULL))->pr_CurrentDir;

                if (excontrol = AllocDosObject(DOS_EXALLCONTROL, NULL))
                {
                    exallhook.h_Entry = ExAllHook;
                    exallhook.h_Data = (VOID *) type;

                    excontrol->eac_MatchString = parsebuffer;
                    excontrol->eac_MatchFunc = &exallhook;

                    do
                    {
                        exmore = ExAll(sourcelock,
                                      buffer,
                                      BUFFERSIZE,
                                      ED_TYPE,
                                      excontrol);

                        error = IoErr();
                        if ((exmore == NULL &&
                             (error != ERROR_NO_MORE_ENTRIES)))
                            break;

                        if (excontrol->eac_Entries == 0)
                            continue;

                        ead = buffer;
                        do
                        {
                            /* Check for CTRL-C */
                            if (SetSignal(0L, SIGBREAKF_CTRL_C) &
                                SIGBREAKF_CTRL_C)

```

```

        {
            error = ERROR_BREAK;
            exmore = FALSE;
            break;
        }

        rargs[0] = (LONG) ead->ed_Name;
        VFPrintf(Output(), "%s\n", rargs);

        ead = ead->ed_Next;
    } while (ead);
} while (exmore);

if (error != ERROR_NO_MORE_ENTRIES)
    PrintFault(error, NULL);

FreeDosObject(DOS_EXALLCONTROL, excontrol);
else
    PrintFault(ERROR_NO_FREE_STORE, NULL);

FreeMem(buffer, BUFFERSIZE);
}
else
    PrintFault(ERROR_NO_FREE_STORE, NULL);
}
else
    PrintFault(ERROR_BAD_TEMPLATE, NULL);
FreeMem(parsebuffer, parselength);
}
else
    PrintFault(ERROR_NO_FREE_STORE, NULL);
FreeArgs(readargs);
}
}
}

BOOL ASM
ExAllHook(REG(a0) struct Hook * hook,
          REG(a1) struct ExAllData * data,
          REG(a2) LONG * datatype)
{
    LONG        neededfiletype = (LONG) hook->h_Data;
    BOOL        success = TRUE;

    if (neededfiletype != 0)
    {
        if (data->ed_Type > 0 && neededfiletype < 0)
            success = FALSE;
        if (data->ed_Type < 0 && neededfiletype > 0)
            success = FALSE;
    }
    return (success);
}

UWORD
StrLen(UBYTE * string)
{
    UBYTE        *length = string + 1;

    while (*string++ != '\0');
    return ((UWORD) (string - length));
}

```

```

/* Find.c - Amiga Mail ExAll() example.
lc -cfis -v -d0 -b0 -j73 Find.c
blink from Find.o to Find lib lib:amiga.lib; if you don't have pragmas
quit
*
* Pure code if pragmas are used.
* Tuesday, 16-Jul-91 16:21:14, Ewout
*
* Compiled with SAS/C 5.10a:
*/
#include <exec/memory.h>
#include <dos/dosextern.h>
#include <dos/rdargs.h>
#include <dos/exall.h>

#include <clib/exec_protos.h>
#include <clib/dos_protos.h>
#include <clib/utility_protos.h>

/* undef PRAGMAS if you don't have them */
/* #define PRAGMAS */
#undef PRAGMAS
#ifdef PRAGMAS
#include <pragmas/exec_pragmas.h>
#include <pragmas/dos_pragmas.h>
#include <pragmas/utility_pragmas.h>
#else
struct ExecBase *SysBase;
struct DosLibrary *DOSBase;
struct Library *UtilityBase;
#endif

/* ExAll buffersize to receive data in */
#define BUFFERSIZE 512
/* Default buffersize for hold fully qualified filenames */
#define NAMEBUFFERSIZE 512

/* Used to pass data around to functions */
struct FindControl
{
    struct DosLibrary *fc_DOSBase;
    UBYTE        *fc_Parsebuffer;    /* Buffer which contains the parsed pattern */
    ULONG        fc_Parsebuffer;    /* The length of this buffer */
    UBYTE        *fc_Namebuffer;    /* Buffer to hold the filename */
    ULONG        fc_Namebuffer;    /* The length of that buffer */
    BOOL        fc_Files;    /* BOOLEAN which tells if we should only look for files */
    BOOL        fc_Dirs;    /* BOOLEAN which tells if we should only look for dirs */
    BOOL        fc_All;    /* ALL keyword? */
};

static UBYTE    *VersTag = "\0$VER: Find 37.1 (16.07.91)";

LONG        main(VOID);
LONG        ScanDirectory(struct FindControl *, UBYTE *);
BOOL        IsAssign(struct FindControl *, UBYTE *);
LONG        MultiScanDirectory(struct FindControl *, UBYTE *);
UWORD        StrLen(UBYTE *);

LONG        main(VOID)
{
#ifdef PRAGMAS
    struct DosLibrary *DOSBase;
    struct Library *UtilityBase;
#endif

#ifdef RDArgs
    struct RDArgs *readargs;
    LONG        rargs[6];
    struct FindControl *fc;
    UBYTE        *pattern, **directories;
    struct Process *process;
    APTR        windowptr;
    COUNT        i;
    LONG        rc = 0, error = 0, fatalerror = 0;

```

```

#ifndef PRAGMAS
/* set up SysBase */
SysBase = (*(struct Library **) 4);
#endif

/* Fail silently if < 37 */
if (DOSBase = (struct DosLibrary *) OpenLibrary("dos.library", 37))
{
    UtilityBase = DOSBase->dl_UtilityBase;

    rargs[0] = 0L;
    rargs[1] = 0L;
    rargs[2] = 0L;
    rargs[3] = 0L;
    rargs[4] = 0L;
    rargs[5] = 0L;

    if (readargs =
        ReadArgs("PATTERN/A,DIRECTORY/A/M,FILES/S,DIRS/S,ALL/S,BUFFER/K/N",
            rargs,
            NULL))
    {
        if (fc = AllocMem(sizeof(struct FindControl), MEMF_CLEAR))
        {
#ifndef PRAGMAS
            fc->fc_DOSBase = DOSBase;
#endif

            pattern = (UBYTE *) rargs[0];

            fc->fc_ParseLength = StrLen(pattern) * 3;
            if (fc->fc_Parsebuffer = AllocMem(fc->fc_ParseLength, MEMF_CLEAR))
            {
                /* Make pattern uppercase for possible character classes */
                i = 0;
                while (pattern[i])
                    pattern[i] = ToUpper(pattern[i++]);

                if ((ParsePatternNoCase(pattern,
                    fc->fc_Parsebuffer,
                    fc->fc_ParseLength)) != -1)
                {
                    directories = (UBYTE **) rargs[1];

                    fc->fc_Files = (BOOL) rargs[2];
                    fc->fc_Dirs = (BOOL) rargs[3];
                    fc->fc_All = (BOOL) rargs[4];

                    /*
                     * Both set or cleared, clear both anyway. Easier checking later on.
                     */
                    if (fc->fc_Files == fc->fc_Dirs)
                        fc->fc_Files = fc->fc_Dirs = FALSE;

                    if (rargs[5])
                        fc->fc_NameLength = *((LONG *) rargs[5]);

                    if (fc->fc_NameLength < NAMEBUFFERSIZE || fc->fc_NameLength > 4096)
                        fc->fc_NameLength = NAMEBUFFERSIZE;

                    if (fc->fc_Namebuffer = AllocMem(fc->fc_NameLength, MEMF_CLEAR))
                    {
                        process = (struct Process *) FindTask(NULL);
                        windowptr = process->pr_WindowPtr;
                        process->pr_WindowPtr = (APTR) - 1L;

                        while (*directories)
                        {
                            /*

```

```

                     * Check if this is a standalone assign which appears in the assign
                     * list?
                     */
                    if (IsAssign(fc, *directories))
                        error = MultiScanDirectory(fc, *directories++);
                    else
                        error = ScanDirectory(fc, *directories++);

                    if (error != 0)
                        break;
                }

                process->pr_WindowPtr = windowptr;

                FreeMem(fc->fc_Namebuffer, fc->fc_NameLength);
            }
            else
                fatalError = ERROR_NO_FREE_STORE;
        }
        else
            fatalError = ERROR_BAD_TEMPLATE;

        FreeMem(fc->fc_Parsebuffer, fc->fc_ParseLength);
    }
    else
        fatalError = ERROR_NO_FREE_STORE;
        FreeMem(fc, sizeof(struct FindControl));
    }
    else
        fatalError = ERROR_NO_FREE_STORE;

    FreeArgs(readargs);
}
else
    fatalError = IoErr();

/*
 * Error handling: To be informative, errors are shown while scanning, so the
 * file name which caused the error can be displayed. Other errors are shown
 * here. Errors which occurred in the main loop are considered fatal, others
 * (except BREAK) just error.
 */

if (fatalerror)
{
    error = fatalError;
    PrintFault(fatalerror, NULL);
}

SetIoErr(error);
if (error != 0)
{
    if (fatalerror)
        rc = RETURN_FAIL;
    else if (error == ERROR_BREAK)
        rc = RETURN_WARN;
    else
        rc = RETURN_ERROR;
}

CloseLibrary((struct Library *) DOSBase);
}
else
    rc = RETURN_FAIL;
return (rc);
}

LONG
ScanDirectory(struct FindControl * fc, UBYTE * source)
{
#ifndef PRAGMAS
    struct DosLibrary *DOSBase = fc->fc_DOSBase;

```

```

#endif
LONG          vargs[1];
struct ExAllControl *excontrol;
struct ExAllData *ead, *buffer;
BPTR          sourcelock, namelock, olddirlock;
BOOL          exmore;
LONG          error;

/*
 * Because this function may be recursively, get a fresh buffer per function call.
 */
if (buffer = AllocMem(BUFFERSIZE, MEMF_CLEAR))
{
    /* Get a lock on the start directory and make it the current directory */
    if (sourcelock = Lock(source, SHARED_LOCK))
    {
        olddirlock = CurrentDir(sourcelock);

        if (excontrol = AllocDosObject(DOS_EXALLCONTROL, NULL))
        {
            do
            {
                /* Get both file name and type to support FILES/DIRS keywords */
                exmore = ExAll(sourcelock, buffer, BUFFERSIZE, ED_TYPE, excontrol);
                error = IoErr();
                if ((exmore == NULL && (error != ERROR_NO_MORE_ENTRIES)))
                {
                    PrintFault(error, source);
                    break;
                }
                if (excontrol->eac_Entries == 0)
                    continue;

                ead = buffer;
                do
                {
                    /* Check for CTRL-C */
                    if (SetSignal(0L, SIGBREAKF_CTRL_C) & SIGBREAKF_CTRL_C)
                    {
                        error = ERROR_BREAK;
                        PrintFault(error, NULL);
                        exmore = FALSE;
                        break;
                    }
                }

                /* Check if this one matches. If it does see if it is of the right type.
                 */
                if (MatchPatternNoCase(fc->fc_Parsebuffer, ead->ed_Name))
                {
                    if ((ead->ed_Type < 0 && fc->fc_Dirs == FALSE)
                        || (ead->ed_Type > 0 && fc->fc_Files == FALSE))
                    {
                        /* It is. Lock it and get the fully qualified file name */
                        if (namelock = Lock(ead->ed_Name, SHARED_LOCK))
                        {
                            if ((NameFromLock(namelock,
                                                fc->fc_Namebuffer,
                                                fc->fc_Namelenhth)) == DOSTRUE)
                            {
                                {
                                    vargs[0] = (LONG) fc->fc_Namebuffer;
                                    VFPrintf(Output(), "%s\n", vargs);
                                }
                                else
                                {
                                    error = IoErr();
                                    PrintFault(error, ead->ed_Name);
                                }
                                Unlock(namelock);
                            }
                        }
                        else
                        {

```

```

                error = IoErr();
                PrintFault(error, ead->ed_Name);
            }
        }
    }

    /*
     * If the ALL keyword is used and this is a directory, step in it by
     * calling this function recursively.
     */
    if (ead->ed_Type > 0 && fc->fc_All)
    {
        error = ScanDirectory(fc, ead->ed_Name);
        if (error != 0)
        {
            exmore = FALSE;
            break;
        }
    }
    ead = ead->ed_Next;
} while (ead);
} while (exmore);

FreeDosObject(DOS_EXALLCONTROL, excontrol);
}
else
    error = ERROR_NO_FREE_STORE;

CurrentDir(olddirlock);
Unlock(sourcelock);
}
else
{
    error = IoErr();
    PrintFault(error, source);
}
FreeMem(buffer, BUFFERSIZE);
}
else
    error = ERROR_NO_FREE_STORE;

if (error == ERROR_NO_MORE_ENTRIES)
    error = 0;
else if (error == ERROR_NO_FREE_STORE)
    PrintFault(error, NULL);

return (error);
}

BOOL
IsAssign(struct FindControl * fc, UBYTE * name)
{
#ifdef PRAGMAS
    struct DosLibrary *DOSBase = fc->fc_DOSBase;
    struct Library *UtilityBase = DOSBase->dl_UtilityBase;
#endif

#endif
    struct DosList *doslist;
    UBYTE          *assignname;
    UCOUNT          assignlength;
    LONG            position;
    BOOL            result = FALSE;

    /* First lets check if this resembles a devicename. */
    position = SplitName(name, ':', fc->fc_Namebuffer, 0, fc->fc_Namelenhth);

    if (position != -1)
    {
        /* Hmmmm. */
        if (name[position] == '\0')
        {
            /*
             * I guess it does. Lets see if we can find it in the assign list. Keep the

```

```

    * DosList locked as briefly as possible. This shouldn't take long.
    */
    if (doslist = AttemptLockDosList(LDF_ASSIGNS | LDF_READ))
    {
        while (doslist = NextDosEntry(doslist, LDF_ASSIGNS))
        {
            /* It's a BPTR */
            assignname = (UBYTE *) BADDR(doslist->dol_Name);
            assignlength = assignname[0];

            if ((Strnicmp(assignname + 1, fc->fc_Namebuffer, assignlength)) == 0)
            {
                /* Yup, it is. */
                result = TRUE;
                break;
            }
        }
        UnlockDosList(LDF_ASSIGNS | LDF_READ);
        /* Can't lock DosList, don't bother */
    }
}
return (result);
}

LONG
MultiScanDirectory(struct FindControl * fc, UBYTE * source)
{
#ifdef PRAGMAS
    struct DosLibrary *DOSBase = fc->fc_DOSBase;
#endif
    struct DevProc *cproc = NULL;
    struct MsgPort *filesystemtask;
    LONG    error;

    filesystemtask = GetFileSysTask();

    do
    {
        /* Find handler */
        if (cproc = GetDeviceProc(source, cproc))
        {
            SetFileSysTask(cproc->dvp_Port);
            if ((NameFromLock(cproc->dvp_Lock,
                fc->fc_Namebuffer,
                fc->fc_Namelength)) == DOSTRUE)
            {
                error = ScanDirectory(fc, fc->fc_Namebuffer);
            }
            else
            {
                error = IoErr();
                PrintFault(error, source);
            }

            if (error != 0)
                break;
        }
        else
        {
            error = IoErr();
            PrintFault(error, source);
        }

        /* Handle multi-assign */
    } while (cproc && (cproc->dvp_Flags & DVPF_ASSIGN));

    SetFileSysTask(filesystemtask);
    if (cproc)
        FreeDeviceProc(cproc);

    return (error);
}

```

```

UWORD
StrLen(UBYTE * string)
{
    UBYTE    *length = string + 1;

    while (*string++ != '\0');
    return ((UWORD) (string - length));
}

```

```

/* ListPattern.c - AmigaMail MatchFirst()/MatchNext() example.
lc -cfls -v -d0 -b0 -j73 ListPattern.c
blink from ListPattern.o to ListPattern lib lib:amiga.lib ;if you don't have pragmas
quit
*/

#include <exec/memory.h>
#include <dos/dosextern.h>
#include <dos/rdargs.h>
#include <clib/exec_protos.h>
#include <clib/dos_protos.h>

/* undef PRAGMAS if you don't have them */
#define PRAGMAS
#undef PRAGMAS
#ifdef PRAGMAS
#include <pragmas/exec_pragmas.h>
#include <pragmas/dos_pragmas.h>
#else

struct ExecBase *SysBase;
struct DosLibrary *DOSBase;
#endif

VOID          main(VOID);
UWORD         StrLen(UBYTE *);

VOID
main(VOID)
{
#ifdef PRAGMAS
    struct DosLibrary *DOSBase;
#endif

    struct RDArgs *readargs;
    LONG          rargs[1];
    LONG          vargs[4];
    UBYTE         *pattern;
    struct AnchorPath *anchorpath;
    LONG          error;

#ifdef PRAGMAS
    /* set up SysBase */
    SysBase = *((struct Library **) 4);
#endif

    /* Fail silently if < 37 */
    if (DOSBase = (struct DosLibrary *) OpenLibrary("dos.library", 37))
    {
        /* See the DOS Autodocs for more information about ReadArgs() */
        if (readargs = ReadArgs("PATTERN/A", rargs, NULL))
        {
            pattern = (UBYTE *) rargs[0];
            if (anchorpath = AllocMem(sizeof(struct AnchorPath) + 512, MEMF_CLEAR))
            {
                anchorpath->ap_Strlen = 512;
                anchorpath->ap_BreakBits = SIGBREAKF_CTRL_C;

                if ((error = MatchFirst(pattern, anchorpath)) == 0)
                {
                    do
                    {
                        vargs[0] = (LONG) anchorpath->ap_Buf;
                        VFPrintf(Output(), "%s\n", vargs);
                    } while ((error = MatchNext(anchorpath)) == 0);
                }

                MatchEnd(anchorpath);

                if (error != ERROR_NO_MORE_ENTRIES)
                    PrintFault(error, NULL);

                FreeMem(anchorpath, sizeof(struct AnchorPath) + 512);
            }
        }
    }
}

```

```

        FreeArgs(readargs);
    }
    else
        PrintFault(IoErr(), NULL);
    CloseLibrary((struct Library *) DOSBase);
}
}

```

```

/* DirComp.c - AmigaMail Directory Compare example using MatchFirst()/Next().
lc -cfis -v -d0 -b0 -j73 DirComp.c
blink from DirComp.o to DirComp lib lib:amiga.lib ; if you don't have pragmas
quit
*
* Pure code if pragmas are used.
* Monday, 15-Jul-91 16:07:31, Ewout
*
* Compiled with SAS/C 5.10a
*/
#include <exec/memory.h>
#include <dos/dosextens.h>
#include <dos/rdargs.h>

#include <clib/exec_protos.h>
#include <clib/dos_protos.h>

/* undef PRAGMAS if you don't have them */
#undef PRAGMAS
#ifdef PRAGMAS
#include <pragmas/exec_pragmas.h>
#include <pragmas/dos_pragmas.h>
#else
struct ExecBase *SysBase;
struct DosLibrary *DOSBase;

#endif

/* Default size of buffer to build full targetpaths in */
#define BUFFERSIZE 256

static UBYTE *VersTag = "\$VER: DirComp 37.1 (15.07.91)";

LONG main(VOID);
LONG GetPath(UBYTE * path, UBYTE * buffer, LONG buffersize);
UBYTE *ItsWild(UBYTE * string);
UWORD StrLen(UBYTE *);

LONG main(VOID)
{
#ifdef PRAGMAS
struct DosLibrary *DOSBase;

#endif
struct RDArgs *readargs;
LONG rargs[5], vargs[5];
UBYTE *source, *target;
ULONG buffersize = 0;
UBYTE *sourcedir, *targetdir;
UBYTE *textbuffer, *tmp, *tmp1, *tmp2;
struct AnchorPath *anchorpath;
struct FileInfoBlock *fib, *targetfib;
struct Process *process;
APTR wptr;
BPTR dirlock, filelock;
BOOL checkdatestamp, all;
LONG date, error, rc = 0;

#ifdef PRAGMAS
/* set up SysBase */
SysBase = (*(struct Library **) 4);
#endif

/* Fail silently if < 37 */
if (DOSBase = (struct DosLibrary *) OpenLibrary("dos.library", 37))
{
rargs[0] = 0L;
rargs[1] = 0L;
rargs[2] = 0L;
rargs[3] = 0L;
rargs[4] = 0L;

if (readargs = ReadArgs("SOURCE/A,TARGET/A,DATE/S,ALL/S,BUFFER/K/N", rargs, NULL))
{

```

```

source = (UBYTE *) rargs[0];
target = (UBYTE *) rargs[1];
checkdatestamp = (BOOL) rargs[2];
all = (BOOL) rargs[3];

if (!(sourcedir = AllocMem(StrLen(source) + 129, MEMF_CLEAR)))
error = ERROR_NO_FREE_STORE;
else
{
/* 128 bytes to print informative text */
textbuffer = sourcedir + StrLen(source) + 1;

/* use user specified buffersize if indicated */
if (rargs[4])
buffersize = *((LONG *) rargs[4]);
if (buffersize < BUFFERSIZE || buffersize > 4096)
buffersize = BUFFERSIZE;

if (!(targetdir = AllocMem(buffersize, MEMF_CLEAR)))
error = ERROR_NO_FREE_STORE;
else
{
if (!(targetfib = AllocDosObject(DOS_FIB, NULL)))
error = ERROR_NO_FREE_STORE;
else
{
/*
* Check if source and target are valid.
*
* Separate source path from pattern (if any). Use the source path figure
* out what to append to the target.
*/

/* No requesters */
process = (struct Process *) FindTask(NULL);
wptr = process->pr_WindowPtr;
process->pr_WindowPtr = (APTR) - 1L;

if ((error = GetPath(source, sourcedir, StrLen(source) + 1) == 0))
{
if (!(dirlock = Lock(sourcedir, SHARED_LOCK)))
error = IoErr();
else
{
Unlock(dirlock);
if (!(dirlock = Lock(target, SHARED_LOCK)))
error = IoErr();
else
{
Unlock(dirlock);

if (anchorpath = AllocMem(sizeof(struct AnchorPath) + buffersize,
MEMF_CLEAR))
{
anchorpath->ap_Strlen = buffersize;

/* Allow to break on CTRL-C */
anchorpath->ap_BreakBits = SIGBREAKF_CTRL_C;

if ((error = MatchFirst(source, anchorpath)) == 0)
{
do
{
fib = &(anchorpath->ap_Info);

/*
* APF_DIDDIR indicates that we used returned from a
* directory. In that case we clear both APF_DIDDIR and
* APF_DODIR, so we can start afresh with the next one.
*/

```

```

if (anchorpath->ap_Flags & APF_DIDDIR)
  anchorpath->ap_Flags &= ~(APF_DODIR | APF_DIDDIR);
else
{
  /*
  * Make a filename for the target directory. First copy
  * targetname into buffer.
  */
  targetdir[0] = '\0';
  tmp = targetdir;
  tmp1 = target;
  while (*tmp++ = *tmp1++);

  /* Skip sourcename in ap_Buf */
  tmp1 = sourcedir;
  tmp2 = anchorpath->ap_Buf;
  while (*tmp1++ == *tmp2++);
  /* Skip back 1 if not after a separator */
  if (*tmp2 - 1) != '/'
    tmp2--;

  /*
  * We hit the source itself, don't compare it, but enter
  * it.
  */
  if (*tmp2 == 0)
  {
    anchorpath->ap_Flags |= APF_DODIR;
    continue;
  }

  /* Build it */
  if (AddPart(targetdir, tmp2, buffersize - 1))
    vargs[0] = (LONG) targetdir;
  else
  {
    PrintFault(ERROR_NO_FREE_STORE, NULL);
    break;
  }

  /* Lock it and check it out */
  if (filelock = Lock(targetdir, SHARED_LOCK))
  {
    if ((Examine(filelock, targetfib)) == DOSTRUE)
    {
      textbuffer[0] = '\0';

      /*
      * To get nice output without work I use AddPart() to
      * add differences to the textbuffer.
      */
      if (targetfib->fib_DirEntryType
          != fib->fib_DirEntryType)
        AddPart(textbuffer, "of different type", 128);
      else
      {
        if (targetfib->fib_Size < fib->fib_Size)
          AddPart(textbuffer, "smaller", 128);
        else if (targetfib->fib_Size > fib->fib_Size)
          AddPart(textbuffer, "larger", 128);

        if (checkdatestamp)
        {
          date = CompareDates((struct DateStamp *)
                              & (fib->fib_Date),
                              (struct DateStamp *) & (targetfib->fib_Date));
          if (date < 0)
            AddPart(textbuffer, "older", 128);
          else if (date > 0)
            AddPart(textbuffer, "newer", 128);
        }
      }
    }
  }
}

```

```

if (*textbuffer != NULL)
{
  vargs[1] = (LONG) textbuffer;
  VFPrintf(Output(), "%s: object %s\n", vargs);
}
else
  PrintFault(IoErr(), targetdir);
Unlock(filelock);
}
else
{
  PrintFault(IoErr(), targetdir);

  /*
  * If and error occurred on a directory name, don't enter
  * it.
  */
  if (fib->fib_DirEntryType > 0)
    continue;
}

/*
* If the ALL keyword has been used and this is a directory
* enter it by setting the APF_DODIR flag.
*/
if (fib->fib_DirEntryType > 0 && all != FALSE)
  anchorpath->ap_Flags |= APF_DODIR;
}
} while ((error = MatchNext(anchorpath)) == 0);

MatchEnd(anchorpath);

if (error == ERROR_NO_MORE_ENTRIES)
  error = 0;

FreeMem(anchorpath, sizeof(struct AnchorPath) + buffersize);
}
}
/* Reset windowpointer */
process->pr_WindowPtr = wptr;
}
else
  PrintFault(error, NULL);
FreeDosObject(DOS_FIB, targetfib);
}
FreeMem(targetdir, buffersize);
}
FreeMem(sourcedir, StrLen(sourcedir) + 129);
}
FreeArgs(readargs);
}
else
  error = IoErr();

SetIoErr(error);
if (error)
{
  PrintFault(error, NULL);
  if (error == ERROR_BREAK)
    rc = RETURN_WARN;
  else
    error = RETURN_FAIL;
}
CloseLibrary((struct Library *) DOSBase);
}
return (rc);
}

```

```

LONG
GetPath(UBYTE * path, UBYTE * buffer, LONG buffersize)
{
    UBYTE      *pathpart, *filepart;
    UBYTE      *tmp1, *tmp2;
    BPTR       lock;
    struct FileInfoBlock *fib;
    LONG       error = 0;

    /* Open own copy of dos.library if pragmas are used so it's standalone */
#ifdef PRAGMAS
    struct Library *DOSBase;

    if (!(DOSBase = OpenLibrary("dos.library", 36)))
        return (1);
#endif

    /*
     * If there seems to be no path, the pathpart will point to the filepart too, so we
     * need to check for that.
     */
    filepart = FilePart(path);
    pathpart = PathPart(path);

    /*
     * This also handles cases where there is only a volume/device name, only a
     * directory name or a combo of those.
     */
    if (pathpart == path)
    {
        /*
         * There seems to be only one component. Copy it if it is not wild. Caller will
         * have to check whether if it exists and if it is a file or directory.
         */
        if (!(ItsWild(pathpart)))
            pathpart = NULL;
    }

    if (pathpart != path)
    {
        /*
         * If pathpart equals filepart (pointer wise) then there is only one component
         * (possible preceeded by a volume name).
         */
        if (pathpart == filepart)
        {
            if (!(ItsWild(pathpart)))
                pathpart = NULL;
        }
        else
        {
            /* Try to lock it to determine if the last component is a directory. */
            if (lock = Lock(path, SHARED_LOCK))
            {
                if (fib = AllocMem(sizeof(struct FileInfoBlock), MEMF_CLEAR))
                {
                    if ((Examine(lock, fib)) == DOSTRUE)
                    {
                        /* Hey it's a directory after all */
                        if (fib->fib_DirEntryType > 0)
                            pathpart = NULL;
                    }
                    FreeMem(fib, sizeof(struct FileInfoBlock));
                }
                Unlock(lock);
            }
            /* else treat it as a filename */
        }
    }

    /* Copy the pathpart in the buffer */
    tmp1 = buffer;
    tmp2 = path;
    while ((*tmp1++ = *tmp2++) && (tmp2 != pathpart))
    {

```

```

        if (tmp1 == (buffer + buffersize))
        {
            error = ERROR_NO_FREE_STORE;
            break;
        }
    }
    *tmp1 = '\0';
}
/* NULL terminate. */

#ifdef PRAGMAS
    CloseLibrary(DOSBase);
#endif
return (error);
}

UBYTE      *
ItsWild(UBYTE * string)
{
    static UBYTE *special = "#?*%([|";
    UBYTE      *tmp = string;
    COUNT      i;

    do
    {
        for (i = 0; special[i] != '\0'; i++)
        {
            if (*tmp == special[i])
                return (tmp);
        }
        tmp++;
    } while (*tmp);

    return (NULL);
}

UWORD
StrLen(UBYTE * string)
{
    UBYTE      *length = string + 1;

    while (*string++ != '\0');
    return ((UWORD) (string - length));
}

```

