

Hardware_Manual

COLLABORATORS

	<i>TITLE :</i> Hardware_Manual		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		July 18, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Hardware_Manual	1
1.1	Amiga® Hardware Reference Manual: Index	1
1.2	Numbers Index	1
1.3	68000 Index	1
1.4	680x0 Index	2
1.5	8520 Index	2
1.6	A Index	2
1.7	A1000 Index	3
1.8	A3000 Index	3
1.9	ADKCON Index	3
1.10	Agnus Index	3
1.11	Audio Index	3
1.12	B Index	4
1.13	Beam position Index	5
1.14	Bitplanes Index	5
1.15	Blitter Index	5
1.16	BLTCON0 Index	6
1.17	BLTCON1 Index	6
1.18	BPLCON0 Index	7
1.19	BPLCON2 Index	7
1.20	C Index	7
1.21	CIAAPRA Index	8
1.22	Clock Index	8
1.23	Collision Index	8
1.24	Color Index	8
1.25	Color registers Index	9
1.26	Color selection Index	9
1.27	Control register Index	9
1.28	Controller Port Index	9
1.29	Controllers Index	10

1.30 Copper Index	10
1.31 Custom Chips Index	11
1.32 D Index	11
1.33 Data-fetch Index	12
1.34 Disk Index	12
1.35 Display window Index	12
1.36 DMA Index	13
1.37 DMACON Index	13
1.38 Dual Playfield Index	13
1.39 E,F,G,H Index	13
1.40 Enhanced Chip Set Index	14
1.41 Genlock Index	14
1.42 Hardware Connection Index	14
1.43 High resolution Index	15
1.44 I,J,K Index	15
1.45 Interlaced mode Index	15
1.46 Interrupt Index	16
1.47 Interrupt Control Register Index	16
1.48 JOY0DAT/JOY1DAT Index	16
1.49 Joystick Index	16
1.50 Keyboard Index	16
1.51 L,M,N,O Index	17
1.52 Light Pen Index	18
1.53 Line Drawing Index	18
1.54 Memory allocation Index	18
1.55 Modulo Index	18
1.56 NTSC Index	18
1.57 P Index	19
1.58 PAL Index	19
1.59 Parallel Port Index	19
1.60 Playfields Index	20
1.61 Ports Index	20
1.62 POTGO / POTINP Index	21
1.63 Priority Index	21
1.64 R,S Index	21
1.65 RAM Index	22
1.66 Scrolling Index	22
1.67 Serial Port Index	22
1.68 Serial Shift Register Index	23

1.69 Sprites Index	23
1.70 T,U,V,W,Z Index	24
1.71 Trackball Index	24
1.72 VHPOSR Index	24
1.73 Video Index	25
1.74 VPOSR Index	25
1.75 Zorro Expansion Bus Index	25

Chapter 1

Hardware_Manual

1.1 Amiga® Hardware Reference Manual: Index

Misc.	Note: Numbers will refer to page numbers in
A	the 'Amiga® Hardware Reference Manual'
B	3rd edition, ISBN 0-201-56776-8
C	
D	
E F G H	
I J K	
L M N O	
P	
R S	
T U V W Z	

1.2 Numbers Index

\$00C00000, 5
60 Pin Edge Connector, 321
68000, -->
68010, 1
68020, 1 , 187
68030, 1
680x0, -->
8361, 5
8370, 5
8371, 5
8372A, 5
8520, -->
86 Pin Edge Connector, 322

1.3 68000 Index

68000, 2 , 187
normal cycle, 196
test-and-set instruction, 196

1.4 680x0 Index

680x0, 19 , 25 , 35 , 194 , 223
 instead of Copper, 35
 interrupting, 35 , 217
 shared memory, 4
 synchronizing with the video beam, 216

1.5 8520 Index

8520, 157 , 223 , 241 , 244 , 251 , 339
 alarm, 344
 handshaking, 341
 input modes, 343
 interval timers, 341
 continuous, 342
 force load, 342
 one-shot, 342
 PB on/off, 342
 start/stop, 342
 Toggle/pulse, 342
 I/O ports, 341
 read bit names, 343
 register map, 340
 signal assignments, 337
 time-of-day clock, 344
 write bit names, 343

1.6 A Index

A1000, -->
A2000, 1 , 5 , 6 , 7 , 7 , 63 , 157 , 238 , 260
A3000, -->
A500, 1 , 5 , 7 , 63 , 157 , 238 , 260
Address Registers, 10
ADKCON, -->
Agnus, -->
Alarm, 344
Aliasing, audio, 154
AllocMem(), 52
Amiga OS, 9
Amplitude Modulation, 4
Animated Objects, 6
Animation, 176
Apple II, 241
Area Fill, 4 , 184
ATTACH, 120
Attachment - audio, 150 , sprites, 120
Audio, -->
Audio Channel, 19
AUDx, 220
AUDxEN, 144 , 222

AUDxLCH, 138 , 298
AUDxLCL, 138
AUDxLEN, 139
AUDxPER, 143 , 298
AUDxVOL, 139
AUTOCONFIG, 7 , 223 , 431

1.7 A1000 Index

A1000, 1 , 5 , 7 , 63 , 64 , 238 , 260
expansion port, 321

1.8 A3000 Index

A3000, 1 , 6 , 7 , 7 , 260
expansion bus, 383

1.9 ADKCON Index

ADKCON, 241 , 250 , 256
disk control bits, 249
in audio, 149-150

1.10 Agnus Index

Agnus, 2 , 5 , 164-165 , 169
ECS fat Agnus, 295
fat agnus, 187

1.11 Audio Index

Audio, 4 , 9 , 20
aliasing distortion, 154
amplitude modulation, 4
channels - attaching, 149 , 164 , choosing, 137
data, 137
data length registers, 139
data location registers, 138 , 139
data output rate, 140
decibel values, 140
DMA, 138 , 144 , 147 , 164
equal-tempered scale, 158
frequency modulation, 4
in ECS, 310
interrupts, 147 , 220

- joining tones, 147
- low-pass filter, 154
- modulation, 164
 - amplitude, 149
 - frequency, 149
- noise reduction, 154
- non-DMA output, 157
- period, 140
- period register, 143
- playing multiple tones, 149
- producing a steady tone, 145
- sampling period, 141
- sampling rate, 141 , 152 , 156 , 164
- state machine, 164
- stopping, 145
- system overhead, 153
- volume, 139 , 163
- volume registers, 139
- waveform transitions, 152

1.12 B Index

- Background color, 46
- Barrel Shifter, 179
- BBUSY, 222
- Beam comparator, 124
- Beam position, -->
- Beam position counter, 216
- BEAMCON0, 298 , 305
- Bitplanes, -->
- Blitter, -->
- Blitter Busy, 186
- Blitter registers - in line-drawing mode, 189
- Blitter shifting, 179
- BLTAXWM, 180
- BLTCON0, -->
- BLTCON0L, 298
- BLTCON1, -->
- BLTEN, 222
- BLTPRI, 222
- BLTSIZE, 169 , 171-173 , 186-187 , 191 , 308
- BLTSIZH, 298
- BLTSIZV, 298 , 308
- BLTXDAT, 170
- BLTXMOD, 172
- BLTXPTH, 170 , 298
- BLTXPTL, 170
- BPL1MOD, 62 , 64
- BPL2MOD, 62 , 64
- BPLCON0, -->
- BPLCON1 - setting scrolling delay, 85
- BPLCON2, -->
- BPLCON3, 298
- BPLCONx, 90 , 307
- BPLEN, 222

BPLxMOD, 84 , 91
BPLxPT, 91
BPLxPTH, 52 , 54 , 61 , 74
BPLxPTL, 52 , 54 , 61 , 74
BPUx, 48 , 87 , 90
Bridgeboard, 7
BZERO, 222

1.13 Beam position Index

Beam position
 comparison enable bits, 24
 detection of, 216
 in Copper use, 31
 registers, 216
 vertical, 23 , 24

1.14 Bitplanes Index

Bitplanes
 coloring, 55
 DMA, 62
 in dual-playfield mode, 68
 setting the number of, 48
 setting the pointers, 54

1.15 Blitter Index

Blitter, 4 , 6 , 9 , 19
 address scanning, 173
 addressing, 170
 animation, 176
 area fill, 4 , 184
 area filling - exclusive, 184 , inclusive, 184
 blit time, 193
 blitter done flag, 186
 blitter-finished disable bit (BFD), 35
 blitter-nasty bit, 198
 block transfers, 171 , 183
 BLTSIZE, 187
 bus sharing, 194
 clock, 193
 cookie-cut, 176 , 181 , 183
 copying, 169 , 183
 cycle time, 193
 data fetch, 170
 data overlap, 182
 descending mode, 182-183
 DisownBlitter(), 187
 DMA enable, 181 , 184 , 187

- DMA priority, 194
- DMA time slots, 194
- equation-to-minterm conversion, 175
- example, 200
- FILL_CARRYIN bit, 185
- height, 171
- immediate data, 170 , 182
- in ECS, 296
- interrupts, 187 , 220
- LF control byte, 174
- line drawing, 4
 - logic function, 191
 - octants, 190
 - registers, 189
- line drawing mode, 189
- line texture, 191
- linear data, 173
- logic equations, 175
- logic operations, 174
- masking, 181 , 183–184
- minterms, 175
- modulo, 172
- modulo registers, 172
- octants, 189
- OwnBlitter(), 187
- packed font, 180
- pipelined, 188
- pointer registers, 170
- sequence of bus cycles, 188
- shifting, 182 , 183
- size of blit, 171
- starting operation, 169
- text, 180
- truth-table, 174
- Venn Diagrams, 178
- WaitBlit(), 187
- width, 171
- with the Copper, 35
- zero detection, 187

1.16 BLTCON0 Index

- BLTCON0, 182
 - DMA enable, 170
 - in line drawing, 189 , 191
 - in logic operations, 174
 - in shift control, 179

1.17 BLTCON1 Index

- BLTCON1, 182 , 189 , 298
 - in area fill, 184

in blitter addressing, 182
in line drawing, 189-191
in shift control, 179

1.18 BPLCON0 Index

BPLCON0, 87 , 229 , 298 , 300
 enabling color, 63
 in dual-playfield mode, 72
 in hold-and-modify mode, 87
 in interlacing, 51
 in resolution mode, 49
 in the Enhanced Chip Set, 300
 selecting bitplanes, 48
 setting bits, 48
 with light pen, 239

1.19 BPLCON2 Index

BPLCON2, 72 , 210 , 298
 in dual-playfield priority, 71

1.20 C Index

Cache, 187 , 388
CDANG, 26
Chip Memory, 5-6 , 20 , 105 , 138 , 169 , 170 , 186 , 223 , 246 , 296
CIA, 9 , 157 , 241 , 251 , 339
CIAA - address map, 339
CIAADDR, 241
CIAAPRA, -->
CIAB - address map, 340
CIABPRB - disk, 244
Clock, -->
Clock Constant, 141 , 159
Clock cycle, 4
Clock Interval, 141
CLXCON, 215
CLXDAT, 214
CNT, 251
Collision, -->
Collision Detection, 4
Color, -->
Color Clock, 60 , 194 , 255 , 304
Color Palette, 3 , 19
Color Registers, 3
Color registers, -->
Color selection, -->
COLOR00, 46 , 55
COLOR_ON, 90

COLORx, 10 , 27 , 28 , 46 , 70-71 , 87
Comparator, 124
Composite Video, 7
Control Register, -->
Controller Port, -->
Controllers, -->
COP1LC, 25 , 30 , 32 , 32 , 35
COP1LCH, 25 , 298
COP1LCL, 25
COP2LC, 25 , 26 , 32
COP2LCH, 25 , 298
COP2LCL, 25
COPCON, 26 , 298
COPEN, 30 , 35 , 222
COPJMP1, 26
COPJMP2, 26
Copper, -->
Coprocessor - 19 , see Copper
Copying data, 169
CP/M, 241
CTRL-AMIGA-AMIGA, 253
Custom Chips, -->

1.21 CIAAPRA Index

CIAAPRA, 229 , 232 , 233 , 241 , 241
disk, 244

1.22 Clock Index

Clock, 260
8520, 344
alarm, 344
audio, 140 , 141 , 142 , 159 , 164
blitter, 193 , 194
color, 194 , 255
keyboard, 251
system, 2 , 193

1.23 Collision Index

Collision, 213
control register, 215
detection register, 214

1.24 Color Index

Color

- attached sprites, 122
- background color, 46
- color indirection, 42
- color table, 46
- enabling, 63
- in dual-playfield mode, 70
- in hold-and-modify mode, 86
- in SuperHires mode, 301
- in the Enhanced Chip Set, 301
- sample register contents, 92
- sprites, 102

1.25 Color registers Index

Color registers

- contents, 46
- loading, 47
- names of registers, 46
- sprites, 130

1.26 Color selection Index

Color selection

- in high resolution mode, 94
- in hold-and-modify mode, 95
- in low resolution mode, 93

1.27 Control register Index

Control Register, 348

- register A, 348
 - bitmap, 349
- register B, 349
 - bitmap, 350

1.28 Controller Port Index

Controller Port

- connection chart, 228
 - joystick, 232
 - mouse, 229
 - output to, 240
 - registers, 229
 - trackball, 229
-

1.29 Controllers Index

Controllers

- light pen, 238
- potentiometers, 236
- proportional - registers, 236
- special, 241
- types, 6

1.30 Copper Index

Copper, 9 , 19 , 45 , 54 , 62 , 64 , 65 , 80 , 81 , 82 , 110 , 122 , 194 ,
197 , 216 , 219

- affecting registers, 26
- at reset, 30
- bus cycles used, 20
- comparison enable, 32
- control register, 26
- danger bit (CDANG), 26
- DMA, 30 , 30
- features, 19
- horizontal beam position, 23
- in interlaced mode, 34
- in memory operations, 20
- in vertical blanking interrupts, 219
- instruction fetch, 25
- instruction lists, 26 , 28
- instructions
 - description, 20
 - ordering, 27
 - summary, 36
- interrupt, 219
- interrupting the 680x0, 35
- jump, 25
- jump strobe addresses, 26
- location registers, 25 , 30 , 32
- loops and branches, 32
- memory cycles, 22
- MOVE instruction, 21
- MOVE to registers, 21
- registers, 25
- resolution, 23 , 24
- SKIP instruction, 31 , 32
- starting, 26 , 30
- stopping, 30
- strobe address, 26
- vertical beam position, 24
- WAIT instruction, 22 , 30 , 32
- with sprites, 113
- with the blitter, 26 , 35

1.31 Custom Chips Index

Custom Chips, 2 , 170 , 255
 control registers, 19
 register, 263
 steal cycles, 4

1.32 D Index

Data-fetch, -->
DBLPF, 87 , 90
DDFSTOP, 60-61 , 80 , 82 , 91 , 99
DDFSTRT, 60 , 80 , 82 , 91 , 99
Decibel values, 163
Denise, 2 , 297
DENISEID, 298
Descending Mode - blitter, 182
DEST, 170
Digital Joystick - connection, 329 , fire buttons, 329
Disk, -->
Disk Port, 320
Display - size of, 57
Display DMA, 20
Display field, 40
Display memory, 57
Display modes, 41
Display window, -->
DIWHIGH, 298 , 306
DIWSTOP, 59 , 78 , 91 , 99 , 219 , 306
DIWSTRT, 58 , 59 , 76 , 91 , 99 , 219 , 306
DMA, -->
DMA Contention, 193
DMA Priority, 194
DMAB_BLTDONE, 186
DMACON, -->
DMACONR, 222
DMAEN, 144 , 222 , 247
DMAF_BLITHOG, 198
DMAF_BLTNZERO, 187
DSK, 244
DSKBLK, 220
DSKBYTR, 241 , 248
DSKCHANGE, 244
DSKDIREC, 244
DSKEN, 222
DSKINDEX, 244
DSKLEN, 241 , 246-247
DSKMOTOR, 244
DSKPROT, 244
DSKPTH, 241 , 246 , 298
DSKRDY, 244
DSKSELx, 244
DSKSIDE, 244
DSKSTEP, 244

DSKSYN, 220
DSKSYNC, 241 , 247 , 250
DSKTRACK0, 244
Dual Playfield, -->

1.33 Data-fetch Index

Data-fetch
 high resolution, 62
 in basic playfield, 60
 in horizontal scrolling, 82
 start - normal, 60
 stop - normal, 60

1.34 Disk Index

Disk, 20
 controller, 6 , 241
 DMA, 246
 DMA pointer registers, 246
 drives, 6
 external
 identification, 335
 interface, 334
 limitations, 335
 pins, 334
 external connector, 367
 device ID, 370
 pins, 367
 signals, 368
 floppy, 4
 input stream synchronization register (DSKSYNC), 250
 internal - pins, 336 ,power, 336
 interrupts, 220 , 250
 MFM Encoding, 250
 read data register, 248
 write, 246

1.35 Display window Index

Display window
 positioning, 57
 size - maximum, 79 , 306 ,normal, 58
 starting position - horizontal, 58 , 77 , 306 ,vertical, 58 , 77 , 306
 stopping position - horizontal, 59 , 78 , 306 ,vertical, 59 , 79 , 306

1.36 DMA Index

DMA, 4 , 207
 audio, 137 , 138 , 141 , 144 , 145 , 147 , 148 , 157 , 164-165 ,
 194 , 220
 bitplanes, 62
 blitter, 50 , 170-173 , 174 , 176 , 179-181 , 183-184 , 187 , 189 ,
 191 , 193 , 194 , 196-198
 control, 222
 control register, 218 , 222
 copper, 19-20 , 30
 disk, 4 , 194 , 220 , 241 , 246 , 247 , 250
 display, 20 , 194 , 300
 playfield, 62
 sprites, 4 , 27 , 97 , 102 , 108 , 109 , 110 , 115 , 116-117 , 118 ,
 120-121 , 123 , 126 , 127 , 128 , 194

1.37 DMACON Index

DMACON, 222 , 247
 blitter done, 186
 DMAF_BLITHOG bit, 198
 in audio, 144
 in playfields, 62
 stopping the Copper, 30
 zero detection, 187

1.38 Dual Playfield Index

Dual Playfield, 44
 bitplane assignment, 68
 description, 67
 enabling, 72
 high resolution colors, 71
 in high resolution mode, 71
 low resolution colors, 70
 priority, 71
 scrolling, 71

1.39 E,F,G,H Index

ECS - sprites, 302 , 303
ECS Registers, 298
Enhanced Chip Set, -->
Examples, 9
Expansion Boards, 7
Expansion Bus, 383
Expansion Connector, 7 , 385
External interrupts, 219

FAST, 249
Fast Memory, 5
Fat Agnus, 5 , 187
Field time, 40
Floppy Disk, 4 , 241 , See DISK
Frame Buffer, 6
Frequency Modulation, 4

Game Controller Port, 327
GAUD, 89
GCR, 250
Genlock, -->
HAM, 86

Hardware Connection, -->
HBSTOP, 298
HBSTRT, 298
HCENTER, 298
High resolution, -->
HIRES, 87
Hold-And-Modify, 3 , 86
HOMOD, 87 , 90
Horizontal blanking interval, 23 , 304
HSSTOP, 298
HSSTRT, 298
HSTART, 59 , 91 , 107 , 107 , 113
HSTOP, 59 , 78 , 91
HTOTAL, 298 , 304

1.40 Enhanced Chip Set Index

Enhanced Chip Set, 295
 blitter, 296
 ECS Registers, 298
 memory, 296

1.41 Genlock Index

Genlock, 2 , 49 , 51 , 89 , 159 , 260
 effect on background color, 46
 in ECS, 296
 in playfield register, 89

1.42 Hardware Connection Index

Hardware Connection, 353
 address inputs, 354
 chip select, 353
 clock input, 353

- data bus I/O, 354
- interrupt request, 354
- read/write input, 353
- reset input, 354

1.43 High resolution Index

High resolution

- color selection, 49 , 94
- memory requirements, 52
- SuperHires, 300
- with dual playfields, 71
- with ECS, 296

1.44 I,J,K Index

IBM PC, 6 , 7 , 241

Include Files, 10 , 22 , 373

INTEN, 218

INTENA, 217

INTENAR, 217

Interlaced mode, -->

Interleaved Memory, 4

Internal Slots, 7

Interrupt, -->

Interrupt Control Register, -->

Interrupts - during vertical blanking, 219

INTF_BLIT, 187

INTREQ, 35 , 218

INTREQR, 218

Joy stick port, 323

JOY0DAT/JOY1DAT, -->

Joystick, -->

JOYxDAT, 229

Keyboard, -->

Keyboard Port, 319

1.45 Interlaced mode Index

Interlaced mode

- Copper in, 34
- memory requirements, 52
- modulo, 62
- setting interlaced mode, 49

1.46 Interrupt Index

Interrupt, 26 , 35 , 35 , 207 , 217
8520, 251
audio, 147 , 148 , 153 , 157 , 164-165 , 220
beam synchronized, 3
blitter, 35 , 171 , 187 , 220
control registers, 217
copper, 25 , 32 , 216 , 219
disk, 220 , 245 , 250
external, 219
graphics, 33
interrupt enable bit, 218
interrupt lines, 217
maskable, 217
nonmaskable, 217
parallel, 259
priorities, 221
registers, 218
serial, 255 , 256 , 258
serial port, 220
setting and clearing bits, 218
vertical blanking, 219

1.47 Interrupt Control Register Index

Interrupt Control Register, 346
read, 347
write, 347

1.48 JOY0DAT/JOY1DAT Index

JOY0DAT/JOY1DAT
with joystick, 232
with mouse/trackball, 230

1.49 Joystick Index

Joystick
connections, 228
port, 323
reading, 232

1.50 Keyboard Index

Keyboard, 251 , 357
 Caps lock, 359
 communications, 357
 errors, 359
 ghosting, 253
 hard reset, 361
 keycodes, 358
 transmission, 358
 matrix, 362
 out-of-sync, 359
 power up, 360
 raw keycodes, 251
 reading, 251
 reset warning, 361
 self test, 360
 signals, 6 , 357
 special codes, 364
 timing diagram, 358

1.51 L,M,N,O Index

LACE, 51
LED - caps-lock, 253
Light Pen, -->
Line Drawing, -->
Low resolution - color selection, 93
LPEN, 89

Manual mode - in sprites, 123
Memory - adding, 7 ,blitter access to, 169
Memory allocation, -->
Memory Allocation - playfields, 76
Memory allocation - sprite data, 105
Memory Cycle Time, 194
Memory map, 388
MFM Encoding, 241 , 250
MFMPREC, 249
MIDI, 318
Minterms, 175
Modulation - amplitude, 149 ,frequency, 149
Modulo, -->
Monitors - 260 , See Video
Mouse - connections, 228 ,reading, 229
Mouse Port, 328
MOVE, 19 , 20 , 21
MSBSYNC, 249-250
MS-DOS, 6 , 7 , 241
Multiprocessor, 223
Multitasking, 9

Noise - audio, 154
NTSC, -->

Octants, 189

OVERRUN, 256
Overscan, 3 , 57 , 99

1.52 Light Pen Index

Light Pen, 333
 connections, 228
 pins, 333
 reading, 238
 registers, 238

1.53 Line Drawing Index

Line Drawing, 4 , 189
 length, 191
 logic function, 191
 octants, 189
 registers, 191

1.54 Memory allocation Index

Memory allocation
 audio, 137
 formula for playfields, 76
 playfields, 52

1.55 Modulo Index

Modulo
 blitter, 172
 in basic playfield, 60-62
 in horizontal scrolling, 82
 in interlaced mode, 62
 in larger playfield, 73

1.56 NTSC Index

NTSC, 62 , 100 , 100
 audio, 140 , 141 , 158-159
 blitter, 193
 clock, 2
 playfield, 49 , 52 , 57 , 58
 serial baud rate, 255
 sprites, 100 , 100
 vertical blank, 219
 video, 3 , 24 , 27 , 34 , 40-41 , 45 , 304

1.57 P Index

Packed Font, 180
Paddle Controller - connections, 228 ,reading, 234
PAL, -->
Parallel, 9
Parallel Port, -->
Paula, 2 , 6 , 255
Peripherals, 6 , 7
Pipeline, 188
Pixels - definition, 40 ,in sprites, 101 , 101
Playfield, 4 , 6 , 9
Playfields, -->
Playfield-sprite priority, 209
Port Signal Assignments, 350
Ports, -->
POT0DAT, 236 , 298
POT1DAT, 236 , 298
POTGO, 229
POTGO / POTINP, -->
POTGOR, 229
POTINP - name changed to POTGOR, 240
POTxDAT, 229
Power up operation, 223
PRECOMPx, 249
Priority, -->
Productivity mode, 3
Proportional Controller, 331 - pins, 332
Proportional Controllers - reading, 234
Proportional Joystick - connections, 228 ,reading, 234

1.58 PAL Index

PAL, 3 , 62
 audio, 140 , 141 , 158-159
 beam position, 216
 blitter, 193
 clock, 2
 playfield, 49 , 52 , 57 , 58
 serial baud rate, 255
 sprites, 100
 vertical blank, 219
 video, 3 , 24 , 34 , 40-41 , 45 , 304

1.59 Parallel Port Index

Parallel Port, 227 , 259 , 319
 pin assignment, 324
 specification, 324
 timing - input, 325 ,output, 325

1.60 Playfields Index

Playfields

- allocating memory, 52 , 61
- bitplane pointers, 54
- collision, 213
- color of pixels, 42-44
- color register contents, 92
- color table, 46
- coloring the bitplanes, 45 , 55
- colors in a single playfield, 45
- defining a scrolled playfield, 85
- defining display window, 57
- defining dual playfields, 72
- defining the basic playfield, 63
- display window size - maximum, 79 , normal, 58
- displaying, 62
- dual-playfield mode, 67
- enabling DMA, 62
- fetching data, 60-61 , 80
- forming, 44
- high resolution, 41
 - color selection, 94
 - example, 66
- hold-and-modify, 95
- hold-and-modify mode, 86
- interlaced, 41
- interlaced example, 66
- low resolution, 41
 - colors, 93
- memory required, 52 , 76
- modulo registers, 62
- multiple-playfield display, 89
- non-interlaced, 42
- normal, 42
- pointer registers, 54 , 61 , 74
- priority, 210
- register summary, 89
- scrolling - horizontal, 82 , vertical, 81
- selecting bitplanes, 48
- setting resolution mode, 49
- specifying modulo, 60-62 , 73
- specifying the data fetch, 76
- with external video source, 89
- with genlock, 89
- with larger display memory, 73

1.61 Ports Index

Ports

- controller, 227
- disk, 241
- parallel, 259
- serial, 255

video, 260

1.62 POTGO / POTINP Index

POTGO / POTINP

as digital I/O, 240

as proportional inputs, 234

1.63 Priority Index

Priority

dual playfields, 71

playfield-sprite, 209

priority control register, 210

sprites, 207

1.64 R,S Index

RAM, -->

RAMEX, 321

Reboot, 223-224

Refresh, 20

Reset, 223

Resolution - setting, 49

RF Modulator, 260

RF Monitor, 320

RGB - analog, 260 ,digital, 260

RGB Video, 7 , 49 , 63 , 64

ROM, 1 , 6 , 223 , 253

RS-232, 6 , 255

RS-232 and MIDI, 318

Sampling - period, 141 ,rate, 152

Scrolling, -->

SCSI Disk Port, 321

SCSI internal disk - pins, 336

SERDAT, 258 , 259

SERDATR, 256

Serial, 9

Serial Port, -->

Serial Shift Register, -->

SERPER, 255

SET/CLR, 35 , 144 , 145 , 218 , 222 , 249 , 257

Shifting - blitter, 182

SKIP, 20

Slow Memory, 5

Sound generation, 134

SPREN, 222

Sprite, 3 , 9 , 19-20

Sprite Colors, 27

Sprite DMA, 27
Sprites, -->
SPRxCtl, 107 , 123 , 124 , 126 , 128-129 , 298 , 303
SPRxDATA, 123 , 126 , 129
SPRxDATB, 123 , 126 , 129
SPRxPOS, 107 , 123 , 124 , 126 , 127-128 , 129 , 303
SPRxPT, 114
SPRxPTH, 110 , 126 , 127
SPRxPTL, 110 , 126 , 127
SRCA, 170
SRCB, 170
SRCD, 170
Stereo, 4
STRLONG, 298
System Clock, 2
System Control Hardware, 9

1.65 RAM Index

RAM, 21 , 47
 address space, 2
 at startup, 223
 chip, 6 , 20 , 138
 disk, 246
 expansion, 2 , 7
 keyboard, 253

1.66 Scrolling Index

Scrolling
 data fetch, 82
 delay, 85
 horizontal, 82
 in dual-playfield mode, 71
 in high resolution mode, 82
 modulo, 82
 vertical, 81

1.67 Serial Port Index

Serial Port, 255
 characteristics, 327
 pin assignment, 326
 specification, 326
 timing, 327

1.68 Serial Shift Register Index

Serial Shift Register, 345
 bidirectional feature, 346
 input mode, 345
 output mode, 345

1.69 Sprites Index

Sprites
 address pointers, 110
 arming and disarming, 123
 attached
 color registers, 131
 colors, 122
 control word, 120
 copper list, 122
 data words, 121 , 123
 clipped, 100
 collision, 113 , 213
 color, 102 , 302
 color registers used, 102-103
 comparator, 124 , 126
 control registers, 124 , 126 , 127
 control words, 107 , 107
 data registers, 126 , 129
 data structure, 104
 data words, 107
 designing, 104
 displaying - example, 111 , steps in, 109
 DMA, 110 , 114
 end-of-data words, 108
 Enhanced Chip Set, 302 , 303
 forming, 98
 manual mode, 123
 memory requirements, 105
 moving, 113
 overlapped, 118
 parallel-to-serial converters, 124
 pixels in sprites, 101 , 101
 pointer registers, 127
 initializing, 110
 resetting, 110
 position registers, 124 , 126
 priorities, 207
 priority, 115 , 118 , 210
 reuse, 114 , 116
 screen position - horizontal, 98 , 107 , vertical, 100
 shape, 101
 size, 101
 vertical position, 107 , 107
 with copper, 113

1.70 T,U,V,W,Z Index

TAS, 196 , 223
Trackball, -->
Trackdisk, 9
TSRE, 259

UART, 255
UARTBRK, 257

VBSTOP, 298
VBSTRT, 298
VCR, 46
Vertical Blanking, 30 , 30 , 32 , 304
VGA, 304
VHPOSR, -->
VHPOSW - with beam counter, 216
Video, -->
Video Beam Position, 26
Video Input, 46
Video Port, 319
Volume, 139
VPOSR, -->
VPOSW - with beam counter, 216
VSSTOP, 298
VSSTRT, 298
VSTART, 59 , 91 , 107 , 107 , 108 , 113
VSTOP, 59 , 78 , 91 , 107 , 108 , 113
VTOTAL, 298 , 304

WAIT, 19 , 20
Waveform, 4
Waveforms - audio, 134
WORDSYNC, 249 , 250

Zero Detection, 187
Zorro Expansion Bus, -->

1.71 Trackball Index

Trackball, 328
 connections, 228
 reading, 229

1.72 VHPOSR Index

VHPOSR, 229
 with beam counter, 216
 with light pen, 238

1.73 Video Index

Video

- analog RGB, 260
- beam position, 3 , 23
- camera input, 7
- composite, 260
- digital RGB, 260
- external sources, 89
- interrupt, 3
- laser disk input, 7
- monitors, 7
- monochrome, 260
- output, 260
- priority, 4
- RF modulator, 260
- RGB, 49 , 63 , 64
- synchronization, 3
- VCR input, 7
- video slot, 260

1.74 VPOSR Index

VPOSR, 229 , 298 , 299

- in playfields, 66
- with beam counter, 216
- with light pen, 238-239

1.75 Zorro Expansion Bus Index

Zorro Expansion Bus, 383

- A2000, 384 , 387 , 387 , 387 , 391
- A3000, 384 , 387 , 387 , 387
- autoconfiguration, 431
- mechanical specifications, 427
- memory mapping, 388
- multiple transfer timing, 420
- quick interrupt timing, 422
- read timing, 416
- write timing, 418
- Zorro II signals, 391 , 437-439
- Zorro III signals, 409 , 437-439
