

DayDream

Antti Häyrynen

Copyright © CopyrightÂ©1995 Antti Häyrynen

COLLABORATORS

	<i>TITLE :</i> DayDream		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	Antti Häyrynen	July 20, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	DayDream	1
1.1	DayDream BBS Documentation	1
1.2	DayDream BBS - Introduction	1
1.3	DayDream BBS - General Information	1
1.4	DayDream BBS - Legal Info	2
1.5	DayDream BBS - Contacting Author	2
1.6	DayDream BBS - Registration	2
1.7	DayDream BBS - Features	3
1.8	DayDream BBS - The Credits	4
1.9	DayDream BBS - Support	5
1.10	DayDream BBS - Requirements	5
1.11	DayDream BBS - Software Requirements	5
1.12	DayDream BBS - Hardware Requirements	6
1.13	DayDream BBS - Installation	6
1.14	DayDream BBS - Directories	6
1.15	DayDream BBS - Executing DayDream	7
1.16	DayDream BBS - BBS Files	7
1.17	DayDream BBS - [Conference]/Data/	7
1.18	DayDream BBS - [Conference]/Bulletins/	8
1.19	DayDream BBS - [Conference]/Display/[Displaymode]/	9
1.20	DayDream BBS - [Conference]/Display/	9
1.21	[Conference]/Messages/[BaseXXX]	10
1.22	DayDream BBS - DayDream:Display/[DisplayMode]/	10
1.23	DayDream BBS - DayDream:Display/	12
1.24	DayDream BBS - DayDream:Data/	12
1.25	DayDream BBS - Questionnaire/	12
1.26	DayDream BBS - DayDream:Batch/	13
1.27	DayDream BBS - Special Control Codes	14
1.28	DayDream BBS - Configuring BBS	15
1.29	DayDream BBS - General Information	15

1.30 DayDream BBS - Main Configuration	16
1.31 DayDream BBS - Main Configuration - BBSNAME	16
1.32 DayDream BBS - Main Configuration - SYSOP	17
1.33 DayDream BBS - Main Configuration - LOCALUPLDPATH	17
1.34 DayDream BBS - Main Configuration - CHATDLPATH	17
1.35 DayDream BBS - Main Configuration - OP_DMODE	17
1.36 DayDream BBS - Main Configuration - SYSTEM_PW	17
1.37 DayDream BBS - Main Configuration - NEWUSER_PW	17
1.38 DayDream BBS - Main Configuration - USERED_PW	17
1.39 DayDream BBS - Main Configuration - FSCAN_BUFFER	18
1.40 DayDream BBS - Main Configuration - NEW_PRESET	18
1.41 DayDream BBS - Main Configuration - IDLE	18
1.42 DayDream BBS - Main Configuration - AUTOCONF	18
1.43 DayDream BBS - Main Configuration - FREEFORUL	18
1.44 DayDream BBS - Main Configuration - ASK_REASON	18
1.45 DayDream BBS - Main Configuration - NAMEMODE	19
1.46 DayDream BBS - Main Configuration - LOCATION	19
1.47 DayDream BBS - Main Configuration - DISABLEWILDS	19
1.48 DayDream BBS - Main Configuration - QUESTIONS	19
1.49 DayDream BBS - Main Configuration - LOGDISA	19
1.50 DayDream BBS - Main Configuration - QUICKLINEED	19
1.51 DayDream BBS - Main Configuration - SYSOP_COL	20
1.52 DayDream BBS - Main Configuration - USER_COL	20
1.53 DayDream BBS - Main Configuration - SHELL_PW	20
1.54 DayDream BBS - Main Configuration - ALIENS	20
1.55 DayDream BBS - Main Configuration - LINEEDCOM	20
1.56 DayDream BBS - Main Configuration - FSED	20
1.57 DayDream BBS - Main Configuration - CHATMODE	21
1.58 DayDream BBS - Main Configuration - LOCALSCREEN	21
1.59 DayDream BBS - Main Configuration - FREEDLLINE	21
1.60 DayDream BBS - Main Configuration - OLMPATH	21
1.61 DayDream BBS - Main Configuration - COSYSOPACCESS	21
1.62 DayDream BBS - Main Configuration - CONTROLCHAR	21
1.63 DayDream BBS - Conferences	22
1.64 DayDream BBS - Conferences - CONF_NUMB	23
1.65 DayDream BBS - Conferences - CONF_NAME	23
1.66 DayDream BBS - Conferences - CONF_PATH	23
1.67 DayDream BBS - Conferences - CONF_FILEAREAS	23
1.68 DayDream BBS - Conferences - CONF_UPLOADSTO	23

1.69 DayDream BBS - Conferences - CONF_MSGBASES	23
1.70 DayDream BBS - Conferences - CONF_COMMENTS	23
1.71 DayDream BBS - Conferences - CONF_ULPATH	24
1.72 DayDream BBS - Conferences - CONF_NSAREAS	24
1.73 DayDream BBS - Conferences - CONF_DEFFSCAN	24
1.74 DayDream BBS - Conferences - CONF_FREELEECH	24
1.75 DayDream BBS - Conferences - CONF_NOCREDS	24
1.76 DayDream BBS - Conferences - CONF_SENTBY	24
1.77 DayDream BBS - Conferences - CONF_LONGNAMES	25
1.78 DayDream BBS - Conferences - CONF_ASKDEST	25
1.79 DayDream BBS - Conferences - CONF_NOWILDS	25
1.80 DayDream BBS - Conferences - CONF_NOWILDFLG	26
1.81 DayDream BBS - Conferences - CONF_NODUPECHK	26
1.82 DayDream BBS - Conferences - CONF_NOFILECHK	26
1.83 DayDream BBS - Conference - CONF_NOREQ	26
1.84 DayDream BBS - Conferences - CONF_PASSWORD	26
1.85 DayDream BBS - Conferences - BASE_NUMBER	26
1.86 DayDream BBS - Conferences - BASE_TYPE	27
1.87 DayDream BBS - Conferences - BASE_LOWEST	27
1.88 DayDream BBS - Conferences - BASE_HIGHEST	27
1.89 DayDream BBS - Conferences - BASE_MAXMSGs	27
1.90 DayDream BBS - Conferences - BASE_NAME	27
1.91 DayDream BBS - Conferences - BASE_FIDOTAG	27
1.92 DayDream BBS - Conferences - BASE_ORIGIN	28
1.93 DayDream BBS - Conferences - BASE_FIDOADD	28
1.94 DayDream BBS - Conferences - BASE_ALLOWPBLc	28
1.95 DayDream BBS - Conferences - BASE_ALLOWPRIV	28
1.96 DayDream BBS - Conferences - BASE_FILEATTAC	28
1.97 DayDream BBS - Conferences - BASE_NAMES	28
1.98 DayDream BBS - Conferences - BASE_ALL=EALL	29
1.99 DayDream BBS - Conferences - BASE_QUOTE	29
1.100DayDream BBS - Conferences - BASE_DEFGRAB	29
1.101DayDream BBS - External Commands	29
1.102DayDream BBS - External Commands - DOOR_COMMAND	30
1.103DayDream BBS - External Commands - DOOR_TYPE	30
1.104DayDream BBS - External Commands - DOOR_SECURITY	31
1.105DayDream BBS - External Commands - DOOR_EXECUTE	31
1.106DayDream BBS - Access Presets	31
1.107DayDream BBS - Access Presets - PRESET_SEC	31

1.108DayDream BBS - Access Presets - PRESET_NUMBER	31
1.109DayDream BBS - Access Presets - PRESET_FFILES	31
1.110DayDream BBS - Access Presets - PRESET_FBYTES	32
1.111DayDream BBS - Access Presets - PRESET_DESC	32
1.112DayDream BBS - Access Presets - PRESET_STATUS	32
1.113DayDream BBS - Archivers	32
1.114DayDream BBS - Archivers - ARC_TYPE	32
1.115DayDream BBS - Archivers - ARC_EXTENSION	33
1.116DayDream BBS - Archivers - ARC_NAME	33
1.117DayDream BBS - Archivers - ARC_TEST	33
1.118DayDream BBS - Archivers - ARC_FAIL1	33
1.119DayDream BBS - Archivers - ARC_FAIL2	33
1.120DayDream BBS - Archivers - ARC_FAIL3	33
1.121DayDream BBS - Archivers - ARC_FIDEXTRACT	33
1.122DayDream BBS - Archivers - ARC_VIEW	34
1.123DayDream BBS - Archivers - ARC_FIDADD	34
1.124DayDream BBS - Archivers - ARC_OFFLINE	34
1.125DayDream BBS - Archivers - ARC_GETDATE	34
1.126DayDream BBS - Archivers - ARC_DELETECOR	34
1.127DayDream BBS - Archivers - ARC_DISPLAY	34
1.128DayDream BBS - Archivers - ARC_SECVIEW	34
1.129DayDream BBS - File Transfer Protocols	35
1.130DayDream BBS - File Transfer Protocols - XPR_ID	35
1.131DayDream BBS - File Transfer Protocols - XPR_NAME	35
1.132DayDream BBS - File Transfer Protocols - XPR_EFFICIENCY	35
1.133DayDream BBS - File Transfer Protocols - XPR_LIB	35
1.134DayDream BBS - File Transfer Protocols - XPR_INIT	36
1.135DayDream BBS - File Transfer Protocols - XPR_TYPE	36
1.136DayDream BBS - Display Modes	36
1.137DayDream BBS - Display Modes - DPL_ID	36
1.138DayDream BBS - Display Modes - DPL_PATH	36
1.139DayDream BBS - Display Modes - DPL_ANSI	37
1.140DayDream BBS - Display Modes - DPL_INCONV	37
1.141DayDream BBS - Display Modes - DPL_OUTCONV	37
1.142DayDream BBS - Display Modes - DPL_FILESCONV	37
1.143DayDream BBS - Display Modes - DPL_STRIPANSI	37
1.144DayDream BBS - Display Modes - DPL_TRYTXT	37
1.145DayDream BBS - Display Modes - DPL_TABLE1	38
1.146DayDream BBS - Display Modes - DPL_TABLE2	38

1.147DayDream BBS - Display Modes - DPL_FONT	38
1.148DayDream BBS - Display Modes - DPL_SIZE	38
1.149DayDream BBS - Display Modes - DPL_STRINGS	38
1.150DayDream BBS - Multinode Stuff	38
1.151DayDream BBS - Multinode Stuff - MNODE_NODE	39
1.152DayDream BBS - Multinode Stuff - MNODE_IODEV	39
1.153DayDream BBS - Multinode Stuff - MNODE_MBAUD	39
1.154DayDream BBS - Multinode Stuff - MNODE_MNBAUD	39
1.155DayDream BBS - Multinode Stuff - MNODE_FONT	39
1.156DayDream BBS - Multinode Stuff - MNODE_FSIZE	40
1.157DayDream BBS - Multinode Stuff - MNODE_STYPE	40
1.158DayDream BBS - Multinode Stuff - MNODE_SHANGHAI	40
1.159DayDream BBS - Multinode Stuff - MNODE_DEFPTOF	40
1.160DayDream BBS - Multinode Stuff - MNODE_AUTOFRNT	40
1.161DayDream BBS - Multinode Stuff - MNODE_AUTOOPEN	40
1.162DayDream BBS - Multinode Stuff - MNODE_FIXRED	41
1.163DayDream BBS - Multinode Stuff - MNODE_OWNDIR	41
1.164DayDream BBS - Multinode Stuff - MNODE_TELNET	41
1.165DayDream BBS - Multinode Stuff - MNODE_NOTIFY	41
1.166DayDream BBS - Multinode Stuff - MNODE_HIDEINAC	41
1.167DayDream BBS - Multinode Stuff - MNODE_HIDEWAIT	41
1.168DayDream BBS - Multinode Stuff - MNODE_HIDECALL	41
1.169DayDream BBS - Multinode Stuff - MNODE_NOPASSWD	42
1.170DayDream BBS - Multinode Stuff - MNODE_COMMAND	42
1.171DayDream BBS - Multinode Stuff - MNODE_PRIORITY	42
1.172DayDream BBS - Multinode Stuff - MNODE_TEMPDIR	42
1.173DayDream BBS - Multinode Stuff - MNODE_PENS	42
1.174DayDream BBS - I/O Devices	43
1.175DayDream BBS - I/O Devices - IO_NUMBER	43
1.176DayDream BBS - I/O Devices - IO_UNIT	43
1.177DayDream BBS - I/O Devices - IO_BAUD	44
1.178DayDream BBS - I/O Devices - IO_DEVICE	44
1.179DayDream BBS - I/O Devices - IO_PREINIT	44
1.180DayDream BBS - I/O Devices - IO_OFFHOOK	44
1.181DayDream BBS - I/O Devices - IO_ANSWER	44
1.182DayDream BBS - I/O Devices - IO_INIT	44
1.183DayDream BBS - I/O Devices - IO_AFTERCALL	44
1.184DayDream BBS - I/O Devices - IO_OK	45
1.185DayDream BBS - I/O Devices - IO_RING	45

1.186DayDream BBS - I/O Devices - IO_NOCARRIER	45
1.187DayDream BBS - I/O Devices - IO_CONNECT	45
1.188DayDream BBS - I/O Devices - IO_SPEED1	45
1.189DayDream BBS - I/O Devices - IO_SPEED2	45
1.190DayDream BBS - I/O Devices - IO_SPEED3	45
1.191DayDream BBS - I/O Devices - IO_SPEED4	46
1.192DayDream BBS - I/O Devices - IO_SPEED5	46
1.193DayDream BBS - I/O Devices - IO_SPEED6	46
1.194DayDream BBS - I/O Devices - IO_SPEED7	46
1.195DayDream BBS - I/O Devices - IO_SPEED8	46
1.196DayDream BBS - I/O Devices - IO_SPEED9	46
1.197DayDream BBS - I/O Devices - IO_SPEED10	46
1.198DayDream BBS - I/O Devices - IO_ERRORCORR	46
1.199DayDream BBS - I/O Devices - IO_DELAY1	47
1.200DayDream BBS - I/O Devices - IO_DELAY2	47
1.201DayDream BBS - I/O Devices - IO_MODE	47
1.202DayDream BBS - Security Levels	47
1.203DayDream BBS - Security Levels - SEC_LEVEL	48
1.204DayDream BBS - Security Levels - SEC_FRATIO	48
1.205DayDream BBS - Security Levels - SEC_BRATIO	48
1.206DayDream BBS - Security Levels - SEC_PAGES	48
1.207DayDream BBS - Security Levels - SEC_TIMELIMIT	49
1.208DayDream BBS - Security Levels - SEC_CONFACC1	49
1.209DayDream BBS - Security Levels - SEC_CONFACC2	49
1.210DayDream BBS - Security Levels - SECF_DOWNLOAD	49
1.211DayDream BBS - Security Levels - SECF_UPLOAD	49
1.212DayDream BBS - Security Levels - SECF_READMSGs	50
1.213DayDream BBS - Security Levels - SECF_ENTERMSG	50
1.214DayDream BBS - Security Levels - SECF_PAGE	50
1.215DayDream BBS - Security Levels - SECF_COMMENT	50
1.216DayDream BBS - Security Levels - SECF_BULLETINS	50
1.217DayDream BBS - Security Levels - SECF_LISTFILES	50
1.218DayDream BBS - Security Levels - SECF_NEWFILES	50
1.219DayDream BBS - Security Levels - SECF_ZIPPY	51
1.220DayDream BBS - Security Levels - SECF_RUNDOOR	51
1.221DayDream BBS - Security Levels - SECF_JOINCONF	51
1.222DayDream BBS - Security Levels - SECF_MSGAREAC	51
1.223DayDream BBS - Security Levels - SECF_CHANGEINF	51
1.224DayDream BBS - Security Levels - SECF_RELOGIN	51

1.225DayDream BBS - Security Levels - SECF_TAGED	51
1.226DayDream BBS - Security Levels - SECF_VIEWSTATS	52
1.227DayDream BBS - Security Levels - SECF_VIEWTIME	52
1.228DayDream BBS - Security Levels - SECF_HYDRA	52
1.229DayDream BBS - Security Levels - SECF_EXPERT	52
1.230DayDream BBS - Security Levels - SECF_EALL	52
1.231DayDream BBS - Security Levels - SECF_FIDOMSG	52
1.232DayDream BBS - Security Levels - SECF_PRIVMSG	52
1.233DayDream BBS - Security Levels - SECF_READALL	53
1.234DayDream BBS - Security Levels - SECF_USERED	53
1.235DayDream BBS - Security Levels - SECF_VIEWLOG	53
1.236DayDream BBS - Security Levels - SECF_SYSOPDL	53
1.237DayDream BBS - Security Levels - SECF_USERLIST	53
1.238DayDream BBS - Security Levels - SECF_DELETEANY	53
1.239DayDream BBS - Security Levels - SECF_SHELL	53
1.240DayDream BBS - Security Levels - SECF_WHO	54
1.241DayDream BBS - Security Levels - SECF_MOVE	54
1.242DayDream BBS - Security Levels - SECF_SFCONFS	54
1.243DayDream BBS - Security Levels - SECF_SMBASES	54
1.244DayDream BBS - Security Levels - SECF_NETMAIL	54
1.245DayDream BBS - Security Levels - SECF_OLM	54
1.246DayDream BBS - Security Levels - SECF_PRVATTACH	54
1.247DayDream BBS - Security Levels - SECF_PUBATTACH	55
1.248DayDream BBS - Security Levels - SECF_REALNAME	55
1.249DayDream BBS - Security Levels - SECF_HANDLE	55
1.250DayDream BBS - Schedule	55
1.251DayDream BBS - Schedule - SCHE_HOUR	55
1.252DayDream BBS - Schedule - SCHE_LOGOFF	55
1.253DayDream BBS - Schedule - SCHE_SYSPW	56
1.254DayDream BBS - Schedule - SCHE_NEWUSERPW	56
1.255DayDream BBS - Server	56
1.256DayDream BBS - Server - SRV_X	56
1.257DayDream BBS - Server - SRV_Y	56
1.258DayDream BBS - Server - SRV_ICONIFY	56
1.259DayDream BBS - Server - SRV_NAMES	57
1.260DayDream BBS - Server - SRV_LOCATION	57
1.261DayDream BBS - Included Utils and Doors	57
1.262DayDream BBS - Included Utils and Doors - DayDream:Utils/	57
1.263DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDCallers	57

1.264DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDTop	58
1.265DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDWeekTop	58
1.266DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DreamConfig	58
1.267DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DreamToss	58
1.268DayDream BBS - Included Utils and Doors - DayDream:Utils/ - FixBases	58
1.269DayDream BBS - Included Utils and Doors - DayDream:Utils/ - ListClean	58
1.270DayDream BBS - Included Utils and Doors - DayDream:Doors/	59
1.271DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Faker	59
1.272DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Grab	59
1.273DayDream BBS - Included Utils and Doors - DayDream:Doors/ - New	59
1.274DayDream BBS - Included Utils and Doors - DayDream:Doors/ - REXX	59
1.275DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Wall	60
1.276DayDream BBS - Included Utils and Doors - DayDream:Doors/ - WhoF	60
1.277DayDream BBS - DayDream:Doors/REXXDir/	60
1.278DayDream BBS - AREXX	60
1.279DayDream BBS - AREXX - General Information	60
1.280DayDream BBS - AREXX - Requirements	60
1.281DayDream BBS - AREXX - Launching Door	61
1.282DayDream BBS - AREXX - Supported Commands	61
1.283DayDream BBS - AREXX - Supported Commands - TRANSMIT	61
1.284DayDream BBS - AREXX - Supported Commands - SHUTDOWN	62
1.285DayDream BBS - AREXX - Supported Commands - PROMPT	62
1.286DayDream BBS - AREXX - Supported Commands - NEWLINE	62
1.287DayDream BBS - AREXX - Supported Commands - SEND	62
1.288DayDream BBS - AREXX - Supported Commands - SENDFILE	63
1.289DayDream BBS - AREXX - Supported Commands - SENDANY	63
1.290DayDream BBS - AREXX - Supported Commands - GETUSER	63
1.291DayDream BBS - AREXX - Supported Commands - PUTUSER	64
1.292DayDream BBS - AREXX - Supported Commands - SYSTEMINFO	64
1.293DayDream BBS - AREXX - Supported Commands - GETCHAR	65
1.294DayDream BBS - AREXX - Supported Commands - QUERY	65
1.295DayDream BBS - AREXX - Supported Commands - QUERYN	65
1.296DayDream BBS - AREXX - Supported Commands - CONFINFO	65
1.297DayDream BBS - AREXX - Supported Commands - DOWNLOAD	66
1.298DayDream BBS - AREXX - Supported Commands - UPLOAD	66
1.299DayDream BBS - AREXX - Supported Commands - GETLRP	66
1.300DayDream BBS - AREXX - Supported Commands - SETLRP	66
1.301DayDream BBS - AREXX - Supported Commands - FLAGFILE	67
1.302DayDream BBS - AREXX - Supported Commands - HANGUP	67

1.303DayDream BBS - ARexx - Supported Commands - DDCOMMAND	67
1.304DayDream BBS - ARexx - Supported Commands - RESETIDLE	67
1.305DayDream BBS - ARexx - Supported Commands - RELOGIN	67
1.306DayDream BBS - ARexx - Supported Commands - JOINCONF	67
1.307DayDream BBS - ARexx - Supported Commands - CHANGEMSGBASE	68
1.308DayDream BBS - ARexx - Supported Commands - INTCOMMAND	68
1.309DayDream BBS - ARexx - Supported Commands - FIFOEXECUTE	68
1.310DayDream BBS - ARexx - Supported Commands - WRITELOG	68
1.311DayDream BBS - ARexx - Debugging	69
1.312DayDream BBS - Developing Doors and Utils	69
1.313DayDream BBS - Developing Doors and Utils - General Guidelines	69
1.314DayDream BBS - Developing Doors and Utils - DayDream BBS Server Commands	70
1.315DayDream BBS - Developing Doors and Utils - Server ARexx Commands	72
1.316SHUTDOWN	72
1.317ICONIFY	73
1.318CLOSENODE	73
1.319OPENSREEN	73
1.320CLOSESCREEN	73
1.321KICKUSER	73
1.322ENTERCHAT	73
1.323CHATON	74
1.324CHATOFF	74
1.325Server ARexx Example	74
1.326Developer information about Examine.DAT/FileCheck.DAT	74
1.327DayDream BBS - How Does It Work	75
1.328DayDream BBS - How Does It Work - General Info	75
1.329DayDream BBS - How Does It Work - Login Procedure	75
1.330DayDream BBS - How Does It Work - General Info - New	76
1.331DayDream BBS - How Does It Work - General Info - Chat	77
1.332DayDream BBS - How Does It Work - General Info - Logoff	77
1.333DayDream BBS - How Does It Work - User Commands	77
1.334DayDream BBS - How Does It Work - User Commands - Alter Userdata	78
1.335DayDream BBS - How Does It Work - User Commands - Bulletins	78
1.336DayDream BBS - How Does It Work - User Commands - Comment	78
1.337DayDream BBS - How Does It Work - User Commands - Download	78
1.338DayDream BBS - How Does It Work - User Commands - Enter Message	79
1.339DayDream BBS - How Does It Work - User Commands - List Files	79
1.340DayDream BBS - How Does It Work - User Commands - Disconnect	80
1.341DayDream BBS - How Does It Work - User Commands - Join Conference	80

1.342DayDream BBS - How Does It Work - User Commands - Local Time	81
1.343DayDream BBS - How Does It Work - User Commands - Change Message Base	81
1.344DayDream BBS - How Does It Work - User Commands - New File Scan	81
1.345DayDream BBS - How Does It Work - User Commands - Operator Page	82
1.346DayDream BBS - How Does It Work - User Commands - Read Messages	82
1.347DayDream BBS - How Does It Work - User Commands - User Statistics	83
1.348DayDream BBS - How Does It Work - User Commands - Tag Editor	83
1.349DayDream BBS - How Does It Work - User Commands - Upload	83
1.350DayDream BBS - How Does It Work - User Commands - View file	84
1.351DayDream BBS - How Does It Work - User Commands - Expert Mode Toggle	84
1.352DayDream BBS - How Does It Work - User Commands - Zippy Search	84
1.353DayDream BBS - How Does It Work - User Commands - Previous Conference	85
1.354DayDream BBS - How Does It Work - User Commands - Next Conference	85
1.355DayDream BBS - How Does It Work - User Commands - Show Mainmenu	85
1.356DayDream BBS - How Does It Work - User Commands - Kewl Little Game	85
1.357DayDream BBS - How Does It Work - User Commands - Prevoius Message Base	85
1.358DayDream BBS - How Does It Work - User Commands - Next Message Base	85
1.359DayDream BBS - How Does It Work - User Commands - Global read	86
1.360DayDream BBS - How Does It Work - User Commands - Mail Scan	86
1.361DayDream BBS - How Does It Work - User Commands - New Files Scan	86
1.362DayDream BBS - How Does It Work - User Commands - Version Information	86
1.363DayDream BBS - How Does It Work - User Commands - Online Message	86
1.364DayDream BBS - How Does It Work - User Commands - Relogin	86
1.365DayDream BBS - How Does It Work - User Commands - Select File Conferences	87
1.366DayDream BBS - How Does It Work - User Commands - Select Messagebases	87
1.367DayDream BBS - How Does It Work - User Commands - Bidir. Hydratransfer	87
1.368DayDream BBS - How Does It Work - User Commands - List of Users	87
1.369DayDream BBS - How Does It Work - User Commands - Change Displaymode	87
1.370DayDream BBS - How Does It Work - User Commands - Who's Online	88
1.371DayDream BBS - How Does It Work - User Commands - Clear Screen	88
1.372DayDream BBS - How Does It Work - SysOp Commands	88
1.373DayDream BBS - How Does It Work - SysOp Commands - UserEditor	88
1.374DayDream BBS - How Does It Work - SysOp Commands - Move File(s)	89
1.375DayDream BBS - How Does It Work - SysOp Commands - SysOp Download	90
1.376DayDream BBS - How Does It Work - SysOp Commands - View Logfile	90
1.377DayDream BBS - How Does It Work - SysOp Commands - Remote Shell	90
1.378DayDream BBS - How Does It Work - SysOp Commands - Test Door	90
1.379DayDream BBS - Pulldown Menus	90
1.380DayDream BBS - Pulldown Menus - DayDream BBS Menu	91

1.381DayDream BBS - Pulldown Menus - DayDream BBS Menu - About	91
1.382DayDream BBS - Pulldown Menus - DayDream BBS Menu - Quit	91
1.383DayDream BBS - Pulldown Menus - Display	91
1.384DayDream BBS - Pulldown Menus - Display - Palette	91
1.385DayDream BBS - Pulldown Menus - Display - Screen Title	91
1.386DayDream BBS - Pulldown Menus - Display - Screen Mode	92
1.387DayDream BBS - Pulldown Menus - Display - Save	92
1.388DayDream BBS - Pulldown Menus - Online	92
1.389DayDream BBS - Pulldown Menus - Online - Ascii Send	92
1.390DayDream BBS - Pulldown Menus - Online - Send File(s)	92
1.391DayDream BBS - Pulldown Menus - Online - Receive File(s)	93
1.392DayDream BBS - Pulldown Menus - Online - Chat Message	93
1.393DayDream BBS - Pulldown Menus - Online - Modem Command	93
1.394DayDream BBS - Pulldown Menus - Online - Local UserEd	93
1.395DayDream BBS - Pulldown Menus - Online - Lo&Re UserEd	93
1.396DayDream BBS - Pulldown Menus - Online - Chat Request Off	93
1.397DayDream BBS - Pulldown Menus - Online - Kick User	94
1.398DayDream BBS - Pulldown Menus - Online - Chat Mode	94
1.399DayDream BBS - Pulldown Menus - Online - Hydra Transfer	94
1.400DayDream BBS - Pulldown Menus - Online - Butt Noise	94
1.401DayDream BBS - Pulldown Menus - Online - Disable Idle	94
1.402DayDream BBS - FidoNet	94
1.403DayDream BBS - FidoNet - Requirements	95
1.404DayDream BBS - FidoNet - Installing Dreamtoss	95
1.405DayDream BBS - FidoNet - Installing Dreamtoss - Akas	95
1.406DayDream BBS - FidoNet - Installing Dreamtoss - Bad Messages	95
1.407DayDream BBS - FidoNet - Installing Dreamtoss - NetMail	96
1.408DayDream BBS - FidoNet - Installing Dreamtoss - In- & OutBound Dirs	96
1.409DayDream BBS - FidoNet - Installing Dreamtoss - Packer Definitions	97
1.410DayDream BBS - FidoNet - Installing Dreamtoss - Outgoing Echo	97
1.411DayDream BBS - FidoNet - Installing Dreamtoss - Inbound Conversion	98
1.412DayDream BBS - FidoNet - Installing Dreamtoss - Area Definitions	98
1.413DayDream BBS - FidoNet - Installing Dreamtoss - Routing	98
1.414DayDream BBS - FidoNet - Installing Mailer	99
1.415DayDream BBS - Other Things You Should Know	100
1.416DayDream BBS - Other Things You Should Know - Chat Mode	100
1.417DayDream BBS - Other Things You Should Know - Making Stuff Resident	100
1.418DayDream BBS - Other Things You Should Know - Multinode Chat	100
1.419DayDream BBS - InterNet	100

1.420DayDream BBS - Compatibility w/ /X	101
1.421DayDream BBS - Daily Updates	101
1.422DayDream BBS - Strings	102
1.423DayDream BBS - Multiple nodes	102
1.424DayDream BBS - History	102
1.425DayDream BBS - History - Version 1.00Beta-1	102
1.426DayDream BBS - History - Version 1.00Beta-2	103
1.427DayDream BBS - History - Version 1.00Beta-3	104
1.428DayDream BBS - History - Version 1.00	106
1.429DayDream BBS - History - Version 1.01	108
1.430DayDream BBS - History - Version 1.02	110
1.431DayDream BBS - History - Version 1.03	110
1.432DayDream BBS - History - Version 1.10	112
1.433DayDream BBS - History - Version 1.11	113
1.434DayDream BBS - History - Version 1.12	114
1.435DayDream BBS - History - Version 1.13	116
1.436DayDream BBS - History - Version 1.14	117
1.437DayDream BBS - History - Version 1.15	119
1.438DayDream BBS - History - Version 1.16	119
1.439DayDream BBS - History - Version 1.17	121
1.440DayDream BBS - History - Version 1.18	123
1.441DayDream BBS - History - Version 1.20	124

Chapter 1

DayDream

1.1 DayDream BBS Documentation

DayDream BBS by Antti Häyrynen
Amigaguide Documentation by Ville Alatalo

Introduction & Features
Requirements and Installation
BBS Files
Configuring BBS
Included Utils & Doors
ARexx
Developing Doors & Utils
How Does It Work
Pulldown Menus
FidoNet
Other Things You Should Know
History

1.2 DayDream BBS - Introduction

Introduction and Features

General information
Legal Info
Contacting Author
Registration
Features
The credits
Support & BBS's

Back To Main

1.3 DayDream BBS - General Information

General information

~~~~~

DayDream BBS was originally developed for the IBM PC and it was some kind of a QuickBBS clone. It was programmed by Tuomas Tonteri. When the A1200 was released Tuomas sold his PC and bought an Amiga. He started to code a new AmiExpress-lookalike BBS-program, but the name was the same, DayDream BBS. At the beginning, DayDream evolved rather rapidly, but after one year of programming Tuomas ran out of time and the studying and his girlfriend took all his time, so he gave the sources etc to me. Soon Tuomas changed back to the PC, but still DayDream is evolving at the full speed.

## 1.4 DayDream BBS - Legal Info

#### Legal Info

~~~~~

I'm not responsible if DayDream causes any damage to your system. You use it at your own risk.

If you find any bugs please inform me. Also, if you have MMU, try to find enforcer hits and tell me where they (hits) occur.

!NOTICE THIS!

If you use cracked version of DayDream BBS please register. DayDream BBS is a result of two years of hard work. I haven't spent my life coding protection, but certain tricks can make the cracked version not to work properly. If you're going to crack this, think twice because I'm not going to throw away this project unless everybody use cracked version. And I'm not going to slow down the progress of this BBS software!

1.5 DayDream BBS - Contacting Author

Contacting Author

~~~~~

The chameleon - nodel :+358-81-5546450 - 24h - v34

Leave mail to Hydra (Antti Häyrynen).

InterNet Address: hydra@freenet.hut.fi.

My own BBS: Humanoid Invasion - +358-81-5409139 - 24h - V32Bis.

Regular non-scene guys should call my BBS because they can have problems to get the access to The Chameleon.

## 1.6 DayDream BBS - Registration

#### Registration

~~~~~

DD is distributed as SHAREWARE. It means that you can test the software before you buy it. After 30 days of using it, you should register it.

The unregistered version of DayDream BBS has one annoying limitation. Before letting user to the system, there's delay of n seconds. $0 < n < 20$.

Note that removing this limitation may enable some nasty boobytraps, so if you're about to use cracked version, your harddisk can be in danger :).

Registration fee is 200FIM or 55USD. If possible, use FIM. This is not much, because I spend several hours a day developing this software. Compare the price to any other GOOD BBS Software, and you'll see that they cost at least TWICE as much!

I suggest that you use cash, because it's the cheapest way to do it.

Send the registration fee with letter containing following information about yourself:

- Full name
- Full Address
- Possible phone number and information about your BBS.
- E-Mail address (if any)

Send them to this address:

Antti Häyrynen
Rysätie 12a1
FIN-90810 Kiviniemi
Finland

If you want to receive the keyfile faster, I can send it via E-Mail in uuencoded format. It's also possible to download the keyfile from my BBS, but then tell me the name and password for your account.

1.7 DayDream BBS - Features

Features

~~~~~

- DayDream BBS looks like AmiExpress, which is a much loved and hated BBS software. Most of the people who like AmiExpress like it because of it's simpliness and because it's very fast to use. However, AmiExpress requires a very fast CPU to operate smoothly and the configurability is rather poor too. DayDream fixes the major problems found in AmiX.
  - 100% assembly code. DayDream is probably the fastest BBS-software ever.
  - Number of conferences is limited to 64. Each conference can have up to 254 messagebases and fileareas.  $64 * 254 = 16256$  (or for Pentium users 16255.999999987.)
  - Maximum security. Each user can have their own securitysettings, but defaults are taken by securitylevel. Every command in DayDream can be toggled on/off.
-

- Basic utilities and doors are included in distribution archive. For example: Faker, whof, new, top list -utilities, weektop etc.
- Configuration is done via an ascii file. This enables quick modifications to the BBS' settings. Ascii file is converted to binary format with utility called DreamConfig. It takes about 0.5 secs to compile the datafiles with it.
- Superb upload handling. Full support for file\_id.diz, gets date from file\_id.diz (if wanted), built-in offline checking, adds file\_id.diz to archives if it didn't exist etc.
- Strings and prompts can be re-defined, so you can customize your BBS any way you like.
- You can have 254 different displaymodes. Each displaymode can have it's own characterconversiontables (=no more linefeeds), prompts and strings and textfiles.
- Multinode support. Supports up to 254 nodes in theory. I suppose you can have at least 5 nodes on regular 030 without too high CPU-Load.
- Door formats supported: DayDream, ARexx, Paragon, stdio. AmiExpress pseudo-rexx "XIM" doors work via external emulation.
- Supports XPR-Protocols, Hydra+SModem (Bidirectional w/ chat).
- Cheap. DayDream costs only 200FIM or 55USD.
- Everything else except DDHydra and SModem can be made resident!

## 1.8 DayDream BBS - The Credits

The credits

~~~~~

Design, programming in 1993-1994, the most of the bugs, frame:

-Tuomas Tonteri

Design, current development, optimizing, programming in 1994 - 20??, manual, utilities, included DDDP-Doors, ideas etc:

-Antti Häyrynen (Hydra/Insane)

Beta testing, discovering the most of the bugs, ideas, spreading, public reactions, included ARexx-doors, whipping etc:

-DarkElf/Insane^TRSi^Scoopex

Beta testing, enforcer testing, documentation "improvement"/grammar checking:

-Allas/Parallax & Damage

Reqtools.library:

-Nico François

Whipping, Ideas:

-CandyMan/Morque

Background music, keeping the programming mood on:

-Sonic Youth, REM, Smashing Pumpkins, CMX, The Ramones,
Rage Against the machine, Pearl Jam, Björk Gudmundsdottir etc...

1.9 DayDream BBS - Support

Support

~~~~~

If you have any comments, discover some bugs or have any suggestions etc feel free to send E-Mail to me at: [hydra@freenet.hut.fi](mailto:hydra@freenet.hut.fi).

You can get the doors and stuff via ftp:

<ftp://pato.vaala.fi/pub/amiga/daydream/>.

Check out also DayDream homepage. <http://www.vaala.fi/~hydra>.

DayDream BBS Support Boards

~~~~~

Name	Nodes	Speed	Number (s)	SysOp
=====				
Humanoid Invasion	1	28800	+358-81-5409139	Hydra
The Chameleon	5	33600	+358-81-5546450	Allah
			(/whois allah for telnet)	
Octavo	1	33600	+44-121-3110359	Skittle
=====				

Experienced DD SysOps wanted for supporters! Mail hydra for more info.

1.10 DayDream BBS - Requirements

Requirements and Installation

Software Requirements

Hardware Requirements

Installation

Directories

Executing DayDream

Back To Main

1.11 DayDream BBS - Software Requirements

Software Requirements

~~~~~

- KickStart 2.04 (V37) or higher.
- Fifo.library and l:fifo-handler running (for remote shell operation)
- Reqtools.library

## 1.12 DayDream BBS - Hardware Requirements

### Hardware Requirements

~~~~~

- Memory: Server requires about 60kb and each node about 300kb of ram.
If DayDream has been made resident, then each node requires abt. 150 kb of ram.
- Harddrive: Not required, but I suggest asylum if you are planning to run your BBS from floppies.

1.13 DayDream BBS - Installation

Installation

~~~~~

#### Step 1)

Just use the supplied installation-script and Commodore's installer-program to install DayDream.

#### Step 2)

Compile DayDream.CFG using supplied config-program, DreamConfig. Eg. DayDream:Utils/DreamConfig DayDream:DayDream.CFG.

#### Step 3)

Create SysOp account. To do this, just start server and type "Run DayDream nl lc".

Now you should be able to test it. Of course you cannot discover all the features with only 5 minutes checking, so I suggest you spend some time testing this. It has lot of features never seen on Amiga BBS programs.

## 1.14 DayDream BBS - Directories

### Directories

~~~~~

DayDream:Data/	- Includes all the configuration and datafiles (like UserBase etc)
DayDream:Batch/	- Includes logoff-batch files.
DayDream:Utils/	- Includes DayDream BBS utilities.
DayDream:Temporary/	- Required for uploads.
DayDream:Display/	- Contains most of the textfiles that are showed to the user when he's cruising in the BBS.
DayDream:Doors/	- Contais external program modules, commands, games etc. that can be executed from the BBS.
DayDream:Hold/	- Private uploads to the SysOp are placed in here.

DayDream:Logfiles/ - Contains your logfiles.

1.15 DayDream BBS - Executing DayDream

Executing DayDream

~~~~~

To execute DayDream BBS, you must have the DayDream BBS Server running. Server handles most of the dos routines and shares access between nodes. To do this, simply type "Run Server" in the main directory.

Commandline parameters for the main executable (DayDream) are:

```
DayDream n[node] (d[baud]) (lo/lc) (h) (c["connectstring"])
```

```
n = node
d = BPS rate for direct connection
lo = Operator login
lc = Local connection
h = Use +++ hangupping instead of DTR hangup
c = parse connectstring and make direct connection
```

```
Examples: run DayDream n1                (Normal wait-for-call mode)
          run DayDream n1 lo              (Local connection)
```

## 1.16 DayDream BBS - BBS Files

BBS Files

```
[Conference]/Data/  
[Conference]/Bulletins/  
[Conference]/Display/[Displaymode]/  
[Conference]/Display/  
[Conference]/Messages/[BaseXXX]  
DayDream:Display/[DisplayMode]/  
DayDream:Display/  
DayDream:Data/  
Questionnaire/  
DayDream:Batch/  
Special Control Codes
```

[Back To Main](#)

### 1.17 DayDream BBS - [Conference]/Data/

[Conference]/Data/  
~~~~~

This directory includes some conference-specific data, such as File catalogs, list of free downloads, list of paths that are used to access downloadable files etc.

- Directory.XXX - File-catalog of XXX - filearea.
- Paths.DAT - This file is used to define directories that are used for searching files. First line=Area 1 etc. Amount of lines can be unlimited. If there are more lines in this file than filedirectories in the conference, rest of the lines are extra dl-paths.
- FreeDownloads.DAT - Contains list of Free downloads. Wildcards allowed. NOTE! Global freedownloads can be specified in DayDream:Data/FreeDownloads.DAT.
- Examine.DAT - Contains list of doors to be launched in upload-checking after user has verified that upload is ok. It can be used for conf top utils, if someone codes one.
Note that doors listed in here MUST be DDDP-doors.

Developer Information about this is available.

Here's an example of Examine.DAT:

```
-----cut-----
doors:conftop %N
doors:svenskatoppen %N
-----cut-----
```

- FileCheck.DAT - Contains list of doors to be launched in upload-checking before outputting user anything about the file. It can be used for dupechecker or stuff like that, though there's good dupechecker inside DD. It can also be used to replace built-in uploadchecker (Replacement must add bytes to user and write file information to filelist and copy file to filebase.) Note that doors listed here MUST be DDDP-doors.

Developer Information about this is available.

Here's an example of FileCheck.DAT:

```
-----cut-----
doors:rexx %N doors:rexxdir/showrules.dd
-----cut-----
```

1.18 DayDream BBS - [Conference]/Bulletins/

[Conference]/Bulletins/
~~~~~

This directory includes bulletins, such as top uploader list or otherwise useful information. Add .GFX or .TXT suffix.

BulletinMenu - List of available bulletins

Bulletin.X - Should be selfexplaining.

## 1.19 DayDream BBS - [Conference]/Display/[Displaymode]/

[Conference]/Display/[Displaymode]/

~~~~~

This directory contains the conference-specific textfiles displayed to the user. If file is not found, it is searched from DayDream:Display/[Displaymode]/. Add .GFX or .TXT suffix.

Commands - List of commands.

FileCatalogs - List of file-areas in the current conference.

MessageBases - List of messagebases in the current conference.

Upload - Showed to the user before uploading. Useful if you want to show some upload-rules etc.

Download - Showed to the user before downloading.

HydraTransfer - Showed to the user before bidirectional Hydra-transfer.

JoinConference - Showed to the user when he/she joins the conference.

ConferencePW - Showed to the user before asking conference password.

AutoReJoin - Showed to the user after JoinConference.TXT in login..

1.20 DayDream BBS - [Conference]/Display/

[Conference]/Display/

~~~~~

This directory contains only one optional file, prompt.txt. It's a custom menu prompt for this conference, and supports following control codes:

| Control code | Meaning             |
|--------------|---------------------|
| %%           | Print %-char        |
| %A           | Last read pointer   |
| %C           | Conference name     |
| %E           | Highest message     |
| %L           | Message base number |
| %M           | Message base name   |

=====

|    |                     |
|----|---------------------|
| %% | Print %-char        |
| %A | Last read pointer   |
| %C | Conference name     |
| %E | Highest message     |
| %L | Message base number |
| %M | Message base name   |



|    |                      |
|----|----------------------|
| %N | Conference number    |
| %T | Time left in minutes |
| %B | Node number          |
| %S | BBS Name             |

## 1.21 [Conference]/Messages/[BaseXXX]

[Conference]/Messages/[BaseXXX]

~~~~~

Contains messages and their headers.

MsgBase.DAT	- Headers of the messages in the current base.
MsgBase.LRP	- Autoscan and lastread pointers.
MsgXXXXX	- Standard messagefile.

1.22 DayDream BBS - DayDream:Display/[DisplayMode]/

DayDream:Display/[DisplayMode]/

~~~~~

Contains most of the textfiles that are showed to the user when he's cruising in the BBS.

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| AccountFrozen      | - Shown when user whose account has been frozen tries to login. |
| Banner             | - Shown before the login prompt.                                |
| BeforeGoodBye      | - Shown to the user when he/she enters G-command.               |
| BiDirProtocols     | - List of Bidirectional protocols                               |
| Commands           | - List of available commands                                    |
| Conferences        | - List of available conferences                                 |
| Download           | - Shown to the user before download                             |
| EditUser           | - Shown to the user when he/she's modifying account info.       |
| FileCatalogs       | - Shown to the user when he/she's listing files.                |
| GoodBye            | - Logoff screen                                                 |
| LineChatOn         | - Shown to the user when sysop enters chat mode.                |
| LineChatOff        | - Shown to the user when sysop exits chat mode.                 |
| LineEditorCommands | - List of available commands in message-editor.                 |

---

---

|                   |                                                                                                          |
|-------------------|----------------------------------------------------------------------------------------------------------|
| MoreHelp          | - Shown when user requests help in more-prompt.                                                          |
| MoveFiles         | - Shown before asking files to move.                                                                     |
| MsgReadCommands   | - List of available commands when reading messages.                                                      |
| NewUser           | - Displayed to the user when he/she decides to create a new account. Useful for rules etc.               |
| NewUserPassword   | - Shown to the user if he/she decides to create new account and the system requires a New User Password. |
| PassWordFailure   | - Displayed to the user if he fails 3 times in the password checking.                                    |
| ProtocolMenu      | - List of available protocols.                                                                           |
| Reg_Realname      | - Shown to the user before asking his/her real name during the registration.                             |
| Reg_Handle        | - Shown to the user before asking his/her handle during the registration.                                |
| Reg_Zip+City      | - Shown to the user before asking his/her Zipcode during the registration.                               |
| Reg_VoiceNumber   | - Shown to the user before asking his/her Voice phone number during the registration.                    |
| Reg_PassWord      | - Shown to the user before asking his/her password during the registration.                              |
| Reg_ComputerModel | - Shown to the user before asking his/her computer-model during the registration.                        |
| Reg_ScreenLength  | - Shown to the user before asking his/her Screen length during the registration.                         |
| ScanDateHelp      | - Shown to the user when he requests help during new file scan.                                          |
| SplitChatOn       | - Shown to the user when sysop enters chat mode.                                                         |
| SplitChatOff      | - Shown to the user when sysop exits chat mode.                                                          |
| SystemPassword    | - Shown to the user before asking for the System Password (if SystemPassword is enabled)                 |
| Upload            | - Shown to the user before uploading.                                                                    |
| UploadCommands    | - Commandlist on prompt requesting save etc.                                                             |
| Welcome           | - Displayed to the user after logon.                                                                     |
| ZippySearch       | - Showed to the user if he/she didn't enter any parameters for Z-command.                                |

---

NOTE! Some of these files can be different for every security level. Eg. Commands.255.GFX will be showed to the user if his/her access level is 255.

## 1.23 DayDream BBS - DayDream:Display/

DayDream:Display/  
~~~~~

DisplayModeHelp.TXT - List of available display modes.

Strings.XXX - Contains nearly all strings and prompts in BBS.

BoardClosed.TXT - If exists, DayDream will display this and disconnect the user before logon.

PermanentlyAway.TXT - If exists, will be displayed to the user when he/she requests chatting. Useful if you are ie. on vacation.

1.24 DayDream BBS - DayDream:Data/

DayDream:Data/
~~~~~

This directory contains some binary files which are generated by DreamConfig or DayDream itself. There's also some textfiles that can be edited using Texteditor and they are:

TrashCan.DAT - List of names that are not allowed in the system.  
Wildcards allowed.

FreeDownloads.DAT - List of free downloads (all conferences).  
Wildcards allowed.

FrontEnds.DAT - Contains list of doors to be launched before asking displaymode from user.  
Note that doors listed in here MUST be DDDP-doors.

If door uses changes displaymode using  
intcommand "mode ??" or similar command, DD doesn't  
ask for display mode.

LogOnDoors.DAT - Contains list of doors to be launched after showing Welcome.TXT. Useful if you want to force a door to be run on startup. (One can abort welcome.txt with ^C.)

## 1.25 DayDream BBS - Questionnaire/

Questionnaire/  
~~~~~

New user questionnaire is based on 2 files: Registration.questions and Registration.

If yhe Registration file exists, it will be displayed to every new user that logs in (or to all users who have not answered the questionnaire, if it's enabled in the DayDream.cfg file (QUESTIONS .. Y/N)).

The basic format of the Registration and Registration.Questions files are as follows:

Each question is followed by ÿN (ASCII-code 255+N) where N is the number of lines user is allowed to use to answer the question.

For example:

Please name atleast 3 presidents of the United States of America (3 lines)

ÿ3

The string "(3 lines)" is not needed for the questionnaire to work, but it's nice to let the user know how many lines he can use.

Now let's suppose this was the first question in the questionnaire file. So in the Registration.Questions file the first line could be like:

Presidents

User won't see this string, but it will be added in front of the answers in the Registration.Answers file. If the user answered ie.:

Ronald Reagan
George Bush
Bill Clinton

The Registration.Answers would then show:

Answers by Real Name / Handle on 01.01.1995 at 18:00:00

```
=====
Qst: President |
Ans: [ Ronald Reagan ]
     : [ George Bush ]
     : [ Bill Clinton ]
etc.
```

The procedure is the same for all the questions. Just make sure that you have as many lines in the Registration.Questions file as you have questions in the Registration file.

1.26 DayDream BBS - DayDream:Batch/

DayDream:Batch/
~~~~~

This directory contains batch files. You must protect +s them, so

DayDream can execute then. Currently supported files are:

LogoffX.bat                   - This will be executed everytime user leaves a BBS.  
Useful, if you want to have up-to-date top users  
list etc in your board etc.

## 1.27 DayDream BBS - Special Control Codes

### Special Control Codes

~~~~~

Textfiles can have special control codes, which will send out some variable text or cause certain things to happen. These control codes begin with asciiicode 255 (ÿ). From DD 1.20 you are able to change the ctrl code in config file. The is the list of the codes:

ÿP	- Pause
ÿN	- Any key to resume (Pause)
ÿR	- Real name
ÿH	- Handle
ÿO	- Organization
ÿZ	- Zip code and city
ÿV	- Voice Phone
ÿA	- Password (!!Use with care!!)
ÿS	- Screen length
ÿT	- Protocol ID
ÿU	- Upload Signature
ÿC	- Computer Model
ÿD<command> [parameters]	- Run a standard DDDP-door
ÿI	- Current Date
ÿM	- Current Time
ÿB<asciifile>	- Display ascii file
ÿL	- Silent any key to resume
ÿQ	- User Id Number
ÿX	- Daily Time
ÿ9	- First Date On
ÿW	- Last Date On
ÿY	- Online Baud
ÿ\$	- Security Level
ÿ0	- Uploaded Bytes
ÿ1	- Uploaded Files
ÿ2	- Downloaded Bytes
ÿ3	- Downloaded Files
ÿ4	- Bytes Avail
ÿ5	- Files Avail
ÿ6	- Messages Posted
ÿ7	- Times Called
ÿ8	- Sysop Pages Remaining
ÿ!	- Conf. name
ÿ£	- Conf. number
ÿ%	- BiDir protocol ID
ÿFxx.yyy	- Forbid printing xx: 01 = Conf access yyy: Parameters
ÿExx.yyy	- Permit printing xx: 01 = Conf access yyy: Parameters
ÿG	- Turn more-prompts off

```

ÿJ<path>|<max value>|      - Shows random file. <Path> is a path and
                             prefix of filename. Postfix for file is a
                             number between 1 and <max value>. Eg.

                             ÿJDayDream:display/iso/Showme|6|
                             could show DayDream:display/iso/Showme3.
                             GFX/TXT extension won't be added!

ÿK<command>|                - Execute standard menu command.

```

Example on ÿD-code:

```

-----
ÿDDayDream:Doors/Wall %N||
-----
^ ^          ^ ^^
| |          | ||
| |          | '--> ..And between these two add
| |          |      the parameters
| |          |--> Pause after running
| |          | '--> Full path to the door
| '--> Run External Door

```

1.28 DayDream BBS - Configuring BBS

Configuring BBS

```

General Information
Main Configuration
Conferences
External Commands
Access Presets
Archivers
File Transfer Protocols
Display Modes
Multinode Stuff
I/O Devices
Security Levels
Schedule
Server

```

Back To Main

1.29 DayDream BBS - General Information

General information
 ~~~~~

Configuration of DayDream BBS is done via external configprogram, DreamConfig. It compiles specified ascii file to the datafiles, that can be found in DayDream:Data/-directory. Be sure you have correct number of lines in each entry, or the DreamConfig will fail. Compiler is quite fast, it takes only few seconds to compile all data-files.

The basic configfile is included in distribution archive, just look at the examples to get the idea.

## 1.30 DayDream BBS - Main Configuration

### 4-2 - Main Configuration

~~~~~

Main configuration in DayDream.CFG looks like this:

```
!DAYDREAM.DAT
BBSNAME..... Windowskiihdytin
SYSOP..... Hydra
LOCALUPLDPATH Dh1:download/
CHATDLPATH... dh1:download/
OP_DMODE..... 1
SYSTEM_PW.... -
NEWUSER_PW... -
USERED_PW.... -
FSCAN_BUFFER. 60
NEW_PRESET... 1
IDLE..... 180
AUTOCONF..... 1
FREEFORUL.... 2000000
ASK_REASON... Y
NAMEMODE..... H
LOCATION..... O
DISABLEWILDS. N
QUESTIONS.... N
LOGDISA..... Y
QUICKLINEED.. N
SYSOP_COL.... ?[36m
USER_COL..... ?[35m
SHELL_PW..... SODOM
ALIENS..... DayDream:Aliens/
LINEEDCOM.... $
FSED..... Doors:FSEd %N
CHATMODE..... S
LOCALSCREEN.. 30
FREEDLLINE... [-] FREE DOWNLOAD <><><><> FREE DOWNLOAD [-]
OLMPATH..... t:
COSYSOPACCESS 250
CONTROLCHAR.. 255
~
```

1.31 DayDream BBS - Main Configuration - BBSNAME

BBSNAME.....

The actual name of your BBS.

1.32 DayDream BBS - Main Configuration - SYSOP

SYSOP.....

Your name/handle.

1.33 DayDream BBS - Main Configuration - LOCALUPLDPATH

LOCALUPLDPATH

Default path used for sending ascii files while in chat mode,
for local uploading etc..

1.34 DayDream BBS - Main Configuration - CHATDLPATH

CHATDLPATH...

Path of directory where the files downloaded during a chat will be
placed.

1.35 DayDream BBS - Main Configuration - OP_DMODE

OP_DMODE.....

Display mode used to run "daydream n? lo" -connections.

1.36 DayDream BBS - Main Configuration - SYSTEM_PW

SYSTEM_PW....

System password (- for none)

1.37 DayDream BBS - Main Configuration - NEWUSER_PW

NEWUSER_PW...

New user password (- for none)

1.38 DayDream BBS - Main Configuration - USERED_PW

USERED_PW....

Password required to enter user editor. To enter usereditor, user
also requires the privilege flag of UserEditor to be set as On.

1.39 DayDream BBS - Main Configuration - FSCAN_BUFFER

FSCAN_BUFFER.

Size of buffer (kb) used by Zippy Search, File scan and New files scan.

1.40 DayDream BBS - Main Configuration - NEW_PRESET

NEW_PRESET...

Access preset used for new users.

1.41 DayDream BBS - Main Configuration - IDLE

IDLE.....

Inactivity timeout in seconds. If nothing happens in the BBS for this period of time, user will be disconnected.

1.42 DayDream BBS - Main Configuration - AUTOCONF

AUTOCONF.....

Conference to join, if user doesn't have access to the Conference where he was on when logged off last time (=autojoin conference)

1.43 DayDream BBS - Main Configuration - FREEFORUL

FREEFORUL.....

Free space required for uploads in bytes. Suggested value about 2000000.

1.44 DayDream BBS - Main Configuration - ASK_REASON

ASK_REASON...

Set wether or not user is asked for a reason when paging for a chat

1.45 DayDream BBS - Main Configuration - NAMEMODE

NAMEMODE.....

If H, use handles in the BBS as default.
If R, use real names in the BBS as default.

1.46 DayDream BBS - Main Configuration - LOCATION

LOCATION.....

If L, use zip code as location.
If O, use organization as location.

1.47 DayDream BBS - Main Configuration - DISABLEWILDS

DISABLEWILDS.

Set wether or not wildcards can be used during login. Be careful with this, as a plain * can be used to list all the handles AND real names that are used in the board.

1.48 DayDream BBS - Main Configuration - QUESTIONS

QUESTIONS....

Y/N switch. If this is Y, DayDream will run Questionnaire for the user if he hasn't answered it yet. (If userbase was converted from /X etc)

1.49 DayDream BBS - Main Configuration - LOGDISA

LOGDISA.....

Y/N switch. If this is Y, DayDream will not write logfile during a local operator login.

1.50 DayDream BBS - Main Configuration - QUICKLINEED

QUICKLINEED..

Y/N switch. If this is Y, CR in empty line will enter command mode in line editor.

1.51 DayDream BBS - Main Configuration - SYSOP_COL

SYSOP_COL.....

Ansicode that will be used for the sysop's colour in the chat mode.

1.52 DayDream BBS - Main Configuration - USER_COL

USER_COL.....

Ansicode that will be used for the user's colour in the chat mode.

1.53 DayDream BBS - Main Configuration - SHELL_PW

SHELL_PW.....

Password required for Remote shell operation (- for none)

1.54 DayDream BBS - Main Configuration - ALIENS

ALIENS.....

Path to place files that are found in Temporary directory when it needs to be cleaned. There can be files eg. if system has crashed during uploading. If this is -, files in temporary directory will be deleted.

1.55 DayDream BBS - Main Configuration - LINEEDCOM

LINEEDCOM.....

Character that activates the command mode in line editor.

1.56 DayDream BBS - Main Configuration - FSED

FSED.....

Command to be executed to start FullScreen Editor or - if you don't want to have FullScreen Editor.

1.57 DayDream BBS - Main Configuration - CHATMODE

CHATMODE.....

L = Line chat, S = Split screen chat, A = Ask

1.58 DayDream BBS - Main Configuration - LOCALSCREEN

LOCALSCREEN..

The length of the local screen.

1.59 DayDream BBS - Main Configuration - FREEDLLINE

FREEDLLINE...

Line to be added after free downloads or -.

1.60 DayDream BBS - Main Configuration - OLMPATH

OLMPATH.....

Path to store multiline OLM's (Introduced in DD 1.17). If this is -, old-fashioned OLM's will be used. (OLM=OnLine message)

1.61 DayDream BBS - Main Configuration - COSYSOPACCESS

COSYSOPACCESS

Access level of Co-SysOp. Currently this is used only in userlist and this should be always lower than 255.

1.62 DayDream BBS - Main Configuration - CONTROLCHAR

CONTROLCHAR..

Ascii code for control character in TXT files. Should be 255.

1.63 DayDream BBS - Conferences

Conferences

~~~~~

```
CONF_NUMB..... 1
CONF_NAME..... Example Conference
CONF_PATH..... DayDream:ExampleConf/
CONF_FILEAREAS 2
CONF_UPLOADSTO 2
CONF_MSGBASES.. 2
CONF_COMMENTS.. 1
CONF_ULPATH... DayDream:ExampleConf/New/
CONF_NSAREAS.. A
CONF_DEFFSCAN.. N
CONF_FREELEECH N
CONF_NOCREDS.. N
CONF_SENTBY... Y
CONF_LONGNAMES N
CONF_ASKDEST.. N
CONF_NOWILDS.. Y
CONF_NOWILDFLG N
CONF_NODUPECHK N
CONF_NOFILECHK N
CONF_NOREQ.... N
CONF_PASSWORD.. -
```

+

The next line specifies what to do next. If it's +, then next block of config file is for message base. If it's \*, then next block of config file is for a new conference and if it's ~, it's the end of the Conferences.DAT.

```
BASE_NUMBER... 1
BASE_TYPE..... L
BASE_LOWEST... -
BASE_HIGHEST.. -
BASE_MAXMSGSGS.. 1000
BASE_NAME..... Comments to SysOp
BASE_FIDOTAG.. -
BASE_ORIGIN... -
BASE_FIDOADD.. -
BASE_ALLOWPBL C N
BASE_ALLOWPRIV Y
BASE_FILEATTAC Y
BASE_NAMES.... R
BASE_ALL=EALL.. N
BASE_QUOTE.... L
BASE_DEFGRAB.. Y
```

~

The next line specifies what to do next. If it's +, then the next block of config file is for message base. If it's \*, then the next block of config file is for new conference and if it's ~, it's the end of the Conferences.DAT.

## 1.64 DayDream BBS - Conferences - CONF\_NUMB

CONF\_NUMB.....

Conference Number. Allowed values are 1-64.

## 1.65 DayDream BBS - Conferences - CONF\_NAME

CONF\_NAME.....

Name of the conference.

## 1.66 DayDream BBS - Conferences - CONF\_PATH

CONF\_PATH.....

Path of the conference. End with / or :

## 1.67 DayDream BBS - Conferences - CONF\_FILEAREAS

CONF\_FILEAREAS

Number of fileareas in conference. Allowed values 0-255.

## 1.68 DayDream BBS - Conferences - CONF\_UPLOADSTO

CONF\_UPLOADSTO

Number of area to place uploads in.

## 1.69 DayDream BBS - Conferences - CONF\_MSGBASES

CONF\_MSGBASES.

Number of message bases. MUST be the same value as number of defined message bases or DD will piss.

## 1.70 DayDream BBS - Conferences - CONF\_COMMENTS

CONF\_COMMENTS.

Number of message base to place comments in. If 0, comments won't be accepted in the conference.

---

## 1.71 DayDream BBS - Conferences - CONF\_ULPATH

CONF\_ULPATH...

Path of the directory where uploads are moved after transfer. End with : or /.

## 1.72 DayDream BBS - Conferences - CONF\_NSAREAS

CONF\_NSAREAS..

Arealist for global new file scan. Area list uses the same routine as N S [....]-menu command. [....] will be placed with this.

## 1.73 DayDream BBS - Conferences - CONF\_DEFFSCAN

CONF\_DEFFSCAN.

If you want this conference to be turned on as default for the global file scan, use Y. If not, then N.

## 1.74 DayDream BBS - Conferences - CONF\_FREELEECH

CONF\_FREELEECH

If you want that all file in the conference are free downloads, set this as Y.

## 1.75 DayDream BBS - Conferences - CONF\_NOCREDS

CONF\_NOCREDS..

If you want that users won't get credits from the files they upload, set this as Y.

## 1.76 DayDream BBS - Conferences - CONF\_SENTBY

CONF\_SENTBY...

If you want that sent-by lines are in use, set this as Y.

---

### 1.77 DayDream BBS - Conferences - CONF\_LONGNAMES

## CONF\_LONGNAMES

Selects filelist format for this conference. If this is Y, 18 characters long filenames are used. If this is N, MS-Dos filenames are used.

If you want to convert 12 chars filelist to 18 chars filelist, use included DayDream:Utils/oldlist2newlist to do it.

The lists look like this:

```

-----] 12 CHARS [-----
ACSD110.LZX P--- 273942 14.05.95
      /      /      /      /      /      /      /      /
     /      /      /      /      /      /      /      /
    /      /      /      /      /      /      /      /
   /      /      /      /      /      /      /      /
  /      /      /      /      /      /      /      /
 /      /      /      /      /      /      /      /
/      /      /      /      /      /      /      /
M@! /
DayDream BBS V1.10 (14 May 95)
The fastest Amiga BBS Package supporting
WWF, BlueWave, Hydra, XPR, ARexx, stdio,
Offline Checking, File_id.diz, FidoNet etc.
The Main executable is 100% ASM!

```

[illegible]

### 1.78 DayDream BBS - Conferences - CONF\_ASKDEST

## CONF ASKDEST..

If you want that user will be asked for filearea for his/her upload instead of placing it in upload directory, set this as Y.

### 1.79 DayDream BBS - Conferences - CONF NOWILDS



CONF\_NOWILDS..

If you don't want filenames to contain wildcards, set this to Y.

## 1.80 DayDream BBS - Conferences - CONF\_NOWILDFLG

CONF\_NOWILDFLG

To disable wildcard support for file flagging, set this to Y. Flagging with wildcards is pretty slow in CD-Rom conferences.

## 1.81 DayDream BBS - Conferences - CONF\_NODUPECHK

CONF\_NODUPECHK

If you want to disable dupechecking in this conference, set this to Y.

## 1.82 DayDream BBS - Conferences - CONF\_NOFILECHK

CONF\_NOFILECHK

If you want to disable filechecking in the conference, set this to Y. Useful for eg. private conferences.

## 1.83 DayDream BBS - Conference - CONF\_NOREQ

If you want to disable filerequesters (NOT A DOS DISK IN DRIVE CD0:) in the conf, set this to Y. Useful if you listen audio-cd's with your CD-Rom.

## 1.84 DayDream BBS - Conferences - CONF\_PASSWORD

CONF\_PASSWORD. -

Password required for the conference or -.

## 1.85 DayDream BBS - Conferences - BASE\_NUMBER

BASE\_NUMBER...

Number of the message base. Allowed values are 1-254.

---

## 1.86 DayDream BBS - Conferences - BASE\_TYPE

BASE\_TYPE.....

Message base type. L = Local, E = FidoNet Echomail, N = FidoNet netmail.

## 1.87 DayDream BBS - Conferences - BASE\_LOWEST

BASE\_LOWEST...

Number of the lowest message. If -, value will be taken from existing Conferences.DAT. This should always be -. If you have blown your message bases up, just use included fixbases-program.

## 1.88 DayDream BBS - Conferences - BASE\_HIGHEST

BASE\_HIGHEST..

Number of the highest message. If -, value will be taken from existing Conferences.DAT. This should always be -. If you have blown your message bases up, just use included fixbases-program.

## 1.89 DayDream BBS - Conferences - BASE\_MAXMSGs

BASE\_MAXMSGs..

Maximum number of messages allowed in this base. Not yet supported, but I'll write a maintenance tool soon which autodeletes these etc.

## 1.90 DayDream BBS - Conferences - BASE\_NAME

BASE\_NAME.....

Name of the message base.

## 1.91 DayDream BBS - Conferences - BASE\_FIDOTAG

BASE\_FIDOTAG..

FidoNet tag for the message base. Case sensitive. Use - if none.

---

## 1.92 DayDream BBS - Conferences - BASE\_ORIGIN

BASE\_ORIGIN...

FidoNet origin for the message base. Use - if none.

## 1.93 DayDream BBS - Conferences - BASE\_FIDOADD

BASE\_FIDOADD..

4d FidoNet address. Use - if none.

## 1.94 DayDream BBS - Conferences - BASE\_ALLOWPBLC

BASE\_ALLOWPBLC

If this is Y, users can write public messages to this base. If N, they can't.

## 1.95 DayDream BBS - Conferences - BASE\_ALLOWPRIV

BASE\_ALLOWPRIV

If this is Y, users can write private message to this base. If N, they can't.

## 1.96 DayDream BBS - Conferences - BASE\_FILEATTAC

BASE\_FILEATTAC

If this is Y, users can attach files to the messages they send.

## 1.97 DayDream BBS - Conferences - BASE\_NAMES

BASE\_NAMES....

If this is R, real names will be used in this base. If this is H, handles will be used.

---

## 1.98 DayDream BBS - Conferences - BASE\_ALL=EALL

BASE\_ALL=EALL.

If you want that users all regular messages to all users will be exclusive all messages (will be shown in mailsan) set this as Y.

## 1.99 DayDream BBS - Conferences - BASE\_QUOTE

BASE\_QUOTE....

Quoting method. If L, /X-like quoteline will be inserted after quote. If this is >, plain > will be inserted before each line of the quote. If this is I, initials of the original message author and ">" will be inserted before quote. EG. "AH> DayDream KiX a\$\$!"

## 1.100 DayDream BBS - Conferences - BASE\_DEFGRAB

BASE\_DEFGRAB..

Y/N switch. Use Y, if you want this messagebase to be turned on as default for new mail scan and message grabbing.

## 1.101 DayDream BBS - External Commands

External Commands

~~~~~

DayDream supports 5 kinds of doors. They are DosScript (not so useful), DDDP (DayDream DoorProtocol, like XIM in AmiX), stdio-doors, ARexx-doors and textfiles. ARexx interface is external, program called rexx in Doors/-directory converts ARexx<->DDDP.

Paragon-door support is not ready yet.

To use any DayDream-door you will need ENV:-variable called DreamUtils. Doors and utils should look for their configfiles from path which is placed in that ENV:-variable. This provides possiblity to you to have configfiles placed where ever you want. Example configfiles are placed in DayDream:Configs/ so type "setenv DreamUtils DayDream:Configs/" to get doors and utils working. Stdio-doors/dos programs support following parameters:

%N - Node
 %R - Real name
 %H - Handle
 %S - Screenlength
 %D - Device
 %U - Unit

```
%B - Bps rate of the current connection
%L - Locked baud rate
%A - Access level
%T - Time left in minutes
```

More will be added if you request something.

```
!EXTERNALCOMMANDS.DAT
DOOR_COMMAND.. WALL
DOOR_TYPE..... 1
DOOR_SECURITY.. 5
DOOR_EXECUTE.. DayDream:Doors/Wall %N
+
```

The next line specifies what to do next. If it's +, then there's another door to compile. If it's ~, it's the end of the ExternalCommands.DAT.

1.102 DayDream BBS - External Commands - DOOR_COMMAND

DOOR_COMMAND..

Command in main menu to launch this door.

1.103 DayDream BBS - External Commands - DOOR_TYPE

DOOR_TYPE.....

Door type. 0 = Dos program without any kind of output or input to the serial or console.

1 = DDDP door (DayDream Door Protocol). DDDP is very flexible method for programming doors. Specifications of DDDP are included in Developer/-directory.

2 = Paragon door. Tuomas wrote this, but it's not finished yet. I don't have specifications for Paragon doors, so I've been unable to finish writing this ready, sorry.

3 = Stdio door. Uses Matthew Dillon's fifo.library and fifo-handler. Standard dos programs which won't open screen or window will work.

4 = Text file. Specified text file from current display directory will be shown to the user. Useful for doormenus etc.

5 = Internal command. Allows you to change commands of the main menu.

1.104 DayDream BBS - External Commands - DOOR_SECURITY

DOOR_SECURITY.

Security level required to run this door.

1.105 DayDream BBS - External Commands - DOOR_EXECUTE

DOOR_EXECUTE..

Command or filename to run the door. %N required for DDDP doors.
- to disable command (if doortype = 5).

1.106 DayDream BBS - Access Presets

Access Presets

~~~~~

```
PRESET_SEC.... 5
PRESET_NUMBER. 1
PRESET_FFILES. 0
PRESET_FBYTES. 0
PRESET_DESC... New User
PRESET_STATUS. 3
```

+

The next line specifies what to do next. If it's +, then there's preset to compile. If it's ~, it's the end of the Access.DAT.

### 1.107 DayDream BBS - Access Presets - PRESET\_SEC

PRESET\_SEC....

Security level of this preset.

### 1.108 DayDream BBS - Access Presets - PRESET\_NUMBER

PRESET\_NUMBER.

Number of preset.

### 1.109 DayDream BBS - Access Presets - PRESET\_FFILES

PRESET\_FFILES.

Free files.

---

### 1.110 DayDream BBS - Access Presets - PRESET\_FBYTES

PRESET\_FBYTES.

Free bytes. (In KB!!!)

### 1.111 DayDream BBS - Access Presets - PRESET\_DESC

PRESET\_DESC...

Description of the preset.

### 1.112 DayDream BBS - Access Presets - PRESET\_STATUS

PRESET\_STATUS.

Status of the preset. 0 = Active, 1 = Deleted, 2 = Frozen, 3 = New

### 1.113 DayDream BBS - Archivers

Archivers

~~~~~

!ARCHIVERS.DAT

```
ARC_TYPE..... F
ARC_EXTENSION. LHA
ARC_NAME..... LHA
ARC_TEST..... dh1:utils/lha -m -M T %A
ARC_FAIL1..... Failed
ARC_FAIL2..... -
ARC_FAIL3..... -
ARC_FIDEXTRACT dh1:utils/lha -m -M E %A %F
ARC_FIDADD.... dh1:utils/lha -m -M A %A %F
ARC_VIEW..... dh1:utils/lha L %A %F
ARC_OFFLINE... Y
ARC_GETDATE... Y
ARC_DELETECOR. Y
ARC_DISPLAY... Y
ARC_SECVIEW... 200
```

+

The next line specifies what to do next. If it's +, then there's archiver to compile. If it's ~, it's the end of the Archivers.DAT.

1.114 DayDream BBS - Archivers - ARC_TYPE

ARC_TYPE.....

Archiver type. F = File archiver, D = Disk archiver.

1.115 DayDream BBS - Archivers - ARC_EXTENSION

ARC_EXTENSION.

Extension of the archive.

1.116 DayDream BBS - Archivers - ARC_NAME

ARC_NAME.....

Archiver name.

1.117 DayDream BBS - Archivers - ARC_TEST

ARC_TEST.....

Test command of the archiver (- for none)

1.118 DayDream BBS - Archivers - ARC_FAIL1

ARC_FAIL1.....

Keyword if archive is corrupted (- for none). Case-sensitive.

1.119 DayDream BBS - Archivers - ARC_FAIL2

ARC_FAIL2.....

Keyword if archive is corrupted (- for none). Case-sensitive.

1.120 DayDream BBS - Archivers - ARC_FAIL3

ARC_FAIL3.....

Keyword if archive is corrupted (- for none). Case-sensitive.

1.121 DayDream BBS - Archivers - ARC_FIDEXTRACT

ARC_FIDEXTRACT

File_id.diz extract command (- for none)

1.122 DayDream BBS - Archivers - ARC_VIEW

ARC_VIEW

Archive view command (- for none)

1.123 DayDream BBS - Archivers - ARC_FIDADD

ARC_FIDADD....

File_id.diz add command (- for none)

1.124 DayDream BBS - Archivers - ARC_OFFLINE

ARC_OFFLINE...

Use offline checking to check the files. (Y/N)

1.125 DayDream BBS - Archivers - ARC_GETDATE

ARC_GETDATE...

Get date from file_id.diz and insert it to the filedescription.
Note that using this isn't wise for textfiles. (Y/N)

1.126 DayDream BBS - Archivers - ARC_DELETECOR

ARC_DELETECOR.

Delete file if it is corrupt. (Y/N)

1.127 DayDream BBS - Archivers - ARC_DISPLAY

ARC_DISPLAY...

Display testing output the the user. (Y/N). Requires FIFO:.

1.128 DayDream BBS - Archivers - ARC_SECVIEW

ARC_SECVIEW...

Minimum security level to view file.

1.129 DayDream BBS - File Transfer Protocols

File transfer protocols

~~~~~

DayDream uses external xpr-protocols for transferring files. Hydra protocol routines and configurations are hard coded, so you don't need to care about Hydra.

```
!PROTOCOLS.DAT
```

```
XPR_ID..... Z
```

```
XPR_NAME..... Z-Modem
```

```
XPR_EFFICIENCY 97
```

```
XPR_LIB..... xprzmodem.library
```

```
XPR_INIT..... TN,OR,B10,DN,KY,SN,RN
```

```
XPR_TYPE..... X
```

~

The next line specifies what to do next. If it's +, then there's protocol to compile. If it's ~, it's the end of the Protocols.DAT.

## 1.130 DayDream BBS - File Transfer Protocols - XPR\_ID

```
XPR_ID.....
```

Protocol ID for Alter userdata menu.

## 1.131 DayDream BBS - File Transfer Protocols - XPR\_NAME

```
XPR_NAME.....
```

Protocol name.

## 1.132 DayDream BBS - File Transfer Protocols - XPR\_EFFICIENCY

```
XPR_EFFICIENCY
```

Protocol efficiency in percents.

## 1.133 DayDream BBS - File Transfer Protocols - XPR\_LIB

```
XPR_LIB.....
```

XPR-library name. (Or -)

---

### 1.134 DayDream BBS - File Transfer Protocols - XPR\_INIT

XPR\_INIT.....

XPR init string. Refer to library's doc for more info.

### 1.135 DayDream BBS - File Transfer Protocols - XPR\_TYPE

XPR\_TYPE.....

Protocol type. X = XPR, S = Smodem, H = Hydra

### 1.136 DayDream BBS - Display Modes

Display Modes

~~~~~

!DISPLAY.DAT

```
DPL_ID..... 1
DPL_PATH..... Iso/
DPL_ANSI..... Y
DPL_INCONV.... N
DPL_OUTCONV... N
DPL_FILESCONV. N
DPL_STRIPANSI. N
DPL_TRYTXT.... N
DPL_TABLE..... 0
DPL_TABLE..... 0
DPL_FONT..... topaz.font
DPL_SIZE..... 8
DPL_STRINGS... 1
```

~

The next line specifies what to do next. If it's +, then there's displaymode to compile. If it's ~, it's the end of the DisplayModes.DAT.

1.137 DayDream BBS - Display Modes - DPL_ID

DPL_ID.....

Display mode number.

1.138 DayDream BBS - Display Modes - DPL_PATH

DPL_PATH.....

Path used by display mode to find menus and text files. If this is "Iso/", text stuff is searched from DayDream:Display/Iso/-directory.

1.139 DayDream BBS - Display Modes - DPL_ANSI

DPL_ANSI.....

If this is Y, ansi colors are enabled. If this is N, only 2 colors are used.

1.140 DayDream BBS - Display Modes - DPL_INCONV

DPL_INCONV....

Activate incoming conversion. If this is Y, incoming characters will be converted.

1.141 DayDream BBS - Display Modes - DPL_OUTCONV

DPL_OUTCONV...

Activate outgoing conversion. If this is Y, outgoing characters will be converted.

1.142 DayDream BBS - Display Modes - DPL_FILESCONV

DPL_FILESCONV.

Activate textfile conversion. If this is Y, outgoing textfiles will be converted.

1.143 DayDream BBS - Display Modes - DPL_STRIPANSI

DPL_STRIPANSI.

Strip ansicodes from textfiles.

1.144 DayDream BBS - Display Modes - DPL_TRYTXT

DPL_TRYTXT....

If GFX file doesn't found, try TXT.

1.145 DayDream BBS - Display Modes - DPL_TABLE1

DPL_TABLE1....

ID of ConversionTableXX.DAT used for incoming conversion.

1.146 DayDream BBS - Display Modes - DPL_TABLE2

DPL_TABLE2....

ID of ConversionTableXX.DAT used for outgoing conversion.

1.147 DayDream BBS - Display Modes - DPL_FONT

DPL_FONT.....

Local font when user is using this displaymode.

1.148 DayDream BBS - Display Modes - DPL_SIZE

DPL_SIZE.....

Size of font when user is using this displaymode.

1.149 DayDream BBS - Display Modes - DPL_STRINGS

DPL_STRINGS...

Number of strings to use.

1.150 DayDream BBS - Multinode Stuff

Multinode stuff

~~~~~

|                |            |
|----------------|------------|
| MNODE_NODE.... | 1          |
| MNODE_IODEV... | 1          |
| MNODE_MBAUD... | 1200       |
| MNODE_MNBAUD.. | 1200       |
| MNODE_FONT.... | topaz.font |
| MNODE_FSIZE... | 8          |
| MNODE_STYPE... | 1          |
| MNODE_SHANGHAI | N          |
| MNODE_DEFPTOF. | N          |
| MNODE_AUTOFRNT | Y          |

```
MNODE_AUTOOPEN  Y
MNODE_FIXRED..  N
MNODE_OWNDIR..  N
MNODE_TELNET..  N
MNODE_NOTIFY..  Y
MNODE_HIDEINAC  N
MNODE_HIDEWAIT  N
MNODE_HIDECALL  N
MNODE_NOPASSWD  N
MNODE_COMMAND.  run daydream nl <>NIL:
MNODE_PRIORITY  2
MNODE_TEMPDIR.  DayDream:Temporary/Node1/
MNODE_PENS....  141146105414
+
```

The next line specifies what to do next. If it's +, then there's more nodes to compile. If it's ~, it's the end of the Multinode.DAT.

### 1.151 DayDream BBS - Multinode Stuff - MNODE\_NODE

```
MNODE_NODE....
```

Node number of this node. DO NOT USE 0!

### 1.152 DayDream BBS - Multinode Stuff - MNODE\_IODEV

```
MNODE_IODEV...
```

Number of IO-Device to use.

### 1.153 DayDream BBS - Multinode Stuff - MNODE\_MBAUD

```
MNODE_MBAUD...
```

Minimum baud to allow logon.

### 1.154 DayDream BBS - Multinode Stuff - MNODE\_MNBAUD

```
MNODE_MNBAUD..
```

Minimum baud to allow new users to logon.

### 1.155 DayDream BBS - Multinode Stuff - MNODE\_FONT

MNODE\_FONT....

Font to use for this node.

### 1.156 DayDream BBS - Multinode Stuff - MNODE\_FSIZE

MNODE\_FSIZE...

Font size for this node.

### 1.157 DayDream BBS - Multinode Stuff - MNODE\_STYPE

MNODE\_STYPE...

Screen type for this node. 0 = Custom screen, 1 = Public Screen.  
If you want that Hydra will open it's windows to the DayDream  
screen, you had better use public screen.

### 1.158 DayDream BBS - Multinode Stuff - MNODE\_SHANGHAI

MNODE\_SHANGHAI

Shanghai windows.

### 1.159 DayDream BBS - Multinode Stuff - MNODE\_DEFPTOF

MNODE\_DEFPTOF.

Default public screen to front when visitor.

### 1.160 DayDream BBS - Multinode Stuff - MNODE\_AUTOFRNT

MNODE\_AUTOFRNT

Screen to front when connected.

### 1.161 DayDream BBS - Multinode Stuff - MNODE\_AUTOOPEN

MNODE\_AUTOOPEN

Open screen when node starts (Not yet available, screen will be  
opened always)

---

## 1.162 DayDream BBS - Multinode Stuff - MNODE\_FIXRED

MNODE\_FIXRED

Fix red/white "distortion". Ansicode 37m should display white and it does, if this is turned on. This is a little "bug" in Amiga's console.device and if you use this option, console output will be a bit slower. I advice you to turn this on only on local nodes.  
NOTE! Requires V39 OS.

## 1.163 DayDream BBS - Multinode Stuff - MNODE\_OWNDIR

MNODE\_OWNDIR..

Get Display stuff from DayDream:Node[number]/Display/ instead of DayDream:Display/.

## 1.164 DayDream BBS - Multinode Stuff - MNODE\_TELNET

MNODE\_TELNET..

If this is Y, DD expects that the node is TELNET node. BPS rate will be same as DTE and WHO shows that node is TELNET node.

## 1.165 DayDream BBS - Multinode Stuff - MNODE\_NOTIFY

MNODE\_NOTIFY..

If this is Y, other nodes will be informed on logins/logouts.

## 1.166 DayDream BBS - Multinode Stuff - MNODE\_HIDEINAC

If this is Y, node will be hidden when inactive.

## 1.167 DayDream BBS - Multinode Stuff - MNODE\_HIDEWAIT

If this is Y, node will be hidden when waiting for call.

## 1.168 DayDream BBS - Multinode Stuff - MNODE\_HIDECALL

If this is Y, node will be hidden when there's caller online.

---



## 1.169 DayDream BBS - Multinode Stuff - MNODE\_NOPASSWD

If this is Y, node will skip System/User passwords.

## 1.170 DayDream BBS - Multinode Stuff - MNODE\_COMMAND

MNODE\_COMMAND.

Command to run when node is inactive and clicked from server.

## 1.171 DayDream BBS - Multinode Stuff - MNODE\_PRIORITY

MNODE\_PRIORITY

Priority for node.

## 1.172 DayDream BBS - Multinode Stuff - MNODE\_TEMPDIR

MNODE\_TEMPDIR.

Path to place uploads while they are being received to the system.

## 1.173 DayDream BBS - Multinode Stuff - MNODE\_PENS

MNODE\_PENS....

This allows you to edit screen pens. You can adjust the pen that is used to draw borders etc in local DD screen.

Colors are like this:

```
0 = BLACK
1 = WHITE (RED if FIXRED is on)
2 = GREEN
3 = YELLOW
4 = BLUE
5 = MAGENTA
6 = CYAN
7 = RED (WHITE if FIXRED is on)
```

Screen looks very good if fixred is off and pens are 141146105414 or if fixred is on and pens are 747746705474.

Try some combinations to get the idea :)

---

## 1.174 DayDream BBS - I/O Devices

I/O Devices

~~~~~

!IO-DEVICES.DAT

```
IO_NUMBER..... 1
IO_UNIT..... 0
IO_BAUD..... 38400
IO_DEVICE..... serial.device
IO_PREINIT.... |ATZ|
IO_OFFHOOK.... AT &D0 M0 H1|
IO_ANSWER..... ATA|
IO_INIT..... AT M0 LOW2%C3\A3\N3\L1|
IO_AFTERCALL.. AT&D2 ATH0|
IO_OK..... OK
IO_RING..... RING
IO_NOCARRIER.. NO CARRIER
IO_CONNECT.... CONNECT
IO_SPEED1..... HST,14400
IO_SPEED2..... -
IO_SPEED3..... -
IO_SPEED4..... -
IO_SPEED5..... -
IO_SPEED6..... -
IO_SPEED7..... -
IO_SPEED8..... -
IO_SPEED9..... -
IO_SPEED10.... -
IO_ERRORCORR.. ARQ
IO_DELAY1..... 1
IO_DELAY2..... 2
IO_MODE..... S
```

~

The next line specifies what to do next. If it's +, then there's more IO-Devices to compile. If it's ~, it's the end of the IO-Devices.

1.175 DayDream BBS - I/O Devices - IO_NUMBER

IO_NUMBER.....

Number of I/O Device.

1.176 DayDream BBS - I/O Devices - IO_UNIT

IO_UNIT.....

Unit number.

1.177 DayDream BBS - I/O Devices - IO_BAUD

IO_BAUD.....

DTE Rate.

1.178 DayDream BBS - I/O Devices - IO_DEVICE

IO_DEVICE.....

Device-name to use.

1.179 DayDream BBS - I/O Devices - IO_PREINIT

IO_PREINIT....

Pre-init string. Will be sent before init string.

1.180 DayDream BBS - I/O Devices - IO_OFFHOOK

IO_OFFHOOK....

Off-hook string. ATH1| for example.

1.181 DayDream BBS - I/O Devices - IO_ANSWER

IO_ANSWER.....

Answer string when modem receives RING.

1.182 DayDream BBS - I/O Devices - IO_INIT

IO_INIT.....

Initialization string.

1.183 DayDream BBS - I/O Devices - IO_AFTERCALL

IO_AFTERCALL..

String to send to the modem after call. You MUST have a command that takes modem back onhook in this string (Eg. ATH0|).

1.184 DayDream BBS - I/O Devices - IO_OK

IO_OK.....

OK string.

1.185 DayDream BBS - I/O Devices - IO_RING

IO_RING.....

RING string.

1.186 DayDream BBS - I/O Devices - IO_NOCARRIER

IO_NOCARRIER..

NO CARRIER string.

1.187 DayDream BBS - I/O Devices - IO_CONNECT

IO_CONNECT....

Connect string.

1.188 DayDream BBS - I/O Devices - IO_SPEED1

IO_SPEED1.....

Speed identifier. If this is found from connection string, bps rate will be taken after ",".

1.189 DayDream BBS - I/O Devices - IO_SPEED2

IO_SPEED2.....

Same as IO_SPEED1.

1.190 DayDream BBS - I/O Devices - IO_SPEED3

Same as IO_SPEED1.

1.191 DayDream BBS - I/O Devices - IO_SPEED4

Same as IO_SPEED1.

1.192 DayDream BBS - I/O Devices - IO_SPEED5

Same as IO_SPEED1.

1.193 DayDream BBS - I/O Devices - IO_SPEED6

Same as IO_SPEED1.

1.194 DayDream BBS - I/O Devices - IO_SPEED7

Same as IO_SPEED1.

1.195 DayDream BBS - I/O Devices - IO_SPEED8

Same as IO_SPEED1.

1.196 DayDream BBS - I/O Devices - IO_SPEED9

Same as IO_SPEED1.

1.197 DayDream BBS - I/O Devices - IO_SPEED10

Same as IO_SPEED1.

1.198 DayDream BBS - I/O Devices - IO_ERRORCORR

IO_ERRORCORR..

Error correction keyword. If this is found from connection string, connection is error correcting.

1.199 DayDream BBS - I/O Devices - IO_DELAY1

IO_DELAY1.....

Delay between connection and first output (secs).

1.200 DayDream BBS - I/O Devices - IO_DELAY2

IO_DELAY2.....

Delay between modem init attempts.

1.201 DayDream BBS - I/O Devices - IO_MODE

IO_MODE.....

Mode. S=Shared, E=Exclusive. Note that you can't use
Hydra-protocol if mode is exclusive.

1.202 DayDream BBS - Security Levels

Security levels

~~~~~

!SECURITY.DAT

|                |                       |
|----------------|-----------------------|
| SEC_LEVEL..... | 1                     |
| SEC_FRATIO.... | 3                     |
| SEC_BRATIO.... | 3                     |
| SEC_PAGES..... | 3                     |
| SEC_TIMELIMIT. | 20                    |
| SEC_CONFACC1.. | XXXXXXXXXXXXXXXX----- |
| SEC_CONFACC2.. | -----                 |
| SECF_DOWNLOAD. | N                     |
| SECF_UPLOAD... | N                     |
| SECF_READMSGs. | N                     |
| SECF_ENTERMSG. | N                     |
| SECF_PAGE..... | N                     |
| SECF_COMMENT.. | N                     |
| SECF_BULLETINS | N                     |
| SECF_LISTFILES | N                     |
| SECF_NEWFILES. | N                     |
| SECF_ZIPPY.... | N                     |
| SECF_RUNDOOR.. | N                     |
| SECF_JOINCONF. | N                     |
| SECF_MSGAREAC. | N                     |
| SECF_CHANGEINF | N                     |
| SECF_RELOGIN.. | N                     |
| SECF_TAGED.... | N                     |
| SECF_VIEWSTATS | N                     |
| SECF_VIEWTIME. | N                     |

```
SECF_HYDRA.... N
SECF_EXPERT... N
SECF_EALL..... N
SECF_FIDOMSG.. N
SECF_PRIVMSG.. N
SECF_READALL.. N
SECF_USERED... N
SECF_VIEWLOG.. N
SECF_SYSOPDL.. N
SECF_USERLIST. N
SECF_DELETEANY N
SECF_SHELL.... N
SECF_WHO..... N
SECF_MOVE..... N
SECF_SFCONFS.. N
SECF_SMBASES.. N
SECF_NETMAIL.. N
SECF_OLM..... N
SECF_PRVATTACH N
SECF_PUBATTACH N
SENF_REALNAME. Y
SENF_HANDLE... Y
~
```

The next line specifies what to do next. If it's +, then there's more Sec levels to compile. If it's ~, it's the end of the Security.DAT.

### 1.203 DayDream BBS - Security Levels - SEC\_LEVEL

```
SEC_LEVEL.....
```

Security level that uses these settings.

### 1.204 DayDream BBS - Security Levels - SEC\_FRATIO

```
SEC_FRATIO.....
```

File ratio for this security level.

### 1.205 DayDream BBS - Security Levels - SEC\_BRATIO

```
SEC_BRATIO.....
```

Byte ratio for this security level.

### 1.206 DayDream BBS - Security Levels - SEC\_PAGES

SEC\_PAGES.....

Pages allowed.

### 1.207 DayDream BBS - Security Levels - SEC\_TIMELIMIT

SEC\_TIMELIMIT.

Time limit.

### 1.208 DayDream BBS - Security Levels - SEC\_CONFACC1

SEC\_CONFACC1..

Conference access for conferences 1-32. X means that user has access to the conference. If it's "-" then he/she is not allowed to join the conference.

### 1.209 DayDream BBS - Security Levels - SEC\_CONFACC2

SEC\_CONFACC2..

Conference access for conferences 33-64. X means that user has access to the conference. If it's "-" then he/she is not allowed to join the conference.

### 1.210 DayDream BBS - Security Levels - SECF\_DOWNLOAD

SECF\_DOWNLOAD.

Everything below this defines access to the specified thing in the BBS. If it's Y user has access to do it, if N then doesn't.

Download.

### 1.211 DayDream BBS - Security Levels - SECF\_UPLOAD

SECF\_UPLOAD...

Upload.

---



### 1.212 DayDream BBS - Security Levels - SECF\_READMSG

SECF\_READMSG.

Read messages.

### 1.213 DayDream BBS - Security Levels - SECF\_ENTERMSG

SECF\_ENTERMSG.

Enter message.

### 1.214 DayDream BBS - Security Levels - SECF\_PAGE

SECF\_PAGE.....

Page SysOp.

### 1.215 DayDream BBS - Security Levels - SECF\_COMMENT

SECF\_COMMENT..

Leave comment to the SysOp.

### 1.216 DayDream BBS - Security Levels - SECF\_BULLETINS

SECF\_BULLETINS

Read bulletins.

### 1.217 DayDream BBS - Security Levels - SECF\_LISTFILES

SECF\_LISTFILES

List files.

### 1.218 DayDream BBS - Security Levels - SECF\_NEWFILES

SECF\_NEWFILES.

New file scan.

---

### 1.219 DayDream BBS - Security Levels - SECF\_ZIPPY

SECF\_ZIPPY....

Zippy Search.

### 1.220 DayDream BBS - Security Levels - SECF\_RUNDOOR

SECF\_RUNDOOR..

Run an external program.

### 1.221 DayDream BBS - Security Levels - SECF\_JOINCONF

SECF\_JOINCONF.

Join conference.

### 1.222 DayDream BBS - Security Levels - SECF\_MSGAREAC

SECF\_MSGAREAC.

Change MSG-Area.

### 1.223 DayDream BBS - Security Levels - SECF\_CHANGEINF

SECF\_CHANGEINF

Alter his/her settings. (Like protocol, handle, phone number etc)

### 1.224 DayDream BBS - Security Levels - SECF\_RELOGIN

SECF\_RELOGIN..

Relogin.

### 1.225 DayDream BBS - Security Levels - SECF\_TAGED

SECF\_TAGED....

Tag Editor.

---

### 1.226 DayDream BBS - Security Levels - SECF\_VIEWSTATS

SECF\_VIEWSTATS

View his/her statistics.

### 1.227 DayDream BBS - Security Levels - SECF\_VIEWTIME

SECF\_VIEWTIME.

Check what time is it.

### 1.228 DayDream BBS - Security Levels - SECF\_HYDRA

SECF\_HYDRA....

Use Hydra-transfer protocol.

### 1.229 DayDream BBS - Security Levels - SECF\_EXPERT

SECF\_EXPERT...

Change to expert/novice mode.

### 1.230 DayDream BBS - Security Levels - SECF\_EALL

SECF\_EALL.....

Leave an Exclusive all-message.

### 1.231 DayDream BBS - Security Levels - SECF\_FIDOMSG

SECF\_FIDOMSG..

Leave an fido message.

### 1.232 DayDream BBS - Security Levels - SECF\_PRIVMSG

SECF\_PRIVMSG..

Send a private message.

---

### 1.233 DayDream BBS - Security Levels - SECF\_READALL

SECF\_READALL..

Read any message including Private messages addressed to someone else.

### 1.234 DayDream BBS - Security Levels - SECF\_USERED

SECF\_USERED...

Use user editor.

### 1.235 DayDream BBS - Security Levels - SECF\_VIEWLOG

SECF\_VIEWLOG..

View log file.

### 1.236 DayDream BBS - Security Levels - SECF\_SYSOPDL

SECF\_SYSOPDL..

SysOp download. Free download from any path.

### 1.237 DayDream BBS - Security Levels - SECF\_USERLIST

SECF\_USERLIST.

List users.

### 1.238 DayDream BBS - Security Levels - SECF\_DELETEANY

SECF\_DELETEANY

Delete any message.

### 1.239 DayDream BBS - Security Levels - SECF\_SHELL

SECF\_SHELL....

Remote shell.

---

### 1.240 DayDream BBS - Security Levels - SECF\_WHO

SECF\_WHO.....

View who's online.

### 1.241 DayDream BBS - Security Levels - SECF\_MOVE

SECF\_MOVE.....

Move file from area to another.

### 1.242 DayDream BBS - Security Levels - SECF\_SFCONFS

SECF\_SFCONFS..

Select conferences to be scanned with NS-command.

### 1.243 DayDream BBS - Security Levels - SECF\_SMBASES

SECF\_SMBASES..

Select message bases to be scanned with MS-command and to be grabbed to offline reading.

### 1.244 DayDream BBS - Security Levels - SECF\_NETMAIL

SECF\_NETMAIL..

Send netmail.

### 1.245 DayDream BBS - Security Levels - SECF\_OLM

SECF\_OLM.....

Send online line message to the user on the another node.

### 1.246 DayDream BBS - Security Levels - SECF\_PRIVATTACH

SECF\_PRIVATTACH

Allow user to attach files to the private messages he/she sends.

---

## 1.247 DayDream BBS - Security Levels - SECF\_PUBATTACH

SECF\_PUBATTACH

Allow user to attach files to the public messages he/she sends.

## 1.248 DayDream BBS - Security Levels - SECF\_REALNAME

SECF\_REALNAME

Allow user to change his/her real name.

## 1.249 DayDream BBS - Security Levels - SECF\_HANDLE

SECF\_HANDLE

Allow user to change his/her handle.

## 1.250 DayDream BBS - Schedule

Schedule  
~~~~~

```
!SCHEDULE.DAT
SCHE_HOUR..... 0
SCHE_LOGOFF...  N
SCHE_SYSPW....  -
SCHE_NEWUSERPW  -
+
```

The next line specifies what to do next. If it's +, then there's more hours to compile. If it's ~, it's the end of the Schedule.DAT. Note that you MUST have all 24 hours in this block!

1.251 DayDream BBS - Schedule - SCHE_HOUR

SCHE_HOUR.....

Hour. 0-23.

1.252 DayDream BBS - Schedule - SCHE_LOGOFF

SCHE_LOGOFF...

Force logoff at the end of this hour.

1.253 DayDream BBS - Schedule - SCHE_SYSPW

SCHE_SYSPW....

System password at this hour (- for none)

1.254 DayDream BBS - Schedule - SCHE_NEWUSERPW

SCHE_NEWUSERPW

New user password at this hour (- for none)

1.255 DayDream BBS - Server

Server

~~~~~

!SERVER.DAT

SRV\_X..... 0

SRV\_Y..... 75

SRV\_ICONIFY... N

SRV\_NAMES..... R

SRV\_LOCATION.. O

~

### 1.256 DayDream BBS - Server - SRV\_X

SRV\_X.....

Server window X-coordinate.

### 1.257 DayDream BBS - Server - SRV\_Y

SRV\_Y.....

Server window Y-coordinate.

### 1.258 DayDream BBS - Server - SRV\_ICONIFY

SRV\_ICONIFY...

Iconify server at start.

---

## 1.259 DayDream BBS - Server - SRV\_NAMES

SRV\_NAMES.....

Use real names or handles in the server's listview. R = Real names, H = Handles.

## 1.260 DayDream BBS - Server - SRV\_LOCATION

SRV\_LOCATION..

Use zipcode or organization in the server's listview. O = Organization, L = Zip code.

## 1.261 DayDream BBS - Included Utils and Doors

Included utils & doors

DayDream:Utils/  
DayDream:Doors/  
DayDream:Doors/RexxDir/

Back To Main

## 1.262 DayDream BBS - Included Utils and Doors - DayDream:Utils/

DayDream:Utils/

DDCallers  
DDTop  
DDWeekTop  
DreamConfig  
DreamToss  
FixBases  
ListClean

Using these utilities shouldn't cause any problems, when you take a look at the example-configfiles etc...

## 1.263 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDCallers

DDCallers

~~~~~

- Generates the list of last 10 callers and weekly statistics. Generates also a "minilog".

1.264 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDTop

DDTop

~~~~~

- Generates a list of top 10 uploaders, downloaders, callers, messagewriters and crapuploaders.  
WARNING! DO NOT USE THIS IF YOU HAVE LESS THAN THREE USERS!!! IT WILL CRASH THE MACHINE! IF YOU HAVE THREE OR MORE USERS, IT IS SAFE TO USE THIS!

## 1.265 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DDWeekTop

DDWeekTop

~~~~~

- Generates list of weekly top 10 uploaders and downloaders. Writes message to the BBS at the end of the week (Optional).
WARNING! DO NOT USE THIS IF YOU HAVE LESS THAN THREE USERS!!! IT WILL CRASH THE MACHINE! IF YOU HAVE THREE OR MORE USERS, IT IS SAFE TO USE THIS!

1.266 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DreamConfig

DreamConfig

~~~~~

- Compiles normal ascii-configfile for DayDream usage.

## 1.267 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - DreamToss

DreamToss

~~~~~

- FidoNet tosser for DayDream BBS.

1.268 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - FixBases

FixBases

~~~~~

- Fixes messagepointers in Conferences.DAT.

## 1.269 DayDream BBS - Included Utils and Doors - DayDream:Utils/ - ListClean

ListClean

~~~~~

- Marks deleted files to the filelist.
-

1.270 DayDream BBS - Included Utils and Doors - DayDream:Doors/

DayDream:Doors/

Faker
Grab
New
Rexx
Wall
WhoF

1.271 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Faker

Faker

~~~~~

- DreamFaker. Allows users to comment files. SysOp can give or take extra credits from the upload user has committed. SysOp can also return credits to the downloaders, delete file and even reward the first commenter. Very useful.

## 1.272 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Grab

Grab

~~~~~

- DreamMail. Allows user or SysOp to read messages offline. Supports 3 formats, ascii, WWF and BlueWave. WWF and BW support also replying.

1.273 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - New

New

~~~~~

- DreamNew. Allows user to read filelists backwards.

## 1.274 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Rexx

Rexx

~~~~~

- External ARexx-interface. Look at the supported commands below. Some example ARexx-doors are included in the distribution archive.

1.275 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - Wall

Wall

~~~~

- Stupid wall program which allows users to write their slogans so everybody can laugh at them :)

## 1.276 DayDream BBS - Included Utils and Doors - DayDream:Doors/ - WhoF

WhoF

~~~~

- Allows user to see who has uploaded and downloaded the file and when.

1.277 DayDream BBS - DayDream:Doors/RexxDir/

DayDream:Doors/RexxDir/

Some example ARexx-scripts are placed here, some of them are written by me, some of them are written by DarkElf.

1.278 DayDream BBS - ARexx

ARexx

General information
Requirements
Launching Door
Supported Commands
Debugging

Back To Main

1.279 DayDream BBS - ARexx - General Information

General information

~~~~~

ARexx-interpreter of DayDream BBS is an external program, DreamRexx. I'm planning to make it a part of the DayDream BBS but for the time being it remains as it is, external.

## 1.280 DayDream BBS - ARexx - Requirements

## Requirements

~~~~~

To use ARexx-doors you'll need DreamRexx (included in DD-Distribution), rx and rexxmast. Rexxmast must be running.

1.281 DayDream BBS - ARexx - Launching Door

Launching Door

~~~~~

Usage : Doors:Rexx [node] [script]

Example : Doors:Rexx %N Doors:Rexxdir/rexxscript.dd

## 1.282 DayDream BBS - ARexx - Supported Commands

### Supported Commands

TRANSMIT  
SHUTDOWN  
PROMPT  
NEWLINE  
SEND  
SENDFILE  
SENDANY  
GETUSER  
PUTUSER  
SYSTEMINFO  
GETCHAR  
QUERY  
QUERYN  
CONFINFO  
DOWNLOAD  
UPLOAD  
GETLRP  
SETLRP  
FLAGFILE  
HANGUP  
DDCOMMAND  
RESETIDLE  
RELOGIN  
JOINCONF  
CHANGMSGBASE  
INTCOMMAND  
FIFOEXECUTE  
WRITELOG

## 1.283 DayDream BBS - ARexx - Supported Commands - TRANSMIT

TRANSMIT "<string>" -

Sends a given string with newline appended. Returns nothing.

Example:

Transmit "Hello World!"

## 1.284 DayDream BBS - ARexx - Supported Commands - SHUTDOWN

SHUTDOWN -

End Arexx-script and close DreamRexx and doorport. Returns nothing.

Example:

Shutdown

## 1.285 DayDream BBS - ARexx - Supported Commands - PROMPT

PROMPT <max length> NORMAL|HIDE|FILE "[<prompt>]\[<default>]" -

Prompts the user to enter text with the given length as the maximum.

Three types of text input are currently supported:

NORMAL: Normal input

HIDE: Replace chars w/ \*

FILE: Don't allow characters illegal in filenames

If a prompt is supplied, it will be displayed before waiting for input. A default answer can be defined with 2 backslashes after prompt-text.

Example:

Prompt 30 NORMAL "Your Name:\Antti Häyrynen"

## 1.286 DayDream BBS - ARexx - Supported Commands - NEWLINE

NEWLINE -

Sends a newline code (a carriage return followed by line feed).

Takes no parameters and returns nothing

Example:

Newline

## 1.287 DayDream BBS - ARexx - Supported Commands - SEND

SEND <string>

Sends a given string. Nothing is added to the string. Returns nothing.

Example:

Send "Hello World!"

---

## 1.288 DayDream BBS - ARexx - Supported Commands - SENDFILE

SENDFILE <filename> -

Sends a given text file to the online user. File is searched from DayDream:Display/<displaymode>-directory and extension is added automatically.

Example:

```
Sendfile "goodbye"
```

## 1.289 DayDream BBS - ARexx - Supported Commands - SENDANY

SENDANY <filename> -

Sends a given text file to the online user. Full pathname must be given.

Example:

```
Sendany "s:user-startup"
```

## 1.290 DayDream BBS - ARexx - Supported Commands - GETUSER

GETUSER <number> -

Returns requested information about user.

- 1 = Real Name
  - 2 = Handle
  - 3 = Organization
  - 4 = Zip code and city
  - 5 = Voice Phone Number
  - 6 = Password
  - 7 = Screen length
  - 8 = Protocol
  - 9 = UL-signature
  - 10 = Bytes Uploaded
  - 11 = Bytes Downloaded
  - 12 = Files Uploaded
  - 13 = Files Downloaded
  - 14 = Public Messages Written
  - 15 = Private Messages Written
  - 16 = Calls made to the system
  - 17 = File ratio (UL:DL <> 1:VALUE)
  - 18 = Byte ratio (UL:DL <> 1:VALUE)
  - 19 = Computer Model
  - 20 = Free Bytes
  - 21 = Failed login attempts since last authorized login
  - 22 = Sec Level
  - 23 = Conference to auto-join during the next login
  - 24 = Conference access indicator (1-32)
  - 25 = Conference access indicator (33-64)
  - 26 = Daily time limit in minutes
  - 27 = Slot number
  - 28 = Time remaining
  - 29 = Free files
-

30 = Faked files  
31 = Faked bytes

Example:  
Getuser 2

## 1.291 DayDream BBS - ARexx - Supported Commands - PUTUSER

PUTUSER <number> <new value> -  
change requested user field

- 1 = Real Name
- 2 = Handle
- 3 = Organization
- 4 = Zip code and city
- 5 = Voice Phone Number
- 6 = Password
- 7 = Screen length
- 8 = Protocol
- 9 = UL-signature
- 10 = Bytes Uploaded
- 11 = Bytes Downloaded
- 12 = Files Uploaded
- 13 = Files Downloaded
- 14 = Public Messages Written
- 15 = Private Messages Written
- 16 = Calls made to the system
- 17 = File ratio (UL:DL <> 1:VALUE)
- 18 = Byte ratio (UL:DL <> 1:VALUE)
- 19 = Computer Model
- 20 = Free Bytes
- 21 = Failed login attempts since last authorized login
- 22 = Sec Level
- 23 = Conference to auto-join during the next login
- 24 = Conference access indicator (1-32)
- 25 = Conference access indicator (33-64)
- 26 = Daily time limit in minutes
- 27 = Slot number
- 28 = Time remaining
- 29 = Free files
- 30 = Faked files
- 31 = Faked bytes

Examples:  
Putuser 23 2  
Putuser 1 "Antti Häyrynen"  
Putuser 24 "XXXXXXXXXX"XX"

## 1.292 DayDream BBS - ARexx - Supported Commands - SYSTEMINFO

SYSTEMINFO <number> -  
Returns requested information about System.

- 1 = System Name

---

```
2 = SysOp
3 = Door parameters
4 = Current conference (Number)
5 = Current messagebase (Number)
6 = Connection type (REMOTE or LOCAL)
7 = Displaymode number
8 = Display type (ANSI/ASCII)
9 = SysOp available (Returns reason if not, else AVAILABLE or PERMANENTLY)
10 = BPS Rate
```

Example:

```
Systeminfo 6
```

### 1.293 DayDream BBS - ARexx - Supported Commands - GETCHAR

GETCHAR -

Get a single character from local console or remote terminal.

Doesn't send anything to modem or console!

Returns received character.

Note, ascii code 250 = Up, 251 = Down, 252 = Right and 253 = left!

Example:

```
Getchar
```

### 1.294 DayDream BBS - ARexx - Supported Commands - QUERY Y

QUERY Y [<prompt>] -

Prompt user for Yes or No response, Yes as default. If a prompt is supplied, it will be displayed before user input. Returns 'Y'

or 'N'.

Example:

```
Queryy 'Are Amigas great computers? (Yes/no) :'
```

### 1.295 DayDream BBS - ARexx - Supported Commands - QUERY N

QUERY N [<prompt>] -

Prompt user for Yes or No response, No as default. If a prompt is supplied, it will be displayed before user input. Returns 'Y'

or 'N'.

Example:

```
Queryn 'Are PCs good computers? (yes/No) :'
```

### 1.296 DayDream BBS - ARexx - Supported Commands - CONFINFO



CONFINFO <conf> <number> -  
Returns requested information about conference.  
1 = Conference name  
2 = Conference path  
3 = Number of fileareas in conference  
4 = Number of the filearea to place uploads in  
5 = Number of messagebases in conference  
6 = Number of the messagebase to place comments in

Example:  
Confinfo 2 1

## 1.297 DayDream BBS - ARexx - Supported Commands - DOWNLOAD

DOWNLOAD <file1> [<file2>] [<file3>] ... -  
Allows user to download files. Note that this will not add user's download bytes!

Example:  
Download 'S:User-startup' 'daydream:wares/data/directory.001'

## 1.298 DayDream BBS - ARexx - Supported Commands - UPLOAD

UPLOAD <path> -  
Allows user to upload files to specified path. Note that this will not add user's upload bytes!

Example:  
Upload 'daydream:temporary/node'node'/'

## 1.299 DayDream BBS - ARexx - Supported Commands - GETLRP

GETLRP <conf> <base> -  
Get lastread-pointer of the current user from the specified base.

Example:  
Getlrp 2 3

## 1.300 DayDream BBS - ARexx - Supported Commands - SETLRP

SETLRP <conf> <base> <lrp> -  
Set lastread-pointer of the current user in the specified base.

Example:  
Setlrp 2 3 14

---

### 1.301 DayDream BBS - ARexx - Supported Commands - FLAGFILE

FLAGFILE <conf> <file> -  
Flag file from specified conf for download. Wildcards allowed.

Example:  
Flagfile 2 '#?.dms'

### 1.302 DayDream BBS - ARexx - Supported Commands - HANGUP

HANGUP  
Disconnect user from BBS.

Example:  
Hangup

### 1.303 DayDream BBS - ARexx - Supported Commands - DDCOMMAND

DDCOMMAND <Command>  
This command makes it possible to run DayDream's main menu commands from arexx-doors (also doors)

Example:  
DDCommand "N S A"

### 1.304 DayDream BBS - ARexx - Supported Commands - RESETIDLE

RESETIDLE  
Resets idle counter.

Example:  
Resetidle

### 1.305 DayDream BBS - ARexx - Supported Commands - RELOGIN

RELOGIN  
Generates new connection.

Example:  
RELOGIN

### 1.306 DayDream BBS - ARexx - Supported Commands - JOINCONF

JOINCONF <conftojoin>

Joins conference using QUICK-mode, without displaying or loading any conference specific data. Before quitting door, join the conference user were when door was started.

Example:

JOINCONF 4

### 1.307 DayDream BBS - ARexx - Supported Commands - CHANGEMSGBASE

CHANGEMSGBASE <basetojoin>

Changes the current messagebase without any output.

Example:

CHANGEMSGBASE 5

### 1.308 DayDream BBS - ARexx - Supported Commands - INTCOMMAND

INTCOMMAND <Command>

This command makes it possible to run DayDream's main menu commands from arexx-doors (only internal, no doors)

Example:

IntCommand "N S A"

### 1.309 DayDream BBS - ARexx - Supported Commands - FIFOEXECUTE

FIFOEXECUTE <Command>

Executes amigados command and routes output to DD.

Some control codes in command are available:

%N = Node, %H = Handle, %R = Real name, %S = Screen length

Example:

FifoExecute "Lha a ram:sihi DayDream:#? -r"

### 1.310 DayDream BBS - ARexx - Supported Commands - WRITELOG

WRITELOG <String>

Writes specified text to the logfile.

Some control codes in command are available:

%A = ARQ Report

%B = Baudrate

%D = Date

%H = Handle

%L = Location

---

```
%N = Node
%O = Organization
%S = Security
%T = Time
%U = Real name
```

Example:

```
WRITELOG "%U aka %H proved that he's gay!"
```

### 1.311 DayDream BBS - ARexx - Debugging

Debugging

~~~~~

Because DreamRexx is a bit kludged program, use TCO for debugging purposes. TCO is included in the OS and can be found in rexxc:.

1.312 DayDream BBS - Developing Doors and Utils

Developing Doors & Utils

General Guidelines

DayDream BBS Server commands

Server ARexx commands

Information about Examine.DAT

Back To Main

1.313 DayDream BBS - Developing Doors and Utils - General Guidelines

General Guidelines

~~~~~

If you plan programming doors & utils for DayDream BBS, you must be familiar with some rules.

- 1) If your door or util has a configfile, it is highly recommended, that it is looked from the path that is given in ENV:-variable DreamUtils.
- 2) If your door uses Data-Structures, please get structuresizes from DayDream:Data/Version.DAT. This will make sure that your program will work with the future versions of DayDream BBS.

Documentation for DDDP-Commands and format of data-structures is included in DayDream:Structures/-directory. Check it out!

If your program needs doorcommand(s) that DD doesn't support, just e-mail me, and it might be available in the next release!

I will do my best to get the development of the DayDream doors&utils working!

### 1.314 DayDream BBS - Developing Doors and Utils - DayDream BBS Server Commands

DayDream BBS Server commands

~~~~~

DayDream BBS server currently supports only a few commands that can be accessed via execmessages. The commands, that are not listed, are only for private use of DayDream BBS.

Portname for DayDream BBS server is "DD-Server".

Format of Servermessage is as follows. Note that offset 0 is the end of standard exec-message header.

OFFSET	TYPE	LENGTH	DESCRIPTION	FLAGS
0000	UBYTE	01	NODENUMBER OR -1 IF EXTERNAL PROGRAM	(-)
0001	UBYTE	01	FREE SPACE	(-)
0002	UWORD	02	MESSAGE CODE	(-)
0004	LONG WORD	04	COMMAND DATA FIELD #1	(-)
0008	LONG WORD	04	COMMAND DATA FIELD #2	(-)
0012	LONG WORD	04	COMMAND DATA FIELD #3	(-)
0016	LONG WORD	04	COMMAND DATA FIELD #4	(-)
0020	STRING	80	ROOM FOR MISCELLANEOUS VARIABLES	(-)
0100	-- END --	00	END OF SERVER MESSAGE	(-)

MESSAGE CODE=3 -> Save Conferences.DAT

~~~~~

This function saves current Conferences.DAT in memory. Use with care.

Input:

Nothing

Output:

Nothing

Other:

Server deletes message and doesn't reply it, so DO NOT WaitPort()!

MESSAGE CODE=10 -> DosRead

~~~~~

This function is standard dos read-command. It opens file and does seeking operations, closes it etc. Useful if you want to access stuff that other nodes can access at the time, so there won't be any conflicts.

Input:

DATA1 = Pointer to the filename to read
DATA2 = Pointer to the destination buffer

DATA3 = Number of bytes to read
 DATA4 = Offset to start reading

Outputs:

DATA1 = Number of bytes read. If -1, error occurred.

MESSAGE CODE=11 -> DosAppend
 ~~~~~

With this function, you can safely add stuff to the filelists etc. If file is not found, it will be created. This function seeks to the end of file and writes the specified data.

Input:

DATA1 = Pointer to the filename  
 DATA2 = Pointer to the source buffer  
 DATA3 = Number of bytes to write

Outputs:

DATA1 = Number of bytes written. If -1, error occurred.

MESSAGE CODE=13 -> SysOp Available  
 ~~~~~

Input:

-none-

Outputs:

DATA1 = Pointer to the reason why SysOp isn't available or 0 if SysOp is available.

MESSAGE CODE=100 -> Add msgpointers
 ~~~~~

This function adds highest msg pointer of the specified messagebase, so you can add message to the messagebase.

Inputs:

DATA1 = Conference number  
 DATA2 = Base number

Outputs:

This function deletes the message automatically, you mustn't wait for the message to be replied!!!

MESSAGE CODE=101 -> Inquire pointers to datafiles  
 ~~~~~

This function helps you to get datafiles directly from server. This saves memory from system and allows you to modify Conferences.DAT etc. You can

also check out what's happening in the BBS. You may modify datafiles, but be careful when modifying Conferences.DAT, because modifications to Conferences.DAT will be saved to the disk!

Inputs:

-Nothing-

Outputs:

OFFSET+MN_SIZE	FILE	VALUE AT THE END OF DATA
0000	Conferences.DAT	255
0004	Protocols.DAT	255
0008	Archivers.DAT	255
0012	DayDream.DAT	-
0016	Display.DAT	255
0020	Access.DAT	0
0024	ExternalCommands.DAT	255
0028	Multinode.DAT	0
0032	Schedule.DAT	255
0036	Security.DAT	0
0040	Node Structures (Not a file)	-

ALLOCATE MN_SIZE+80 BYTES OF MEMORY FOR THE MESSAGE!!!

I will add lot of commands to the server soon! If you want something, just e-mail me!

1.315 DayDream BBS - Developing Doors and Utils - Server ARexx Commands

Portname is SERVER-REXX, and it supports following commands:

```
SHUTDOWN
ICONIFY
CLOSENODE
OPENSSCREEN
CLOSESCREEN
KICKUSER
ENTERCHAT
CHATON
CHATOFF
```

Example script

1.316 SHUTDOWN

SHUTDOWN - Close DD Server. Works only if all nodes have been closed too.

example:

SHUTDOWN

1.317 ICONIFY

ICONIFY - Iconifies the server.

example:
ICONIFY

1.318 CLOSENODE

CLOSENODE [node] - Close the specified node. Closes even if there's user online.

example:
CLOSENODE 1

1.319 OPENSREEN

OPENSREEN [node] - Open the screen of the specified node.

example:
OPENSREEN 1

1.320 CLOSESCREEN

CLOSESCREEN [node] - Close the screen of the specified node.

example:
CLOSESCREEN 1

1.321 KICKUSER

KICKUSER [node] - Disconnect user from the specified node.

example:
KICKUSER 1

1.322 ENTERCHAT

ENTERCHAT [node] - Activate chat mode on the specified node.

example:
ENTERCHAT 1

1.323 CHATON

CHATON - Turn SysOp available flag on.

example:
CHATON

1.324 CHATOFF

CHATOFF [reason] - Turn off SysOp available flag. Requires a reason.

example:
CHATOFF "Shut up, I'm hunting wabbits.."

1.325 Server ARexx Example

```
/* Testing Server ARexx... */

Options results
servid="SERVER-REXX"
address value servid

iconify
chatoff "I'm not available right now, sorry."

exit
```

1.326 Developer information about Examine.DAT/FileCheck.DAT

Filename is passed to door in DD's commandline parameters. Do NOT trash it, since there can be more doors in Examine.DAT to be launched. The current directory is temporary directory where uploads are placed, so you don't need to do any CurrentDir()s or generate path to find the file.

Here's a VERY simple example written in ARexx:

```
-----cut-----
/* Introducing Examine.DAT */

parse arg node
Options results
nodeid="DREAMREXX"node
address value nodeid

systeminfo 3
file = result
transmit "[36mThank you for uploading ?[0m"file"?[36m!"
if file = "RYLDD110.LHA" then call deleteit
```

```

call awaywego
deleteit:
address command "delete "file
transmit '[0mOnly nerds upload such crap!'

awaywego:
transmit '[0m'
shutdown
exit
-----cut-----

```

1.327 DayDream BBS - How Does It Work

How does it work

General Info
 Login Procedure
 User Commands
 SysOp Commands

Back To Main

1.328 DayDream BBS - How Does It Work - General Info

General info

~~~~~

This chapter explains how this thing works. Description of the commands is kinda brief, but you should be able to customize your system etc after reading this chapter carefully.

## 1.329 DayDream BBS - How Does It Work - Login Procedure

Login procedure

~~~~~

- 1) When ring is received from modem, or local connection is initiated, first thing DayDream does is to display to user that he/she has entered to the BBS running DayDream BBS and tells node number and bps-rate.

Serial number is displayed, if the system is running registered DayDream BBS. If system is running unregistered version of DayDream it's informed to the user and DD does some gambling :). If user has bad luck he will be hung up on.

- 2) Then DayDream displays file "DayDream:Display/DisplayModeList.TXT" which contains list of available display modes. Then user will be prompted to select the displaymode (default is 1). If user requests help, "DayDream:Display/DisplayModeHelp.TXT" is shown.

- 3) If SysOp has specified system password, it will be asked now. File "SystemPassword.TXT/GFX" will be shown from the specified directory
-

(specified in Display.DAT)

- 4) DD Displays file DayDream:Display/[mode]/Banner.TXT/GFX.
- 5) Now account name will be asked. User account name is required or NEW to create a new account, CHAT to chat with SysOp of LOGOFF to disconnect from the BBS.
- 6) Password of the user is asked now. User has 3 attempts and if something went wrong, user will be kicked out and DayDream:Display/[mode]/PassWordFailure.TXT/GFX will be shown.
- 7) Next DayDream checks that user's account has been filled in correctly. Some fields may be missing, if account has been converted from another BBS software. Information will be queried until it's filled correctly.
- 8) File DayDream:Display[mode]/Welcome.TXT/GFX is shown.
- 9) Checks if user has any uploads without descriptions. If so, asks user to describe them.
- 10) Checks if user has unfinished upload. If so, allows user to continue uploading it.
- 11) Selected conferences will be scanned for new files. (If user wants that)
- 12) Selected messagebases will be scanned for new mail addressed to the user. (If user wants that)
- 13) User joins the conference where he/she was last time he/she disconnected.

1.330 DayDream BBS - How Does It Work - General Info - New

NEW - Create new account

~~~~~

- 1) DayDream checks if system requires password to enter. If so, DayDream:Display/[mode]/NewUserPassword.TXT/GFX is displayed and the password is asked from the user.
  - 2) File DayDream:Display/[mode]/NewUser.TXT/GFX is displayed and user is queried if he/she is absolutely certain that he/she want to create account.
  - 3) Next the BBS will ask things such as real name etc from the user. Textfile will be shown from DayDream:Display/[mode]/ if it's exist before each question (see above for filenames).
  - 4) New user questionnaire will be asked now (described earlier on)
  - 5) When account is created, user may change the data (equal to A-command) he entered.
-

6) DD jumps to the login procedure (step 5)

### 1.331 DayDream BBS - How Does It Work - General Info - Chat

CHAT

~~~~

Just pages SysOp for chatting...

1.332 DayDream BBS - How Does It Work - General Info - Logoff

LOGOFF

~~~~~

Disconnects the user from BBS.

### 1.333 DayDream BBS - How Does It Work - User Commands

User commands

A	- Alter userdata
B	- Bulletins
C	- Comment to SysOp
D	- Download
E	- Enter message
F	- List files
G	- Logoff
J	- Join Conference
L	- Local time
M	- Change msg-base
N	- New file scan
O	- Operator Page
R	- Read messages
S	- User Statistics
T	- Tag Editor
U	- Upload
V	- View file
X	- Expertmode toggle
Z	- Zippy Search
<	- Previous Conference
>	- Next Conference
?	- Show mainmenu
l	- Kewl little game :)
<<	- Previous Messagebase
>>	- Next Messagebase
GR	- Global new message read
MS	- Mailscan
NS	- Global new file scan
VER	- Displays version information
OLM	- Send line message to the another node
RELOGIN	- Relogin
SF	- Select fileareas

SM	- Select Messagebases
UD	- Bidirectional Hydra-transfer
USERLIST	- List of users
MODE	- Change displaymode
WHO	- Who's online
CLS	- Clear Screen

### 1.334 DayDream BBS - How Does It Work - User Commands - Alter Userdata

[ A ] - Alter userdata

~~~~~

User can change his personal information such as phone number, sent-by line, password etc.. Some switches can be altered behind this command too.

1.335 DayDream BBS - How Does It Work - User Commands - Bulletins

[B] - Bulletins

~~~~~

Every conference can contain it's own bulletins. Bulletins will be searched from [Conference]/Bulletins/ directory and the naming system is as follows:

BulletinMenu.TXT/GFX - Menu of available bulletins

Bulletin.XXX.TXT/GFX - Textfile containing the information.

User can toggle between view and download mode.

If conference doesn't contain any bulletins, they will be snooped from DayDream:Bulletins/.

### 1.336 DayDream BBS - How Does It Work - User Commands - Comment

[ C ] - Comment

~~~~~

User can leave comment to system administration using this command.

1.337 DayDream BBS - How Does It Work - User Commands - Download

[D] - Download

~~~~~

Performs file downloading using XPR-Protocols.

1) Shows Download.TXT/GFX from Conferences displaydirectory or from DayDream:Display/[Mode]/.

- 2) Asks for files to download.
- 3) Shows list of files to download, their sizes and estimated transfer time.
- 4) Asks if user wants to start transfer, disconnect after transfer, edit list of the files to download or abort.
- 5) Performs transfer using XPR-Library.

### 1.338 DayDream BBS - How Does It Work - User Commands - Enter Message

[ E ] - Enter Message

~~~~~

Allows user to write public/private/echo/netmail messages.

- 1) Asks for receiver. If message is public or private, receiver will be looked from userbase. If user presses just enter, message will be addressed to everyone. If receiver is EALL, message will be shown to everyone at the mailsan.
- 2) Asks for subject. If user just enters return, message will be aborted.
- 3) If message base allows both public and private messages, DD will ask if user wants to send it as a private message.
- 4) User enters internal line-editor. It's very easy to use, but still quite efficient. When user types \$ in empty line, user will enter commandmode. Supported commands:
 - A)bort - Aborts message entry.
 - C)ommands - Shows DayDream:Display/[mode]/LineEditorCommands.TXT/GFX
 - D)eleate - Allows user to delete lines from the message.
 - E)dit - Allows user to edit line in message.
 - F)ile attach- Allows user to attach file to the message.
 - I)nsert - Allows user to insert line anywhere in the message.
 - P)assword - Equips message with password.
 - Q)uote - Quotes message (works only in reply mode)
 - R)esume - Back to the message-editor.
 - S)ave - Saves message.

1.339 DayDream BBS - How Does It Work - User Commands - List Files

[F] - List files

~~~~~

Lists files available for downloading.

- 1) If number of filedirectories is 0 in the conference, drops user back to the main prompt.
- 2) Displays the file FileCatalogs.TXT/GFX from the displaydirectory of the conference or from DayDream:Display/[mode]/.
- 3) Asks areas to scan or A)ll or U)pload.
- 4) Shows filelists from the specified areas. In more prompt there are following options available:
  - Y)es - Shows more files
  - N)o - Quits filelisting
  - F)lag or T)ag - Adds file for download request.
  - C)ontinuous - Non-stop listing, no more more-prompts.

### 1.340 DayDream BBS - How Does It Work - User Commands - Disconnect

[ G ] - Goodbye (Disconnect)

~~~~~

This command disconnects user from the system.

- 1) Asks if user is absolutely certain about leaving the BBS.
- 2) Displays the file DayDream:Display/[Mode]/GoodBye.TXT/GFX.
- 3) Drops the carrier.
- 4) Checks if there are any uploads to be checked. If so, checks them.
- 5) Executes the file "DayDream:Batch/Logoff[node].BAT". If this is a shell-script, make sure it's equipped with "s"-flag.

Note that dropping carrier anywhere in the BBS will bring user to phase 3 of this command.

1.341 DayDream BBS - How Does It Work - User Commands - Join Conference

[J] - Join conference

~~~~~

This command allows user to change to the another conference from the current conference.

- 1) Shows the file DayDream:Display/[mode]/Conferences.TXT/GFX.
-

- 2) Prompts for the conference user wishes to join. User must have access to the conference he tries to join.
- 3) Shows [Conference]/Display/[Mode]/JoinConference.TXT/GFX if exists.

### 1.342 DayDream BBS - How Does It Work - User Commands - Local Time

```
[ L ] - Local time
~~~~~
Just shows what time is it...
```

### 1.343 DayDream BBS - How Does It Work - User Commands - Change Message Base

```
[M] - Change message base
~~~~~
This command allows user to change to another message base.
```

- 1) If the conference doesn't have more than 1 message bases, informs user that this command has no effect and quits.
- 2) Shows file [Conf]/Display/[Mode]/MessageBases.TXT/GFX.
- 3) Prompts for the number of message base user wants to enter.

### 1.344 DayDream BBS - How Does It Work - User Commands - New File Scan

```
[ N ] - New file scan
~~~~~
Scan conference for new files. Uses the same routine for showing files as
F-Command (File list).
```

- 1) If number of filedirectories is 0 in the conference, drops user back to the main prompt.
- 2) Asks date to start scanning from.
- 3) Asks for filecatalogs to be scanned for new files:  
A=All, L=List or H=Help.  
If user requested for help, DayDream:Display/[mode]/CatalogHelp.TXT/GFX will be displayed.
- 4) Scans new files from requested directories.

NOTE! To scan new files in current conference, just type N S A in main prompt.

---



## 1.345 DayDream BBS - How Does It Work - User Commands - Operator Page

[ O ] - Operator Page

~~~~~

Pages sysop for chatting.

- 1) Checks if SysOp is available. If there's no chat message enabled in pulldownmenus and DayDream:Display/PermanentlyAway.TXT doesn't exist, step 2 will take place. Otherwise chat message or PermanentlyAway.TXT will be displayed.
- 2) If DayDream:Display/[Mode]/BeforeChat.TXT/GFX exist, DD displays it.
- 3) If SysOp has enabled "Ask Reason"-flag in configuration, user will be prompted for reason.
- 4) Pages SysOp with annoying beep or screen flashes if DD cannot allocate audio channels. Page can be aborted using CTRL-C. SysOp can enter chat mode by pressing CTRL-C.
- 5) If page wasn't canceled or SysOp didn't enter chat mode, window will be opened to the screen informing that user has paged and telling the reason for chat.

## 1.346 DayDream BBS - How Does It Work - User Commands - Read Messages

[ R ] - Read Messages

~~~~~

This command allows user to read messages. It also allows user to reply to a certain message.

Shows the read prompt, looks like this:

Message Read Command: <Enter> Next, <C>ommands (5/6;-):

^ ^ ^

| | +- Reading direction

| +--- Highest message

+----- Current message

Available commands:

A)gain - Redisplay message

D)etele - Delete current message

R)eply - Reply to the current message. Same as Enter Message - command, but the receiver of the message is the author of the message to be replied and when entering message editor, lines to be quoted will be asked.

Q)uit - Quit reading messages

+ - Set reading direction forward (-->)

- - Set reading direction backward (<--)
- <Number> - Read specified message (if available)
- <CR> - Read next message

### 1.347 DayDream BBS - How Does It Work - User Commands - User Statistics

[ S ] - User statistics

~~~~~

Shows information about user, eg. his/her name, organization, upload bytes etc.

### 1.348 DayDream BBS - How Does It Work - User Commands - Tag Editor

[ T ] - Tag editor

~~~~~

Allows user to edit his/her download batch. User can add/remove files to/from download batch using this command. This also displays the total size of files in the batch and an estimated transfer time.

### 1.349 DayDream BBS - How Does It Work - User Commands - Upload

[ U ] - Upload

~~~~~

Allows user to send files to the system using XPR-Protocol.

- 1) If number of filedirectories is 0 in the conference, drops user back to the main prompt and informs that uploads are not allowed in the current conference.
- 2) Displays Upload.GFX/TXT from the display directory of the confernce or from DayDream:Display/[Mode]/. Useful for telling users what they should and should not upload.
- 3) Checks free space on hard disk. If there's not enough free space, drops user back to the main prompt.
- 4) Asks if user wants to Proceed, Disconnect after transfer or Abort. If user decides to disconnect after transfer, archives should contain FILE\_ID.DIZ. Otherwise descriptions will be asked next time the user calls.
- 5) Cleans up the DayDream:Temporary/Node[Node]/ directory. Uploads will be placed here.
- 6) Remote mode (=normal user upload):  
Starts XPR-Transfer.  
  
Local mode (=sysop upload from local connection):

Asks SysOp to copy files to be uploaded to directory called DayDream:Temporary/Node[Node]/. Press return when all the files are copied.

- 7) Checks if there are any files in temporary directory to be processed, and if there's not, exits.
- 8) Checks if filename is longer than 12 characters. If it is, asks user to rename it.
- 9) Executes doors listed in [CONF]/Data/FileCheck.DAT. If file doesn't exist after this procedure, jumps to step 7.
- 10) Scans BBS for duplicates. If file already exists, it will be deleted.
- 11) Tests archive integrity. If offline checking is enabled, this will be done after the user has disconnected.
- 12) Checks if archive contains file\_id.diz. If it does, then DD displays it and asks if user wants to save it, edit it, discard it, save upload to SysOp's private directory or turn autosave mode on. In autosave mode, file\_id.diz will be used automatically from the next archives.  
  
If archive doesn't contain file\_id.diz, description will be asked. Description may contain up to 13 lines.
- 13) Executes doors listed in [CONF]/Data/Examine.DAT. If file doesn't exist after this procedure, jumps to step 7.
- 14) Saves file and adds credits to the user.
- 15) Jump to step 7.

### 1.350 DayDream BBS - How Does It Work - User Commands - View file

[ V ] - View file

~~~~~

Allows user to view archive contests. Executes VIEW-command and displays output to the user.

### 1.351 DayDream BBS - How Does It Work - User Commands - Expert Mode Toggle

[ X ] - Expert mode toggle

~~~~~

Turns expert mode on/off. In expertmode, menu will be shown only if user requests it with ?-command.

### 1.352 DayDream BBS - How Does It Work - User Commands - Zippy Search

---

[ Z ] - Zippy Search

~~~~~

Scans file catalogs for a match for a specified string. When match is found, it will display the whole entry to the user.

### 1.353 DayDream BBS - How Does It Work - User Commands - Previous Conference

[ < ] - Previous Conference

~~~~~

Joins previous conference user has access to. Very fast method to move around the BBS.

### 1.354 DayDream BBS - How Does It Work - User Commands - Next Conference

[ > ] - Next Conference

~~~~~

Joins next conference user has access to. Very fast method to move around the BBS.

### 1.355 DayDream BBS - How Does It Work - User Commands - Show Mainmenu

[ ? ] - Show Mainmenu

~~~~~

Shows the mainmenu.

### 1.356 DayDream BBS - How Does It Work - User Commands - Kewl Little Game

[ 1 ] - Kewl Little Game

~~~~~

Nice game.

### 1.357 DayDream BBS - How Does It Work - User Commands - Prevoius Message Base

[ << ] - Previous message base

~~~~~

Joins previous message base in the current conference.

### 1.358 DayDream BBS - How Does It Work - User Commands - Next Message Base

[ >> ] - Next message base

~~~~~

Joins next message base in the current conference.

---

### 1.359 DayDream BBS - How Does It Work - User Commands - Global read

[ GR ] - Global read

~~~~~

Read new messages globally from selected message bases. Works like R-command.

### 1.360 DayDream BBS - How Does It Work - User Commands - Mail Scan

[ MS ] - Mail scan

~~~~~

Scans selected message bases for new mail addressed to the user. When new message is found, it will be shown to the user.

### 1.361 DayDream BBS - How Does It Work - User Commands - New Files Scan

[ NS ] - New files scan

~~~~~

Scans selected conferences for new files. Uses N-Command.

### 1.362 DayDream BBS - How Does It Work - User Commands - Version Information

[ VER ] - Version information

~~~~~

Shows some version specific information, serial number and the name of the registered user.

### 1.363 DayDream BBS - How Does It Work - User Commands - Online Message

[ OLM ] - Online message

~~~~~

Send line of text to the user on the another node. If user on the another node has disabled OLMs, then message won't be sent.

### 1.364 DayDream BBS - How Does It Work - User Commands - Relogin

[ RELOGIN ] - Relogin

~~~~~

This command allows user to relogin to the system without calling again.

---

### 1.365 DayDream BBS - How Does It Work - User Commands - Select File Conferences

[ SF ] - Select file conferences

~~~~~

This command allows user to select conferences he/she wants to be scanned in the new files scan during logon or when he/she enters the NS-command.

### 1.366 DayDream BBS - How Does It Work - User Commands - Select Messagebases

[ SM ] - Select messagebases

~~~~~

This command allows user to select messagebases he/she wants to be scanned in the new mail scan and to be grabbed for offline reading.

### 1.367 DayDream BBS - How Does It Work - User Commands - Bidir. Hydratransfer

[ UD ] - Bidirectional Hydratransfer

~~~~~

This command performs file transfer using bidirectional Hydra-protocol.

- 1) Shows HydraTransfer.TXT/GFX from Conferences displaydirectory or from DayDream:Display/[Mode]/.
- 2) Asks for files to be downloaded.
- 3) Shows list of files to be downloaded, their sizes and estimated transfer time.
- 4) Asks if user wants to start transfer, disconnect after transfer, edit download request or abort.
- 5) Performs the file transfer.
- 6) Jumps to the phase 7 of Upload-command to process possible incoming uploads.

### 1.368 DayDream BBS - How Does It Work - User Commands - List of Users

[ USERLIST ] - List of users

~~~~~

Lists users that has access to the system.

### 1.369 DayDream BBS - How Does It Work - User Commands - Change Displaymode

[ MODE ] - Change displaymode

~~~~~

Exactly the same as the first question after handshaking.

### 1.370 DayDream BBS - How Does It Work - User Commands - Who's Online

[ WHO ] - Who's online

~~~~~

Displays users that are using the system on other nodes and what they are doing.

### 1.371 DayDream BBS - How Does It Work - User Commands - Clear Screen

[ CLS ] - Clear Screen

~~~~~

Clears the display.

### 1.372 DayDream BBS - How Does It Work - SysOp Commands

SysOp commands

|        |                                  |
|--------|----------------------------------|
| USERED | - Online UserEditor              |
| MOVE   | - Move file from area to another |
| SD     | - SysOp download                 |
| LOG    | - View logfile                   |
| SHELL  | - Remote Shell                   |
| \$     | - Test door                      |

### 1.373 DayDream BBS - How Does It Work - SysOp Commands - UserEditor

[ USERED ] - Usereditor

~~~~~

Enters the user editor. Ansimode is required to use this.

1) Shows menu with the following commands:

C)urrent user	- Edit current user
S)earch from userbase	- Searches user from the userbase, wildcards allowed.
N)ew accounts scan	- Scans userbase for new accounts.
Q)uit	- Quit usereditor.

2) When user to edit is selected, DD will show this kind of a screen:

```
----- cut -----
A) Name : Antti Häyrynen L) Security : 255
```

```

B) Handle : Hydra
C) Organization : Windowskiihdytin
D) Zip & City : 90810 Kiviniemi
E) Voice Phone : -----
F) PassWord : NOTFORYOU!
G) CPU Model : 020

H) Uploaded : 7097404 | 32
 Downloaded : 0 | 0

N) Time Left : 289
Q) Calls Made : 73
R) Protocol : Z
S) Auto-Join : 6
T) Free Bytes : 0
U) PW Failures : 0
V) Scr Length : 30
W) Acc. Status : Active

```

X) Access Presets

Z) Edit Security

I) UL Signature : -Hydra

Select field to be altered (SAve, ABort or VIew):

----- cut -----

Now sysop may alter any of these fields. With X-command he can select pre-defined accesslevels which is the fastest method to edit the access of the user.

Using Z-command screen like this will be shown:

----- cut -----

```

1) Security Level : 255 2) Daily Time : 300
3) Byte Ratio : 0 4) File Ratio : 0
5) Conference Access (01-32): XXXXXXXX_____
6) Conference Access (33-64): _____

7) Download : On 8) Upload : On 9) Read Message : On
A) Enter Message : On B) Page SysOp : On C) Comment : On
D) Bulletins : On E) List Files : On F) New Files : On
G) Zippy Search : On H) Run Door : On I) Join Conference: On
J) Change Msg Area: On K) Change Info : On L) Relogin : On
M) Tag Editor : On N) User Stats : On O) View Time : On
P) Hydra Transfer : On Q) Expert Mode : On R) Eall-Message : On
S) Fidomessage : On T) Public Message: On U) Privateread : On
V) User Editor : On W) View Log : On X) SysOp DL : On
Y) Userlist : On Z) Delete Any Msg: On !) Remote Shell : On
") Who is online : On £) Move file : On $) Select FConfs : On
%) Select Bases : On &) Send Netmail : On

```

Select field to be altered (SAve, ABort or VIew):

----- cut -----

SysOp is able to edit these fields, too. It's not advisable to edit access information from here, because when new securityflags appear, they will be always set to OFF if user has his/her own custom security information.

### 1.374 DayDream BBS - How Does It Work - SysOp Commands - Move File(s)



[ MOVE ] - Move file(s)

~~~~~

This command allows SysOp to move files from conference/catalog to the another. Wildcards are supported. Should be easy to figure out.

### 1.375 DayDream BBS - How Does It Work - SysOp Commands - SysOp Download

[ SD ] - SysOp download

~~~~~

This command allows SysOp to download any file from the harddisk. File won't be marked to the download bytes/files.

### 1.376 DayDream BBS - How Does It Work - SysOp Commands - View Logfile

[ LOG ] - View logfile

~~~~~

This command allows SysOp to view logfile of the specified node.

### 1.377 DayDream BBS - How Does It Work - SysOp Commands - Remote Shell

[ SHELL ] - Remote shell

~~~~~

This command allows SysOp to enter to the remote shell. If normal user gets access to this command, he can de serious damage to your harddisk. !! He could even format it !!

### 1.378 DayDream BBS - How Does It Work - SysOp Commands - Test Door

[ \$ ] - Test door

~~~~~

This command allows SysOp to test a door program before installing it.

### 1.379 DayDream BBS - Pulldown Menus

Pulldown Menus

DayDream BBS menu

Display

Online

Back To Main

---

### 1.380 DayDream BBS - Pulldown Menus - DayDream BBS Menu

DayDream BBS Menu

About (Ramiga+A)

Quit (Ramiga+Q)

### 1.381 DayDream BBS - Pulldown Menus - DayDream BBS Menu - About

About (Ramiga+A)

~~~~~

Shows information about DayDream BBS.

### 1.382 DayDream BBS - Pulldown Menus - DayDream BBS Menu - Quit

Quit (Ramiga+Q)

~~~~~

Shutdown node. Requester with three gadgets will appear when you choose this. They are:

Exit - Quit DayDream BBS

ReCycle - Exit to Waiting for call mode

Cancel - Abort, do not exit.

### 1.383 DayDream BBS - Pulldown Menus - Display

Display

Palette

Screen Title (Ramiga+O)

Screen Mode

Save

### 1.384 DayDream BBS - Pulldown Menus - Display - Palette

Palette

~~~~~

Behind this you will find some palette specific stuff.

### 1.385 DayDream BBS - Pulldown Menus - Display - Screen Title

Screen Title (Ramiga+O)

~~~~~

Turn screen title on/off.

---

### 1.386 DayDream BBS - Pulldown Menus - Display - Screen Mode

Screen Mode

~~~~~

Allows you to change screen mode for the local screen.

### 1.387 DayDream BBS - Pulldown Menus - Display - Save

Save

~~~~

Allows you to save display configuration.

### 1.388 DayDream BBS - Pulldown Menus - Online

Online

ASCII Send (Ramiga+S)  
Send file(s) (Ramiga+U)  
Receive file(s) (Ramiga+D)  
Chat Message (Ramiga+E)  
Modem Command (Ramiga+M)  
Local UserEd (Ramiga+1)  
Lo&Re UserEd (Ramiga+2)  
Chat Request Off (Ramiga+W)  
Kick User (Ramiga+H)  
Chat Mode (Ramiga+-)  
Hydra Transfer (Ramiga+T)  
Butt noise (Ramiga+B)  
Disable idle

### 1.389 DayDream BBS - Pulldown Menus - Online - Ascii Send

ASCII Send (Ramiga+S)

~~~~~

Send ascii file to the user. If file contains those 255-codes, they will be executed also.

### 1.390 DayDream BBS - Pulldown Menus - Online - Send File(s)

Send file(s) (Ramiga+U)

~~~~~

Send binary file(s) to the user using xpr-libraries. Uses reqtools -file requester to select files for transfer. Files won't be marked to the user's download bytes/files.

---

### 1.391 DayDream BBS - Pulldown Menus - Online - Receive File(s)

Receive file(s) (Ramiga+D)

~~~~~

Receive file(s) from the user using xpr-libraries. Files will be placed in "chat download"-directory. Uploaded files won't be marked.

### 1.392 DayDream BBS - Pulldown Menus - Online - Chat Message

Chat Message (Ramiga+E)

~~~~~

Edit message to send to the user when he pages. If this is empty, paging is allowed.

### 1.393 DayDream BBS - Pulldown Menus - Online - Modem Command

Modem Command (Ramiga+M)

~~~~~

Send an Hayes AT command to the modem. Useful if you want to disable DTR-hangupping etc.

### 1.394 DayDream BBS - Pulldown Menus - Online - Local UserEd

Local UserEd (Ramiga+l)

~~~~~

Edit user locally. Output won't be shown to the user. Exacly same as UserEd mainmenu command.

### 1.395 DayDream BBS - Pulldown Menus - Online - Lo&Re UserEd

Lo&Re UserEd (Ramiga+2)

~~~~~

Exactly same as UserEd mainmenu command. Output will be shown to the user, so be careful with this.

### 1.396 DayDream BBS - Pulldown Menus - Online - Chat Request Off

Chat Request Off (Ramiga+W)

~~~~~

Closes chat request window if such exists.

---

### 1.397 DayDream BBS - Pulldown Menus - Online - Kick User

```
Kick User (Ramiga+H)
~~~~~
Hang up user.
```

### 1.398 DayDream BBS - Pulldown Menus - Online - Chat Mode

```
Chat Mode (Ramiga+-)
~~~~~
Starts chatmode. To quit from chat, just press ESC.
```

### 1.399 DayDream BBS - Pulldown Menus - Online - Hydra Transfer

```
Hydra Transfer (Ramiga+T)
~~~~~
Transfer files using Hydra/SModem -protocol. Received files will be placed
in "chat download"-directory.
```

### 1.400 DayDream BBS - Pulldown Menus - Online - Butt Noise

```
Butt noise (Ramiga+B)
~~~~~
Sends some random characters to the user. Emulates linenoise.
```

### 1.401 DayDream BBS - Pulldown Menus - Online - Disable Idle

```
Disable idle
~~~~~
Disable idle. User won't be kicked out because of inactivity.
```

### 1.402 DayDream BBS - FidoNet

```
FidoNet

Requirements
Installing Dreamtoss
Installing Mailer

Back To Main
```

## 1.403 DayDream BBS - FidoNet - Requirements

### 10-1 - Requirements

~~~~~

To join FidoNet, you need:

- 1) FidoNet address of your own. You can get it from most of the BBS'es near you, due to the popularity of the net.
- 2) Mailer software. DayDream has been tested with JamMail and Trapdoor. It works fine.
- 3) Cron utility to execute mailer to poll messages, Dreamtoss to pack messages etc.

1.404 DayDream BBS - FidoNet - Installing Dreamtoss

10-2 - Installing Dreamtoss

~~~~~

Configfile of DreamToss must be placed in Mail:-directory and it's called DreamToss.CFG. DreamToss doesn't require any kind of nodelist compiler or so.

Akas  
Bad Messages  
NetMail  
Inbound & Outbound directories  
Packer Definitions  
Outgoing Echo  
Inbound Conversion  
Area Definitions  
Routing

## 1.405 DayDream BBS - FidoNet - Installing Dreamtoss - Akas

### Akas

~~~~~

DreamToss supports AKA-addresses, so you can have multiple networks in your BBS. Standard AKA-line looks like this

AKA?? XX:XX/XX.XX

AKA1 is your primary FidoNet address. So if your primary address is for example 9:866/3.0, put in your configfile:

AKA1 9:866/3.0

1.406 DayDream BBS - FidoNet - Installing Dreamtoss - Bad Messages

Bad messages

~~~~~

There can be some bad messages in the message packet, for example there might be message to the area you have not configured. That kind of messages are imported to the area, you have defined as a bad message base. It should be local area because then you know what went wrong from the message kludges, and so you can configure DayDream so it will work.

Standard BAD-line looks like this:

```
BAD [CONF]:[BASE]
```

For example, if you want to have base 6 of conference 10 as a bad base, put to your config file:

```
BAD 10:6
```

## 1.407 DayDream BBS - FidoNet - Installing Dreamtoss - NetMail

### Netmail

~~~~~

There might be a message in the inbound directory, that doesn't have an AREA:-kludge. This kind of messages will be imported as Netmail. Netmail can be sent anywhere on the globe, and is always private. Line NETMAIL in config-file defines the base to be used for Netmail messages.

Standard NETMAIL-line looks like this:

```
NETMAIL [CONF]:[BASE]
```

For example, if you want to have base 5 of conference 10 as a netmail base, put to your config file:

```
NETMAIL 10:5
```

1.408 DayDream BBS - FidoNet - Installing Dreamtoss - In- & OutBound Dirs

Inbound & Outbound directories

~~~~~

DreamToss needs to know, where the received messages are located. It also needs to know, where you want to pack outgoing messages. Path for received messages is defined in INBOUND-line and for outgoing in OUTBOUND-line.

Here are examples:

```
INBOUND "Mail:Inbound"
OUTBOUND "Mail:Outbound"
```

Note that / will be added automatically after path and path must be enclosed with quotes.

## 1.409 DayDream BBS - FidoNet - Installing Dreamtoss - Packer Definitions

Packer definitions

~~~~~

You can have multiple packers for packing outgoing mail, but only 1 for decrunching mail. If you want to have more decrunchers, get a extractor, which detects which packer is used for packing message packets.

Standard packer line looks like this:

PACK[PACKERNUMBER] "[Commandline]". First %s is for name of archive and the second %s is for source file.

Eg:

PACK1 "Lha a %s %s"

Standard unpack line looks like this:

UNPACK "[Commandline]". %s is a archive name to extract.

Eg:

UNPACK "Lha e %s"

1.410 DayDream BBS - FidoNet - Installing Dreamtoss - Outgoing Echo

Outgoing echo

~~~~~

To specify nodes/points which get some mail from you, you need to use list of outbound nodes. List begins with line "OUT:". The next lines are for specifications about nodes/points which get the mail packets from you. The line format is:

[4D ADDRESS] [TYPE] [PACKER] [AKA]

4D Address is a typical fidonet 4D address, eg. 9:866/3.0. Type specifies the method which is used to deliver packets to the current node. If it's H, node will call you to exchange the packets. If it's N, you will call the current node to exchange packets.

Packer specifies packer number to use.

Aka specifies aka to use in messages to this node.

~ is end of the outbound definitions.

---



Example list:

```
OUT:
9:866/1.0 N 1 1
9:866/2.0 H 1 1
~
```

## 1.411 DayDream BBS - FidoNet - Installing Dreamtoss - Inbound Conversion

Inbound conversion

~~~~~

It's possible to convert incoming messages. If you live in Scandinavia and you are member of PC-network, those linefeeds are really annoying. If you want to use conversion table, specify the conversion table number in "CONVERSION" line. Table will be taken from DayDream:Data/-directory.

1.412 DayDream BBS - FidoNet - Installing Dreamtoss - Area Definitions

Area definitions

~~~~~

To export echomail messages, you need to specify nodes who are polling area. Every area requires this. Format for AREA-line is

```
AREA [CONF]:[BASE] [List of 4d-addresses].
```

Eg:

```
AREA 4:5 9:866/1.0 9:866/2.0
```

## 1.413 DayDream BBS - FidoNet - Installing Dreamtoss - Routing

Routing

~~~~~

Routing is required for sending netmail via many nodes, not directly to the destination. This makes netmail transferring cheaper and slower.

This is how it works:

```
.-----
| Netmail for eg. node 2:447/3.0. |
\-----/
```

```

      |
Is this defined in outbound nodes?  eg. 2:477/3.0 N 1 1
      |
      +----- yes -- Send it directly to it.
      |
      no
      |
```

```

Is there route entry for dest?      eg. 2:477/#? 2:477/2.0
      |
      +----- yes -- Send it to 2:477/2.0
      |
      no
      |
Crashmail it to 2:477/3.0

```

To specify routing, you'll need a table of route entries.
List begins with line "ROUTE:" and next lines are for specifications
about nodes to use for routing.

Format for lines is:

```
[PATTERN] [4D ADDRESS]
```

Pattern is an Amigados pattern. If destination matches with it,
netmail will be sent to [4D ADDRESS].

4D Address is a typical fidonet 4D address, eg. 9:866/3.0.
If it's -, mail won't be sent. First lines of the routetable
should be used for your addresses to prevent tosser from sending your
netmails forward.

~ is end of the routing definitions.

Example list:

```

ROUTE:
9:866/3.0 -
9:#? 9:866/1.0
~

```

1.414 DayDream BBS - FidoNet - Installing Mailer

Mailer, Front End or whatever you call it is required to make FidoNet work properly. There's two major mailers on Amiga, TrapDoor and JamMail. TrapDoor is better, but you'll need to register it for BBS usage. JamMail is free, but eats lots of memory, is slow etc..

To make mailer and DD work properly, you must be sure that:

- 1) Both mailer and DD use same serial driver, unit and Baud rate.
- 2) Both mailer and DD open serial in SHARED mode.

Spawn command looks like this:
DayDream n[node] d[baud] h

eg, spawn command from trapdoor would be:

```
BBSCommand "daydream:daydream n1 d%B h"
```

For more information, take a look at Trapdoor's manual.

1.415 DayDream BBS - Other Things You Should Know

Other Things You Should Know

Chat Mode
Making Stuff Resident
Multinode Chat
InterNet
Compatibility w/ /X
Daily Updates
Configuring strings
Multinode support

Back To Main

1.416 DayDream BBS - Other Things You Should Know - Chat Mode

11-1 - Chat mode

~~~~~

When user is paging you, press CTRL-A to enter the chat. Otherwise, use Amiga+C. To exit chatmode, just hit <ESC>.

## 1.417 DayDream BBS - Other Things You Should Know - Making Stuff Resident

11-2 - Making stuff resident

~~~~~

The most of the included programs are pure. That means you can make them resident, using "resident [program] pure" command. This makes the programs start quicker and in some cases saves some memory too. If you're running multinode system, then you should make at least DD-executable resident, because you save over 100kb of memory per node.

DDHydra and Server are NOT residentable.

1.418 DayDream BBS - Other Things You Should Know - Multinode Chat

11-3 - Multinode chat

~~~~~

DayDream supports multinode chat that's supplied in distribution archive. It's IRC-styled, but there aren't that many commands and it's not so complex as IRC is. To use it, you'll need to run DDRcserver which is included in Utils/-directory as it handles the communication between nodes.

## 1.419 DayDream BBS - InterNet

You can offer Usenet News and E-Mail access to users. At least following utils are required (available at the aminet).

AmigaElm:

AmigaElm-v6.lha      comm/mail    356K    1+Mail-Reader (UUCP/Internet), v6 (6.24)

AmigaTin:

tin130beta.lha      comm/news    198K    5+TIN 1.3 PL0 Beta - \*The\* Newsreader

AmigaUUCP:

AmigaUUCP1\_16.lha   comm/uucp    1.1M 140 UUCP for the Amiga, V 1.16

You'll need also an message editor, so your users can post mail also. There's no software for that purpose in Aminet, but you can get one at least from my board. (vised.lzx, conference 8).

## 1.420 DayDream BBS - Compatibility w/ /X

DayDream itself is not compatible with AmiExpress and it will never be. But, there's XIM emulation, Userbase converters etc available in my BBS. They are not included in distribution archive, because there could be a courtcase between me and Hodge, because I am not planning to pay royalties for Lightspeed technologies.

About 50-60% of doors work through DD's XIM emulation. In general, all doors that don't use userbase, messagebase or filelists work.

There has been complaining because some commands are not the same in /X (or should I say PCBoard???) and DD. This is because Tuomas went rebel while designing DD. This is not a problem because you can configure the commands to be equal. Just add this to your ExternalCommands.DAT section of configfile:

```
DOOR_COMMAND.. W
DOOR_TYPE..... 5
DOOR_SECURITY.. 1
DOOR_EXECUTE.. A
+
DOOR_COMMAND.. A
DOOR_TYPE..... 5
DOOR_SECURITY.. 1
DOOR_EXECUTE.. T
+
DOOR_COMMAND.. T
DOOR_TYPE..... 5
DOOR_SECURITY.. 1
DOOR_EXECUTE.. L
+
```

## 1.421 DayDream BBS - Daily Updates

New version of DayDream BBS is always downloadable from Humanoid Invasion. Use command GETDD to get the new version.

---

## 1.422 DayDream BBS - Strings

DayDream:Display/ directory contains file Strings.XXX, that contains nearly all strings of the BBS. You can configure the outlook of your BBS or add languages etc by editing these files.

You can also replace those strings with external door by replacing the string with following syntax:

<ascii-255><external or internal command of dd>

Eg: ÿFREE

would run command FREE. (Command MUST be internal command of DD or specified in ExternalCommands).

## 1.423 DayDream BBS - Multiple nodes

If you are using external serial card (MFC, GVP IO or similar) you may run to troubles when using default settings. Serial drivers of those cards can crash when DD is using DTR hangupping, so normal +++ATH hangupping is recommended. To use +++ATH run DD like this.

```
run daydream nl h
```

## 1.424 DayDream BBS - History

History

Version 1.00Beta-1  
Version 1.00Beta-2  
Version 1.00Beta-3  
Version 1.00  
Version 1.01  
Version 1.02  
Version 1.03  
Version 1.10  
Version 1.11  
Version 1.12  
Version 1.13  
Version 1.14  
Version 1.15  
Version 1.16  
Version 1.17  
Version 1.18  
Version 1.20

Back To Main

## 1.425 DayDream BBS - History - Version 1.00Beta-1

===( Version 1.00Beta-1 - 060195 )=====

- Initial release

## 1.426 DayDream BBS - History - Version 1.00Beta-2

===( Version 1.00Beta-2 - 150195 )=====

- Fixed stupid outlook bug in waiting for call-mode.
  - I forgot example characterconversiontables from 1.00B-1. Included now.
  - If user was too lazy to hit return when uploading, idle timeout took place when he auto-described lots of files. Fixed.
  - If carrier lost when user wrote descriptions and archive didn't contain file\_id.diz, DayDream added 0 byte FILE\_ID.DIZ. Fixed.
  - If user hadn't got upload-signature, stupid "None"-string added as signature when he saved description w/ S-command. Fixed.
  - Server pissed listview when DayDream was inactivated. Fixed.
  - If message is deleted, header won't be shown to anyone!
  - Added 2 new mainmenu commands, NS and MS. NS is a global newfile scan and MS is a global mail scan.
  - Added finally those Switches in alter settings menu.
  - Fixed a stupid bug in DreamRexx which caused it to wait forever once a day :)
  - Improved crackprotection. Should be harder to crack now!
  - Disconnection after transfer is done IMMEDIATELY now. User is now free to go right after upload, so he/she doesn't need to wait for testing archives etc.
  - "Are you sure"-question removed from message deletion.
  - Added command 101 to server: Inquire pointers to the datafiles. Programmers can easily fetch configfiles of the system from here!
  - Activity "uploading" was left out from who and server's listview. Fixed.
  - If SysOp started DayDream using "DayDream n?? lo" and userbase didn't exist, system crashed. Fixed.
  - Fixed a stupid bug in Questionnaire() that caused really strange things to the System. This fix should reduce 80% crashes of DayDream :)
  - Fixed a bug in DreamConfig that messed up Handles/Realnames/Organization/
-

Location in server.

- Made a tiny utility called FixBases. It fixes high and low message pointers to your Conferences.DAT, if Conferences.DAT has blown up for reason or another.
- Added command 3 to server. Save Conferences.DAT.
- Fixed outlook bugs in DDTOP.
- Fixed a bug in AskDisplayMode() which caused system to crash when used mode command in main menu and just pressed return or dropped carrier. Thanx to Zeus for crashing my system :)
- Faker supports now commandline stacking. User can fake multiple files at once. Thanks to Patrician for suggesting this.

### 1.427 DayDream BBS - History - Version 1.00Beta-3

==( Version 1.00Beta-3 - 280195 )=====

- FreeDownloads work now. FreeDownloads.DAT trashed path of file to download. Fixed.
  - Added wildcard support for Move-command.
  - Added 2 new text files: MoveFiles.TXT/GFX and ZippySearch.TXT/GFX.
  - SystemPassword.TXT/GFX is now searched from DayDream:Display/[mode]/directory.
  - Global newfiles can areas are now configurable by SysOp via Config-program. Configuration is done via Conferences.DAT, check out included DayDream.CFG for more info.
  - Fixed a bug in DeleteMessage() which caused it to be not working at all :) Thanks to Patrician for reporting this.
  - Fixed a bug in DreamRexx. Prompt() was looped if carrier lost.
  - Line-editor supports word wrap now. This was suggested by lot of guys, and finally it's available!
  - DayDream sends ESC[Om before "Send Ascii" pulldown menu command.
  - Improved DDWeekTop a bit. New outlook, possibility to use custom header, ansi messages... Update your config file!
  - Fixed a bug in Upload(). If file type was unknown and previously described file contained FILE\_ID.DIZ, description was taken from previous file.
  - Fixed a bug in Upload(). If file\_id.diz had 13 lines and user's signature didn't fit to the last line, system crashed. I hope upload is working now without crashes or bugs :) (Keep on DayDreaming...)
-

- If upload directory didn't exist, all files were deleted after uploading. Now DD doesn't allow uploading, if there's no upload directory.
  - New files scan had a bug when counting screen length. This didn't occur that often if there was not so many file areas in the conference, but it was still really annoying. I tried to find the bug for 4 hours, but I couldn't find it. Then the More-prompt will be displayed after each base when scanning new files.
  - Changed ReplyMessage() a bit, so it can handle lines longer than 80 chars.
  - Removed /X conversion tools from distribution package, because the "Programming fool" threatened to sue me.
  - Major update! Added FidoNet support. Utility called DreamToss is included in DayDream:Utils/-directory. It still has alot of bugs, but at least you can operate a smaller network with it. Please report if you can find any bugs, so i can fix them immediatily (as usual) :)
  - Added new control code for textfiles. `ÿJ<file>|<max value>|` shows random file. `<file>` is a path for file and prefix for filename. Postfix is a number between 1 and `<max value>`.
  - Added SF-Command. User can now select areas to be scanned at global new file scan.
  - Added new command to the pulldown menus. It's called Butt noise, and is meant to tease users :)
  - Added SM-command. User can new select messages bases which he/she wants to be scanned at the mailscan and to be packed to WWF/Ascii message packets.
  - Added new door command: Inquire Pointers 2, programmers can now fetch some more info from DayDream.
  - Added some features to DreamMail, such as support for Selected.DAT, fidonet-kludge stripping etcetc.
  - Improved Download() a bit. If transfer was aborted, bytes of the whole transfer were added to user.
  - Added more strings to Strings.XXX. Now it's possible to configure even reply line in messages etc. Be sure to update these strings, when updating from Beta-1/2!
  - Added ansi-stripping for File\_id.diz. If FID had ansis, only esc was stripped, now whole ansi code will be stripped. Reason for this is that IMHO description is a description, not a bloody rainbow :)
  - Improved documentation a bit.
  - Added 3 new securityflags. Check the configfile!
  - Fixed a bug in Questionnaire(). First line was stripped off.
-



## 1.428 DayDream BBS - History - Version 1.00

==( Version 1.00 - 190295 )=====

- If file already exist in the conference, DDHydra gently skips it :)
  - J-Command now shows the list of conferences when nothing else but J is entered.
  - User was able to enter conference list with > or < command even if he hadn't access to use J-Command.
  - Promptstring in main menu pissed if it was over 100 Bytes. New limit is 300, i guess no body has longer promptstring than that. Also optimized main prompt a bit.
  - Fixed DDCallers so it doesn't crash if log entry for last user is longer than 4kb.
  - Added new textfile: DayDream:Display/DisplayModeList.TXT. This will be shown before asking for the displaymode, so you can inform those moron users, what is displaymode 2 etc :) Also default selection added. Default is hardcoded as 1.
  - Fixed a little bug in move files. File wasn't always found from filelist.
  - Fixed a bug in ReplyMessage(). Messed an /X-style replyline sometimes.
  - Added a new runtime library with DayDream. DayDream itself doesn't use it, but I suppose many doorprogrammers will use it, so place dreamdoor.library in the libs:.
  - Improved ReadMessages() a lot. Advantages with this new version:
    - Better multinode capability.
    - Doesn't eat memory like a horse, messageheaders will be loaded to 30kb buffer.
    - Faster sometimes, sometimes slower than the old one.
  - M-command shows list of messagebases if user enters nothing else than M.
  - If SysOp entered chat mode when user was in prompt, LF was required after chatting to get the prompt visible again. Fixed.
  - Added possiblity to disable log file when running daydream with LO-option.
  - DreamConfig won't compile files anymore if server is running.
  - If user press enter or waits 3 secs in Insert file\_id.diz question, file\_id.diz won't be showed again.
  - Added built-in offline checker. Now user don't need to wait when files are being checked, because uploaded files will be checked after user has logged off. Note that this is optional, so you may still use the old online checking.
-

- Added possiblity to delete corrupt files.
  - Added possiblity to get date of file from file\_id.diz. Date will be inserted to the description, so you and users can see how old the file actually is. Of course this requires that the file\_id.diz was made by the author and he had the clock set to the right time..
  - Optimized code a bit. These optimizations should fix the cache problems also.
  - Redesigned the "use this file\_id.diz" question. Now it's possible to automatically save all files equipped with file\_id.diz by selecting Quick mode. User can also put upload to sysop's private directory in file\_id.diz prompt..
  - Added possiblity to set priority for each node.
  - Fixed couple of enforcer hits.
  - ReplyMessage() had stupid code and probably trashed memory sometimes.
  - If filename contained more dots than one, it was not recognized.
  - Added xpr\_squery() for XPR-Interface().
  - Bps rate conversion pissed w/ some modems. Fixed.
  - Added global bulletins. If conference doesn't have any bulletins, they are searched from DayDream:Bulletins/ directory.
  - Added IO-Devices.DAT to Inquire Pointers 2-door command.
  - If modem is initialized once, it won't be initialized after each call anymore. Added hotkey to Waiting for call mode (Initialize modem).
  - Added couple of parameters to the run stdio/dos command. Now it's possible to have nearly every BBS program as a door from DayDream BBS. To do this, just define the other BBS program in External commands as a shell script and run it like it was run from TrapDoor or similar FidoNet frontend.
  - Documentation is now ready, everything should be explained.
  - Added possiblity to iconify the Server.
  - Added possiblity to run node just by double-clicking the node in the server's listview gadget. If node is running already, it's screen will be moved to front.
  - Improved Configprogram a bit. It generates Conferences automatically now, so you don't need to make directories etc...
  - Added 3 new door commands. They are 1) Join Conference, 2) Change msg base, 3) Internal command. DDCommand launches doors also, but IntCommand doesn't.
-

## 1.429 DayDream BBS - History - Version 1.01

==( Version 1.01 - 120395 )=====

- Added new control code for Textfiles. `ÿK<command>|`. Allows you to execute main menu command of DayDream.
  - Added support for global Free Downloads. They are specified in ascii file `DayDream:Data/FreeDownloads.DAT`.
  - Fixed "a couple" of enforcer hits. :)
  - If modem initialization failed, DD Jammed. Fixed.
  - Added possiblity to copy files from Temporary directory before deleting them. (There can be files if the system crashes or so...)
  - Added OLM command. This allows user to send line of text to the user on the other node. Be sure to update your securitylevels so users can use this command.
  - Optimized code a bit. DD is now phaster and 5 kilobytes shorter.
  - Removed all `Execute()` functions from DayDream since they might cause enforcer hits on some high end Amigas.
  - Door commands don't need `RUN` command anymore. So remove them EVERYWHERE in your configfile and textfiles.
  - Fixed a bug in `EnterMessage()`. Crashed sometimes.
  - Added wildcard support for `EnterMessage()`.
  - New and enchanced `WeekTop`-utility included. Old one was buggy etc.. New one has customizable outlook etc..
  - `NewFilesScan()` didn't free all of it's memory. Fixed.
  - Local uploading uses `Reqtools` requester by now. Old method was lame.
  - Ascii Send path is now called Local upload path.
  - Added local downloading. (Asks path where files to be downloaded will be copied). Useful if your friend want to copy software to him/herself from your board.
  - Removed built-in strings. Nobody used them and they ate 20 kb of memory.
  - New Shell blabla won't be shown anymore in `stdio-doors`.
  - User has now two attempts for system password.
  - Extended `Multinode.DAT` 100 bytes because old structure was not big enough. This shouldn't cause any compatibility problems.
  - `TypeText()` doesn't strip cursor movements anymore if user is using ANSI.
-

Only colors will be stripped.

- If message contains ansi, it will be stripped if user has ansi mode turned off.
  - Temporary directory is now configurable. Specify it in Multinode.DAT.
  - Improved Hydra-protocol a bit. Now calculates downloads right even if transfer is aborted.
  - Added new doorcommand (CheckKey).
  - Added new option for Getkey doorcommand (automatic cursor detection). This fixes the problems with cursor key detections...
  - New users are finally marked to the logfile :)
  - Fixed N, F and Z commands so they don't crash anymore. This bug caused all the problems with highend machines.
  - ReadMessages() looped sometimes and made DD to load MsgBase.DAT continuously. (Hi Darkelf, total 20 hours HDD loading it, hehe)
  - If wildcards are disabled in logon, names and handles can include wildcards. Strange things happened to the dudes such as [-traitor-] etc :)
  - If file\_id.diz contains empty lines they will be stripped.
  - Default sentby line is now "-[handle]", eg. -Hydra.
  - Added possiblity to configure line editor less userfrindly :) (IMHO!). Entering command mode pressing alone in the empty line is now possible. (I didn't like the idea, but many dudes requested it...)
  - Added screen mode requester. If screen mode hasn't been chosen yet, DD will ask for one. Now dudes with SVGA-monitors etc can use DD.
  - Added possiblity to save the palette. Palette and screenmode are saved in DayDream:Data/ScreenInfo[node].DAT.
  - If upload was over 10mb, DD crashed. Fixed.
  - Added new door command, LineEditor().
  - Removed unused lines from Strings, happy updating :-)
  - Each node can have own display directory. This option is node specific and if it's turned on, textfiles will be looked from DayDream:Display/Node[node]/. Strings.XXX can also be there.
  - XPR-Transfer jammed sometimes when there was large cpu usage. This was really spiritual bug and took 5 hours to found, but i managed to fix it.
  - Toggling mode in bulletins is now possible by pressing T.
-

### 1.430 DayDream BBS - History - Version 1.02

==( Version 1.02 - 020495 )=====

- Local node jammed sometimes when entered usereditor in Hotkey().
- DayDream crashed when user used wildcards when entered message and message base used realnames.
- DayDream screen can be opened/closed from the server. When local screen is closed, DayDream will work much faster.
- If carrier was lost while asking user to rename the file he uploaded (if the name was too long) DayDream crashed. Fixed.
- Move-command didn't always delete the file. Fixed.
- Added possiblity to resume transfer if it was aborted.
- Local up/downloading had a bug that appeared when they were started somewhere else than u and d commands.. fixed.
- Improved "waiting for call..." mode a bit.
- Switches are now more logical. (No more "Disable"-stuff).
- Entering chat mode when user was reading messages was broken. Fixed.
- Changed cripples in unregistered version a bit. User won't be kicked out in 60% of calls. DayDream will wait n seconds instead. :)
- Added possiblity to attach files to messages.
- Added possiblity to redirect output of filechecking to the user.
- Added possiblity to change and disable commands. Eg to alter A->W etc. This is done via ExternalCommands.DAT (Doortype 5).
- DayDream doesn't get stuck anymore if there's more than one ARexx door running at once.
- DayDream doesn't allow names like SysOp, All and All users anymore.
- If idle happened, disconnection took place when BBS entered main prompt. Now disconnects user out immediatily.
- Added new datafile, DayDream:Data/TrashCan.DAT. This is list of names that are not allowed in the system and when somebody claims to be one of the listed users, he/she will be disconnected. Wildcards allowed.
- When user edited line in file description, : and / didn't work. Fixed.

### 1.431 DayDream BBS - History - Version 1.03

---

====( Version 1.03 - 230495 )=====

- Fixed a couple of enforcer hits again.
  - If message base doesn't allow private and public messages, then user is not able to enter messages at all.
  - Rewrote Read\_SC() (Reads data from serial and console in Waiting for Call-mode) and SendModem() routines.
  - Screen will be cleared after displaymode change (Speeds up ASCII-mode if user had used ANSI previously).
  - Fixed a bug in ScanForNewMail(). EALL messages made with version 1.02 or older won't be shown anymore, sorry.
  - Added 2 new door commands. FifoCommand() and WriteLog(). FifoCommand() executes command and routes output to the user (realtime). WriteLog() writes specified text to the logfile.
  - Added possiblity to make conference password protected.
  - Added possiblity to make conference as free download conf.
  - Added possiblity to make conference as "no credits" conference. Users won't be credited from files they upload to the conf.
  - Added possiblity to disable ul signatures in conference.
  - Made the stupid \$ key in line-editor configurable.
  - If the Quickcommandmode in line-editor was enabled and message was 0 bytes, DD wrote abt 80kb of buttnoise to the disk.
  - When user enters just "a" as a file he/she wants to download, DD throws him/her back to the menu.
  - Added some flags for the door command DisplayFile().
  - Fixed a bug in Queryy and Queryn ARexx functions.
  - Fixed a bug in Bulletins. If user entered "JOrma:sod" DayDream tried to open Bulletin.Jorma:sod.gfx.
  - Stdio doors don't crash anymore if user drops carrier.
  - Added new control code for STDIO doors. %A = Access level.
  - If wildcards are disabled, they are still usable if there's only one match.
  - Made cursor hidden in text files. This speeds up output a lot.
  - Added support for CSI-codes. If user wants to use them, ANSI codes are converted to CSI-codes realtime. (Speeds up output a bit).
-

- DreamMail supports now BlueWave format. It also displays packer output to the user (Realtime).
- Added new utility - ListClean. It scans filelist for missing files. If file that is in the list doesn't exist in filedirectories, it will be marked as deleted.
- Resume doesn't piss anymore. It should be FINALLY working.

## 1.432 DayDream BBS - History - Version 1.10

===( Version 1.10 - 140595 )=====

- Access flags for public/private file attaches pissed. Fixed.
  - If log file was disabled on operator logins, log was still written when SysOp entered to the board using O key in Waiting for call mode.
  - Fixed some enforcer hits.
  - 0 byte file\_id.dizes won't be added to archives anymore.
  - Fixed cursorkeys so they should work with shitty and slow lines too.
  - Grab door trashed last read pointers sometimes (not so often). Fixed.
  - SM and SF saves stuff when you press return. No more stupid prompt after return..
  - Documentation format is now AmigaGuide. Daft sacrificed 6 hours of his life to do it, thanx..
  - DayDream supports now external Full Screen editor.
  - Added Full Screen editor door. It's about 5 kbytes long, but is kinda userfriendly. I suppose it's the smallest FSEditor around. It took about week to code (aprx 1 1/2 hours a day).
  - HotKey routine supports inbound character conversion now.
  - Remote Shell supports inbound character conversion now.
  - "TERESUOMI" launched tag files routine in main menu and this annoyed some dudes so much that I made DD to launch tag files only on T <parameters>, not on T<parameters> command. Several other commands are changed in the same way.
  - If door program doesn't exist, DD reports it rather than jams..
  - If rexx-script doesn't exist, DreamRexx tells it and quits nicely.
  - Chat mode can be started in SysOp page from pull down menus also.
  - Message password protection pissed, it wasn't converted uppercase.
-

- If user replied password protected message and didn't know the password, he saw the message anyway, fixed.
- If OS39 or higher is found, DD will open screen in interleaved mode. This removes flicking when scrolling text.
- Fixed red<->white "distortion" (esc[31m was white as it should be red and esc[37m was red as it should be white). This is an optional feature, because it slows down the local console a bit and therefore should be only used on local nodes.
- Enhanced ansi-stripping a bit. (No more flows in some XIM doors..)
- Added support for new conference-datafile. [CONF]/Data/Examine.DAT is list of doors to be executed in upload checking after getting file description but before saving the file.
- DayDream works through nullmodem.device now.. There was a little problem with CheckAbort() routine that made nullmodem.device jam. Probably pissed on some serialcards too.
- Added possiblity to send string to the modem after call.
- Text outputting is lots of faster now if the screen is open and user is not using character conversions.
- If carrier is lost in stdio door, logoff is handled correctly now.
- Enhanced Built-in user editor a bit (Only some internal changes to make the security system better).
- If user dropped carrier in user editor, DD jammed. Fixed.
- If user has no access to some conference, other users are not able to send him/her a message.
- Added support for new conference-datafile. [CONF]/Data/FileCheck.DAT is list of doors to be executed in upload checking before dupe check or anything..
- Offline checking outputted stuff to the modem also. Fixed.
- NEW E-MAIL ADDRESS! Do not use hydra@tolsun.oulu.fi anymore, because they kicked all outsiders out from the local university, including me also. My new E-Mail address is hydra@freenet.hut.fi. Freenet sucks, btw :)

### 1.433 DayDream BBS - History - Version 1.11

==( Version 1.11 - 120695 )=====

- Rewrote Archivers.DAT format.
  - Added internal V-command. (View files)
  - Added Sysop-command \$ (Test door).
-



- Rewrote filetagging routines. DD uses standard AmigaOS lists for flagged files now.
- If user has flagged files and loses carrier or logs off, files will be re-flagged on his/her next call..
- Up/down-keys in prompt do not make the screen to change color any more.
- If screen was closed and user used CLS command, DD crashed.
- New version of DreamNew. DreamNew supports now cursor keys, ctrl-c in continuous mode etc.
- NewFilesScan() is now "slightly" faster. I guess Tuomas had brains on vacation when coding this (ANSI coloring was done before date comparison)
- Tag Editor now recognizes eg. T R \*.
- Removed a bug in Enter Message. All/All users was broken. Thanx to Bytejammer for reporting this, though the way he told it to me wasn't a nice surprise..
- Fixed a bug in Full Screen Editor. If first line was empty, message was aborted when saved..
- DayDream supports now alternative filelisting format. New format has 18 characters long filenames, so you don't need to suffer because of 8+3 filenames anymore. Useful for Module/C64 etc conferences. Aminet filenames are also 18 characters long, so there is no need to rename them anymore.. Ofcourse you can still use 8+3 filenames if you want.
- Local transfers are now logged to the log file. CPS is hardcoded to 1400.
- If filename was too long and then renamed, this is logged too.
- Server enchanged a lot! GUI is better, more buttons, more information etc.
- Mail scan, message reading and DreamMail are now faster.
- Fixed a bug in Mail scan. If message was deleted, next message was shown.
- Enchanged LineEditor-doorcommand a bit..
- Faker pissed sometimes when it was looking for logentries..
- Coded a little example door in C.. It's an interactive status door. Included in Doors/ directory (Stat). Sourcecode is in developer directory.

### 1.434 DayDream BBS - History - Version 1.12

==( Version 1.12 - 020795 )=====

- Added r-command in upload editor. (Resume)

- Added cursor support for N and F commands.
  - Added split screen chat.
  - Fixed a bug in Upload(). If there was upload to conference with 8+3 filenames and after that to conference with 18 char filenames, output pissed.
  - Fixed a bug in Hotkey(). If screen was closed during Hotkey()-routine, DD crashed.
  - Added new flag to GetKey() - HOTKEY\_DETECT.
  - Added new door command - CleanTemp(). Cleans up temporary directory.
  - Fixed a bug in InquirePointers() door command. Security information was not properly given.
  - FSEditor supports now file attach.
  - Coded a little utility, RoboWriter. See RoboWriter.DOC for more info.
  - Fixed a little bug in faker.. File wasn't searched properly from the log.
  - Added new user configurable switch - CLS's in filelists.
  - Added cursor support for Z command.
  - Added new flag to switches - CLS's in filelists. If CLS's are enabled, cursor keys are also usable for fileflagging.
  - Implemented display mode specific fonts. Local screen can be now using IBM font if user is using IBM display mode, ISO font if user is using ISO mode etc...
  - Added new door command - FetchKey(). Same as GetKey() but timeout is possible. Useful for multinode chatters etc.
  - Added new door command - ChangeActivity(). Changes the activity in server and WHO-command.
  - Added possibility for frontend doors. Execution commands are listed in DayDream:Data/FrontEnds.DAT and they MUST be DDDP doors.
  - Added support for ConferencePW-txt file.
  - It is not necessary to press Y key after Hydra transfer anymore. 3 seconds without activity in that prompt does the same thing.
  - Fixed a bug in Grab-door. If configuration was wrong and user grabbed msgs in ascii format, it pissed.
  - Added new option for archivers. ARC\_SECVIEW specifies minimum security to view archive.
  - Added DPL\_STRIPANSI flag to Display.DAT. If this is on, ansicodes will be stripped from textfiles.
-

- Added DPL\_TRYTXT flag to Display.DAT. If this and ansi is turned on and .GFX file doesn't found, DD tries to open .TXT file.
- Added GetConf() and GetBase() door commands to dreamdoor.library.
- Added regtools.library to distribution, since it has caused problems because people were using old versions of it that don't work with DD.
- Enchanged installer-script a bit :)
- Added commandline history to main prompt. (Cursor up/down)
- Files over 1MB pissed on 18 on conferences that use 18 character long filenames.

### 1.435 DayDream BBS - History - Version 1.13

==( Version 1.13 - 020895 )=====

- Fixed a bug in tosser. Netmail for known up/downlinks was not packed properly.
  - Added global read command (GR)
  - Added Edit message command (E in message prompt)
  - Enchanced FSEditor a bit.
  - Fixed a bug in mailscan. If conference had over 127 msg bases, it didn't work properly
  - Server autoiconify didn't work properly if workbench was running.
  - RoboWriter didn't close message text if destination base was echomail area.
  - DL Prompt should show flagged and available files properly now, even if there are free downloads tagged.
  - Added possiblity to add external commands to strings-file..  
ÿ[COMMAND]<ctrl-a> will replace the string with [COMMAND]. Command must be either internal DD command or external command. Parameters can be included.
  - Enchanged DDCallers and changed the version number to 1.0. Changes:
    - removed some debugging stuff
    - shouldn't piss with small files anymore
    - counts daily hours and new users
  - Fixed some problems with FetchKey() door command.. Timer sigbits were fucked up sometimes.
  - If user deleted message when DD asked "Delete Original Message (Y/n)" and user replied Y and then replied again DD asked Delete Original Message again. Fixed.
-

- Paragon door support works now.
- Added IRC-style multinodechat.
- ByteJammer's dream came true. Added BASE\_ALL=EALL option.
- Added CONF\_ASKDEST flag. Asks for destination file area from uploader.
- New version of DreamNew added. New stuff: Bug fixes, better outlook and added possibility for separator between dates.
- FSEd crashed if TAB was pressed at the end of line.
- If download was aborted, non-downloaded files were also deleted from the batch. Fixed.

### 1.436 DayDream BBS - History - Version 1.14

==( Version 1.14 - 100995 )=====

- Commandline history didn't work properly in ascii mode.
  - If message was written from 2 nodes to the same base at the same time, the other one got lost. Fixed. Thanx to Carebear for reporting this :-)
  - Bizarre bug found when tagged files flagged on previous call :) JoinConf.TXT was shown between every single file. Fixed.
  - If download was aborted Tagged files counter was screwed up. Sorry.
  - ReqTools Filerequester remembers the last path entered now.
  - Removing files from batch supports now spaces between files.  
(T R [file1] [file2]...)
  - If SysOp pressed Enter chat many times, chat was started as many times as it was pressed. Fixed.
  - Server warns if SysOp tries to shutdown node that has user online.
  - Added new ARexx command - Putuser. See manual for details.
  - Added ARexx-port to server. Consult the manual for more info.
  - Examine.DAT won't be run anymore if file is saved as private to sysop.
  - If user has no password, it won't be asked.
  - Added user's slotnumber (read only) to user editor.
  - Changed security flag editor to use numbers instead of those stupid Z, % etc stuff..
  - Added FREEDLLINE to configfile. Adds automatically the specified line after
-

Free Download files.

- Added DownloadLog.DAT and UploadLog.DAT to LogFiles directory. These are binary logfiles for \*FAST\* log access that Faker and Whof for example could use instead of the old and slow DayDreamXX.log reading.
  - Included faster/better/cooler faker.
  - Description saving in upload is now more secure and faster.
  - DDCallers supports now commandlines without node (Just generate output, all input from datafile).
  - If user transferred over 10MB, DDCallers bugged. fixed.
  - Server changes CurrentDir() to GetProgramDir(). Got it?
  - WHOF is now faster.
  - If someone enters or leaves the system, it will be informed to other nodes. (In case they have node messages enabled)
  - File being currently uploaded is shown in activity field of Server/WHO.
  - Added EH (Edit message header)-command to message reading prompt.
  - Added keyboard shortcuts for chatmode requester as well as Cancel button.
  - Infamous screentitle bug is now fixed. Thanks to everyone of you who reported this (especially dAft who was complaining all the time about this). It took 2 minutes to fix.
  - If conf was asking destination area for uploads and it was saved as private to sysop, it was still asked. Fixed.
  - Fixed an enforcer hit in DDHydra. This probably caused some problems in skipping already existing files.
  - Changed DreamConfig to inform errors more accurately.
  - MailScan() now allows user to change his/her AutoScan pointer.
  - DD puts modem offhook after call now to make modem busy while running offline checker and logoff batch.
  - Added 060 support for VER command :)
  - Fixed several enforcer hits in DD executable.
  - Decreased registration fee :) New registration fee is 200FIM / 55USD.
  - Added little eall2all (BJ's nightmare, hoho) utility. Figure out how to use it.
  - Removed Bulk and Usered from Utils/ directory since I lost interest in them. If someone wants to continue their development, ask me for sources.
-

### 1.437 DayDream BBS - History - Version 1.15

==( Version 1.15 - 111095 )=====

- Ooops, forgot to test whof :) Download header appeared between every dl.. fixed.
- Carrier detection pissed in certain places, sorry.
- Maximum number of fileareas was 127. Fixed to 255.
- Tag editor pissed a bit if same file was in two conferences with the filenames in different cases. Fixed.
- Olm accepts now \* as node (All nodes)
- Added character conversion to grab.
- Fixed some problems with OLMs...
- DreamToss created corrupted bundles, sorry..
- Added %T parameter (Time left) to stdio commandline.
- Fixed some probs with WHO command when user was logging off.
- L in destination conf prompt brings list of confs in MOVE command.
- Fixed enforcer hits if opening node failed..
- Added DoorCommand IsAway(). Check if SysOp is available. Also added SYSTEMINFO 9 - command to do this from Arexx.
- If display mode changes font - the screen that was in front before, will be in front after too.
- Added netmail routing and support for TOPT, FMPT and INTL-kludges for DreamToss.
- BlueWave replying was broken and it crashed if user used Offline Orbit.
- BIG SECURITY BUG FIXED. I won't tell it to anyone because then BBS's running older DD would be in danger. Thanks dEMOLEECHER/mOTIVE :)
- Added SendMessage() and SendMsgToAll() door commands to send OLM's from doors.
- Added /OLM command for DDRc.
- People have addressed E-Mail for me to janus.otol.fi. Don't use it anymore, janus will be dead at 1.11.95.

### 1.438 DayDream BBS - History - Version 1.16

==( Version 1.16 - 091195 )=====

- If stdio program outputted ascii 255, DD perhaps worked improperly.  
Fixed.
  - Compiled DDHydra with optimization on.
  - Fixed some security problems with upload/view/filelist etc commands..  
(Aaaaarght). User was able to see userbase's size etc..
  - Fixed a little bug in usereditor...
  - Fixed some problems with uploads containing wildcards.
  - Passwords are now crypted. Algorithm used is MD5. Use included cryptpw  
utility to crypt passwords of users. Method should be quite secure.  
(Read: More secure than DES which is used in UN\*Xes). For more information,  
get pub/docs/rfc/rfc.1300-1399/1321.txt from a decent ftp site :)
  - S in NS command allows stopping of the whole global search thingie..
  - Added possiblity to center upload signature automatically.
  - If the whole conference is free dl, Free leech tag won't be added.
  - If DD used +++ATH hangupping and SysOp quitted node, carrier was lost  
even if modem was in "at&d0-mode". Fixed.
  - Improved protocol handling a bit. Default protocol is first one in the  
list and not that stupid hard coded Z. If protocol is unknown, the first  
one will be picked automatically.
  - DreamDoor.library caused enforcer hit in Prompt() if default string was 0.  
Fixed.
  - SysOp download caused enforcer hits and sometimes crashed. Fixed.
  - Added ASK switch for "Scan for new mail", "Fullscreen editor" and  
"Scan for new files".
  - New look for DreamFaker, DreamWhof and DreamMail. Thanks dARKeLf :)
  - If file has to be moved and is located in the same partition, it will  
be renamed.
  - Rewrote XPR dupe checking routines, should be a bit faster now..
  - Added SetSerial(), ChatMode() and Pause() door commands..
  - Entry to uploadlog.dat is saved after upload now..
  - DD is now compiled using SNMA.
  - Fixed some enforcer hits..
  - Updated some developer material (C&E).
-

- Added sanity checks for filenames.
- A is same as Q in file\_id.diz "use this blabla"-prompt.
- Added possibility to deny filenames including wildcards (Users can't upload them)
- Added possibility to disable conference from global upload checking. (Caused problems with CD-Rom changers)
- Added possibility to disable fileflagging using wildcards (Can be \*SLOW\* in CD-ROM conferences etc).
- Files will be tested \*AFTER\* user has decided to save them.
- There were some strings hardcoded in message entering.. Fixed.
- IsAway() door command didn't tell if chat was disabled from pulldownmenu. Fixed.
- Improved TELNET-support a bit..
- Added possibility to disable node to notify other nodes about logons and logoffs.
- Wildcard message entering had some problems. Fixed.
- Filetagging in ascii mode looks better now.
- Added some % codes for Prompt.TXT..
- If O command is replaced with a door and user enter "oooorgh" or similar, the door will be launched anyway.
- "Download attached file?" questions defaults to no now.
- If conference had custom prompt and user changed display mode, default prompt was loaded. Fixed.
- DDTop pissed if there was more than 2 gigs of uploads..

### 1.439 DayDream BBS - History - Version 1.17

==( Version 1.17 - 161295 )=====

- Fixed a bug in Grab-door. Private/Public bits were mixed..
  - Added some ÿ codes for text files..
  - Added AutoReJoin.GFX/TXT. It is shown after JoinConference.TXT/GFX when user logs in.
  - Added Questionnaire.GFX/TXT. This enables possibility to replace internal questionnaire with a door etc..
-



- It was possible to start user editor many times -> caused crash. Fixed.
  - Fixed door type 5 a bit.. There were some problems in replacing commands etc..
  - Fixed a bug in Tag editor. If there was no files flagged, it showed header and tailer anyway.. Fixed
  - DD tells max filename length, protocol etc before uploading now..
  - If SysOp closed screen when DD was in chat mode, DD crashed. Fixed.  
(Hi HDC Staff :)
  - ChatMode() door command had a bug.. If screen was closed, DD probably crashed.
  - DreamRexx didn't set remaining time correctly with putuser 28 [time] command. Fixed.
  - Added possibility for doors to get pointer to the list of tagged files.
  - Added ReCountFiles() function. If door changes filechain, it should call this function to update filecounters of DD.  
See Developer/DreamDoor/Sas\_C/Examples/Filechain.c for more info.
  - Added SetRemainingTime() function to set the remaining time :)
  - FullScreen editor had a small bug. Wordwrap didn't work 100%. Fixed.
  - Avoided a bug in FetchKey() door command. If timeout was big, random seglist invalidations happened. Probably a bug of AmigaOS.
  - OLMs appear now in mainprompt if it's empty. There's no need to press returns anymore, if user is waiting for OLM.
  - UploadLog.DAT and DownloadLog.DAT should be a bit cleaner now :)
  - Added possibility to set the DRIPens. SysOp can change colors of the local DD screen.
  - Added possibility to set the cosysop access level. (For userlist)
  - Corrupt released couple of hacked keyfiles. They won't work anymore. Stop releasing them or I'll do something nasty..
  - Local transfer pissed if download path was missign / or :... Fixed.
  - Added DATE parameter for RoboWriter.
  - Added possibility for multiline OLM's.
  - Fixed some invisible bugs in MailScan :)))
  - MailScan now shows the amount of new messages since last call.
  - Fixed bugs in filelist. If user pressed I in more prompt -> crash. Also
-

"Y" didn't work properly if CLS's were disabled.

- I programmed a small utility for maintaining message bases. It scans messagebases for deleted messages and deletes unused headers from MSGBase.DAT. It also keeps messagebase in the SysOp configured size. (BASE\_MAXMSGs). It is pretty slow, but it works. Run it once a week or so. It should make the message bases much faster. (Utils/MsgBaseOpt)
- Failed transfer are marked to the logfile now..
- Local transfers are now 0 BPS in Upload/downloadlog.dat
- Replaced old strings.001 with a new one by DarkElf. Some might say it looks better now :)
- Fixed a small bug in Z/F/N.. If list of areas was too big, DD pissed.
- Improved message quoting a bit.

## 1.440 DayDream BBS - History - Version 1.18

===( Version 1.18 - 060196 )=====

- There was an emergency release of DD 1.17. It had following bugs fixed:
    - ~FetchKey() door command crashed in some machines
    - ~Hydra didn't work
    - DD didn't work on 68000.
  - Move-command now asks if user (sysop?) wants to move the tagged files.
  - AAAARGGHHH! If user aborted upload -> crash! Fixed. One of those bugs due to the rush in 1.17 release.
  - If "Chat -> UserEditor -> (still chatting) Transfer in the same chat" DD crashed. Fixed. Was really annoying.
  - Added Keyboard shortcuts to server.
  - ReWrote pulldown menu initializations. DD uses now gadtools.library to initialize menus. Previous intuition stuff made DD unpure (you may have noticed something strange if you have had DD resident)
  - Changed chat-startkey from RAmiga c to RAmiga -. This made OS Snapping possible (works now, though it's lame consolebuffer based).
  - Someone released new fifo-handler and fifo.library. It's really good now.
  - CoSysOpaccess level didn't work properly. Fixed.
  - If skipdupe flag is set, DD won't scan conf for possible upload when resuming losscarrier file.
  - Date/time of first call pissed in the logs (DD 1.17). Fixed.
-

- Added (Yes/no/quit) prompt in UserEd for S)can and N)ew user scan.
- MailScan didn't always inform user about amount of new messages. Fixed.
- Replaced PWFails with Free Files in usered.
- Fixed the infamous resume-bug =)
- Added ARexx doorcommand to get the current BPS rate.
- Added possibility to disable passwords for a node.
- Added possibility to hide a node in who command.
- Added LogOnDoors.DAT. It's a list of doors to be launched after displaying welcome.txt/.gfx. Useful if you want to force a door to be run on start. (Welcome.TXT/GFX can be aborted w/ ctrl-c).
- Fixed some carrier detection problems with Hotkey() routine.
- Changed that Transfer Failed thingie to Upload/Download Failed (Logfile)

## 1.441 DayDream BBS - History - Version 1.20

===( Version 1.20 - 170296 )=====

- Added possibility to change control code (ÿ -> something else).  
Use with extreme care.
  - Fixed a bug in menu initializations. Sometimes taglist was bugged -  
caused enforcer hits, crashes etc.
  - Added possibility to disable file requesters in a conference. I was  
annoyed when I had an audio cd in my CD-Rom and user tried to flag a file  
on CD conf -> requester appeared..
  - I ported SModem file transfer protocol for Amiga - DD supports it now.
  - Added Use FullScreen Editor (Yes/no/ask) for new users..
  - Made those Yes/No responses inside DD configurable
  - Wrote a completely new faker. Sourcecode included (WARNING! It's not  
residentable!!)
  - Rexx updates now SystemInfo stuff more often.
  - DDTop outlook for top 10 faker uploaders pissed, fixed.
  - Added a small utility to convert Aminet CD files.bbs to DD format.
  - Added kill option to listclean. It removes deleted files from the list,  
completely.
-