

WBStartup+

John Hughes

COLLABORATORS

	<i>TITLE :</i> WBStartup+		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY	John Hughes	July 20, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	WBStartup+	1
1.1	WBStartup+	1
1.2	Installation Instructions	1
1.3	Author & Tech	2
1.4	Contributions	3
1.5	Synopsis	3
1.6	Launcher.library Info	3
1.7	Bugs	4
1.8	Where to get Updates	4
1.9	History	4
1.10	How to use WBStartup+	8
1.11	How to use WBStartup+Prefs	9
1.12	Changing execution order	10
1.13	Tooltypes	10
1.14	Tooltype: ENABLEDPATH	10
1.15	Tooltype: DISABLEDPATH	10
1.16	Tooltype: PROGRESSWINDOW	11
1.17	Tooltype: BACKGROUNDPIC	11
1.18	Tooltype: PREFSPATH	11
1.19	Tooltype: ALPHABETIZE	12
1.20	Startup Programs	12
1.21	Tooltype: STARTPRI	12
1.22	Tooltype: WAIT	13
1.23	Tooltype: TOOLPRI	13
1.24	Catalogs	13
1.25	Index	14

Chapter 1

WBStartup+

1.1 WBStartup+

WBStartup+
March 3, 1996

by: John Hughes
johughes@heartland.bradley.edu

WBStartup+ © 1996 John Hughes. All Rights Reserved.

Installing/Updating	How to install or update WBStartup+.
Author & Tech	About the author and compiler.
PostcardWare	This is Postcardware.
Features	What WBStartup+ does.
libs:launcher.library	launcher.library info
Bugs	Bugs in WBStartup+.
Where to get Updates	Places to get newer versions
Catalogs	Information on included catalogs
History	Previous versions.

How to use:

WBStartup+
WBStartup+Prefs

Changing execution order

1.2 Installation Instructions

INSTALLATION:

Double click the "Install" icon to install WBStartup+ for the first time

or to upgrade from a previous version.

The installation script makes 2 directories, "WBStartup (Enabled)" and "WBStartup (Disabled)". "WBStartup (Enabled)" holds all the programs that you want to run at startup, and the other holds all your disabled startup programs (ie, ones that you don't want to run at startup). Everything in your SYS:WBStartup directory is moved to the "WBStartup (Enabled)" directory. The WBStartup+ program is copied to your SYS:WBStartup directory. The WBStartup+Prefs program is copied to your SYS:Prefs directory.

1.3 Author & Tech

About the author
and other tid-bits.

Program: WBStartup+
Version: 2.7
Date: Marxh 3, 1996
Coded by: John Hughes
Email: johughes@heartland.bradley.edu
WWW: <http://rhf.bradley.edu/~jhughes/>
Compiled with: SAS/C 6.56
Machine: A4000 68EC030/25 AmigaDOS 3.1
Required: AmigaDOS 2.0 or above
The preferences program requires AmigaDos 3.0 or above.

Send me a postcard

Distribution: WBStartup+ is Postcardware.
As long as all of the archive stays intact and unmodified, WBStartup+ may be distributed anywhere.

I have released: PointerEyes 4.4 - Very configurable eyes that watch your mouse pointer. Any size, and # of colors.
aminet:util/wb/PointerEyes4.4.lha

WBMakeLink - Menu in WB tools menu which makes links to files and drawers, and makes an icon for them.
aminet:util/wb/WBMakeLink.lha

Unreleased: A raytracer for Amiga Dos 3.x, but is designed to be portable ↔

1.4 Contributions

Postcardware

WBStartup+ is Post Cardware.

If you use WBStartup+, please send me a post card of your country or city.

Of course I will take any type of donations. :)

Send to:

John Hughes
901 Highview Rd.
East Peoria, IL 61611 USA

And even if you don't use WBStartup+, or don't like it, please send me EMail telling me why. Thanks. :)

I receive a very large amount of email from all over the world from WBStartup+ users who have requests, bug reports, etc. But I have received very few postcards compared to email. If you use WBStartup+, please send me a postcard... It is a very cheap way to show your appreciation for the product.

Special thanks go out to all the Europeans who have send me postcards. This is because out of all the postcards I have received, I have only one from the USA, which is rediculous considering I live in Illinois, USA!

1.5 Synopsis

WBStartup+ does the following:

- o Easy to use GUI preferences program for OS3.x.
- o Lets you choose the order in which the startup programs run.
- o Lets you enable and disable the running of each program quickly.
- o Allows you to have access to Workbench while all of your startup programs are being loaded.
- o Can be disabled at startup by holding left shift key down.
- o Progress window shows the icon of the program that is being loaded, and a progress bar with userdefine window background.

1.6 Launcher.library Info

Launcher.library

launcher.library was written by Olaf Barthel at Amiga Technologies and

may not be distributed without the entirety of this archive, unless you have authorized permission.

launcher.library (c) Copyright 1996 by ESCOM AG. All Rights Reserved.

ESCOM is not responsible for any damage this library may do.

1.7 Bugs

Bugs

All known bugs have been removed.

Thanks go out to all those who reported bugs to me.

I have no MMU, so it is very difficult to locate enforcer hits once they are present.

Please keep me informed of any bugs that you find.
E-Mail: johughes@heartland.bradley.edu

1.8 Where to get Updates

Locations to find Updates

All WBStartup updates are first posted to Aminet at:

<ftp://ftp.wustl.edu/~aminet/util/boot/WBStartupPlus.lha>

Versions 1.0 to 2.0 were put in /util/wb, sorry for the change.

Updates are also available at my web site:

<http://rhf.bradley.edu/~jhughes/>

1.9 History

History

V1.0 June 26, 1995

First release.

Thanks go to David Swasbrook for showing me an example of how to use `↔`
`GTLV_CallBack`.

V1.1 July 16, 1995

Corrected a "July" to "June" in the docs.
I accidentally asked for money in the "About" menu in the prefs program, all I want is a postcard.
Added MWB icons for the enabled and disabled directories.
Fixed the install script so that no files are deleted, making it much safer.
Minor changes in the documentation.
Added Title node to Prefs program's listview.
You can now change the loading priority of each startup program within the prefs program.
Fixed menus so they are the right colors.

V1.2 July 17, 1995

Bug Fix: You could change the priority of title nodes.
You can now get the WB info requester for any of the programs in the listview gadget of the Prefs program from a pulldown menu.

V1.3 July 18, 1995

Now runs programs without icons. Sorry about that :(
Bug Fix: Forgot to reply to a message in the Prefs program.
Forgot to free up some memory in the Prefs program.

V1.4 July 19, 1995

Prefs program now lists programs without icons, and no longer displays subdirectories. ←

V1.5 July 25, 1995

Bug Fix: Font was not being shown if it wasn't already loaded.
WBStartup+ Prefs now uses the screen font for it's text.
Added DELAY as a tooltip for WBStartup+.
WBStartup+ Prefs is completely font adaptive.
Bug Fix: It was possible to free gadgets more than once if all of them were not created. ←

V1.6 August 6, 1995

Selected entries in the listview are now shaded differently.
Added where to get l:wbstart-handler in the docs.
The list can be alphabetized from "Alphabetize list" in the "Edit" menu.
Added "ALPHABETIZE" as a tooltip. If the tooltip exists, then the list of programs will be alphabetized.
Now recognizes STARTPRI as the priority tooltip to conform more to OS3.x.
STARTUPPRI is still recognized, but obsolete, so if both STARTPRI and STARTUPPRI are present, STARTUPPRI is ignored.
Changed the priority integer gadget to a slider gadget.

V1.7 August 15, 1995

WBStartup+Prefs window is now resizable.
WBStartup+Prefs window now opens larger, depending on the visible screen size and the number of lines in the listview gadget.
Can switch between Alphabetical sorting and Priority sorting via a menu.

If the list is sorted by priority, an edited priority will be moved into the correct location in the list.

Fixed a couple font adaptive miscalculations.

V2.0 August 26, 1995

Programs can now be assigned to groups, making quick changes in the preferences program quicker.

Holding the Left Shift key down during boot time, causes WBStartup+ to be disabled.

MAJOR BUG FIX: Programs without icons (projects) were not being recognized.

Added several Group management menu items.

Added Select All, None, Toggle menu items.

WBStartup+ will not run any program with the name of "WBStartup+", that way if you have the WBStartup+ program in the enabled directory, it will not run recursively forever.

The alphabetic ordering in WBStartup+Prefs is now case insensitive using Locale.

Prefs window opening width is smarter.

Changed the look of the WBStartup+Prefs icon to look like the standard MWB prefs icons.

V2.1 September 24, 1995

Now uses Memory Pooling instead of AllocVec().

Fixed potential bug in a list structure when alphabetizing.

Received permission to include L:WBStart-Handler in this archive.

Archive has moved to Aminet:util/boot

Removed accidental FreePool() when "Delete Group" was done, and there were no groups.

Enforcer Hit removed: forgot to initialize glist=NULL before CreateContext().

Did I release V2.0 WBStartup+Prefs with a missing tail parenthesis in two path tooltypes? Sorry.

A requester now appears when you quit without saving, and there was a group modification.

WBStartup+ now has an optional Progress Indicator when it runs, which can have a user defined background.

Changed the name of drawer icon images, so they don't have parentheses in them, that way

they can be archived with lzx. They are copied by the installer script and given their

proper default names with parentheses.

Included a WBStartup+ version for OS2.x and OS3.x

Updated installer script to recognize OS2.x and OS3.x

V2.2 September 27, 1995

Removed bug causing possible crash when disabling the PROGRESSWINDOW tooltype.

V2.3 October 3, 1995

The WBStartup+Prefs window is now a WB AppWindow, so you can drop icons into it and a requester appears asking you if you want to copy or move the files to the enabled or disabled directory.

Was allocating pathname size, and deallocating filename size.

Possible program crash removed due to another forgotten glist=NULL.

Add "... " to some menu items.

V2.4 October 4, 1995

Was allocating one byte less than needed for groupnames when creating them from the menu. ↵
When resizing the window, the gadgets are remade, but glist was not initialized to NULL again. ↵
WBStartup+ now sets the stack size for each loaded program, although WBStartup- Handler seems ↵
to not always use the exacts stack size specified. ↵
Was allocating sizeof(struct Node) instead of sizeof(struct WBStartupNode) in the OS2.x version of WBStartup+. ↵

V2.5 October 23, 1995

Now supports Localization. Included catalogs: Deutsch, Français, Italiano, Norsk, Svenska. ↵
Holding the Ctrl key down when WBStartup+ is run will cause WBStartup+Prefs to be ↵
run before any programs are loaded, allowing you to choose which programs get loaded. ↵
Holding the left Alt key when WBStartup+ is run causes the user to be asked which of the ↵
enabled programs should be run. ↵
Added PREFSPATH tooltype to WBStartup+ icon. This is the location of the preferences file. ↵
Program names are shown in WBStartup+'s progress window. ↵
If the case of the letters in the filename and icon name varied, the same program name ↵
would be recognized as two different programs. This is now fixed. ↵
Added Cancel and Ok gadgets to the Copy File window. ↵
The OS3.x version of WBStartup+ was getting it's bottom border of the prefs window ↵
overwritten by the background pattern under the right icon image, if the user was ↵
using sysihack. ↵
WBStartup+ now recognizes the WAIT= tooltype as the # of seconds to wait before loading the next program. ↵
WBStartup+ now recognizes the TOOLPRI= tooltype as the priority that the program should have when running. ↵
The DELAY= tooltype is now obsolete, therefore it has been removed. ↵
WBStartup+ now knows if it has already been run, and if it is run more than once, the user ↵
will see a requester asking if it is ok to run it again. ↵
The STARTUPPRI tooltype is no longer recognized, please use STARTPRI instead. ↵
When the WBStartup+Prefs window is opened on a virtual screen, it is centered vertically in the visible section, and is 100 pixels to the right of the leftmost ↵
visible section. ↵
The Amiga Workbench x.x text is now properly centered in WBStartup+'s progress window. ↵
The busy pointer is now shown when a secondary window is opened, such as the Priority Window. ↵
Sizing the main window is now impossible when a secondary window is opened since IDCMP is cut off. ↵
Priority Window is now activated when opened. ↵
You may use the keyboard up and down arrow keys to change the selected element in the listview gadget. ↵

V2.6 February 3, 1996

When no program is highlighted in WBStartup+Prefs, and the menu item "Icon Window" is selected, a requester appears telling the user to select a program first. However this requester is NOT localized, because not all of the catalog authors gave me a translation. Changed all MEMF_ANY's to MEMF_PUBLIC.

If the "Choose Group" window failed to open and set up properly, the program still would cycle through the list nodes and return an invalid pointer and crash. It now will return NULL.

Increased the height of all the button gadgets by 2.

Better calculations on the listview gadget's height and the button gadgets positions.

I'm Working on fixing the alias/local var environment problem. The problem IS in WBStart-Handler, which I did not write, and I can't get ahold of the author. I have found the bug in his program, but can not include my updated version due to copyright laws.

V2.7 March 3, 1996

Now uses launcher.library instead of WBStart-Handler. Local variables and paths are now inherited by launched applications. (Sorry it took so long.)

Included more catalog files.

Included WBStartupPlus.cd

1.10 How to use WBStartup+

How to use WBStartup+

Tooltypes

ENABLEDPATH
 DISABLEDPATH
 PROGRESSWINDOW
 BACKGROUNDPIC (for OS3.x only)
 PREFSPATH

Startup Programs

HotKeys

Ctrl	Bringing up WBStartup+Prefs before running any programs.
Left-Alt	Asks user which of the enabled programs should be run.
Left-Shift	Disabling WBStartup+, no programs will be run.

Changing execution order

1.11 How to use WBStartup+Prefs

How to use WBStartup+Prefs

The Prefs program allows you to choose which program to run at startup, and in which order to run them.

Tooltypes

ENABLEDPATH	Must be the same as that of	WBStartup+
DISABLEDPATH	Must be the same as that of	WBStartup+
ALPHABETIZE		

App Window

You can easily copy or move files into the enabled or disabled directory by simply dropping icons into the window from workbench.

A window will appear asking you if you want to copy or move the files, and whether to put the files in the Enabled or Disabled directory.

The Listview Gadget

Each item in the list that has a checkmark will be run at startup. To toggle the checkmark, just click the left mouse button on the checkbox.

To change the startup priority of a program, click in that area of the listview, set the slider gadget to the desired priority and close the window.

To bring up the Workbench icon information window for one of the programs listed in the listview gadget, select the program name, and then select "Icon Window" from the "Edit" pulldown menu.

Creating Groups

Set the checkmarks in the listview to your desired settings.

Choose "Create Group" from the "Edit" menu.

Type the name that you want to call the group and press enter.

You now have a new group.

You MUST save the settings, or the new group will be forgotten.

A requester will appear to allow you to save any group modifications on quitting. ←

Selecting a Group

Choose "Group" from the "Select" menu.

Select the name of the group you want to use from the list and select "Ok". (Double clicking works too)

Other Gadgets

Select "Save" to save the settings.

Select "Cancel" to exit the program without making any changes.

Select the "Restore" menu to restore the setting to what they were when WBStartup+Prefs was run.

1.12 Changing execution order

How to change the order in which the startup programs are run.

Use the WBStartup+Prefs program.

OR

You may add the tooltip STARTPRI to any of the startup programs icons.

1.13 Tooltypes

Tooltypes

Choose the program:

WBStartup+

WBStartup+Prefs

Startup Programs

1.14 Tooltype: ENABLEDPATH

ENABLEDPATH=

Set ENABLEDPATH to the directory where the programs are that you want to run at startup (boot time).

Default:

ENABLEDPATH=SYS:WBStartup/WBStartup (Enabled)

1.15 Tooltype: DISABLEDPATH

DISABLEDPATH=

Set DISABLEDPATH to the directory where programs that should not be run at startup are. This is like a storage directory.

Default:

DISABLEDPATH=SYS:WBStartup/WBStartup (Disabled)

1.16 Tooltype: PROGRESSWINDOW

PROGRESSWINDOW

This allows you to disable the progress window.

This tooltype has NO values, it either exists or it doesn't.

To disable the progress window, simple place parenthesis around the tooltype name.

Examples:

PROGRESSWINDOW	The progress window will be shown
(PROGRESSWINDOW)	No progress window will be shown

Default:

PROGRESSWINDOW

1.17 Tooltype: BACKGROUNDPIC

BACKGROUNDPIC=

For OS3.x only.

This allows you to choose what the progress window's background picture. The `datatypes.library` is used, so you may use any picture format for which you have the corresponding datatype, ie. jpeg, gif, ilbm, tiff, targa, pict, pcx, bmp, etc. Although since some datatypes are slow, I recommend using ilbm pictures.

Values:

NONE	No picture is used.
SCREEN	The default Workbench Screen picture is used.
WINDOWS	The default Workbench Window/Drawer picture is used.
WORKBENCH	The default Workbench Root (non-backdrop) picture is used ↔
.	
filename	Type the pathname and filename of any picture you want.

Default:

BACKGROUNDPIC=WINDOWS

Example:

BACKGROUNDPIC=sys:pictures/favoritepic.iff

1.18 Tooltype: PREFSPATH

PREFSPATH=

Set PREFSPATH to the path of the preferences program.

Default:

PREFSPATH=SYS:Prefs/WBStartup+Prefs

1.19 Tooltype: ALPHABETIZE

ALPHABETIZE

If this tooltype exists, the list of programs will be in alphabetical order, otherwise it will be in order by priority.

Examples:

ALPHABETIZE	The list will be alphabetized from A to Z.
(ALPHABETIZE)	The list will be ordered by priority.

1.20 Startup Programs

Tooltypes that WBStartup+ looks at

STARTPRI
WAIT
TOOLPRI

1.21 Tooltype: STARTPRI

STARTPRI=

This is the startup priority for each program. The program with the highest priority will be loaded and run first.

The values can be 127 to -128, where 127 has the highest priority and would be run first.

Programs without this tooltype are considered to have a priority of 0.

Example:

STARTPRI=100

For instance, I gave MagicCopper : STARTPRI=127 since I want that ugly plain looking screen to go away as soon as possible.

And I gave ToolManager : STARTPRI=120 so it will load second, and I will have access to all my hotkeys quicker.

1.22 Tooltype: WAIT

WAIT=

If a program's icon has this tooltype, there will a delay of xxx seconds after that program is run (before then next program in loaded and run).

Example:

```
WAIT=3
```

So after thae program with this tooltype is run, there will be a 3 seconds delay before the next program is loaded and run.

1.23 Tooltype: TOOLPRI

TOOLPRI=

This is the priority that the program is to have after it is loaded.

Programs with high priorities get use of the CPU more than programs with low priorites.

A priority of 0 is default.

The maximum priority is 127.
The minimum priority is -128.

Most priorities are in the range -5 to 5.
Usually this should just be 0, or not set.

1.24 Catalogs

Catalogs

The following is a list of catalogs and their authors.

Language	Author
Dansk	Jacob Laursen
Deutsch	Arno Eigenwillig with assistance from Hubert Feyrer
Français	Eric Sauvageau
Italiano	Giacomo Magnini
Norsk	Stian S. Olsen
Suomi	Arttu E. Kdrpinlehto
Svenska	Daniel Stenberg

The current .ct file is included in the locale directory. If you would like to see WBStartup+ in your language, please add your translations to that file and email it to me :)

1.25 Index

Documents

Author & Tech
Bugs
Catalogs
Changing execution order
Contributions
History
How to use WBStartup+
How to use WBStartup+Prefs
Installation Instructions
Startup Programs
Synopsis
Tooltype: ENABLEDPATH
Tooltype: BACKGROUNDPIC
Tooltype: ALPHABETIZE
Tooltype: DISABLEDPATH
Tooltype: PREFSPATH
Tooltype: PROGRESSWINDOW
Tooltype: STARTPRI
Tooltype: TOOLPRI
Tooltype: WAIT
Tooltypes
Launcher.library Info
WBStartup+
Where to get Updates

Buttons

ALPHABETIZE
Author & Tech
BACKGROUNDPIC
Bugs
Catalogs
Changing execution order
DISABLEDPATH
ENABLEDPATH
Features
History
Installing/Updating
libs:launcher.library
PostcardWare
PREFSPATH
PROGRESSWINDOW
Send me a postcard
STARTPRI
Startup Programs
TOOLPRI
WAIT
WBStartup+
WBStartup+
WBStartup+
WBStartup+Prefs
WBStartup+Prefs

WBStartup+Prefs
Where to get Updates