

NOTE: This Technical Note has been [retired](#). Please see the [Technical Notes](#) page for current documentation.

Technical Note DV11

Opening the Serial Driver

CONTENTS

[OpenDriver](#)

[References](#)

[Change History](#)

[Downloadables](#)

This Technical Note describes the recommended, safe, and compatible way to open the Macintosh serial driver, and it explains why you should no longer check for port availability.

Updated: [October 01 1989]

OpenDriver

Starting with the 128K ROM, we recommend that applications do not check the low-memory globals `SPConfig`, `PortAUse`, and `PortBUse` before opening the serial driver. It is no longer the application's responsibility to test for the availability of the serial ports. When running AppleTalk Phase 2, it is now possible to use the printer port for asynchronous serial communication while AppleTalk is active and using an alternate connection, such as EtherTalk or TokenTalk.

The serial driver automatically verifies that the serial port is correctly configured and free for an asynchronous driver; if it is not correctly configured or free, the serial driver returns either the result code `portNotCf` or `portInUse`. The serial driver already has all the code built into it for testing the availability of the serial ports before trying to complete the `_Open` call. Therefore, since all of the required checks are made inside the driver itself, we recommend that a simple `OpenDriver` call be made when you need to use a serial port.

By using just the `OpenDriver` call to the serial driver, you ensure that your code is both user-friendly and compatible with future versions of the System Software.

Pascal

```
result := OpenDriver('.AOut',AoutRefNumber);
        {Check result codes in a real application. }

result := OpenDriver('.AIn',AinRefNumber);
        {See failure mechanism in Sample Code. }
```

```
result = OpenDriver("\p.AOut",&AoutRefNumber);
/*Check result codes in a real app.*/

result = OpenDriver("\p.AIn",&AinRefNumber);
/* See failure mechanism in Sample Code.*/
```

If you must maintain compatibility with the 64K ROMs, call `_SysEnviron`s, then either call `RAMSDOpen` for the 64K ROM machines or `OpenDriver` for the others.

[Back to top](#)

References

Inside Macintosh , Volume II-249, The Serial Driver

Inside Macintosh , Volume IV-225, The Serial Driver

Technical Note M.OV.GestaltSysenvirons -- [Gestalt and Sysenvirons : a Never Ending Story](#)

DTS Q & A Stack

[Back to top](#)

Change History

| | |
|-----------------|---|
| 01-August-1989 | Originally written. |
| 01-October-1989 | Corrected syntax errors in the sample code. |

[Back to top](#)

Downloadables



Acrobat version of this Note (K)

[Download](#)

[Back to top](#)

Technical Notes by [Date](#) | [Number](#) | [Technology](#) | [Title](#)
[Developer Documentation](#) | [Technical Q&As](#) | [Development Kits](#) | [Sample Code](#)